

As required by Florida Statute 553.842 and Florida Administrative Code 9B-72, please provide the information and approval numbers on the building components listed below if they will be utilized on the construction project for which you are applying for a building permit. We recommend you contact your local product supplier should you not know the product approval number for any of the applicable listed products. Statewide approved products are listed online @ [www.floridabuilding.org](http://www.floridabuilding.org)

Category/Subcategory	Manufacturer	Product Description	Approval Number(s)
<b>1. EXTERIOR DOORS</b>	<i>Plastpro</i>	<i>Series N Fiberglass</i>	<i>FL 15220.11</i>
A. SWINGING			
B. SLIDING			
C. SECTIONAL/ROLL UP			
D. OTHER			
<b>2. WINDOWS</b>			
A. SINGLE/DOUBLE HUNG	<i>Kolbe</i>	<i>Forgent Series Double hung</i>	<i>FL 22655</i>
B. HORIZONTAL SLIDER			
C. CASEMENT			
D. FIXED			
E. MULLION			
F. SKYLIGHTS			
G. OTHER			
<b>3. PANEL WALL</b>	<i>Union Corrugating Co.</i>		
A. SIDING	<i>Master Rib</i>	<i>36" w 3/4" high ribs 9" oc</i>	<i>FL 9555.5-R5</i>
B. SOFFITS			
C. STOREFRONTS			
D. GLASS BLOCK			
E. OTHER			
<b>4. ROOFING PRODUCTS</b>			
A. ASPHALT SHINGLES			
B. NON-STRUCT METAL	<i>Union Corrugating Co</i>	<i>36" w 3/4" high ribs 9" oc</i>	<i>FL 9555.5-R5</i>
C. ROOFING TILES			
D. SINGLE PLY ROOF			
E. OTHER			
<b>5. STRUCT COMPONENTS</b>			
A. WOOD CONNECTORS			
B. WOOD ANCHORS			
C. TRUSS PLATES			
D. INSULATION FORMS			
E. LINTELS			
F. OTHERS			
<b>6. NEW EXTERIOR ENVELOPE PRODUCTS</b>			


The products listed below did not demonstrate product approval at plan review. I understand that at the time of inspection of these products, the following information must be available to the inspector on the jobsite; 1) copy of the product approval, 2) performance characteristics which the product was tested and certified to comply with, 3) copy of the applicable manufacturers installation requirements.

Further, I understand these products may have to be removed if approval cannot be demonstrated during inspection.

*Paul M. C. [Signature]*

Contractor or Owner Signature

NOTES: \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_



EXTERIOR ELEVATION

MAX. FRAME SIZE (IN.)	IMPACT
48 X 75	NO
APPLICABLE FOR SINGLE UNITS ONLY	

INSTALLATION METHOD	
Nailing Fin	4" from each corner and 4" on center
Installation Clips	6" from each corner and 16" on center
Screw Thru Frame	6" from each corner and 16" on center

FRAME ANCHOR REQUIREMENTS TABLE		
FRAME/CLIP & FIN TO OPENING FASTENER TYPE	MINIMUM EMBED	MINIMUM EDGE DIST.
#10 PFH screws into frame and wood substrate	1-1/4"	See pg. 2
#8 PFH Zinc treated screws into clip and wood substrate at an angle	1-1/2"	—
#8 PPH Zinc treated screws into clip and frame	FULL	See pg. 2
#11 Galvanized roofing nails	FULL	See pg. 2

#### GENERAL NOTES

1. These units have been tested, analyzed, Hallmark certified, and FBC approved.
2. Bucking, openings, and bucking fasteners must be properly designed and installed to transfer wind loads to the structure. The unit was tested with 1/2" rough opening gap.
3. These units were tested with ponderosa pine bucks, Florida building code requires preservative treated southern pine bucks.
4. All hardware and fasteners shall be in accordance with these drawings and may not vary unless specifically mentioned on the drawings.
5. These units have been tested in accordance with and meet the requirements of the Florida Building Code.
6. Impact shutters are required only with non-impact units.
7. All anchors shall be installed as specified on these drawings. Specified embedment base material shall be beyond wall finish or stucco.
8. Shims are required at each anchor location. When installation clips are used, a shim is required to be placed on each side of the installation clip.
9. Any fixed geometric shape that fits within the tested/approved size for a particular product type is qualified by the rectangular shape provided that the frame, sash components, and construction remain the same.
10. All fixed shaped units must fit inscribed into the allowable rectangular units and be governed by allowable design pressure of the respective rectangular unit.




1211 Depot Street  
Manawa, WI 54949  
920-596-2501


#### Forgent Series Operating Double Hung Window

FL# 22655	R&D No. 16126 & 16127
Revision	Drawn By: MKL
A	Date: 7/7/17
B	Sheet: 1 of 3
C	Drawing No. FDH-100


### Nail Fin Installation



### Installation Clip Installation



### Screw Installation



#### GENERAL NOTES

1. These units have been tested, analyzed, Hallmark certified, and FBC approved.
2. Bucking, openings, and bucking fasteners must be properly designed and installed to transfer wind loads to the structure. The unit was tested with 1/2" rough opening gap.
3. These units were tested with ponderosa pine bucks, Florida building code requires preservative treated southern pine bucks.
4. All hardware and fasteners shall be in accordance with these drawings and may not vary unless specifically mentioned on the drawings.
5. These units have been tested in accordance with and meet the requirements of the Florida Building Code.
6. Impact shutters are required only with non-impact units.
7. All anchors shall be installed as specified on these drawings. Specified embedment base material shall be beyond wall finish or stucco.
8. Shims are required at each anchor location. When installation clips are used, a shim is required to be placed on each side of the installation clip.
9. Any fixed geometric shape that fits within the tested/approved size for a particular product type is qualified by the rectangular shape provided that the frame, sash components, and construction remain the same.
10. All fixed shaped units must fit inscribed into the allowable rectangular units and be governed by allowable design pressure of the respective rectangular unit.

**KOLBE**  
■ WINDOWS & DOORS ■

1211 Depot Street  
Manawa, WI 54949  
920-596-2501

#### Forgent Series Operating Double Hung Window

FL# 22655	R&D No. 16126 & 16127
Revision	Drawn By: MKL
A	Date: 7/7/17
B	Sheet: 2 of 3
C	Drawing No. FDH-100A

# Nail Fin Installation

The diagrams illustrate the installation of a Nail Fin system in exterior and interior applications. The exterior view shows the nail fin being driven through a wood block into the structural member, with a 1/4" maximum gap allowed. The interior view shows the nail fin being driven through a wood block into the structural member, with a 1/4" maximum gap allowed. The diagrams also show the location of the nail fin relative to the edge of the structural member, with a 1/4" maximum gap allowed. The diagrams are labeled with dimensions and material specifications.

**EXTERIOR**

Labels for the exterior diagram include:

- MIN. 2x4 P.T. WOOD BLOCK 8" THICK
- 11 GA. 9" 5-1/2" ROD
- EDGE DISTANCE PRE-DETERMINED BY PRE-DRILLED HOLE LOCATION
- 1/4" MAX. G-48
- SEAL JAMB

**HEAD**

**EXTERIOR**

Labels for the exterior diagram include:

- NAILING FIN
- SPRINT & BACKER ROD BY OTHERS
- 1/4" MAX. G-48

**EXTERIOR**

Labels for the exterior diagram include:


- 1/4" MAX. G-48

GENERAL NOTES

1. These units have been tested, analyzed, Hallmark certified, and FBC approved.
2. Bucking, openings, and bucking fasteners must be properly designed and installed to transfer wind loads to the structure. The unit was tested with 1/2" rough opening gap.
3. These units were tested with ponderosa pine bucks. Florida building code requires preservative treated southern pine bucks.
4. All hardware and fasteners shall be in accordance with these drawings and may not vary unless specifically mentioned on the drawings.
5. These units have been tested in accordance with and meet the requirements of the Florida Building Code.
6. Impact shutters are required only with non-impact units.
7. All anchors shall be installed as specified on these drawings. Specified embedment base material shall be beyond wall finish or stucco.
8. Shims are required at each anchor location. When installation clips are used, a shim is required to be placed on each side of the installation clip.
9. Any fixed geometric shape that fits within the tested/approved size for a particular product type is qualified by the rectangular shape provided that the frame, sash components, and construction remain the same.
10. All fixed shaped units must fit inscribed into the allowable rectangular units and be governed by allowable design pressure of the respective rectangular unit.

1211 Depot Street  
Manawa, WI 54949  
920-596-2501

FL# 22655		R&D No. 16126 & 16127
Revision		Drawn By: JRK
A		Date: 06/19/18
B		Sheet: 3 of 3
C		Drawing No. FDH-100B



EXTERIOR ELEVATION

MAX. FRAME SIZE (IN.)	IMPACT
48 X 75	NO
APPLICABLE FOR SINGLE UNITS ONLY	

INSTALLATION METHOD	
Nailing Fin	4" from each corner and 4" on center
Installation Clips	6" from each corner and 16" on center
Screw Thru Frame	6" from each corner and 16" on center

FRAME ANCHOR REQUIREMENTS TABLE		
FRAME/CLIP & FIN TO OPENING FASTENER TYPE	MINIMUM EMBED	MINIMUM EDGE DIST.
#10 PFH screws into frame and wood substrate	1-1/4"	See pg. 2
#8 PFH Zinc treated screws into clip and wood substrate at an angle	1-1/2"	—
#8 PPH Zinc treated screws into clip and frame	FULL	See pg. 2
#11 Galvanized roofing nails	FULL	See pg. 2

#### GENERAL NOTES

1. These units have been tested, analyzed, Hallmark certified, and FBC approved.
2. Bucking, openings, and bucking fasteners must be properly designed and installed to transfer wind loads to the structure. The unit was tested with 1/2" rough opening gap.
3. These units were tested with ponderosa pine bucks, Florida building code requires preservative treated southern pine bucks.
4. All hardware and fasteners shall be in accordance with these drawings and may not vary unless specifically mentioned on the drawings.
5. These units have been tested in accordance with and meet the requirements of the Florida Building Code.
6. Impact shutters are required only with non-impact units.
7. All anchors shall be installed as specified on these drawings. Specified embedment base material shall be beyond wall finish or stucco.
8. Shims are required at each anchor location. When installation clips are used, a shim is required to be placed on each side of the installation clip.
9. Any fixed geometric shape that fits within the tested/approved size for a particular product type is qualified by the rectangular shape provided that the frame, sash components, and construction remain the same.
10. All fixed shaped units must fit inscribed into the allowable rectangular units and be governed by allowable design pressure of the respective rectangular unit.


**KOLBE** 1211 Depot Street  
Manawa, WI 54949  
920-596-2501  
• WINDOWS & DOORS •

Forgent Series  
Operating Double Hung Window


FL# 22655	R&D No. 16126 & 16127
Revision	Drawn By: MKL
A	Date: 7/7/17
B	Sheet: 1 of 3
C	Drawing No. FDH-100




### Nail Fin Installation



### Installation Clip Installation



### Screw Installation



#### GENERAL NOTES

1. These units have been tested, analyzed, Hallmark certified, and FBC approved.
2. Bucking, openings, and bucking fasteners must be properly designed and installed to transfer wind loads to the structure. The unit was tested with 1/2" rough opening gap.
3. These units were tested with ponderosa pine bucks, Florida building code requires preservative treated southern pine bucks.
4. All hardware and fasteners shall be in accordance with these drawings and may not vary unless specifically mentioned on the drawings.
5. These units have been tested in accordance with and meet the requirements of the Florida Building Code.
6. Impact shutters are required only with non-impact units.
7. All anchors shall be installed as specified on these drawings. Specified embedment base material shall be beyond wall finish or stucco.
8. Shims are required at each anchor location. When installation clips are used, a shim is required to be placed on each side of the installation clip.
9. Any fixed geometric shape that fits within the tested/approved size for a particular product type is qualified by the rectangular shape provided that the frame, sash components, and construction remain the same.
10. All fixed shaped units must fit inscribed into the allowable rectangular units and be governed by allowable design pressure of the respective rectangular unit.


**KOLBE**  
■ WINDOWS & DOORS ■

1211 Depot Street  
Manawa, WI 54949  
920-596-2501


#### Forgent Series Operating Double Hung Window

FL# 22655	R&D No. 16126 & 16127
Revision	Drawn By: MKL
A	Date: 7/7/17
B	Sheet: 2 of 3
C	Drawing No. FDH-100A


### Nail Fin Installation



### Installation Clip Installation



### Screw Installation



#### GENERAL NOTES

1. These units have been tested, analyzed, Hallmark certified, and FBC approved.
2. Bucking, openings, and bucking fasteners must be properly designed and installed to transfer wind loads to the structure. The unit was tested with 1/2" rough opening gap.
3. These units were tested with ponderosa pine bucks, Florida building code requires preservative treated southern pine bucks.
4. All hardware and fasteners shall be in accordance with these drawings and may not vary unless specifically mentioned on the drawings.
5. These units have been tested in accordance with and meet the requirements of the Florida Building Code.
6. Impact shutters are required only with non-impact units.
7. All anchors shall be installed as specified on these drawings. Specified embedment base material shall be beyond wall finish or stucco.
8. Shims are required at each anchor location. When installation clips are used, a shim is required to be placed on each side of the installation clip.
9. Any fixed geometric shape that fits within the tested/approved size for a particular product type is qualified by the rectangular shape provided that the frame, sash components, and construction remain the same.
10. All fixed shaped units must fit inscribed into the allowable rectangular units and be governed by allowable design pressure of the respective rectangular unit.




1211 Depot Street  
Manawa, WI 54949  
920-596-2501

#### Forgent Series Operating Double Hung Window New Construction Frame


FL# 22655	R&D No. 16126 & 16127
Revision	Drawn By: JRK
A	Date: 06/19/18
B	Sheet: 3 of 3
C	Drawing No. FDH-100B







July 27, 2020										<div>STATE OF FLORIDA PROFESSIONAL ENGINEER</div>									
Documents Prepared By: Lyndon F. Schmidt P.E. No. 43409																			
DRAWING NO.: FL-15220.11										PRODUCT: PLASTPRO INC FIBERGLASS DOOR									
SHEET 2 of 9										PART OR ASSEMBLY: DOOR PANEL DETAILS AND GLAZING DETAIL									
DATE 02/20/12										REVISIONS									
SCALE N.T.S.																			
CHK. BY: LFS																			
DATE 08/02/17										3 7/27/20 UPDATE TO 7TH ED (2020) FBC LFS									
DATE 04/22/15										2 08/02/17 UPDATE TO 6TH ED. (2017) FBC JK									
DATE 04/22/15										1 04/22/15 UPDATE TO 5TH ED. (2014) FBC JK									
NO. DATE										BY									







NO.	DATE	REVISIONS	BY
3	7/27/20	UPDATE TO 7TH ED. (2020) FBC	LFS
2	08/02/17	UPDATE TO 6TH ED. (2017) FBC	JK
1	04/22/15	UPDATE TO 5TH ED. (2014) FBC	JK

PRODUCT:	PLASTPRO INC FIBERGLASS DOOR
PART OR ASSEMBLY:	HORIZONTAL & VERTICAL CROSS SECTIONS (2X BUCK)




July 27, 2020  
Documents Prepared By:  
Lyndon F. Schmidt  
P.E. No. 43409

*RW* BUILDING CONSULTANTS, INC.  
P.O. Box 230, Valrico, FL 33595  
Phone No.: 813.659.9197  
FBPE Registry No. 9813







DATE: 02/20/12 SCALE: N.T.S. DWG. BY: JK CHK. BY: LFS DRAWING NO.: FL-15220.11 SHEET 4 OF 9				PRODUCT: PLASTPRO INC FIBERGLASS DOOR PART OR ASSEMBLY: HORIZONTAL & VERTICAL CROSS SECTIONS (1X BUCK)		Documents Prepared By: Lyndon F. Schmidt P.E. No. 43409 July 27, 2020 L.F. SCHMIDT LICENSE No. 43409 STATE OF FLORIDA PROFESSIONAL ENGINEER R.W. BUILDING CONSULTANTS, INC. P.O. Box 230, Valrico, FL 33595 Phone No.: 813.659.9197 FBPE Registry No. 9813	
REVISIONS NO. DATE 1 04/22/15 UPDATE TO 5TH ED. (2014) FBC JK 2 08/02/17 UPDATE TO 6TH ED. (2017) FBC JK 3 7/27/20 UPDATE TO 7TH ED (2020) FBC LFS							



SHEET 5 OF 9		DATE: 02/20/12		SCALE: N.T.S.		CHK. BY: LFS		DRAWING NO.: FL-15220.11	
NO.		DATE		REVISIONS		BY		PRODUCT:	
3		7/27/20		UPDATE TO 7TH ED (2020) FBC		LFS		PLASTPRO INC	
2		08/02/17		UPDATE TO 6TH ED. (2017) FBC		JK		FIBERGLASS DOOR	
1		04/22/15		UPDATE TO 5TH ED. (2014) FBC		JK		PART OR ASSEMBLY:	
								HORIZONTAL & VERTICAL CROSS	
								SECTIONS (DIRECT TO MASONRY)	
								DOCUMENTS PREPARED BY:	
								Lyndon F. Schmidt	
								P.E. No. 43409	
								BUILDING CONSULTANTS, INC.	
								P.O. Box 230, Valrico, FL 33595	
								Phone No.: 813.659.9197	
								FBPE Registry No. 9813	



July 27, 2020

Documents Prepared By:  
Lyndon F. Schmidt  
P.E. No. 43409

RW


BUILDING CONSULTANTS, INC.  
P.O. Box 230, Valrico, FL 33595  
Phone No.: 813.659.9197  
FBPE Registry No. 9813




REVISIONS				PRODUCT:	
				PLASTPRO INC FIBERGLASS DOOR	
				PART OR ASSEMBLY:	
				VERTICAL CROSS SECTIONS (THRESHOLDS)	
NO.	DATE	DESCRIPTION	BY		
3	7/27/20	UPDATE TO 7TH ED (2020) FBC	LFS		
2	08/02/17	UPDATE TO 6TH ED. (2017) FBC	JK		
1	04/22/15	UPDATE TO 5TH ED. (2014) FBC	JK		




**1 HORIZONTAL CROSS SECTION**  
Shown Direct to Masonry  
Outswing only w/ 4-9/16" jamb




**2 HORIZONTAL CROSS SECTION**  
Shown Direct to Masonry  
Outswing only w/ 4-9/16" jamb




**3 HORIZONTAL CROSS SECTION**  
Shown Direct to Masonry  
Outswing only w/ 6-9/16" jamb




**4 HORIZONTAL CROSS SECTION**  
Shown Direct to Masonry  
Outswing only w/ 6-9/16" jamb



**5 VERTICAL CROSS SECTION**  
Shown Direct to Masonry  
Outswing only w/ 4-9/16" jamb




**6 VERTICAL CROSS SECTION**  
Shown Direct to Masonry  
Outswing only w/ 6-9/16" jamb



July 27, 2020

Documents Prepared By:  
Lyndon F. Schmidt  
P.E. No. 43409

**Rw** BUILDING CONSULTANTS, INC.  
P.O. Box 230, Valrico, FL 33595  
Phone No.: 813.659.9197  
FBPE Registry No. 9813




NO.	DATE	REVISIONS	BY
3	7/27/20	UPDATE TO 7TH ED. (2020) FBC	LFS
2	08/02/17	UPDATE TO 6TH ED. (2017) FBC	JK
1	04/22/15	UPDATE TO 5TH ED. (2014) FBC	JK

WOOD SCREW INSTALLATION NOTES:  
1. Maintain a minimum 5/8" edge distance, 1" end distance, & 1" o.c. spacing of wood screws to prevent the splitting of wood.



ANCHOR TYPE	ANCHOR SIZE	MIN. EMBEDMENT	MIN. CLEARANCE TO MASONRY	MIN. CLEARANCE TO ADJACENT ANCHOR
ITW <sup>®</sup> TAPCON <sup>®</sup>	1/4"	1-1/4"	2"	4"
ITW <sup>®</sup> ETCO ULTRACON <sup>®</sup>	1/4"	1-1/4"	1"	4"
ITW <sup>®</sup> TAPCON <sup>®</sup>	3/16"	1-1/4"	3"	1-1/2"

- CONCRETE ANCHOR NOTES:  
1. Concrete anchor locations at the corners may be adjusted to maintain the min. edge distance to mortar joints.  
2. Concrete anchor locations noted as "MAX. ON CENTER" must be adjusted to maintain the min. edge distance to mortar joints; additional concrete anchors may be required to ensure the "MAX. ON CENTER" dimension are not exceeded.  
3. Concrete anchor table:


#### BUCK ANCHORING





#### STRIKE JAMB



#### FRAME ANCHORING



#### HINGE JAMB










NO.	DATE	REVISIONS	BY
3	7/27/20	UPDATE TO 7TH ED (2020) FBC	LFS
2	08/02/17	UPDATE TO 6TH ED. (2017) FBC	JK
1	04/22/15	UPDATE TO 5TH ED. (2014) FBC	JK

PRODUCT: PLASTPRO INC FIBERGLASS DOOR  
PART OR ASSEMBLY: BUCK AND FRAME ANCHORING

July 27, 2020  
Documents Prepared By: Lyndon F. Schmidt  
P.E. No. 43409  
RWB BUILDING CONSULTANTS, INC.  
P.O. Box 230, Valrico, FL 33595  
Phone No.: 813.659.9197  
FBPE Registry No. 9813



ITEM #	DESCRIPTION	MATERIAL
A	1X BUCK SG >= 0.55	WOOD
B	2X BUCK SG >= 0.55	WOOD
C	1/4" MAX. SHIM SPACE	-
D	1/4" X 2-3/4" PHH ELCO OR ITW CONCRETE SCREW	STEEL
E	MASONRY - 3,000 PSI MIN. CONCRETE CONFORMING TO ACI 301 OR HOLLOW BLOCK CONFORMING TO ASTM C90	CONCRETE
G	3/16" X 3-1/4" PHH ITW CONCRETE SCREW	STEEL
H	1/4" X 3-1/4" PHH ELCO OR ITW CONCRETE SCREW	STEEL
I	1/4" X 3-3/4" PHH ELCO OR ITW CONCRETE SCREW	STEEL
J	1/4" X 3-3/4" PHH ELCO OR ITW CONCRETE SCREW	STEEL
K	1/4" X 2-1/4" ITW CONCRETE SCREW	STEEL
L	#10 X 2-1/2" PHH WOOD SCREW [1.5" MIN. EMBEDMENT]	STEEL
M	3/16" X 2-1/4" ITW CONCRETE SCREW	STEEL
N	3/16" X 2-3/4" ITW CONCRETE SCREW	STEEL
P	1/4" X 2-1/4" PHH ELCO CONCRETE SCREW	STEEL
1	POLY FIBER JAMB	COMP. / VINYL
2	FINGER JOINED PINE FRAME	WOOD
7	WEATHERSTRIP	FOAM
8	DOOR BOTTOM SWEEP	VINYL
9	4" X 4" BUTT HINGE	STEEL
11	#9 X 3/4" PHH WOOD SCREW	STEEL
27	LATCH STRIKE PLATE	STEEL
28	DEADBOLT STRIKE PLATE	STEEL
30	OUTSWING THRESHOLD	ALUM/WOOD
34	OUTSWING THRESHOLD	ALUM/WOOD
37	INSWING THRESHOLD	ALUM/WOOD
40	DOOR PANEL - SEE DOOR PANEL DETAIL SHEET FOR CONSTRUCTION DETAILS	-
58	#8 X 2" PHH WOOD SCREW	STEEL



NO.	DATE	REVISIONS	BY
3	7/27/20	UPDATE TO 7TH ED (2020) FBC	LFS
2	08/02/17	UPDATE TO 6TH ED. (2017) FBC	JK
1	04/22/15	UPDATE TO 5TH ED. (2014) FBC	JK

PRODUCT:	PLASTPRO INC FIBERGLASS DOOR
PART OR ASSEMBLY:	BILL OF MATERIALS

July 27, 2020

Documents Prepared By:  
Lyndon F. Schmidt  
P.E. No. 43409

RW BUILDING CONSULTANTS, INC.  
P.O. Box 230, Valrico, FL 33595  
Phone No.: 813.659.9197  
FBPE Registry No. 9813



**EVALUATION REPORT OF  
UNION CORRUGATING COMPANY  
'29 GA. MASTERBIB PANEL'  
OVER WOOD SUPPORTS**

**FLORIDA BUILDING CODE 7TH EDITION (2020)  
FLORIDA PRODUCT APPROVAL  
FL 9555.5-R5  
STRUCTURAL COMPONENTS  
ROOF DECK**

**Prepared For:  
Union Corrugating Company  
701 S. King St.  
Fayetteville, NC 28301  
Telephone: (910) 483-0479  
Fax: (910) 483-1091**

**Prepared By:  
Bala Sockalingam, Ph.D., P.E.  
Florida Professional Engineer #62240  
1216 N Lansing Ave., Suite C  
Tulsa, OK 74106  
Telephone: (918) 492-5992  
FAX: (866) 366-1543**

**This report consists of  
Evaluation Report (3 Pages including cover)  
Installation Details (1 Page)  
Load Span Table (1 Page)**

**Report No. C2373-5  
Date: 8.8.2020**




Manufacturer:	Union Corrugating Company
Product Name:	MasterRib Panel
Panel Description:	36" wide coverage with 3/4" high ribs at 9" o.c.
Materials:	Minimum 29 ga., 80 ksi steel. Galvanized coated steel (ASTM A653) or Galvalume coated steel (ASTM A792) or painted steel (ASTM A755). Corrosion resistant as per FBC 2020 Section 1507.4.3.
Support Description:	Nom. 2" x 2" (min) SPF, SYP or DF lumber. (Must be designed by others)
Slope:	1/2:12 or greater in accordance with FBC 2020 Section 1507.4.2
Design Pressure: (Based on testing)	+27.1 and -36.2 psf at support spacing of 48" o.c. (at 3 span condition with FS = 2.0)
Panel Attachment:	#9-15 or #10-14 x 1.5" long wood screws with washers. Fasteners are corrosion resistant as per FBC 2020 Section 1507.4.4.
At panel ends	at 3.5"-5.5"-3.5" o.c. across panel width
At intermediate	at 9" o.c. across panel width
Sidelap Attachment:	1/4"-14 x 7/8" long SDS with washer at 24" o.c. Fasteners are corrosion resistant as per FBC 2020 Section 1507.4.4.
Test Standards:	Panel assembly tested in accordance with ASTM E1592-01 'Test Method for Structural Performance of Sheet Metal Roof and Siding Systems by Uniform Static Air Pressure Difference' and FM 4470 Section 5.5 'Resistance to Foot Traffic'.
Test Equivalency:	The test procedure in ASTM E1592-01 comply with test procedure prescribed in ASTM E1592-05(2012). The test procedure in FM 4470 (1992) comply with test procedure prescribed in FM 4470 (2016) Section 4.6 'Resistance to Foot Traffic'.
Code Compliance:	The product described herein has demonstrated compliance with FBC 2020 Section 1507.4.
Product Limitations:	Design wind loads shall be determined for each project in accordance with FBC 2020 Section 1609 or ASCE 7-16 using allowable stress design. The maximum support spacing listed herein shall not be exceeded. The design pressure for reduced support spacing may be computed using rational analysis prepared by a Florida Professional Engineer or based on Union Corrugating load span table. This product is not approved for use in the High Velocity Hurricane Zone. Fire




classification is not within scope of this Evaluation Report. Refer to FBC 2020 Section 1505 and current approved roofing materials directory for fire ratings of this product.

Supporting Documents: ASTM E1592 Test Report  
ENCON Technology Inc.  
C1514-1 (Test #2 & 3), Reporting Date 9/8/07

FM 4470 Test Report  
ENCON Technology Inc.  
C1583-2, Reporting Date 7/24/08



- GENERAL NOTES:**
1. ROOF PANEL HAS BEEN DESIGNED IN ACCORDANCE WITH THE FLORIDA BUILDING CODE (FBC).
  2. ROOF PANELS SHALL BE 29 GA. (t = 0.013"). EFFECTIVE COVERING WIDTH OF PANEL = 36".
  3. ROOF PANELS SHALL BE INSTALLED OVER STRUCTURE AS SPECIFIED ON THIS DRAWING.
  4. REQUIRED DESIGN WIND LOADS SHALL BE DETERMINED FOR EACH PROJECT. THIS PANEL SYSTEM MAY NOT BE INSTALLED WHEN THE REQUIRED DESIGN WIND LOADS ARE GREATER THAN THE ALLOWABLE DESIGN LOADS.
  5. ALL FASTENERS MUST BE IN ACCORDANCE WITH THIS DRAWING & THE FLORIDA BUILDING CODE. IF A DIFFERENCE OCCURS BETWEEN THE MINIMUM REQUIREMENTS OF THIS DRAWING & THE CODE, THE CODE SHALL CONTROL.
  6. SUPPORTS MUST BE DESIGNED TO WITHSTAND WIND LOADS AS REQUIRED FOR EACH APPLICATION AND ARE THE RESPONSIBILITY OF OTHERS.
  7. PANELS MAY SPAN BETWEEN EAVE TO RIDGE SUPPORTS OR RAKE TO RAKE SUPPORTS.



**UNION CORRUGATING COMPANY**  
**MasterRib Roof Panel**  
 36" wide, 29 ga. (min) Steel Panel over Wood Supports

Span Condition	Loading Type	Allowable Load (psf)								
		Support Spacing (ft)								
		1.50	1.75	2.00	2.25	2.50	2.75	3.00	3.50	4.00
Two Span	Gravity	106.4	91.2	79.8	70.9	63.9	58.0	53.2	45.6	34.7
	Uplift	84.9	72.8	63.7	56.6	51.0	46.3	42.5	36.4	29.0
Three Span	Gravity	120.9	103.7	90.7	80.6	72.6	66.0	60.5	40.5	27.1
	Uplift	96.5	82.7	72.4	64.4	57.9	52.7	48.3	41.4	36.2
Four or More Spans	Gravity	116.4	99.8	87.3	77.6	69.8	63.5	58.2	43.0	28.8
	Uplift	92.9	79.6	69.7	61.9	55.7	50.7	46.5	39.8	33.8

**Notes:**

1. Allowable load for each condition is the smallest load calculated based on fastener capacity, panel strength and deflection limit of  $L/180$ . Allowable loads are calculated for minimum 29 ga. panel.
2. The wind load is taken as 0.7 times the "component and cladding" loads for the purpose of determining deflection limit.
3. The panel allowable properties are determined from full scale ASTM E1592 tests at 4' 0" span.
4. The panel fasteners are #9-16 or 10-14 x 1-1/2" long wood screws with washers. Fastener spacing across panel width is 9.0" o.c. in the interior supports and 3.5"-5.5"-3.5" o.c. at panel ends.
5. Sidelap fasteners are 1/4"-14 x 7/8" long self drilling screws with washers at 24" o.c.
6. Wood supports are minimum 2" x 2" lumber. All supports must be designed to resist all loads imposed on the panel.
7. Minimum bearing width of support is 1.5".
8. The panels may span from eave to ridge or rake to rake.
9. Panels must be installed as per Evaluation Report FL 9555.5 and Union current installation procedure.



1216 N Lansing Ave, Suite C  
 Tulsa, OK 74106  
 918 492 5992

Bala Sockalingam, Ph.D., P.E.  
 PE 62240