

DATE 06/24/2008

Columbia County Building Permit

This Permit Must Be Prominently Posted on Premises During Construction

PERMIT
000027113

APPLICANT	RICHARD J. KEEN		PHONE	386.623.4629	
ADDRESS	650	SW MAIN BLVD	LAKE CITY	FL	32025
OWNER	RICHARD KEEN		PHONE	386.623.4629	
ADDRESS	285	SE BREAM LOOP	LAKE CITY	FL	32025
CONTRACTOR	JAMES H. JOHNSTON		PHONE	386.365.5999	
LOCATION OF PROPERTY	41-S TO C-252, TL TO PEBBLE CREEK, TL TO BREAM LOOP, TL 5TH PLACE ON L.				
TYPE DEVELOPMENT	SF/UTILITY		ESTIMATED COST OF CONSTRUCTION	82500.00	
HEATED FLOOR AREA	1650.00	TOTAL AREA	1650.00	HEIGHT	14.11
STORIES	1				
FOUNDATION	CONC	WALLS	FRAMED	ROOF PITCH	6'12
FLOOR	CONC				
LAND USE & ZONING	RSF-2		MAX. HEIGHT	35	
Minimum Set Back Requirments:	STREET-FRONT		25.00	REAR	15.00
SIDE	10.00				
NO. EX.D.U.	0	FLOOD ZONE	X	DEVELOPMENT PERMIT NO.	

PARCEL ID	15-4S-17-08359-049	SUBDIVISION	COUNTRY CREEK
LOT	9	BLOCK	
PHASE		UNIT	
TOTAL ACRES	0.50		

000001623	CRC1328128		
Culvert Permit No.	Culvert Waiver	Contractor's License Number	Applicant/Owner/Contractor
18"X32"MITERED	08-0093	BLK	JTH
Driveway Connection	Septic Tank Number	LU & Zoning checked by	Approved for Issuance
			New Resident

COMMENTS: 1 FOOT ABOVE ROAD.

Check # or Cash 1951

FOR BUILDING & ZONING DEPARTMENT ONLY

(footer/Slab)

Temporary Power	Foundation	Monolithic
date/app. by	date/app. by	date/app. by
Under slab rough-in plumbing	Slab	Sheathing/Nailing
date/app. by	date/app. by	date/app. by
Framing	Rough-in plumbing above slab and below wood floor	
date/app. by	date/app. by	
Electrical rough-in	Heat & Air Duct	Peri. beam (Lintel)
date/app. by	date/app. by	date/app. by
Permanent power	C.O. Final	Culvert
date/app. by	date/app. by	date/app. by
M/H tie downs, blocking, electricity and plumbing	Pool	
date/app. by	date/app. by	
Reconnection	Pump pole	Utility Pole
date/app. by	date/app. by	date/app. by
M/H Pole	Travel Trailer	Re-roof
date/app. by	date/app. by	date/app. by

BUILDING PERMIT FEE \$	415.00	CERTIFICATION FEE \$	8.25	SURCHARGE FEE \$	8.25
MISC. FEES \$	0.00	ZONING CERT. FEE \$	50.00	FIRE FEE \$	0.00
WASTE FEE \$					
FLOOD DEVELOPMENT FEE \$		FLOOD ZONE FEE \$	25.00	CULVERT FEE \$	25.00
				TOTAL FEE	531.50
INSPECTORS OFFICE			CLERKS OFFICE		

NOTICE: IN ADDITION TO THE REQUIREMENTS OF THIS PERMIT, THERE MAY BE ADDITIONAL RESTRICTIONS APPLICABLE TO THIS PROPERTY THAT MAY BE FOUND IN THE PUBLIC RECORDS OF THIS COUNTY. AND THERE MAY BE ADDITIONAL PERMITS REQUIRED FROM OTHER GOVERNMENTAL ENTITIES SUCH AS WATER MANAGEMENT DISTRICTS, STATE AGENCIES, OR FEDERAL AGENCIES.

"WARNING TO OWNER: YOUR FAILURE TO RECORD A NOTICE OF COMMENCEMENT MAY RESULT IN YOUR PAYING TWICE FOR IMPROVEMENTS TO YOUR PROPERTY. IF YOU INTEND TO OBTAIN FINANCING, CONSULT WITH YOUR LENDER OR AN ATTORNEY BEFORE RECORDING YOUR NOTICE OF COMMENCEMENT."

EVERY PERMIT ISSUED SHALL BECOME INVALID UNLESS THE WORK AUTHORIZED BY SUCH PERMIT IS COMMENCED WITHIN 180 DAYS AFTER ITS ISSUANCE, OR IF THE WORK AUTHORIZED BY SUCH PERMIT IS SUSPENDED OR ABANDONED FOR A PERIOD OF 180 DAYS AFTER THE TIME THE WORK IS COMMENCED. A VALID PERMIT RECIEVES AN APPROVED INSPECTION EVERY 180 DAYS. WORK SHALL BE CONSIDERED TO BE IN ACTIVE PROGRESS WHEN THE PERMIT HAS RECIEVED AN APPROVED INSPECTION WITHIN 180 DAYS.

The Issuance of this Permit Does Not Waive Compliance by Permittee with Deed Restrictions.

Columbia County Building Permit Application

For Office Use Only Application # 0801-142 Date Received 1/27 By JW Permit # 1623/2713
 Zoning Official BLK Date 07.02.08 Flood Zone X FEMA Map # N/A Zoning RSF-2
 Land Use R2D Elevation N/A MFE 1st River N/A Plans Examiner OKJTH Date 1-31-08
 Comments CITY WATER
☒ NOC ☐ EH ☐ Deed or PA ☐ Site Plan ☐ State Road Info ☐ Parent Parcel # _____
☐ Dev Permit # _____ ☐ In Floodway ☐ Letter of Authorization from Contractor
☐ Unincorporated area ☐ Incorporated area ☐ Town of Fort White ☐ Town of Fort White Compliance letter

Septic Permit No. 08-0093N RICHARD KEEN Fax 752-0078

Name Authorized Person Signing Permit James Johnston Phone 365-5999

Address 650 SW Main Blvd LAKE CITY FL 32025

Owners Name Richard Keen Phone 623-4629

911 Address 285 SE Bream Loop LAKE CITY FL 32025

Contractors Name James Johnston Phone 365-5999

Address 650 SW Main Blvd L.C. FL 32025

Fee Simple Owner Name & Address _____

Bonding Co. Name & Address _____

Architect/Engineer Name & Address Mark Disosway P.O. Box 868 L.C. FL 32056

Mortgage Lenders Name & Address N/A

Circle the correct power company - FL Power & Light - Clay Elec. - Suwannee Valley Elec. - Progress Energy

Property ID Number 15-45-17-08359-049 Estimated Cost of Construction 100,000⁰⁰

Subdivision Name Country Creek S/D Lot 9 Block _____ Unit _____ Phase _____

Driving Directions 415 to CR 252 turn left, go to Pebble Creek Terr. turn left, go to SE Bream Loop turn left 5th place on left
 Number of Existing Dwellings on Property 0

Construction of SFD Total Acreage 1/2 Lot Size 145x155

Do you need a - Culvert Permit or ~~Culvert Waiver~~ or Have an Existing Drive Total Building Height 14' 11"

Actual Distance of Structure from Property Lines - Front 30 Side 15 Side 30 Rear 90

Number of Stories 1 Heated Floor Area 1170 Total Floor Area 1650 Roof Pitch 6/12

Application is hereby made to obtain a permit to do work and installations as indicated. I certify that no work or installation has commenced prior to the issuance of a permit and that all work be performed to meet the standards of all laws regulating construction in this jurisdiction.

Th. called RE: 2.7.08

Columbia County Building Permit Application

WARNING TO OWNER: YOUR FAILURE TO RECORD A NOTICE OF COMMENCEMENT MAY RESULT IN YOU PAYING TWICE FOR IMPROVEMENTS TO YOUR PROPERTY. A NOTICE OF COMMENCEMENT MUST BE RECORDED AND POSTED ON THE JOB SITE BEFORE THE FIRST INSPECTION. IF YOU INTEND TO OBTAIN FINANCING, CONSULT WITH YOUR LENDER OR ATTORNEY BEFORE RECORDING YOUR NOTICE OF COMMENCEMENT.


FLORIDA'S CONSTRUCTION LIEN LAW: Protect Yourself and Your Investment

According to Florida Law, those who work on your property or provide materials, and are not paid-in-full, have a right to enforce their claim for payment against your property. This claim is known as a construction lien. If your contractor fails to pay subcontractors or material suppliers or neglects to make other legally required payments, the people who are owed money may look to your property for payment, even if you have paid your contractor in full. This means if a lien is filed against your property, it could be sold against your will to pay for labor, materials or other services which your contractor may have failed to pay.

NOTICE OF RESPONSIBILITY TO BUILDING PERMITEE:

YOU ARE HEREBY NOTIFIED as the recipient of a building permit from Columbia County, Florida, you will be held responsible to the County for any damage to sidewalks and/or road curbs and gutters, concrete features and structures, together with damage to drainage facilities, removal of sod, major changes to lot grades that result in ponding of water, or other damage to roadway and other public infrastructure facilities caused by you or your contractor, subcontractors, agents or representatives in the construction and/or improvement of the building and lot for which this permit is issued. No certificate of occupancy will be issued until all corrective work to these public infrastructures and facilities has been corrected.

OWNERS CERTIFICATION: I hereby certify that all the foregoing information is accurate and all work will be done in compliance with all applicable laws and regulating construction and zoning. I further understand the above written responsibilities in Columbia County for obtaining this Building Permit.



Owners Signature


CONTRACTORS AFFIDAVIT: By my signature I understand and agree that I have informed and provided this written statement to the owner of all the above written responsibilities in Columbia County for obtaining this Building Permit.



Contractor's Signature (Permitee)


Contractor's License Number CRC1328128
Columbia County
Competency Card Number _____

Affirmed under penalty of perjury to by the Contractor and subscribed before me this 29 day of Jan 2008
Personally known X or Produced Identification _____



State of Florida Notary Signature (For the Contractor)

SEAL:



This Instrument Prepared By:
Michael H. Harrell
Abstract & Title Services, Inc.
283 NW Cole Terrace
Lake City, Florida 32055
ATS# 16961

GENERAL WARRANTY DEED

Individual to Individual (or Corporation/LLC)

This Warranty Deed made this 23rd day of January, 2008 by

Carlos Enrique Ruiz, and his wife, Ruth Izules Ruiz

hereinafter called the Grantor, to

Inst:200812001499 Date:1/24/2008 Time:2:08 PM
Doc Stamp-Deed:154.00
✓ DC, P. DeWitt Cason, Columbia County Page 1 of 1

Richard Keen

whose post office address is 1256 SW CR 240, Lake City, FL 32025, hereinafter called the Grantee.

(Wherever used herein the terms "Grantor" and "Grantee" include all the parties to this instrument and the heirs, legal representatives and assigns of Individuals, and the successors and assigns of Corporation.)

The Grantor, for and in consideration of the sum of \$10.00 and other valuable considerations, receipt whereof is hereby acknowledged, hereby grants, bargains, sells, unto the Grantee all that certain land, situate in Columbia County, Florida, viz: TAX ID: R08359-049 :

Lot 9 of Country Creek, a subdivision according to the plat thereof according to the plat thereof recorded in Plat Book 4, Page 81, of the Public Records of Columbia County, Florida.

Together with all the tenements, hereditaments, and appurtenances thereto belonging or in anyways appertaining.

To have and to hold, the same in fee simple forever.

And the Grantor hereby covenants with said Grantee that the Grantor is lawfully seized of said land in fee simple; that the Grantor has good right and lawful authority to sell and convey said land, and hereby warrants the title to said land and will defend the same against the lawful claims of all persons whomsoever; and that said land is free of all encumbrances except taxes accruing subsequent to .

In witness whereof, the said Grantor has signed and sealed these presents the day and year first above written.

Cheryl Beaty
WITNESS

Printed Name: Cheryl Beaty

Ruth Izules Ruiz
WITNESS

Printed Name: Doris M Drake


Carlos Enrique Ruiz
Carlos Enrique Ruiz

Ruth Izules Ruiz
Ruth Izules Ruiz

State of Florida
County of Columbia

I hereby certify that on this 23rd day of January, 2008, before me, an officer duly authorized to administer oaths and take acknowledgements, personally appeared Carlos Enrique Ruiz, and his wife, Ruth Izules Ruiz, who is personally known to me or produced a D.C. for identification, and known to me to be the person described in and who executed the foregoing instrument, who acknowledged before me that he/she/they executed the same, and an oath was not taken.

(SEAL)



[Signature]
NOTARY PUBLIC

My Commission Expires:

08-6093

PART II - SITEPLAN

A hand-drawn site plan of a property. The plan shows a large rectangular area with a diagonal line on the left side. Dimensions are given in feet: 155' along the top, 16' along the left diagonal, 55' along the bottom-left horizontal line, 60' along the bottom-right horizontal line, and 145' along the right vertical line. A north arrow points to the right, labeled 'NORTH'. A 'SLOPE' arrow points upwards and to the right. A 'WATER DITCH' is shown at the bottom right, with an arrow pointing left towards the property. A 'S E BREAM' is indicated at the bottom. The property is divided into several sections. A central section is labeled '61 1170 SQ' and '26'. To its right is a section labeled 'GAR' and '15'. Below the central section is a section labeled 'DRIVE' and '30'. To the left of the central section is a section labeled '30'. A 'BM' (benchmark) is marked near the top left. A 'SLOPE' arrow points upwards and to the right. A 'WATER DITCH' is shown at the bottom right, with an arrow pointing left towards the property. A 'S E BREAM' is indicated at the bottom.

Site Plan submitted by: Robert D. [Signature] **MASTER CONTRACTOR**
 Plan Approved ☒ Not Approved ☐ Date 1/23/08
 By Mar A. [Signature] Columbia County Health Department

Page 2 of 4


STATE OF FLORIDA
DEPARTMENT OF HEALTH
APPLICATION FOR ONSITE SEWAGE DISPOSAL SYSTEM CONSTRUCTION PERMIT

Permit Application Number _____

----- PART II - SITEPLAN -----

Scale: 1 inch = 50 feet.

(St. 9 Country Creek)



Notes: _____

Site Plan submitted by: Rock D F

Plan Approved _____ Not Approved _____

By _____ Date _____

MASTER CONTRACTOR

County Health Department

ALL CHANGES MUST BE APPROVED BY THE COUNTY HEALTH DEPARTMENT

DH 4016, 10/98 (Replaces HR8-H Form 4016 which may be used)
(Stock Number: 5744-002-4016-6)

Page 2 of 4

COLUMBIA COUNTY 9-1-1 ADDRESSING / GIS DEPARTMENT

P. O. Box 1787, Lake City, FL 32056-1787

Telephone: (386) 758-1125 * Fax: (386) 758-1365 * E-mail: ron_croft@columbiacountyfla.com

ADDRESS ASSIGNMENT DATA

The Columbia County Board of County Commissioners has passed Ordinance 2001-9, which provides for a uniform numbering system. A copy of this ordinance is available in the Clerk of Court records, located in the courthouse. This new numbering system will increase the efficiency of POLICE, FIRE AND EMERGENCY MEDICAL vehicles responding to calls within Columbia County by immediately identifying the location of the caller.

Residential or Other Structure on Parcel Number:

15-4S-17-08359-049 (LOT 9 COUNTRY CREEK S/D)

Address Assignments:

285 SE BREAM LOOP, LAKE CITY, FL, 32025

Any questions concerning this information should be referred to the Columbia County 9-1-1 Addressing / GIS Department at the address or telephone number above.

FLORIDA ENERGY EFFICIENCY CODE FOR BUILDING CONSTRUCTION

Florida Department of Community Affairs Residential Whole Building Performance Method A

Project Name: 801221KeenRichard Address: Lot: 9, Sub: Country Creek E, Plat: City, State: , FL Owner: Spec House Climate Zone: North	Builder: Permitting Office: Columbia Permit Number: 27113 Jurisdiction Number: 221000
-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------

<ol style="list-style-type: none"> 1. New construction or existing New <input type="checkbox"/> 2. Single family or multi-family Single family <input type="checkbox"/> 3. Number of units, if multi-family 1 <input type="checkbox"/> 4. Number of Bedrooms 3 <input type="checkbox"/> 5. Is this a worst case? Yes <input type="checkbox"/> 6. Conditioned floor area (ft²) 1170 ft² <input type="checkbox"/> 7. Glass type¹ and area: (Label reqd. by 13-104.4.5 if not default) <table style="width: 100%;"> <tr> <td style="width: 30%;">a. U-factor:</td> <td style="width: 30%;">Description</td> <td style="width: 40%;">Area</td> </tr> <tr> <td>(or Single or Double DEFAULT)</td> <td>7a. (Dble Default)</td> <td>95.0 ft² <input type="checkbox"/></td> </tr> <tr> <td>b. SHGC:</td> <td>7b. (Clear)</td> <td>95.0 ft² <input type="checkbox"/></td> </tr> <tr> <td>(or Clear or Tint DEFAULT)</td> <td></td> <td></td> </tr> </table> 8. Floor types <table style="width: 100%;"> <tr> <td style="width: 30%;">a. Slab-On-Grade Edge Insulation</td> <td style="width: 70%;">R=0.0, 142.0(p) ft <input type="checkbox"/></td> </tr> <tr> <td>b. N/A</td> <td><input type="checkbox"/></td> </tr> <tr> <td>c. N/A</td> <td><input type="checkbox"/></td> </tr> </table> 9. Wall types <table style="width: 100%;"> <tr> <td style="width: 30%;">a. Frame, Wood, Exterior</td> <td style="width: 70%;">R=13.0, 825.0 ft² <input type="checkbox"/></td> </tr> <tr> <td>b. Frame, Wood, Adjacent</td> <td>R=13.0, 156.0 ft² <input type="checkbox"/></td> </tr> <tr> <td>c. N/A</td> <td><input type="checkbox"/></td> </tr> <tr> <td>d. N/A</td> <td><input type="checkbox"/></td> </tr> <tr> <td>e. N/A</td> <td><input type="checkbox"/></td> </tr> </table> 10. Ceiling types <table style="width: 100%;"> <tr> <td style="width: 30%;">a. Under Attic</td> <td style="width: 70%;">R=30.0, 1204.0 ft² <input type="checkbox"/></td> </tr> <tr> <td>b. N/A</td> <td><input type="checkbox"/></td> </tr> <tr> <td>c. N/A</td> <td><input type="checkbox"/></td> </tr> </table> 11. Ducts <table style="width: 100%;"> <tr> <td style="width: 30%;">a. Sup: Unc. Ret: Unc. AH: Interior</td> <td style="width: 70%;">Sup. R=6.0, 125.0 ft <input type="checkbox"/></td> </tr> <tr> <td>b. N/A</td> <td><input type="checkbox"/></td> </tr> </table> 	a. U-factor:	Description	Area	(or Single or Double DEFAULT)	7a. (Dble Default)	95.0 ft² <input type="checkbox"/>	b. SHGC:	7b. (Clear)	95.0 ft² <input type="checkbox"/>	(or Clear or Tint DEFAULT)			a. Slab-On-Grade Edge Insulation	R=0.0, 142.0(p) ft <input type="checkbox"/>	b. N/A	<input type="checkbox"/>	c. N/A	<input type="checkbox"/>	a. Frame, Wood, Exterior	R=13.0, 825.0 ft² <input type="checkbox"/>	b. Frame, Wood, Adjacent	R=13.0, 156.0 ft² <input type="checkbox"/>	c. N/A	<input type="checkbox"/>	d. N/A	<input type="checkbox"/>	e. N/A	<input type="checkbox"/>	a. Under Attic	R=30.0, 1204.0 ft² <input type="checkbox"/>	b. N/A	<input type="checkbox"/>	c. N/A	<input type="checkbox"/>	a. Sup: Unc. Ret: Unc. AH: Interior	Sup. R=6.0, 125.0 ft <input type="checkbox"/>	b. N/A	<input type="checkbox"/>	<ol style="list-style-type: none"> 12. Cooling systems <table style="width: 100%;"> <tr> <td style="width: 30%;">a. Central Unit</td> <td style="width: 70%;">Cap: 24.0 kBtu/hr <input type="checkbox"/> SEER: 13.00 <input type="checkbox"/></td> </tr> <tr> <td>b. N/A</td> <td><input type="checkbox"/></td> </tr> <tr> <td>c. N/A</td> <td><input type="checkbox"/></td> </tr> </table> 13. Heating systems <table style="width: 100%;"> <tr> <td style="width: 30%;">a. Electric Heat Pump</td> <td style="width: 70%;">Cap: 24.0 kBtu/hr <input type="checkbox"/> HSPF: 7.90 <input type="checkbox"/></td> </tr> <tr> <td>b. N/A</td> <td><input type="checkbox"/></td> </tr> <tr> <td>c. N/A</td> <td><input type="checkbox"/></td> </tr> </table> 14. Hot water systems <table style="width: 100%;"> <tr> <td style="width: 30%;">a. Electric Resistance</td> <td style="width: 70%;">Cap: 40.0 gallons <input type="checkbox"/> EF: 0.93 <input type="checkbox"/></td> </tr> <tr> <td>b. N/A</td> <td><input type="checkbox"/></td> </tr> <tr> <td>c. Conservation credits (HR-Heat recovery, Solar DHP-Dedicated heat pump)</td> <td><input type="checkbox"/></td> </tr> </table> 15. HVAC credits (CF-Ceiling fan, CV-Cross ventilation, HF-Whole house fan, PT-Programmable Thermostat, MZ-C-Multizone cooling, MZ-H-Multizone heating) <input type="checkbox"/> 	a. Central Unit	Cap: 24.0 kBtu/hr <input type="checkbox"/> SEER: 13.00 <input type="checkbox"/>	b. N/A	<input type="checkbox"/>	c. N/A	<input type="checkbox"/>	a. Electric Heat Pump	Cap: 24.0 kBtu/hr <input type="checkbox"/> HSPF: 7.90 <input type="checkbox"/>	b. N/A	<input type="checkbox"/>	c. N/A	<input type="checkbox"/>	a. Electric Resistance	Cap: 40.0 gallons <input type="checkbox"/> EF: 0.93 <input type="checkbox"/>	b. N/A	<input type="checkbox"/>	c. Conservation credits (HR-Heat recovery, Solar DHP-Dedicated heat pump)	<input type="checkbox"/>
a. U-factor:	Description	Area																																																							
(or Single or Double DEFAULT)	7a. (Dble Default)	95.0 ft² <input type="checkbox"/>																																																							
b. SHGC:	7b. (Clear)	95.0 ft² <input type="checkbox"/>																																																							
(or Clear or Tint DEFAULT)																																																									
a. Slab-On-Grade Edge Insulation	R=0.0, 142.0(p) ft <input type="checkbox"/>																																																								
b. N/A	<input type="checkbox"/>																																																								
c. N/A	<input type="checkbox"/>																																																								
a. Frame, Wood, Exterior	R=13.0, 825.0 ft² <input type="checkbox"/>																																																								
b. Frame, Wood, Adjacent	R=13.0, 156.0 ft² <input type="checkbox"/>																																																								
c. N/A	<input type="checkbox"/>																																																								
d. N/A	<input type="checkbox"/>																																																								
e. N/A	<input type="checkbox"/>																																																								
a. Under Attic	R=30.0, 1204.0 ft² <input type="checkbox"/>																																																								
b. N/A	<input type="checkbox"/>																																																								
c. N/A	<input type="checkbox"/>																																																								
a. Sup: Unc. Ret: Unc. AH: Interior	Sup. R=6.0, 125.0 ft <input type="checkbox"/>																																																								
b. N/A	<input type="checkbox"/>																																																								
a. Central Unit	Cap: 24.0 kBtu/hr <input type="checkbox"/> SEER: 13.00 <input type="checkbox"/>																																																								
b. N/A	<input type="checkbox"/>																																																								
c. N/A	<input type="checkbox"/>																																																								
a. Electric Heat Pump	Cap: 24.0 kBtu/hr <input type="checkbox"/> HSPF: 7.90 <input type="checkbox"/>																																																								
b. N/A	<input type="checkbox"/>																																																								
c. N/A	<input type="checkbox"/>																																																								
a. Electric Resistance	Cap: 40.0 gallons <input type="checkbox"/> EF: 0.93 <input type="checkbox"/>																																																								
b. N/A	<input type="checkbox"/>																																																								
c. Conservation credits (HR-Heat recovery, Solar DHP-Dedicated heat pump)	<input type="checkbox"/>																																																								

Glass/Floor Area: 0.08

Total as-built points: 16788

Total base points: 20279

PASS

I hereby certify that the plans and specifications covered by this calculation are in compliance with the Florida Energy Code.

PREPARED BY: [Signature]

DATE: 1-23-08

I hereby certify that this building, as designed, is in compliance with the Florida Energy Code.

OWNER/AGENT: [Signature]

DATE: 1/28/08

Review of the plans and specifications covered by this calculation indicates compliance with the Florida Energy Code. Before construction is completed this building will be inspected for compliance with Section 553.908 Florida Statutes.

BUILDING OFFICIAL: _____

DATE: _____



¹ Predominant glass type. For actual glass type and areas, see Summer & Winter Glass output on pages 2&4.

SUMMER CALCULATIONS

Residential Whole Building Performance Method A - Details

ADDRESS: Lot: 9, Sub: Country Creek E, Plat: , , FL,

PERMIT #:

BASE				AS-BUILT						
GLASS TYPES										
.18 X Conditioned X BSPM = Points Floor Area				Type/SC	Overhang Ornt Len Hgt		Area X	SPM X	SOF = Points	
.18	1170.0	20.04	4220.4	Double, Clear	W	1.5 5.5	15.0	38.52	0.90	518.3
				Double, Clear	W	1.5 5.5	20.0	38.52	0.90	691.0
				Double, Clear	E	1.5 5.5	30.0	42.06	0.90	1131.0
				Double, Clear	E	8.0 5.5	30.0	42.06	0.44	553.3
				As-Built Total:			95.0			2893.5
WALL TYPES Area X BSPM = Points				Type	R-Value		Area X	SPM	= Points	
Adjacent	156.0	0.70	109.2	Frame, Wood, Exterior	13.0		825.0	1.50	1237.5	
Exterior	825.0	1.70	1402.5	Frame, Wood, Adjacent	13.0		156.0	0.60	93.6	
Base Total:				As-Built Total:			981.0			1331.1
DOOR TYPES Area X BSPM = Points				Type			Area X	SPM	= Points	
Adjacent	20.0	1.60	32.0	Exterior Insulated			20.0	4.10	82.0	
Exterior	40.0	4.10	164.0	Exterior Insulated			20.0	4.10	82.0	
				Adjacent Insulated			20.0	1.60	32.0	
Base Total:				As-Built Total:			60.0			196.0
CEILING TYPES Area X BSPM = Points				Type	R-Value		Area X	SPM X SCM	= Points	
Under Attic	1170.0	1.73	2024.1	Under Attic	30.0		1204.0	1.73 X 1.00	2082.9	
Base Total:				As-Built Total:			1204.0			2082.9
FLOOR TYPES Area X BSPM = Points				Type	R-Value		Area X	SPM	= Points	
Slab	142.0(p)	-37.0	-5254.0	Slab-On-Grade Edge Insulation	0.0		142.0(p)	-41.20	-5850.4	
Raised	0.0	0.00	0.0							
Base Total:				As-Built Total:			142.0			-5850.4
INFILTRATION Area X BSPM = Points							Area X	SPM	= Points	
	1170.0	10.21	11945.7				1170.0	10.21	11945.7	

SUMMER CALCULATIONS

Residential Whole Building Performance Method A - Details

ADDRESS: Lot: 9, Sub: Country Creek E, Plat: , , FL,

PERMIT #:

BASE				AS-BUILT						
Summer Base Points: 14643.9				Summer As-Built Points: 12598.9						
Total Summer Points	X System Multiplier	=	Cooling Points	Total Component (System - Points)	X Cap Ratio	X Duct Multiplier (DM x DSM x AHU)	X System Multiplier	X Credit Multiplier	=	Cooling Points
14643.9	0.4266		6247.1	(sys 1: Central Unit 24000 btuh ,SEER/EFF(13.0) Ducts:Unc(S),Unc(R),Int(AH),R6.0(INS) 12599	1.00	(1.09 x 1.147 x 0.91)	0.263	1.000		3763.2
				12598.9	1.00	1.138	0.263	1.000		3763.2

WINTER CALCULATIONS

Residential Whole Building Performance Method A - Details

ADDRESS: Lot: 9, Sub: Country Creek E, Plat: , , FL,

PERMIT #:

BASE				AS-BUILT							
GLASS TYPES											
.18 X Conditioned X BWPM = Points Floor Area				Type/SC	Overhang Ornt Len Hgt		Area X WPM X WOF = Points				
.18	1170.0	12.74	2683.0	Double, Clear	W	1.5	5.5	15.0	20.73	1.03	319.7
				Double, Clear	W	1.5	5.5	20.0	20.73	1.03	426.2
				Double, Clear	E	1.5	5.5	30.0	18.79	1.04	587.1
				Double, Clear	E	8.0	5.5	30.0	18.79	1.38	779.3
As-Built Total:								95.0	2112.3		
WALL TYPES				Area X BWPM = Points		Type	R-Value	Area X WPM = Points			
Adjacent	156.0	3.60	561.6	Frame, Wood, Exterior		13.0	825.0	3.40	2805.0		
Exterior	825.0	3.70	3052.5	Frame, Wood, Adjacent		13.0	156.0	3.30	514.8		
Base Total:				981.0		3614.1		As-Built Total:		981.0 3319.8	
DOOR TYPES				Area X BWPM = Points		Type	Area X WPM = Points				
Adjacent	20.0	8.00	160.0	Exterior Insulated			20.0	8.40	168.0		
Exterior	40.0	8.40	336.0	Exterior Insulated			20.0	8.40	168.0		
				Adjacent Insulated			20.0	8.00	160.0		
Base Total:				60.0		496.0		As-Built Total:		60.0 496.0	
CEILING TYPES				Area X BWPM = Points		Type	R-Value	Area X WPM X WCM = Points			
Under Attic	1170.0	2.05	2398.5	Under Attic		30.0	1204.0	2.05 X 1.00	2468.2		
Base Total:				1170.0		2398.5		As-Built Total:		1204.0 2468.2	
FLOOR TYPES				Area X BWPM = Points		Type	R-Value	Area X WPM = Points			
Slab	142.0(p)	8.9	1263.8	Slab-On-Grade Edge Insulation		0.0	142.0(p)	18.80	2669.6		
Raised	0.0	0.00	0.0								
Base Total:				1263.8		As-Built Total:		142.0		2669.6	
INFILTRATION				Area X BWPM = Points		Area X WPM = Points					
1170.0 -0.59 -690.3						1170.0 -0.59 -690.3					

WINTER CALCULATIONS

Residential Whole Building Performance Method A - Details

ADDRESS: Lot: 9, Sub: Country Creek E, Plat: , , FL,

PERMIT #:

BASE				AS-BUILT						
Winter Base Points:		9765.1		Winter As-Built Points:				10375.6		
Total Winter Points	X System Multiplier	= Heating Points		Total Component (System - Points)	X Cap Ratio	X Duct Multiplier (DM x DSM x AHU)	X System Multiplier	X Credit Multiplier	= Heating Points	
9765.1	0.6274	6126.7		(sys 1: Electric Heat Pump 24000 btuh ,EFF(7.9) Ducts:Unc(S),Unc(R),Int(AH),R6.0 10375.6 1.000 (1.069 x 1.169 x 0.93) 0.432 1.000 5204.9 10375.6 1.00 1.162 0.432 1.000 5204.9						

WATER HEATING & CODE COMPLIANCE STATUS

Residential Whole Building Performance Method A - Details

ADDRESS: Lot: 9, Sub: Country Creek E, Plat: , , FL,

PERMIT #:

BASE					AS-BUILT					
WATER HEATING										
Number of Bedrooms	X	Multiplier	=	Total	Tank Volume	EF	Number of Bedrooms	X	Tank X Ratio	Multiplier X Credit = Total Multiplier
3		2635.00		7905.0	40.0	0.93	3		1.00	2606.67
					As-Built Total:					7820.0

CODE COMPLIANCE STATUS									
BASE					AS-BUILT				
Cooling Points	+	Heating Points	+	Hot Water Points = Total Points	Cooling Points	+	Heating Points	+	Hot Water Points = Total Points
6247		6127		7905 20279	3763		5205		7820 16788

Code Compliance Checklist

Residential Whole Building Performance Method A - Details

ADDRESS: Lot: 9, Sub: Country Creek E, Plat: , , FL,

PERMIT #:

6A-21 INFILTRATION REDUCTION COMPLIANCE CHECKLIST

COMPONENTS	SECTION	REQUIREMENTS FOR EACH PRACTICE	CHECK
Exterior Windows & Doors	606.1.ABC.1.1	Maximum: .3 cfm/sq.ft. window area; .5 cfm/sq.ft. door area.	
Exterior & Adjacent Walls	606.1.ABC.1.2.1	Caulk, gasket, weatherstrip or seal between: windows/doors & frames, surrounding wall; foundation & wall sole or sill plate; joints between exterior wall panels at corners; utility penetrations; between wall panels & top/bottom plates; between walls and floor. EXCEPTION: Frame walls where a continuous infiltration barrier is installed that extends from, and is sealed to, the foundation to the top plate.	
Floors	606.1.ABC.1.2.2	Penetrations/openings >1/8" sealed unless backed by truss or joint members. EXCEPTION: Frame floors where a continuous infiltration barrier is installed that is sealed to the perimeter, penetrations and seams.	
Ceilings	606.1.ABC.1.2.3	Between walls & ceilings; penetrations of ceiling plane of top floor; around shafts, chases, soffits, chimneys, cabinets sealed to continuous air barrier; gaps in gyp board & top plate; attic access. EXCEPTION: Frame ceilings where a continuous infiltration barrier is installed that is sealed at the perimeter, at penetrations and seams.	
Recessed Lighting Fixtures	606.1.ABC.1.2.4	Type IC rated with no penetrations, sealed; or Type IC or non-IC rated, installed inside a sealed box with 1/2" clearance & 3" from insulation; or Type IC rated with < 2.0 cfm from conditioned space, tested.	
Multi-story Houses	606.1.ABC.1.2.5	Air barrier on perimeter of floor cavity between floors.	
Additional Infiltration reqts	606.1.ABC.1.3	Exhaust fans vented to outdoors, dampers; combustion space heaters comply with NFPA, have combustion air.	

6A-22 OTHER PRESCRIPTIVE MEASURES (must be met or exceeded by all residences.)

COMPONENTS	SECTION	REQUIREMENTS	CHECK
Water Heaters	612.1	Comply with efficiency requirements in Table 612.1.ABC.3.2. Switch or clearly marked circuit breaker (electric) or cutoff (gas) must be provided. External or built-in heat trap required.	
Swimming Pools & Spas	612.1	Spas & heated pools must have covers (except solar heated). Non-commercial pools must have a pump timer. Gas spa & pool heaters must have a minimum thermal efficiency of 78%.	
Shower heads	612.1	Water flow must be restricted to no more than 2.5 gallons per minute at 80 PSIG.	
Air Distribution Systems	610.1	All ducts, fittings, mechanical equipment and plenum chambers shall be mechanically attached, sealed, insulated, and installed in accordance with the criteria of Section 610. Ducts in unconditioned attics: R-6 min. insulation.	
HVAC Controls	607.1	Separate readily accessible manual or automatic thermostat for each system.	
Insulation	604.1, 602.1	Ceilings-Min. R-19. Common walls-Frame R-11 or CBS R-3 both sides. Common ceiling & floors R-11.	

ENERGY PERFORMANCE LEVEL (EPL) DISPLAY CARD

ESTIMATED ENERGY PERFORMANCE SCORE* = 86.5

The higher the score, the more efficient the home.

Spec House, Lot: 9, Sub: Country Creek E, Plat: , , FL,

1. New construction or existing	New	___	12. Cooling systems	
2. Single family or multi-family	Single family	___	a. Central Unit	Cap: 24.0 kBtu/hr
3. Number of units, if multi-family	1	___		SEER: 13.00
4. Number of Bedrooms	3	___	b. N/A	___
5. Is this a worst case?	Yes	___	c. N/A	___
6. Conditioned floor area (ft²)	1170 ft²	___		___
7. Glass type ¹ and area: (Label reqd. by 13-104.4.5 if not default)		___	13. Heating systems	
a. U-factor:	Description Area	___	a. Electric Heat Pump	Cap: 24.0 kBtu/hr
(or Single or Double DEFAULT)	7a. (Dble Default) 95.0 ft²	___		HSPF: 7.90
b. SHGC:		___	b. N/A	___
(or Clear or Tint DEFAULT)	7b. (Clear) 95.0 ft²	___	c. N/A	___
8. Floor types		___	14. Hot water systems	
a. Slab-On-Grade Edge Insulation	R=0.0, 142.0(p) ft	___	a. Electric Resistance	Cap: 40.0 gallons
b. N/A	___	___		EF: 0.93
c. N/A	___	___	b. N/A	___
9. Wall types		___	c. Conservation credits	___
a. Frame, Wood, Exterior	R=13.0, 825.0 ft²	___	(HR-Heat recovery, Solar	___
b. Frame, Wood, Adjacent	R=13.0, 156.0 ft²	___	DHP-Dedicated heat pump)	___
c. N/A	___	___	15. HVAC credits	___
d. N/A	___	___	(CF-Ceiling fan, CV-Cross ventilation,	___
e. N/A	___	___	HF-Whole house fan,	___
10. Ceiling types		___	PT-Programmable Thermostat,	___
a. Under Attic	R=30.0, 1204.0 ft²	___	MZ-C-Multizone cooling,	___
b. N/A	___	___	MZ-H-Multizone heating)	___
c. N/A	___	___		___
11. Ducts		___		___
a. Sup: Unc. Ret: Unc. AH: Interior	Sup. R=6.0, 125.0 ft	___		___
b. N/A	___	___		___

I certify that this home has complied with the Florida Energy Efficiency Code For Building Construction through the above energy saving features which will be installed (or exceeded) in this home before final inspection. Otherwise, a new EPL Display Card will be completed based on installed Code compliant features.

Builder Signature: [Signature] Date: 1/28/08

Address of New Home: 285 SE Bream Loop City/FL Zip: Lake City FL 32025



*NOTE: The home's estimated energy performance score is only available through the FLA/RES computer program. This is not a Building Energy Rating. If your score is 80 or greater (or 86 for a US EPA/DOE EnergyStarTM designation), your home may qualify for energy efficiency mortgage (EEM) incentives if you obtain a Florida Energy Gauge Rating. Contact the Energy Gauge Hotline at 321/638-1492 or see the Energy Gauge web site at www.fsec.ucf.edu for information and a list of certified Raters. For information about Florida's Energy Efficiency Code For Building Construction, contact the Department of Community Affairs at 850/487-1824.

¹ Predominant glass type. For actual glass type and areas, see Summer & Winter Glass output on pages 2&4.
EnergyGauge® (Version: FLR2PB v4.1)

Columbia County Building Department Culvert Permit

Culvert Permit No.
000001623

DATE 06/24/2008 PARCEL ID # 15-4S-17-08359-049

APPLICANT RICHARD J. KEEN

PHONE 386.623.4629

ADDRESS 650 SW MAIN BLVD

LAKE CITY

FL 32025

OWNER RICHARD KEEN

PHONE 386.623.4629

ADDRESS 285 SE BREAM LOOP

LAKE CITY

FL 32025

CONTRACTOR JAMES H. JOHNSTON

PHONE 386.365.5999


LOCATION OF PROPERTY 41-S TO C-252, TL TO PEBBLE CREEK, TL TO BREAM LOOP, TL

5TH PLACE ON L.

SUBDIVISION/LOT/BLOCK/PHASE/UNIT COUNTRY CREEK

9

SIGNATURE



INSTALLATION REQUIREMENTS

☒ X

Culvert size will be 18 inches in diameter with a total length of 32 feet, leaving 24 feet of driving surface. Both ends will be mitered 4 foot with a 4 : 1 slope and poured with a 4 inch thick reinforced concrete slab.

INSTALLATION NOTE: Turnouts will be required as follows:

- a) a majority of the current and existing driveway turnouts are paved, or;
- b) the driveway to be served will be paved or formed with concrete.

Turnouts shall be concrete or paved a minimum of 12 feet wide or the width of the concrete or paved driveway, whichever is greater. The width shall conform to the current and existing paved or concreted turnouts.

☐

Culvert installation shall conform to the approved site plan standards.

☐

Department of Transportation Permit installation approved standards.

☐

Other _____

ALL PROPER SAFETY REQUIREMENTS SHOULD BE FOLLOWED
DURING THE INSTALLATION OF THE CULVERT.

135 NE Hernando Ave., Suite B-21

Lake City, FL 32055

Phone: 386-758-1008 Fax: 386-758-2160

Amount Paid 25.00



27113

NOTICE OF COMMENCEMENT

Tax Parcel Identification Number 15-45-17-08359-049

County Clerk's Office Stamp or Seal

THE UNDERSIGNED hereby gives notice that improvements will be made to certain real property, and in accordance with Section 713.13 of the Florida Statutes, the following information is provided in this NOTICE OF COMMENCEMENT.

1. Description of property (legal description): Lot 9 Country Creek S/D
 a) Street (job) Address: 285 SE Bream Loop
2. General description of improvements: Build SFR
3. Owner Information
 a) Name and address: Richard Keen 1256 SW CR 240 Lake City FL 32025
 b) Name and address of fee simple titleholder (if other than owner) _____
 c) Interest in property: 100%
4. Contractor Information
 a) Name and address: James Johnston
 b) Telephone No.: 386-755-8585 Fax No. (Opt.) _____
5. Surety Information
 a) Name and address: N/A
 b) Amount of Bond: _____
 c) Telephone No.: _____ Fax No. (Opt.) _____
6. Lender
 a) Name and address: N/A
 b) Phone No.: _____
7. Identity of person within the State of Florida designated by owner upon whom notices or other documents may be served:
 a) Name and address: _____
 b) Telephone No.: _____ Fax No. (Opt.) _____
8. In addition to himself, owner designates the following person to receive a copy of the Lienor's Notice as provided in Section 713.13(l)(b), Florida Statutes:
 a) Name and address: _____
 b) Telephone No.: _____ Fax No. (Opt.) _____
9. Expiration date of Notice of Commencement (the expiration date is one year from the date of recording unless a different date is specified): _____

WARNING TO OWNER: ANY PAYMENTS MADE BY THE OWNER AFTER THE EXPIRATION OF THE NOTICE OF COMMENCEMENT ARE CONSIDERED IMPROPER PAYMENTS UNDER CHAPTER 713, PART I, SECTION 713.13, FLORIDA STATUTES, AND CAN RESULT IN YOUR PAYING TWICE FOR IMPROVEMENTS TO YOUR PROPERTY; A NOTICE OF COMMENCEMENT MUST BE RECORDED AND POSTED ON THE JOB SITE BEFORE THE FIRST INSPECTION. IF YOU INTEND TO OBTAIN FINANCING, CONSULT YOUR LENDER OR AN ATTORNEY BEFORE COMMENCING WORK OR RECORDING YOUR NOTICE OF COMMENCEMENT.

STATE OF FLORIDA
 COUNTY OF COLUMBIA


10. Richard Keen
 Signature of Owner or Owner's Authorized Office/Director/Partner/Manager
Richard Keen
 Print Name

The foregoing instrument was acknowledged before me, a Florida Notary, this 19th day of September, 2008, by:
Richard Keen as owner (type of authority, e.g. officer, trustee, attorney)

fact) for Richard Keen (name of party on behalf of whom instrument was executed).

Personally Known X OR Produced Identification _____ Type _____

Notary Signature Carey F. Chandler Notary Stamp or Seal:



---AND---

11. Verification pursuant to Section 92.525, Florida Statutes. Under penalties of perjury, I declare that I have read the foregoing and that the facts stated in it are true to the best of my knowledge and belief.

Richard Keen
 Signature of Natural Person Signing (in line #10 above.)

COLUMBIA COUNTY FLORIDA DEPARTMENT OF BUILDING AND ZONING INSPECTION

OCCUPANCY

COLUMBIA COUNTY, FLORIDA

Department of Building and Zoning Inspection

This Certificate of Occupancy is issued to the below named permit holder for the building and premises at the below named location, and certifies that the work has been completed in accordance with the Columbia County Building Code.

Parcel Number 15-4S-17-08359-049

Building permit No. 000027113

Use Classification SF/UTILITY

Fire: 70.62

Permit Holder JAMES H. JOHNSTON

Waste: 184.25

Owner of Building RICHARD KEEN

Total: 254.87

Location: 285 SE BREAM LOOP, LAKE CITY, FL

Date: 11/13/2008

Building Inspector

POST IN A CONSPICUOUS PLACE
(Business Places Only)



Residential System Sizing Calculation

Summary

Spec House

Project Title:
801221KeenRichard

Class 3 Rating
Registration No. 0
Climate: North


1/23/2008

Location for weather data: Gainesville - Defaults: Latitude(29) Altitude(152 ft.) Temp Range(M)			
Humidity data: Interior RH (50%) Outdoor wet bulb (77F) Humidity difference(54gr.)			
Winter design temperature	33 F	Summer design temperature	92 F
Winter setpoint	70 F	Summer setpoint	75 F
Winter temperature difference	37 F	Summer temperature difference	17 F
Total heating load calculation	20615 Btuh	Total cooling load calculation	15773 Btuh
Submitted heating capacity	% of calc Btuh	Submitted cooling capacity	% of calc Btuh
Total (Electric Heat Pump)	116.4 24000	Sensible (SHR = 0.75)	152.8 18000
Heat Pump + Auxiliary(0.0kW)	116.4 24000	Latent	150.2 6000
		Total (Electric Heat Pump)	152.2 24000

WINTER CALCULATIONS

Winter Heating Load (for 1170 sqft)


Load component		Load	
Window total	95 sqft	3058	Btuh
Wall total	981 sqft	3222	Btuh
Door total	60 sqft	777	Btuh
Ceiling total	1204 sqft	1419	Btuh
Floor total	142 sqft	6200	Btuh
Infiltration	147 cfm	5940	Btuh
Duct loss		0	Btuh
Subtotal		20615	Btuh
Ventilation	0 cfm	0	Btuh
TOTAL HEAT LOSS		20615	Btuh



SUMMER CALCULATIONS

Summer Cooling Load (for 1170 sqft)

Load component		Load	
Window total	95 sqft	4439	Btuh
Wall total	981 sqft	1956	Btuh
Door total	60 sqft	588	Btuh
Ceiling total	1204 sqft	1994	Btuh
Floor total		0	Btuh
Infiltration	76 cfm	1423	Btuh
Internal gain		1380	Btuh
Duct gain		0	Btuh
Sens. Ventilation	0 cfm	0	Btuh
Total sensible gain		11779	Btuh
Latent gain(ducts)		0	Btuh
Latent gain(infiltration)		2794	Btuh
Latent gain(ventilation)		0	Btuh
Latent gain(internal/occupants/other)		1200	Btuh
Total latent gain		3994	Btuh
TOTAL HEAT GAIN		15773	Btuh



For Florida residences only

EnergyGauge® System Sizing

PREPARED BY: *[Signature]*

DATE: 1-23-08

System Sizing Calculations - Winter

Residential Load - Whole House Component Details

Spec House
, FL

Project Title:
801221KeenRichard

Class 3 Rating
Registration No. 0
Climate: North

Reference City: Gainesville (Defaults) Winter Temperature Difference: 37.0 F
This calculation is for Worst Case. The house has been rotated 315 degrees.

1/23/2008

Component Loads for Whole House

Window	Panes/SHGC/Frame/U	Orientation	Area(sqft)	X	HTM=	Load
1	2, Clear, Metal, 0.87	NW	15.0		32.2	483 Btuh
2	2, Clear, Metal, 0.87	NW	20.0		32.2	644 Btuh
3	2, Clear, Metal, 0.87	SE	30.0		32.2	966 Btuh
4	2, Clear, Metal, 0.87	SE	30.0		32.2	966 Btuh
Window Total			95(sqft)			3058 Btuh
Walls	Type	R-Value	Area	X	HTM=	Load
1	Frame - Wood - Ext(0.09)	13.0	825		3.3	2709 Btuh
2	Frame - Wood - Adj(0.09)	13.0	156		3.3	512 Btuh
Wall Total			981			3222 Btuh
Doors	Type		Area	X	HTM=	Load
1	Insulated - Adjacent		20		12.9	259 Btuh
2	Insulated - Exterior		20		12.9	259 Btuh
3	Insulated - Exterior		20		12.9	259 Btuh
Door Total			60			777Btuh
Ceilings	Type/Color/Surface	R-Value	Area	X	HTM=	Load
1	Vented Attic/D/Shin)	30.0	1204		1.2	1419 Btuh
Ceiling Total			1204			1419Btuh
Floors	Type	R-Value	Size	X	HTM=	Load
1	Slab On Grade	0	142.0	ft(p)	43.7	6200 Btuh
Floor Total			142			6200 Btuh
Zone Envelope Subtotal:						14675 Btuh
Infiltration	Type	ACH X	Zone Volume	CFM=		
	Natural	0.94	9360	146.6		5940 Btuh
Ductload	Average sealed, R6.0, Supply(Attic), Return(Attic) (DLM of 0.00)					0 Btuh
Zone #1	Sensible Zone Subtotal					20615 Btuh

WHOLE HOUSE TOTALS

	Subtotal Sensible	20615 Btuh
	Ventilation Sensible	0 Btuh
	Total Btuh Loss	20615 Btuh

Manual J Winter Calculations

Residential Load - Component Details (continued)

Spec House

Project Title:
801221KeenRichard

Class 3 Rating
Registration No. 0
Climate: North

, FL

Key: Window types (SHGC - Shading coefficient of glass as SHGC numerical value or as clear
(Frame types - metal, wood or insulated metal)
(U - Window U-Factor or 'DEF' for default)
(HTM - ManualJ Heat Transfer Multiplier)

Key: Floor size (perimeter(p) for slab-on-grade or area for all other floor types)



For Florida residences only

System Sizing Calculations - Winter

Residential Load - Room by Room Component Details

Spec House

Project Title:
801221KeenRichard

Class 3 Rating
Registration No. 0
Climate: North

, FL

Reference City: Gainesville (Defaults) Winter Temperature Difference: 37.0 F

1/23/2008

This calculation is for Worst Case. The house has been rotated 315 degrees.

Component Loads for Zone #1: Main

Window	Panes/SHGC/Frame/U	Orientation	Area(sqft)	X	HTM=	Load
1	2, Clear, Metal, 0.87	NW	15.0		32.2	483 Btuh
2	2, Clear, Metal, 0.87	NW	20.0		32.2	644 Btuh
3	2, Clear, Metal, 0.87	SE	30.0		32.2	966 Btuh
4	2, Clear, Metal, 0.87	SE	30.0		32.2	966 Btuh
Window Total			95(sqft)			3058 Btuh
Walls	Type	R-Value	Area	X	HTM=	Load
1	Frame - Wood - Ext(0.09)	13.0	825		3.3	2709 Btuh
2	Frame - Wood - Adj(0.09)	13.0	156		3.3	512 Btuh
Wall Total			981			3222 Btuh
Doors	Type		Area	X	HTM=	Load
1	Insulated - Adjacent		20		12.9	259 Btuh
2	Insulated - Exterior		20		12.9	259 Btuh
3	Insulated - Exterior		20		12.9	259 Btuh
Door Total			60			777Btuh
Ceilings	Type/Color/Surface	R-Value	Area	X	HTM=	Load
1	Vented Attic/D/Shin)	30.0	1204		1.2	1419 Btuh
Ceiling Total			1204			1419Btuh
Floors	Type	R-Value	Size	X	HTM=	Load
1	Slab On Grade	0	142.0	ft(p)	43.7	6200 Btuh
Floor Total			142			6200 Btuh
Zone Envelope Subtotal:						14675 Btuh
Infiltration	Type	ACH X	Zone Volume	CFM=		
	Natural	0.94	9360	146.6		5940 Btuh
Ductload	Average sealed, R6.0, Supply(Attic), Return(Attic) (DLM of 0.00)					0 Btuh
Zone #1	Sensible Zone Subtotal					20615 Btuh

WHOLE HOUSE TOTALS

	Subtotal Sensible	20615 Btuh
	Ventilation Sensible	0 Btuh
	Total Btuh Loss	20615 Btuh

Manual J Winter Calculations

Residential Load - Component Details (continued)

Spec House

Project Title:
801221KeenRichard

Class 3 Rating
Registration No. 0
Climate: North

, FL

Key: Window types (SHGC - Shading coefficient of glass as SHGC numerical value or as clear
(Frame types - metal, wood or insulated metal)
(U - Window U-Factor or 'DEF' for default)
(HTM - ManualJ Heat Transfer Multiplier)

Key: Floor size (perimeter(p) for slab-on-grade or area for all other floor types)



For Florida residences only

System Sizing Calculations - Summer

Residential Load - Whole House Component Details

Spec House

Project Title:
801221KeenRichard

Class 3 Rating
Registration No. 0
Climate: North

, FL

Reference City: Gainesville (Defaults) Summer Temperature Difference: 17.0 F

1/23/2008

This calculation is for Worst Case. The house has been rotated 315 degrees.

Component Loads for Whole House

Window	Type*		Overhang		Window Area(sqft)			HTM		Load	
	Pn/SHGC/U/InSh/ExSh/IS	Ornt	Len	Hgt	Gross	Shaded	Unshaded	Shaded	Unshaded		
1	2, Clear, 0.87, None,N,N	NW	1.5ft.	5.5ft.	15.0	0.0	15.0	29	60	901	Btuh
2	2, Clear, 0.87, None,N,N	NW	1.5ft.	5.5ft.	20.0	0.0	20.0	29	60	1201	Btuh
3	2, Clear, 0.87, None,N,N	SE	1.5ft.	5.5ft.	30.0	12.1	17.9	29	63	1468	Btuh
4	2, Clear, 0.87, None,N,N	SE	8ft.	5.5ft.	30.0	30.0	0.0	29	63	869	Btuh
Window Total					95 (sqft)					4439 Btuh	
Walls	Type	R-Value/U-Value			Area(sqft)		HTM		Load		
1	Frame - Wood - Ext	13.0/0.09			825.0		2.1		1721 Btuh		
2	Frame - Wood - Adj	13.0/0.09			156.0		1.5		235 Btuh		
Wall Total					981 (sqft)				1956 Btuh		
Doors	Type				Area (sqft)		HTM		Load		
1	Insulated - Adjacent				20.0		9.8		196 Btuh		
2	Insulated - Exterior				20.0		9.8		196 Btuh		
3	Insulated - Exterior				20.0		9.8		196 Btuh		
Door Total					60 (sqft)				588 Btuh		
Ceilings	Type/Color/Surface	R-Value			Area(sqft)		HTM		Load		
1	Vented Attic/DarkShingle	30.0			1204.0		1.7		1994 Btuh		
Ceiling Total					1204 (sqft)				1994 Btuh		
Floors	Type	R-Value			Size		HTM		Load		
1	Slab On Grade	0.0			142 (ft(p))		0.0		0 Btuh		
Floor Total					142.0 (sqft)				0 Btuh		
	Zone Envelope Subtotal:									8977 Btuh	
Infiltration	Type	ACH			Volume(cuft)		CFM=		Load		
	SensibleNatural	0.49			9360		76.4		1423 Btuh		
Internal gain	Occupants			Btuh/occupant			Appliance		Load		
	6			X 230 +			0		1380 Btuh		
Duct load	Average sealed, R6.0, Supply(Attic), Return(Attic)							DGM = 0.00		0.0 Btuh	
	Sensible Zone Load									11779 Btuh	

Manual J Summer Calculations

Residential Load - Component Details (continued)

Spec House

Project Title:
801221KeenRichard

Class 3 Rating
Registration No. 0
Climate: North

1/23/2008

WHOLE HOUSE TOTALS

Whole House Totals for Cooling	Sensible Envelope Load All Zones	11779 Btuh
	Sensible Duct Load	0 Btuh
	Total Sensible Zone Loads	11779 Btuh
	Sensible ventilation	0 Btuh
	Blower	0 Btuh
	Total sensible gain	11779 Btuh
	Latent infiltration gain (for 54 gr. humidity difference)	2794 Btuh
	Latent ventilation gain	0 Btuh
	Latent duct gain	0 Btuh
	Latent occupant gain (6 people @ 200 Btuh per person)	1200 Btuh
	Latent other gain	0 Btuh
	Latent total gain	3994 Btuh
	TOTAL GAIN	15773 Btuh

*Key: Window types (Pn - Number of panes of glass)
 (SHGC - Shading coefficient of glass as SHGC numerical value or as clear or tint)
 (U - Window U-Factor or 'DEF' for default)
 (InSh - Interior shading device: none(N), Blinds(B), Draperies(D) or Roller Shades(R))
 (ExSh - Exterior shading device: none(N) or numerical value)
 (BS - Insect screen: none(N), Full(F) or Half(H))
 (Ornt - compass orientation)



For Florida residences only

System Sizing Calculations - Summer

Residential Load - Room by Room Component Details

Spec House

Project Title:
801221KeenRichard

Class 3 Rating
Registration No. 0
Climate: North

, FL

Reference City: Gainesville (Defaults) Summer Temperature Difference: 17.0 F
This calculation is for Worst Case. The house has been rotated 315 degrees.

1/23/2008

Component Loads for Zone #1: Main

Window	Type*		Overhang		Window Area(sqft)			HTM		Load	
	Pn/SHGC/U/InSh/ExSh/IS	Ornt	Len	Hgt	Gross	Shaded	Unshaded	Shaded	Unshaded		
1	2, Clear, 0.87, None,N,N	NW	1.5ft.	5.5ft.	15.0	0.0	15.0	29	60	901	Btuh
2	2, Clear, 0.87, None,N,N	NW	1.5ft.	5.5ft.	20.0	0.0	20.0	29	60	1201	Btuh
3	2, Clear, 0.87, None,N,N	SE	1.5ft.	5.5ft.	30.0	12.1	17.9	29	63	1468	Btuh
4	2, Clear, 0.87, None,N,N	SE	8ft.	5.5ft.	30.0	30.0	0.0	29	63	869	Btuh
Window Total					95 (sqft)					4439 Btuh	
Walls	Type	R-Value/U-Value			Area(sqft)		HTM		Load		
1	Frame - Wood - Ext	13.0/0.09			825.0		2.1		1721 Btuh		
2	Frame - Wood - Adj	13.0/0.09			156.0		1.5		235 Btuh		
Wall Total					981 (sqft)				1956 Btuh		
Doors	Type				Area (sqft)		HTM		Load		
1	Insulated - Adjacent				20.0		9.8		196 Btuh		
2	Insulated - Exterior				20.0		9.8		196 Btuh		
3	Insulated - Exterior				20.0		9.8		196 Btuh		
Door Total					60 (sqft)				588 Btuh		
Ceilings	Type/Color/Surface	R-Value			Area(sqft)		HTM		Load		
1.	Vented Attic/DarkShingle	30.0			1204.0		1.7		1994 Btuh		
Ceiling Total					1204 (sqft)				1994 Btuh		
Floors	Type	R-Value			Size		HTM		Load		
1	Slab On Grade	0.0			142 (ft(p))		0.0		0 Btuh		
Floor Total					142.0 (sqft)				0 Btuh		
	Zone Envelope Subtotal:									8977 Btuh	
Infiltration	Type	ACH			Volume(cuft)		CFM=		Load		
	SensibleNatural	0.49			9360		76.4		1423 Btuh		
Internal gain	Occupants			Btuh/occupant			Appliance		Load		
	6			X 230 +			0		1380 Btuh		
Duct load	Average sealed, R6.0, Supply(Attic), Return(Attic)							DGM = 0.00		0.0 Btuh	
	Sensible Zone Load									11779 Btuh	

Manual J Summer Calculations

Residential Load - Component Details (continued)

Spec House
, FL

Project Title:
801221KeenRichard

Class 3 Rating
Registration No. 0
Climate: North

1/23/2008

WHOLE HOUSE TOTALS

Whole House Totals for Cooling	Sensible Envelope Load All Zones	11779 Btuh
	Sensible Duct Load	0 Btuh
	Total Sensible Zone Loads	11779 Btuh
	Sensible ventilation	0 Btuh
	Blower	0 Btuh
	Total sensible gain	11779 Btuh
	Latent infiltration gain (for 54 gr. humidity difference)	2794 Btuh
	Latent ventilation gain	0 Btuh
	Latent duct gain	0 Btuh
	Latent occupant gain (6 people @ 200 Btuh per person)	1200 Btuh
	Latent other gain	0 Btuh
	Latent total gain	3994 Btuh
	TOTAL GAIN	15773 Btuh

*Key: Window types (Pn - Number of panes of glass)
 (SHGC - Shading coefficient of glass as SHGC numerical value or as clear or tint)
 (U - Window U-Factor or 'DEF' for default)
 (InSh - Interior shading device: none(N), Blinds(B), Draperies(D) or Roller Shades(R))
 (ExSh - Exterior shading device: none(N) or numerical value)
 (BS - Insect screen: none(N), Full(F) or Half(H))
 (Ornt - compass orientation)



For Florida residences only

Residential Window Diversity

MidSummer

Spec House

Project Title:
801221KeenRichard


Class 3 Rating
Registration No. 0
Climate: North

1/23/2008

Weather data for: Gainesville - Defaults

Summer design temperature	92 F	Average window load for July	3793 Btuh
Summer setpoint	75 F	Peak window load for July	5021 Btuh
Summer temperature difference	17 F	Excursion limit(130% of Ave.)	4931 Btuh
Latitude	29 North	Window excursion (July)	89 Btuh

WINDOW Average and Peak Loads



Warning: This application has glass areas that produce relatively large heat gains for part of the day. Variable air volume devices may be required to overcome spikes in solar gain for one or more rooms. A zoned system may be required or some rooms may require zone control.

EnergyGauge® System Sizing for Florida residences only

PREPARED BY: *[Signature]*

DATE: *1-23-08*

EnergyGauge® FLR2PB v4.1



Location: Lot 9 Country Creek Project Name: Keen Job

As required by Florida Statute 553.842 and Florida Administrative Code 9B-72, please provide the information and the product approval number(s) on the building components listed below if they will be utilized on the construction project which you are applying for a building permit on or after April 1, 2004. We recommend you contact your local product supplier should you not know the product approval number for any of the applicable listed products. More information about statewide product approval can be obtained at www.floridabuilding.org

Category/Subcategory	Manufacturer	Product Description	Approval Number
A. EXTERIOR DOORS	Masonite International	Metal Ext. Doors	FL 4242-
1. Swinging			
2. Sliding			
3. Sectional			
4. Roll up			
5. Automatic			
6. Other			
B. WINDOWS			
1. Single hung	mI Windows	Single Hung Windows	FL 5108
2. Horizontal Slider			FL 5451
3. Casement			
4. Double Hung			
5. Fixed			FL 5418
6. Awning			
7. Pass-through			
8. Projected			
9. Mullion			
10. Wind Breaker			
11. Dual Action			
12. Other			
C. PANEL WALL			
1. Siding	James Hardie Building Prod.	Masonry Siding	FL 889-R
2. Soffits	KayCan LTD	Aluminum Soffit	FL 4899
3. EIFS			
4. Storefronts			
5. Curtain walls			
6. Wall louver			
7. Glass block			
8. Membrane			FL 3820-R1
9. Greenhouse			
10. Other			
D. ROOFING PRODUCTS			
1. Asphalt Shingles	EIK Corp.	Arch. Asphalt Shingles	FL 586-R2
2. Underlayments	Woodland Ind.	30* Felt	FL 1814-R1
3. Roofing Fasteners			
4. Non-structural Metal Rf			
5. Built-Up Roofing			FL 7518.1
6. Modified Bitumen			
7. Single Ply Roofing Sys			
8. Roofing Tiles			
9. Roofing Insulation			
10. Waterproofing			
11. Wood shingles /shakes			
12. Roofing Slate			

Subcategory (cont.)	Manufacturer	Product Description	Approval Number
Liquid Applied Roof Sys			
Cements-Adhesives - Coatings			FL 1960-R
15. Roof Tile Adhesive			
16. Spray Applied Polyurethane Roof			
17. Other			
E. SHUTTERS			
1. Accordion			
2. Bahama			
3. Storm Panels			
4. Colonial			
5. Roll-up			
6. Equipment			
7. Others			
F. SKYLIGHTS			
1. Skylight			FL 451-R
2. Other			
G. STRUCTURAL COMPONENTS			
1. Wood connector/anchor	Simpson Strong Tie	metal straps	FL 474-R1
2. Truss plates			
3. Engineered lumber	Georgia Pacific	Eng. Lumber	FL 1008-R2
4. Railing			
5. Coolers-freezers			
6. Concrete Admixtures			
7. Material			
8. Insulation Forms			
9. Plastics			
10. Deck-Roof			
11. Wall			
12. Sheds			
13. Other			
H. NEW EXTERIOR ENVELOPE PRODUCTS			
1.			
2.			

The products listed below did not demonstrate product approval at plan review. I understand that at the time of inspection of these products, the following information must be available to the inspector on the jobsite: 1) copy of the product approval, 2) the performance characteristics which the product was tested and certified to comply with, 3) copy of the applicable manufacturers installation requirements.

I understand these products may have to be removed if approval cannot be demonstrated during inspection

Contractor or Contractor's Authorized Agent Signature

Print Name

Date

Location

Permit # (FOR STAFF USE ONLY)

**COLUMBIA COUNTY BUILDING DEPARTMENT
RESIDENTIAL MINIMUM PLAN REQUIREMENTS AND CHECKLIST
FOR THE FLORIDA RESIDENTIAL BUILDING CODE 2004 with 2005 & 2006
Supplements and One (1) and Two (2) Family Dwellings**

ALL REQUIREMENTS ARE SUBJECT TO CHANGE

ALL BUILDING PLANS MUST INDICATE COMPLIANCE with the Current FLORIDA BUILDING CODES and the Current FLORIDA RESIDENTIAL CODE. ALL PLANS OR DRAWING SHALL PROVIDED CALCULATIONS AND DETAILS THAT HAVE THE SEAL AND SIGNATURE OF A CERTIFIED ARCHITECT OR ENGINEER REGISTERED IN THE STATE OF FLORIDA, OR ALTERNATE METHODOLOGIES, APPROVED BY THE STATE OF FLORIDA BUILDING COMMISSION FOR ONE- AND-TWO FAMILY DWELLINGS.

FOR DESIGN PURPOSES THE FOLLOWING BASIC WIND SPEEDS ARE PER FIGURE R301.2(4) of the Residential Code (Florida Wind speed map) SHALL BE USED.

WIND SPEED LINE SHALL BE DEFINED AS FOLLOWS: THE CENTERLINE OF INTERSTATE 75.

1. ALL BUILDINGS CONSTRUCTED EAST OF SAID LINE SHALL BE ----- 100 MPH
2. ALL BUILDINGS CONSTRUCTED WEST OF SAID LINE SHALL BE -----110 MPH
3. NO AREA IN COLUMBIA COUNTY IS IN A WIND BORNE DEBRIS REGION

GENERAL REQUIREMENTS:

- ✓ Two (2) complete sets of plans containing the following:
- ✓ All drawings must be clear, concise and drawn to scale, details that are not used shall be marked void
- ✓ Condition space (Sq. Ft.) and total (Sq. Ft.) under roof shall be shown on the plans.
- ✓ Designers name and signature shall be on all documents and a licensed architect or engineer, signature and official embossed seal shall be affixed to the plans and documents per FBC 106.1.

Site Plan information including:

- ✓ Dimensions of lot or parcel of land
- ✓ Dimensions of all building set backs
- ✓ Location of all other structures (include square footage of structures) on parcel, existing or proposed well and septic tank and all utility easements.
- ✓ Provide a full legal description of property.

Wind-load Engineering Summary, calculations and any details required:

- ✓ Plans or specifications must meet state compliance with FRC Chapter 3
- ✓ The following information must be shown as per section FRC
- ✓ Basic wind speed (3-second gust), miles per hour
- ✓ Wind importance factor and nature of occupancy
- ✓ Wind exposure – if more than one wind exposure is used, the wind exposure and applicable wind direction shall be indicated
- ✓ The applicable internal pressure coefficient, Components and Cladding The design wind pressure in terms of psf (kN/m²), to be used for the design of exterior component and cladding materials not specifiically designed by the registered design professional.

Elevations Drawing including:

- ✓ All side views of the structure
- ✓ Roof pitch
- ✓ Overhang dimensions and detail with attic ventilation
- Location, size and height above roof of chimneys
- Location and size of skylights with Florida Product Approval
- ✓ Number of stories
- ✓ e) Building height from the established grade to the roofs highest peak

Floor Plan including:

- ✓ Dimensioned area plan showing rooms, attached garage, breeze ways, covered porches, deck, balconies and raised floor surfaces located more than 30 inches above the floor or grade
- ✓ All exterior and interior shear walls indicated
- ✓ Shear wall opening shown (Windows, Doors and Garage doors)
- ✓ Emergency escape and rescue opening in each bedroom (net clear opening shown)
- Safety glazing of glass where needed
- Fireplaces types (gas appliance) (vented or non-vented) or wood burning with Hearth (see chapter 10 of FRC)
- Stairs with dimensions (width, tread and riser and total run) details of guardrails, Handrails (see FRC 311)
- ✓ Plans must show and identify accessibility of bathroom (see FRC 322)

All materials placed within opening or onto/into exterior shear walls, soffits or roofs shall have Florida product approval number and mfg. installation information submitted with the plans (see Florida product approval form)

Foundation Plans Per FRC 403:

- ✓ a) Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.
- ✓ b) All posts and/or column footing including size and reinforcing
- c) Any special support required by soil analysis such as piling.
- ✓ d) Assumed load-bearing value of soil _____ (psf)
- e) Location of horizontal and vertical steel, for foundation or walls (include # size and type)

CONCRETE SLAB ON GRADE Per FRC R506

- ✓ Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed)
- ✓ Show control joints, synthetic fiber reinforcement or welded wire fabric reinforcement and Supports

PROTECTION AGAINST TERMITES Per FRC 320:

- ✓ Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or submit other approved termite protection methods. Protection shall be provided by registered termiticides

Masonry Walls and Stem walls (load bearing & shear Walls) FRC Section R606

- Show all materials making up walls, wall height, and Block size, mortar type
 - Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement
- Metal frame shear wall and roof systems shall be designed, signed and sealed by Florida Prof. Engineer or Architect**

Floor Framing System: First and/or second story

- Floor truss package shall including layout and details, signed and sealed by Florida Registered Professional Engineer
- Show conventional floor joist type, size, span, spacing and attachment to load bearing walls, stem walls and/or piers
- Girder type, size and spacing to load bearing walls, stem wall and/or piers
- Attachment of joist to girder
- Wind load requirements where applicable
- Show required under-floor crawl space
- Show required amount of ventilation opening for under-floor spaces
- Show required covering of ventilation opening.
- Show the required access opening to access to under-floor spaces
- Show the sub-floor structural panel sheathing type, thickness and fastener schedule on the edges & intermediate of the areas structural panel sheathing
- Show Draft stopping, Fire caulking and Fire blocking
- Show fireproofing requirements for garages attached to living spaces, per FRC section R309
- Provide live and dead load rating of floor framing systems (psf).

WOOD WALL FRAMING CONSTRUCTION FRC CHAPTER 6

- ✓ Stud type, grade, size, wall height and oc spacing for all load bearing or shear walls.
- ✓ Fastener schedule for structural members per table R602.3 (1) are to be shown.
- ✓ Show wood structural panel's sheathing attachment to studs, joist, trusses, rafters and structural members, showing fastener schedule attachment on the edges & intermediate of the areas structural panel sheathing
- ✓ Show all required connectors with a max uplift rating and required number of connectors and oc spacing for continuous connection of structural walls to foundation and roof trusses or rafter systems.
- ✓ Show sizes, type, span lengths and required number of support jack studs, king studs for shear wall opening and girder or header per FRC Table R502.5 (1)
- ✓ Indicate where pressure treated wood will be placed.
- ✓ Show all wall structural panel sheathing, grade, thickness and show fastener schedule for structural panel sheathing edges & intermediate areas
- ✓ A detail showing gable truss bracing, wall balloon framing details or/ and wall hinge bracing detail

ROOF SYSTEMS:

- ✓ Truss design drawing shall meet section FRC R802.10 Wood trusses. Include a layout and truss details and be signed and sealed by Fl. Pro. Eng.
- ✓ Show types of connector's assemblies' and resistance uplift rating for all trusses and rafters
- Show gable ends with rake beams showing reinforcement or gable truss and wall bracing details
- ✓ Provide dead load rating of trusses

Conventional Roof Framing Layout Per FRC 802:

- Rafter and ridge beams sizes, span, species and spacing
- Connectors to wall assemblies' include assemblies' resistance to uplift rating.
- Valley framing and support details
- Provide dead load rating of rafter system.

ROOF SHEATHING FRC Table R602,3(2) FRC 803

- ✓ Include all materials which will make up the roof decking, identification of structural panel sheathing, grade, thickness and show fastener schedule for structural panel sheathing on the edges & intermediate areas

ROOF ASSEMBLIES FRC Chapter 9

- ✓ Include all materials which will make up the roof assemblies covering; with Florida Product Approval numbers for each component of the roof assemblies covering.

FCB Chapter 13 Florida Energy Efficiency Code for Building Construction

- ✓ Residential construction shall comply with this code by using the following compliance methods in the FBC Subchapter 13-6, Residential buildings compliance methods. Two of the required forms are to be submitted, showing dimensions condition area equal to the total condition living space area
- ✓ Show the insulation R value for the following areas of the structure: Attic space, Exterior wall cavity and Crawl space (if applicable)

HVAC information shown

- ✓ Manual J sizing equipment or equivalent computation
- ✓ Exhaust fans locations in bathrooms

Plumbing Fixture layout shown

- ✓ All fixtures waste water lines shall be shown on the foundation plan

Electrical layout shown including:

- ✓ Switches, outlets/receptacles, lighting and all required GFCI outlets identified
- ✓ Ceiling fans
- ✓ Smoke detectors
- ✓ Service panel, sub-panel, location(s) and total ampere ratings

- ✓ On the electrical plans identify the electrical service overcurrent protection device for the main electrical service. This device shall be installed on the exterior of structures to serve as a disconnecting means for the utility company electrical service. Conductors used from the exterior disconnecting means to a panel or sub panel shall have four-wire conductors, of which one conductor shall be used as an equipment ground. Indicate if the utility company service entrance cable will be of the overhead or underground type.
- ✓ Appliances and HVAC equipment and disconnects
- ✓ Arc Fault Circuits (AFCI) in bedrooms
- Notarized Disclosure Statement for Owner Builders
- Notice of Commencement Recorded (in the Columbia County Clerk Office) Notice Of Commencement is required to be filed with the building department Before Any Inspections Will Be Done.

Private Potable Water

- Size of pump motor
- Size of pressure tank
- Cycle stop valve if used

city water

THE FOLLOWING ITEMS MUST BE SUBMITTED WITH BUILDING PLANS

- ✓ Building Permit Application: A current Building Permit Application form is to be completed and submitted for all residential projects.
- ✓ Parcel Number: The parcel number (Tax ID number) from the Property Appraiser (386) 758-1084 is required. A copy of property deed is also requested.
- Environmental Health Permit or Sewer Tap Approval: A copy of the Environmental Health permit, existing septic approval or sewer tap approval is required before a building permit can be issued. (386) 758-1058 (Toilet facilities shall be provided for construction workers)
- City Approval: If the project is to be located within the city limits of the Town of Fort White, prior approval is required. The Town of Fort White approval letter is required to be submitted by the owner or contractor to this office when applying for a Building Permit. (386) 497-2321
- Flood Information: All projects within the Floodway of the Suwannee or Santa Fe Rivers shall require permitting through the Suwannee River Water Management District, before submitting application to this office. Any project located within a flood zone where the base flood elevation (100 year flood) has been established shall meet the requirements of Section 8.8 of the Columbia County Land Development Regulations. Any project located within a flood zone where the base flood elevation has not been established (Zone A) shall meet the requirements of Section 8.7 of the Columbia County Land Development Regulations. **CERTIFIED FINISHED FLOOR ELEVATIONS WILL BE REQUIRED ON ANY PROJECT WHERE THE BASE FLOOD ELEVATION (100 YEAR FLOOD) HAS BEEN ESTABLISHED.** A development permit will also be required. The permit cost is \$50.00.
- ✓ Driveway Connection: If the property does not have an existing access to a public road, then an application for a culvert permit (\$25.00) must be made. If the applicant feels that a culvert is not needed, they may apply for a culvert waiver (\$50.00). All culvert waivers are sent to the Columbia County Public Works Department for approval or denial.
- ✓ 911 Address: If the project is located in an area where the 911 address has been issued, then the proper Paper work from the 911 Addressing Departments must be submitted. (386) 758-1125

ALL REQUIRED INFORMATION IS TO BE SUBMITTED FOR REVIEW. NOTIFICATION WILL BE GIVEN WHEN THE APPLICATION AND PLANS ARE APPROVED AND READY TO PERMIT.



Project Information for: L266503

Builder: Richard Keen
Lot: 9
Subdivision: Country Creek
County: Columbia
Truss Count: 19
Design Program: MiTek 20/20 6.3
Building Code: FBC2004/TPI2002

Truss Design Load Information:

Gravity: **Wind:**

Roof (psf): 42.0 Wind Standard: ASCE 7-02 Wind Exposure: B
Floor (psf): N/A Wind Speed (mph): 110

Note: See the individual truss drawings for special loading conditions.

Contractor of Record, responsible for structural engineering:


James H. Johnston, III Florida Registered Residential Contractor License No. RR0066976
Address: RT. #15 Box 3693 Lake City, Florida 32024

Truss Design Engineer: Julius Lee, PE Florida P.E. License No. 34869

Address: 1109 Coastal Bay Blvd. Boynton Beach, FL 33435

Notes:

1. Determination as to the suitability of these truss components for the structure is the responsibility of the building designer/engineer of record, as defined in ANSI/TPI 1-2002 Section 2.2
2. The seal date shown on the individual truss component drawings must match the seal date on this index sheet.
3. The Truss Design Engineer's responsibility relative to this structure consists solely of the design of the individual truss components and does not include the design of any additional structural elements including but not limited to continuous lateral bracing elements in the web and chord planes. See Florida Administrative Code 61G15-31.003 sections 3 c) & 5 and Chapter 2 of the National Design Standard for Metal Plate Connected Wood Truss Construction ANSI/TPI 1-2002 for additional information on the responsibilities of the delegated "Truss Design Engineer". Builders FirstSource and Julius Lee, PE do not accept any additional delegations beyond the scope of work described in the referenced documents above.




No.	Drwg. #	Truss ID	Date
1	J1928307	CJ1	1/21/08
2	J1928308	CJ3	1/21/08
3	J1928309	CJ5	1/21/08
4	J1928310	EJ4	1/21/08
5	J1928311	EJ5	1/21/08
6	J1928312	EJ7	1/21/08
7	J1928313	HJ5	1/21/08
8	J1928314	HJ9	1/21/08
9	J1928315	T01	1/21/08
10	J1928316	T02	1/21/08
11	J1928317	T03	1/21/08
12	J1928318	T04	1/21/08
13	J1928319	T05	1/21/08
14	J1928320	T06	1/21/08
15	J1928321	T07	1/21/08
16	J1928322	T08	1/21/08
17	J1928323	T09	1/21/08
18	J1928324	T10	1/21/08
19	J1928325	T11	1/21/08

Job	Truss	Truss Type	Qty	Ply	J1928307
	CJ1	JACK	14	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:34 2008 Page 1



Scale: 1.5"=1'

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.28	Vert(LL)	-0.00	2	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.01	Vert(TL)	-0.00	2	>999	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.00	Horz(TL)	0.00	3	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
									Weight: 7 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 1-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 2=256/0-3-8, 4=5/Mechanical, 3=-90/Mechanical

Max Horz 2=87(load case 6)

Max Uplift 2=-286(load case 6), 4=-9(load case 4), 3=-90(load case 1)

Max Grav 2=256(load case 1), 4=14(load case 2), 3=127(load case 6)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-69/75

BOT CHORD 2-4=0/0

JOINT STRESS INDEX

2 = 0.14

NOTES

1) Wind: ASCE 7-02; 110mph (3-second gust); h=12ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS gable end zone and C-C Exterior(2) zone; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.

2) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

3) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi

4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 286 lb uplift at joint 2, 9 lb uplift at joint 4 and 90 lb uplift at joint 3.

Continued on page 2

Julius Lee
Truss Design Engineer
Florida PE No. 3-4888
1405 Coastal Bay Blvd
Boynton Beach, FL 33435

January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928307
	CJ1	JACK	14	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:34 2008 Page 2

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida PE No. 34888
1100 Coastal Bay Blvd
Boynton Beach, FL 33435

January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE


This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928308
	CJ3	JACK	14	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:35 2008 Page 1



Scale = 1:12.5

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.29	Vert(LL)	0.01	2-4	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.08	Vert(TL)	-0.01	2-4	>999	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.00	Horz(TL)	-0.00	3	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
									Weight: 13 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or
3-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc
bracing.

REACTIONS (lb/size) 3=31/Mechanical, 2=250/0-3-8, 4=14/Mechanical
Max Horz 2=132(load case 6)
Max Uplift 3=-28(load case 7), 2=-238(load case 6), 4=-27(load case 4)
Max Grav 3=31(load case 1), 2=250(load case 1), 4=42(load case 2)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-57/7
BOT CHORD 2-4=0/0

JOINT STRESS INDEX

2 = 0.13

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=12ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS gable end zone and C-C Exterior(2) zone; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- 2) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 28 lb uplift at joint 3, 238 lb uplift at joint 2 and 27 lb uplift at joint 4.

Continued on page 2

Julius Lee
Truss Design Engineer
Florida PE No. 3-4888
1100 Coastal Bay Blvd
Boynton Beach, FL 33435

January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928308
	CJ3	JACK	14	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:35 2008 Page 2

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida PE No. 34888
1406 Coastal Bay Blvd
Boynton Beach, FL 33436

January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE


This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928309
	CJ5	JACK	12	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:35 2008 Page 1



LOADING (psf)	SPACING	2'-0"	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.29	Vert(LL)	0.09	2-4	>663	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.24	Vert(TL)	-0.05	2-4	>999	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.00	Horz(TL)	-0.00	3	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
									Weight: 19 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 5'-0" oc purlins.
BOT CHORD Rigid ceiling directly applied or 10'-0" oc bracing.

REACTIONS (lb/size)

3=103/Mechanical, 2=295/0-3-8, 4=24/Mechanical
Max Horz 2=178(load case 6)
Max Uplift 3=-87(load case 6), 2=-260(load case 6), 4=-46(load case 4)
Max Grav 3=103(load case 1), 2=295(load case 1), 4=72(load case 2)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-88/36
BOT CHORD 2-4=0/0

JOINT STRESS INDEX

2 = 0.14

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=12ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS gable end zone and C-C Exterior(2) zone; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- 2) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 87 lb uplift at joint 3, 260 lb uplift at joint 2 and 46 lb uplift at joint 4.

Continued on page 2

Julius Lee
Truss Design Engineer
Florida PE No. 34888
1100 Coastal Bay Blvd
Boynton Beach, FL 33426

January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928309
	CJ5	JACK	12	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:35 2008 Page 2

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida FE No. 34859
1400 Coastal Bay Blvd
Boynton Beach, FL 33436

January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE


This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928310
	EJ4	JACK	1	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:36 2008 Page 1



LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.29	Vert(LL)	-0.01	2-4	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.10	Vert(TL)	-0.02	2-4	>999	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.00	Horz(TL)	-0.00	3	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
									Weight: 16 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or
3-10-8 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc
bracing.

REACTIONS (lb/size) 3=65/Mechanical, 2=267/0-3-8, 4=18/Mechanical
Max Horz 2=152(load case 6)
Max Uplift 3=-50(load case 6), 2=-198(load case 6)
Max Grav 3=65(load case 1), 2=267(load case 1), 4=55(load case 2)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-62/21
BOT CHORD 2-4=0/0

JOINT STRESS INDEX

2 = 0.13

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=12ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS gable end zone and C-C Exterior(2) zone; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- 2) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 50 lb uplift at joint 3 and 198 lb uplift at joint 2.

Continued on page 2

Julius Lee
Truss Design Engineer
Florida PE No. 34558
1409 Coastal Bay Blvd
Boynton Beach, FL 33435

January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITTEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928310
	EJ4	JACK	1	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:36 2008 Page 2

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida PE No. 34888
1100 Coastal Bay Blvd
Boynton Beach, FL 33435

January 21, 200



Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE


This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	Job Reference (optional)
	EJ5	MONO HIP	1	1	J1928311

Builders FirstSource, Lake City, FL 32055

6.300 s Apr 19 2006 MiTek Industries, Inc. Mon Jan 21 09:47:08 2008 Page 1



Scale: 1"=1'

Simpson HTU26

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.21	Vert(LL)	-0.04	1-5	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.62	Vert(TL)	-0.07	1-5	>832	240		
BCLL 10.0	Rep Stress Incr	NO	WB 0.65	Horz(TL)	0.00	4	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
									Weight: 27 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 6 SYP No.1D
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 5-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 1=1365/0-3-8, 4=1448/Mechanical
Max Horz 1=88(load case 5)
Max Uplift 1=-661(load case 5), 4=-742(load case 5)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=-890/393, 2-3=-0/0, 3-4=-37/28
BOT CHORD 1-5=-385/760, 4-5=-459/915
WEBS 2-5=-983/2035, 2-4=-2000/1004

JOINT STRESS INDEX

1 = 0.38, 2 = 0.88, 3 = 0.02, 4 = 0.65 and 5 = 0.66

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=12ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS gable end zone; Lumber DOL=1.60 plate grip DOL=1.60.
- 2) Provide adequate drainage to prevent water ponding.
- 3) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 661 lb uplift at joint 1 and 742 lb uplift at joint 4.

Julius Lee
Truss Design Engineer
Florida P.E. No. 3-1888
1100 Coastal Bay Blvd
Boynton Beach, FL 33435

January 21,2008

Continued on page 2

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928311
	EJ5	MONO HIP	1	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Apr 19 2006 MiTek Industries, Inc. Mon Jan 21 09:47:08 2008 Page 2

NOTES

6) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

1) Regular: Lumber Increase=1.25, Plate Increase=1.25

Uniform Loads (plf)

Vert: 1-2=-54, 2-3=-75(F=-21), 1-5=-517(F=-507), 4-5=-521(F=-511)

Concentrated Loads (lb)

Vert: 5=-98(F)

Julius Lee
Truss Design Engineer
Florida P.E. No. 34868
1400 Coastal Bay Blvd.
Boynton Beach, FL 33435

January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE


This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928312
	EJ7	MONO TRUSS	14	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Apr 19 2006 MiTek Industries, Inc. Mon Jan 21 09:43:19 2008 Page 1



LOADING (psf)	SPACING	2'-0'-0'	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.50	Vert(LL)	0.33	2-4	>250	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.45	Vert(TL)	-0.16	2-4	>501	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.00	Horz(TL)	-0.00	3	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
									Weight: 26 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 6'-0'-0' oc purlins.
BOT CHORD Rigid ceiling directly applied or 10'-0'-0' oc bracing.

REACTIONS

(lb/size) 3=154/Mechanical, 2=352/0-3-8, 4=45/Mechanical
Max Horz 2=161(load case 6)
Max Uplift 3=-94(load case 6), 2=-224(load case 6), 4=-65(load case 5)
Max Grav 3=154(load case 1), 2=352(load case 1), 4=94(load case 2)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-131/54
BOT CHORD 2-4=0/0

JOINT STRESS INDEX

2 = 0.58

NOTES

1) Wind: ASCE 7-02; 110mph (3-second gust); h=12ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS and C-C Exterior(2) zone; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.

2) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

3) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi

4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 94 lb uplift at joint 3, 224 lb uplift at joint 2 and 65 lb uplift at joint 4.

LOAD CASE(S) Standard

January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE


This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928313
	HJ5	JACK	1	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:37 2008 Page 1



LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.53	Vert(LL)	-0.04	2-4	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.18	Vert(TL)	-0.05	2-4	>999	240		
BCLL 10.0	* Rep Stress Incr	NO	WB 0.00	Horz(TL)	-0.00	3	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							Weight: 21 lb

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or
5-5-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc
bracing.

REACTIONS (lb/size) 3=75/Mechanical, 2=289/0-4-15, 4=22/Mechanical
Max Horz 2=120(load case 3)
Max Uplift 3=-43(load case 3), 2=-243(load case 3)
Max Grav 3=75(load case 1), 2=289(load case 1), 4=74(load case 2)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/50, 2-3=-40/14
BOT CHORD 2-4=0/0

JOINT STRESS INDEX

2 = 0.11

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=12ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS gable end zone; Lumber DOL=1.60 plate grip DOL=1.60.
- 2) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 43 lb uplift at joint 3 and 243 lb uplift at joint 2.
- 5) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

Continued on page 2

Julius Lee
Truss Design Engineer
Florida P.E. No. 34885
1406 Coastal Bay Blvd
Boynton Beach, FL 33435

January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928313
	HJ5	JACK	1	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:38 2008 Page 2

LOAD CASE(S) Standard

1) Regular: Lumber Increase=1.25, Plate Increase=1.25

Uniform Loads (plf)

Vert: 1-2=-54

Trapezoidal Loads (plf)

Vert: 2=-3(F=26, B=26)-to-3=-71(F=-8, B=-8), 2=-0(F=5, B=5)-to-4=-13(F=-2, B=-2)

Julius Lee
Truss Design Engineer
Florida P.E. No. 3-1889
1100 Coastal Bay Blvd
Boynton Beach, FL 33426

January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE


This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928314
	HJ9	MONO TRUSS	6	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:38 2008 Page 1



LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.61	Vert(LL)	0.10	6-7	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.40	Vert(TL)	-0.12	6-7	>986	240		
BCLL 10.0	* Rep Stress Incr	NO	WB 0.34	Horz(TL)	0.01	5	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)						Weight: 45 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 7-11-9 oc bracing.

REACTIONS (lb/size) 4=268/Mechanical, 2=456/0-5-11, 5=218/Mechanical
Max Horz 2=269(load case 3)
Max Uplift 4=-233(load case 3), 2=-401(load case 3), 5=-181(load case 3)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/50, 2-3=-647/363, 3-4=-105/65
BOT CHORD 2-7=-535/599, 6-7=-535/599, 5-6=0/0
WEBS 3-7=-94/190, 3-6=-624/557

JOINT STRESS INDEX

2 = 0.77, 3 = 0.22, 6 = 0.17 and 7 = 0.13

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=12ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS gable end zone; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60.
- 2) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 233 lb uplift at joint 4, 401 lb uplift at joint 2 and 181 lb uplift at joint 5.

Julius Lee
Truss Design Engineer
Florida P.E. No. 34889
1409 Coastal Bay Blvd
Boynton Beach, FL 33435

Continued on page 2

January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928314
	HJ9	MONO TRUSS	6	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:38 2008 Page 2

NOTES

5) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

1) Regular: Lumber Increase=1.25, Plate Increase=1.25

Uniform Loads (plf)

Vert: 1-2=-54

Trapezoidal Loads (plf)

Vert: 2=-3(F=25, B=25)-to-4=-134(F=-40, B=-40), 2=-0(F=5, B=5)-to-5=-25(F=-7, B=-7)

Julius Lee
Truss Design Engineer
Florida PE No. 31888
1100 Coastal Bay Blvd
Boynton Beach, FL 33426

January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928315
	T01	HIP	1	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:39 2008 Page 1




Plate Offsets (X,Y): [2:0-1-11,Edge], [6:0-1-11,Edge]

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.39	Vert(LL)	-0.11	8-10	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.60	Vert(TL)	-0.32	8-10	>809	240		
BCLL 10.0	* Rep Stress Incr	NO	WB 0.26	Horz(TL)	0.09	6	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
									Weight: 99 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 3-6-5 oc purlins.
BOT CHORD Rigid ceiling directly applied or 7-0-2 oc bracing.

REACTIONS (lb/size) 2=1521/0-3-8, 6=1521/0-3-8
Max Horz 2=-77(load case 6)
Max Uplift 2=-511(load case 5), 6=-511(load case 6)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-2708/817, 3-4=-2363/765, 4-5=-2363/765, 5-6=-2708/817, 6-7=0/47
BOT CHORD 2-10=-692/2332, 9-10=-808/2589, 8-9=-808/2589, 6-8=-658/2332
WEBS 3-10=-235/822, 4-10=-421/231, 4-8=-421/231, 5-8=-235/822

JOINT STRESS INDEX

2 = 0.67, 3 = 0.67, 4 = 0.35, 5 = 0.67, 6 = 0.67, 8 = 0.52, 9 = 0.84 and 10 = 0.52

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=12ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS; Lumber DOL=1.60 plate grip DOL=1.60.
- Provide adequate drainage to prevent water ponding.
- *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi

Continued on page 2

Julius Lee
Truss Design Engineer
Florida P.E. No. 3-48899
1105 Coastal Bay Blvd
Boynton Beach, FL 33435

January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928315
	T01	HIP	1	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:39 2008 Page 2

NOTES

- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 511 lb uplift at joint 2 and 511 lb uplift at joint 6.
- 7) Girder carries hip end with 7'-0" end setback.
- 8) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- 1) Regular: Lumber Increase=1.25, Plate Increase=1.25

Uniform Loads (plf)

Vert: 1-3=-54, 3-5=-118(F=-64), 5-7=-54, 2-10=-10, 8-10=-22(F=-12), 6-8=-10

Concentrated Loads (lb)

Vert: 10=-411(F) 8=-411(F)

Julius Lee
Truss Design Engineer
Florida PE No. 34889
1409 Coastal Bay Blvd
Boynton Beach, FL 33435

January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928316
	T02	HIP	1	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:40 2008 Page 1




Plate Offsets (X,Y): [2:0-8-0,0-0-10], [7:0-8-0,0-0-10]

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.29	Vert(LL)	-0.15	7-9	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.38	Vert(TL)	-0.27	7-9	>952	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.12	Horz(TL)	0.04	7	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)						Weight: 111 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 5-8-5 oc purlins.
BOT CHORD Rigid ceiling directly applied or 9-8-7 oc bracing.

REACTIONS (lb/size) 2=811/0-3-8, 7=811/0-3-8
Max Horz 2=-89(load case 7)
Max Uplift 2=-237(load case 6), 7=-237(load case 7)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/47, 2-3=-1200/638, 3-4=-945/522, 4-5=-802/520, 5-6=-945/522, 6-7=-1200/638, 7-8=0/47
BOT CHORD 2-11=-409/1016, 10-11=-210/801, 9-10=-210/801, 7-9=-409/1016
WEBS 3-11=-246/223, 4-11=-54/236, 5-11=-102/103, 5-9=-54/236, 6-9=-246/223

JOINT STRESS INDEX

2 = 0.68, 3 = 0.33, 4 = 0.41, 5 = 0.56, 6 = 0.33, 7 = 0.68, 9 = 0.34, 10 = 0.43 and 11 = 0.56

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=12ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS and C-C Exterior(2) zone; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- Provide adequate drainage to prevent water ponding.
- *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

Continued on page 2

Julius Lee
Truss Design Engineer
Florida P.E. No. 3-1888
1109 Coastal Bay Blvd
Boynton Beach, FL 33435

January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928316
	T02	HIP	1	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:40 2008 Page 2

NOTES

- 5) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 237 lb uplift at joint 2 and 237 lb uplift at joint 7.

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida PE No. 34888
1100 Coastal Bay Blvd.
Boynton Beach, FL 33435

January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928317
	T03	COMMON	5	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Apr 19 2006 MiTek Industries, Inc. Mon Jan 21 09:45:17 2008 Page 1




Plate Offsets (X,Y): [2:0-2-5,0-0-9], [6:0-2-5,0-0-9]

LOADING (psf)	SPACING		CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	2-0-0	TC 0.38	Vert(LL)	0.26	8-10	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.69	Vert(TL)	-0.39	8-10	>667	240		
BCLL 10.0	Rep Stress Incr	NO	WB 0.25	Horz(TL)	0.05	6	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
									Weight: 105 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-8-11 oc purlins.
BOT CHORD Rigid ceiling directly applied or 7-7-12 oc bracing.

REACTIONS (lb/size) 2=1025/0-3-8, 6=1025/0-3-8
Max Horz 2=101(load case 6)
Max Uplift 2=-306(load case 6), 6=-306(load case 7)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/47, 2-3=-1698/919, 3-4=-1531/903, 4-5=-1531/903, 5-6=-1698/919, 6-7=0/47
BOT CHORD 2-10=-649/1443, 9-10=-339/993, 8-9=-339/993, 6-8=-649/1443
WEBS 3-10=-240/227, 4-10=-322/606, 4-8=-322/606, 5-8=-240/227

JOINT STRESS INDEX
2 = 0.64, 3 = 0.34, 4 = 0.69, 5 = 0.34, 6 = 0.64, 8 = 0.46, 9 = 0.80 and 10 = 0.46

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=12ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS and C-C Exterior(2) zone; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 306 lb uplift at joint 2 and 306 lb uplift at joint 6.
- In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

Julius Lee
Truss Design Engineer
Florida PE No. 34888
1100 Coastal Bay Blvd
Boynton Beach, FL 33435

January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928317
	T03	COMMON	5	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Apr 19 2006 MiTek Industries, Inc. Mon Jan 21 09:45:17 2008 Page 2

LOAD CASE(S) Standard

1) Regular: Lumber Increase=1.25, Plate Increase=1.25

Uniform Loads (plf)

Vert: 1-4=-54, 4-7=-54, 2-10=-10, 8-10=-70(F=-60), 6-8=-10

Julius Lee
Truss Design Engineer
Florida PE No. 34868
1100 Coastal Bay Blvd
Boynton Beach, FL 33435

January 21, 200



Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Oonofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928318
	T04	SPECIAL	1	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Apr 19 2006 MiTek Industries, Inc. Mon Jan 21 09:48:16 2008 Page 1




Plate Offsets (X,Y): [2:0-8-0,0-0-6], [6:0-3-0,0-2-0], [7:0-2-15,0-0-14]

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.37	Vert(LL)	-0.25	11-12	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.63	Vert(TL)	-0.49	11-12	>626	240		
BCLL 10.0	Rep Stress Incr	NO	WB 0.61	Horz(TL)	0.08	7	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
									Weight: 140 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
 BOT CHORD 2 X 4 SYP No.1D *Except*
 7-11 2 X 6 SYP No.1D
 WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 2-9-5 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 8-9-13 oc bracing.

REACTIONS (lb/size) 2=1390/0-3-8, 7=2365/0-3-8
 Max Horz 2=-102(load case 6)
 Max Uplift 2=-389(load case 5), 7=-682(load case 6)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-2473/548, 3-4=-2309/554, 4-5=-3151/791, 5-6=-3892/986, 6-7=-4544/1121, 7-8=0/51
 BOT CHORD 2-12=-481/2131, 11-12=-328/1728, 10-11=-861/3916, 9-10=-727/3284, 7-9=-896/3998
 WEBS 3-12=-227/135, 4-12=-135/553, 4-11=-493/1900, 5-11=-1662/491, 5-10=-438/119, 6-10=-151/722, 6-9=-398/1585

JOINT STRESS INDEX

2 = 0.78, 3 = 0.34, 4 = 0.83, 5 = 0.86, 6 = 0.89, 7 = 0.88, 9 = 0.45, 10 = 0.42, 11 = 0.76 and 12 = 0.42

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=12ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS; Lumber DOL=1.60 plate grip DOL=1.60.
- Provide adequate drainage to prevent water ponding.
- *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

5) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi

Julius Lee
 Truss Design Engineer
 Florida PE No. 33889
 1100 Coastal Bay Blvd
 Boynton Beach, FL 33435

January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITTEK REFERENCE PAGE MII-7473 BEFORE USE
 This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928318
	T04	SPECIAL	1	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Apr 19 2006 MiTek Industries, Inc. Mon Jan 21 09:48:16 2008 Page 2

NOTES

- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 389 lb uplift at joint 2 and 682 lb uplift at joint 7.
- 7) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- 1) Regular: Lumber Increase=1.25, Plate Increase=1.25

Uniform Loads (plf)

Vert: 1-4=-54, 4-5=-54, 5-6=-54, 6-8=-54, 2-12=-10, 11-12=-70(F=-60), 7-11=-10

Concentrated Loads (lb)

Vert: 9=-1448(F)

Julius Lee
Truss Design Engineer
Florida PE No. 34869
1100 Coastal Bay Blvd
Boynton Beach, FL 33435

January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928319
	T05	SPECIAL	1	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:42 2008 Page 1




Plate Offsets (X,Y): [2:0-4-12,0-1-8], [7:0-1-13,0-0-7]

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.45	Vert(LL)	0.34 11-12	>906	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.94	Vert(TL)	-0.55 11-12	>556	240		
BCLL 10.0	* Rep Stress Incr	NO	WB 0.64	Horz(TL)	0.07 7	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)						
								Weight: 129 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 3-10-1 oc purlins.
BOT CHORD Rigid ceiling directly applied or 6-2-1 oc bracing.

REACTIONS

(lb/size) 2=1201/0-3-8, 7=1139/0-3-8
Max Horz 2=101(load case 6)
Max Uplift 2=-337(load case 6), 7=-343(load case 7)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-2086/1127, 3-4=-1920/1111, 4-5=-2407/1437, 5-6=-1587/941,
6-7=-1848/968, 7-8=0/47
BOT CHORD 2-12=-833/1787, 11-12=-524/1332, 10-11=-966/2108, 9-10=-966/2108,
7-9=-675/1568
WEBS 3-12=-230/228, 4-12=-323/620, 4-11=-771/1343, 5-11=-708/467, 5-9=-708/386,
6-9=-182/460

JOINT STRESS INDEX

2 = 0.76, 3 = 0.33, 4 = 0.57, 5 = 0.62, 6 = 0.58, 7 = 0.77, 9 = 0.35, 10 = 0.93, 11 = 0.94 and 12 = 0.45

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=12ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS and C-C Exterior(2) zone; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- Provide adequate drainage to prevent water ponding.

Julius Lee
Truss Design Engineer
Florida PE No. 34888
1100 Coastal Bay Blvd
Boynton Beach, FL 33435

January 21,2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and/or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928319
	T05	SPECIAL	1	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:43 2008 Page 2

NOTES

- 4) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 337 lb uplift at joint 2 and 343 lb uplift at joint 7.
- 7) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- 1) Regular: Lumber Increase=1.25, Plate Increase=1.25

Uniform Loads (plf)

Vert: 1-4=-54, 4-5=-54, 5-6=-54, 6-8=-54, 2-12=-10, 11-12=-70(F=-60), 7-11=-10

Julius Lee
Truss Design Engineer
Florida PE No. 34865
1100 Coastal Bay Blvd.
Boynton Beach, FL 33435


January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:43 2008 Page 1



Builders
FirstSource

Job	Truss	Truss Type	Qty	Ply	J1928320
	T06	SPECIAL	1	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:43 2008 Page 2

NOTES

- 4) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 322 lb uplift at joint 2 and 325 lb uplift at joint 8.
- 7) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- 1) Regular: Lumber Increase=1.25, Plate Increase=1.25

Uniform Loads (plf)

Vert: 1-4=-54, 4-5=-54, 5-6=-54, 6-9=-54, 2-13=-10, 12-13=-70(F=-60), 8-12=-10

Julius Lee
Truss Design Engineer
Florida PE No. 34889
1100 Coastal Bay Blvd
Boynton Beach, FL 33495

January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928321
	T07	HIP	2	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:44 2008 Page 1




Plate Offsets (X,Y): [2:0-0-10,Edge], [7:0-0-10,Edge]

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.35	Vert(LL)	-0.32	7-9	>968	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.56	Vert(TL)	-0.58	7-9	>531	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.22	Horz(TL)	0.05	7	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
									Weight: 131 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 5-0-13 oc purlins.
BOT CHORD Rigid ceiling directly applied or 8-6-15 oc bracing.

REACTIONS (lb/size) 2=939/0-3-8, 7=939/0-3-8
Max Horz 2=101(load case 6)
Max Uplift 2=-264(load case 6), 7=-264(load case 7)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=0/47, 2-3=-1438/787, 3-4=-1113/634, 4-5=-939/627, 5-6=-1112/634, 6-7=-1438/787, 7-8=0/47
BOT CHORD 2-11=-530/1221, 10-11=-266/938, 9-10=-266/938, 7-9=-530/1221
WEBS 3-11=-326/300, 4-11=-92/285, 5-11=-126/128, 5-9=-92/285, 6-9=-327/300

JOINT STRESS INDEX

2 = 0.91, 3 = 0.33, 4 = 0.50, 5 = 0.65, 6 = 0.33, 7 = 0.91, 9 = 0.34, 10 = 0.70 and 11 = 0.57

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=12ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS and C-C Exterior(2) zone; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- Provide adequate drainage to prevent water ponding.
- *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

Continued on page 2

Julius Lee
Truss Design Engineer
Florida PE No. 34869
1109 Coastal Bay Blvd.
Boynton Beach, FL 33435

January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928321
	T07	HIP	2	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:44 2008 Page 2

NOTES

- 5) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 264 lb uplift at joint 2 and 264 lb uplift at joint 7.

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida PE No. 34869
1100 Coastal Bay Blvd.
Boynton Beach, FL 33435

January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928322
	T08	COMMON	11	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:45 2008 Page 1




Plate Offsets (X,Y): [2:0-6-8,0-0-6], [6:0-6-8,0-0-6]

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.32	Vert(LL)	-0.13	2-10	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.40	Vert(TL)	-0.25	2-10	>999	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.26	Horz(TL)	0.05	6	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)						Weight: 122 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 5-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 8-10-10 oc bracing.

REACTIONS (lb/size) 2=939/0-3-8, 6=939/0-3-8
Max Horz 2=-113(load case 7)
Max Uplift 2=-274(load case 6), 6=-274(load case 7)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-1427/770, 3-4=-1236/765, 4-5=-1236/765, 5-6=-1427/770, 6-7=0/47
BOT CHORD 2-10=-505/1199, 9-10=-216/813, 8-9=-216/813, 6-8=-505/1199
WEBS 3-10=-324/301, 4-10=-239/435, 4-8=-239/435, 5-8=-324/301

JOINT STRESS INDEX

2 = 0.70, 3 = 0.33, 4 = 0.74, 5 = 0.33, 6 = 0.70, 8 = 0.42, 9 = 0.32 and 10 = 0.42

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=12ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS and C-C Exterior(2) zone; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi

Julius Lee
Truss Design Engineer
Florida PE No. 34888
1400 Coastal Bay Blvd.
Boynton Beach, FL 33435

January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928322
	T08	COMMON	11	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:45 2008 Page 2

NOTES

- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 274 lb uplift at joint 2 and 274 lb uplift at joint 6.

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida PE No. 34888
1400 Coastal Bay Blvd
Boynton Beach, FL 33435

January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928323
	T09	HIP	1	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:46 2008 Page 1




Plate Offsets (X,Y): [2:0-1-11, Edge], [7:0-1-11, Edge]

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.49	Vert(LL)	-0.19 10	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.71	Vert(TL)	-0.37 10-12	>829	240		
BCLL 10.0	* Rep Stress Incr	NO	WB 0.42	Horz(TL)	0.14 7	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)						
								Weight: 123 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 3-1-7 oc purlins.
BOT CHORD Rigid ceiling directly applied or 6-0-12 oc bracing.

REACTIONS (lb/size) 2=1799/0-3-8, 7=1799/0-3-8
Max Horz 2=77(load case 5)
Max Uplift 2=-585(load case 5), 7=-585(load case 6)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-3302/1037, 3-4=-2903/964, 4-5=-3491/1133, 5-6=-2903/964,
6-7=-3302/1037, 7-8=0/47
BOT CHORD 2-12=-887/2860, 11-12=-1098/3455, 10-11=-1098/3455, 9-10=-1083/3455,
7-9=-854/2860
WEBS 3-12=-334/1094, 4-12=-859/351, 4-10=0/135, 5-10=0/135, 5-9=-859/351,
6-9=-334/1094

JOINT STRESS INDEX

2 = 0.80, 3 = 0.71, 4 = 0.42, 5 = 0.42, 6 = 0.71, 7 = 0.80, 9 = 0.69, 10 = 0.42, 11 = 0.94 and 12 = 0.69

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-02; 110mph (3-second gust); h=12ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS; Lumber DOL=1.60 plate grip DOL=1.60.
- 3) Provide adequate drainage to prevent water ponding.

Continued on page 2

Julius Lee
Truss Design Engineer
Florida PE No. 34888
1409 Coastal Bay Blvd
Boynton Beach, FL 33495

January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCS-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928323
	T09	HIP	1	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:46 2008 Page 2

NOTES

- 4) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 585 lb uplift at joint 2 and 585 lb uplift at joint 7.
- 7) Girder carries hip end with 7-0-0 end setback.
- 8) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- 1) Regular: Lumber Increase=1.25, Plate Increase=1.25

Uniform Loads (plf)

Vert: 1-3=-54, 3-6=-118(F=-64), 6-8=-54, 2-12=-10, 9-12=-22(F=-12), 7-9=-10

Concentrated Loads (lb)

Vert: 12=-411(F) 9=-411(F)

Julius Lee
Truss Design Engineer
Florida PE No. 34888
1100 Coastal Bay Blvd
Boynton Beach, FL 33435

January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928324
	T10	HIP	1	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:47 2008 Page 1




Plate Offsets (X,Y): [2:0-1-1,0-0-7], [5:0-4-3,Edge], [7:0-1-1,0-0-7]

LOADING (psf)	SPACING		CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	2-0-0	TC 0.45	Vert(LL)	-0.14	7-9	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.39	Vert(TL)	-0.27	7-9	>999	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.09	Horz(TL)	0.05	7	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)						Weight: 127 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 5-0-13 oc purlins.
BOT CHORD Rigid ceiling directly applied or 8-8-2 oc bracing.
WEBS T-Brace: 2 X 4 SYP No.3 - 5-11
Fasten T and I braces to narrow edge of web with 10d Common wire nails, 9in o.c., with 4in minimum end distance.
Brace must cover 90% of web length.

REACTIONS (lb/size) 2=939/0-3-8, 7=939/0-3-8
Max Horz 2=89(load case 6)
Max Uplift 2=-252(load case 6), 7=-252(load case 7)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-1456/765, 3-4=-1244/678, 4-5=-1088/669, 5-6=-1244/679,
6-7=-1456/765, 7-8=0/47
BOT CHORD 2-11=-516/1236, 10-11=-360/1088, 9-10=-360/1088, 7-9=-516/1236
WEBS 3-11=-173/177, 4-11=-26/291, 5-11=-121/122, 5-9=-25/291, 6-9=-173/176

JOINT STRESS INDEX

2 = 0.87, 3 = 0.33, 4 = 0.66, 5 = 0.65, 6 = 0.33, 7 = 0.87, 9 = 0.34, 10 = 0.38 and 11 = 0.56

Julius Lee
Truss Design Engineer
Florida PE No. 34889
1100 Coastal Bay Blvd
Boynton Beach, FL 33436

Continued on page 2

January 21,200



Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928324
	T10	HIP	1	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:47 2008 Page 2

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-02; 110mph (3-second gust); h=12ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS and C-C Exterior(2) zone; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- 3) Provide adequate drainage to prevent water ponding.
- 4) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 252 lb uplift at joint 2 and 252 lb uplift at joint 7.

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida PE No. 34888
1100 Coastal Bay Blvd
Boynton Beach, FL 33426

January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TP1 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928325
	T11	HIP	1	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:48 2008 Page 1




Plate Offsets (X,Y): [1:0-2-0,0-0-7], [4:0-2-0,0-0-7]

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.45	Vert(LL)	0.14	1-6	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.51	Vert(TL)	-0.16	1-6	>999	240		
BCLL 10.0	* Rep Stress Incr	NO	WB 0.20	Horz(TL)	0.04	4	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
									Weight: 65 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-3-4 oc purlins.
BOT CHORD Rigid ceiling directly applied or 7-1-11 oc bracing.

REACTIONS (lb/size) 1=987/0-3-8, 4=987/0-3-8
Max Horz 1=46(load case 4)
Max Uplift 1=-498(load case 5), 4=-498(load case 6)

FORCES (lb) - Maximum Compression/Maximum Tension
TOP CHORD 1-2=-1825/836, 2-3=-1573/803, 3-4=-1828/838
BOT CHORD 1-6=-721/1550, 5-6=-732/1570, 4-5=-689/1553
WEBS 2-6=-265/505, 3-5=-305/611, 2-5=-177/190

JOINT STRESS INDEX

1 = 0.86, 2 = 0.98, 3 = 0.61, 4 = 0.86, 5 = 0.39 and 6 = 0.36

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=12ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60.
- Provide adequate drainage to prevent water ponding.
- *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi

Continued on page 2

Julius Lee
Truss Design Engineer
Florida PE No. 34888
1100 Coastal Bay Blvd
Boynton Beach, FL 33435

January 21, 2008

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITTEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	J1928325
	T11	HIP	1	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Fri Jan 18 16:30:48 2008 Page 2

NOTES

- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 498 lb uplift at joint 1 and 498 lb uplift at joint 4.
- 7) Girder carries hip end with 7'-0" end setback.
- 8) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- 1) Regular: Lumber Increase=1.25, Plate Increase=1.25

Uniform Loads (plf)

Vert: 1-2=-54, 2-3=-118(F=-64), 3-4=-54, 1-6=-10, 5-6=-22(F=-12), 4-5=-10

Concentrated Loads (lb)

Vert: 6=-411(F) 5=-411(F)

Julius Lee
Truss Design Engineer
Florida PE No. 34888
1100 Coastal Bay Blvd
Boynton Beach, FL 33435

January 21, 2008


Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719




Symbols

PLATE LOCATION AND ORIENTATION



* Center plate on joint unless dimensions indicate otherwise. Dimensions are in inches. Apply plates to both sides of truss and securely seat.



* For 4 x 2 orientation, locate plates 1/8" from outside edge of truss and vertical web.



* This symbol indicates the required direction of slots in connector plates.

PLATE SIZE

4 X 4


The first dimension is the width perpendicular to slots. Second dimension is the length parallel to slots.

LATERAL BRACING




Indicates location of required continuous lateral bracing.

BEARING



Indicates location of joints at which bearings (supports) occur.

Numbering System



JOINTS AND CHORDS ARE NUMBERED CLOCKWISE AROUND THE TRUSS STARTING AT THE LOWEST JOINT FARTHEST TO THE LEFT.

WEBS ARE NUMBERED FROM LEFT TO RIGHT

CONNECTOR PLATE CODE APPROVALS

BOCA	96-31, 96-67
ICBO	3907, 4922
SBCCI	9667, 9432A
WISC/DLHR	960022-W, 970036-N
NER	561



MITek Engineering Reference Sheet: MIT-7473



General Safety Notes


Failure to Follow Could Cause Property Damage or Personal Injury

1. Provide copies of this truss design to the building designer, erection supervisor, property owner and all other interested parties.
2. Cut members to bear tightly against each other.
3. Place plates on each face of truss at each joint and embed fully. Avoid knots and wane at joint locations.
4. Unless otherwise noted, locate chord splices at 1/4 panel length ($\pm 6"$ from adjacent joint.)
5. Unless otherwise noted, moisture content of lumber shall not exceed 19% at time of fabrication.
6. Unless expressly noted, this design is not applicable for use with fire retardant or preservative treated lumber.
7. Camber is a non-structural consideration and is the responsibility of truss fabricator. General practice is to camber for dead load deflection.
8. Plate type, size and location dimensions shown indicate minimum plating requirements.
9. Lumber shall be of the species and size, and in all respects, equal to or better than the grade specified.
10. Top chords must be sheathed or purlins provided at spacing shown on design.
11. Bottom chords require lateral bracing at 10 ft. spacing, or less, if no ceiling is installed, unless otherwise noted.
12. Anchorage and / or load transferring connections to trusses are the responsibility of others unless shown.
13. Do not overload roof or floor trusses with stacks of construction materials.
14. Do not cut or alter truss member or plate without prior approval of a professional engineer.
15. Care should be exercised in handling, erection and installation of trusses.

© 1993 MITek® Holdings, Inc.

ASCE 7-02: 130 MPH WIND SPEED, 15' MEAN HEIGHT, ENCLOSED, I = 1.00, EXPOSURE C

MAX GABLE VERTICAL LENGTH																
GABLE VERTICAL SPACING	2x4 SPECIES	BRACE	NO. BRACES	(1) 1x4 T" BRACE • (1) 2x4 T" BRACE • (2) 2x4 T" BRACE •• (1) 2x6 T" BRACE • (2) 2x8 T" BRACE ••												
				GROUP A	GROUP B	GROUP A	GROUP B	GROUP A	GROUP B	GROUP A	GROUP B	GROUP A	GROUP B	GROUP A	GROUP B	
24" O.C.	SPF	#1 / #2	3' 4"	6' 10"	6' 0"	6' 11"	7' 1"	8' 3"	8' 6"	10' 10"	11' 2"	12' 11"	13' 3"			
		#3 STUD	3' 3"	4' 11"	4' 11"	6' 6"	6' 6"	8' 3"	8' 3"	10' 1"	10' 1"	12' 11"	12' 11"			
	HF	STANDARD	3' 3"	4' 2"	4' 2"	5' 6"	5' 6"	7' 5"	7' 5"	8' 3"	8' 3"	11' 8"	11' 8"			
		#1	3' 8"	5' 10"	6' 3"	6' 11"	7' 5"	8' 3"	8' 11"	10' 10"	11' 8"	12' 11"	13' 11"			
	SP	#2	3' 7"	6' 10"	6' 3"	6' 11"	7' 5"	8' 3"	8' 11"	10' 10"	11' 8"	12' 11"	13' 11"			
		#3	3' 6"	5' 0"	6' 0"	6' 8"	6' 8"	8' 3"	8' 5"	10' 4"	10' 4"	12' 11"	13' 7"			
	DFL	STUD	3' 6"	5' 0"	5' 0"	6' 7"	6' 7"	8' 3"	8' 8"	10' 3"	10' 3"	12' 11"	13' 7"			
		STANDARD	3' 4"	4' 3"	4' 3"	5' 8"	5' 8"	7' 8"	7' 8"	8' 10"	8' 10"	12' 0"	12' 0"			
	16" O.C.	SPF	#1 / #2	3' 10"	6' 8"	6' 10"	7' 11"	8' 1"	9' 6"	9' 8"	12' 6"	12' 9"	14' 0"			
			#3 STUD	3' 9"	6' 0"	6' 0"	7' 11"	8' 1"	9' 6"	9' 8"	12' 4"	12' 4"	14' 0"			
HF		STANDARD	3' 9"	5' 2"	6' 2"	7' 11"	7' 11"	9' 6"	9' 8"	12' 4"	12' 4"	14' 0"				
		#1	4' 3"	6' 8"	7' 2"	7' 11"	8' 6"	9' 5"	10' 2"	10' 7"	10' 7"	14' 0"				
SP		#2	4' 2"	6' 8"	7' 2"	7' 11"	8' 6"	9' 6"	10' 2"	12' 6"	13' 5"	14' 0"				
		#3 STUD	4' 0"	6' 1"	6' 2"	7' 11"	8' 2"	9' 5"	9' 11"	12' 5"	12' 5"	14' 0"				
DFL		STANDARD	3' 10"	5' 3"	5' 3"	6' 11"	6' 11"	9' 4"	9' 4"	10' 10"	10' 10"	14' 0"				
		#1 / #2	4' 3"	6' 11"	6' 11"	8' 9"	8' 9"	10' 6"	10' 6"	13' 8"	13' 8"	14' 0"				
12" O.C.		SPF	#3 STUD	4' 2"	6' 11"	6' 11"	8' 9"	8' 9"	10' 5"	10' 5"	13' 8"	13' 8"	14' 0"			
			STANDARD	4' 2"	6' 11"	6' 11"	8' 9"	8' 9"	10' 5"	10' 5"	13' 8"	13' 8"	14' 0"			
	HF	#1	4' 8"	7' 4"	7' 4"	8' 9"	8' 9"	10' 6"	11' 2"	13' 6"	14' 0"					
		#2	4' 7"	7' 4"	7' 4"	8' 9"	8' 9"	10' 6"	11' 2"	13' 6"	14' 0"					
	SP	#3	4' 4"	7' 2"	7' 2"	8' 9"	8' 9"	10' 6"	10' 11"	13' 6"	14' 0"					
		STUD	4' 4"	7' 1"	7' 1"	8' 9"	8' 9"	10' 6"	10' 11"	13' 6"	14' 0"					
	DFL	STANDARD	4' 3"	6' 1"	6' 1"	8' 0"	8' 0"	10' 5"	10' 8"	12' 6"	12' 6"	14' 0"				
		#1 / #2	4' 3"	6' 1"	6' 1"	8' 0"	8' 0"	10' 5"	10' 8"	12' 6"	12' 6"	14' 0"				



BRACING GROUP SPECIES AND GRADES:		GROUP A:		GROUP B:	
SPECIES-PURPOSE	GRADE	#1 / #2	STUD	#1 / #2	STUD
DOUGLAS FIR-LARCH	STUD	#3	STUD	#3	STUD
SOUTHERN PINE	STUD	#3	STUD	#3	STUD

CABLE VERTICAL PLATE SIZES		GROUP A:		GROUP B:	
VERTICAL LENGTH	NO BRACE	#1 / #2	STUD	#1 / #2	STUD
LESS THAN 4' 0"	2X4	#3	STUD	#3	STUD
GREATER THAN 4' 0", BUT LESS THAN 11' 6"					
GREATER THAN 11' 6"	2X6	#3	STUD	#3	STUD
GREATER THAN 11' 6"					


WARNING TRUSSES REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO ASCE 7-02 (BUILDING CONVENTIONAL SAFETY INFORMATION, PUBLISHED BY THE STRUCTURAL STEEL INSTITUTE, 5835 JONES BLVD., SUITE 200, ANN ARBOR, MI 48106) AND AISC 360 (STEEL DESIGN, 3RD EDITION, 2005) FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, TOP CHORD SHALL HAVE PERMANENTLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED ROOF CEILING.

JULIUS LEE'S
CONS. ENGINEERS P.A.
1455 67th AVE. N.E.
MARIETTA, GA 30067-2161

No. 34889
STATE OF FLORIDA

MAX. TOT. LD. 60 PSF
MAX. SPACING 24.0"

REF ASCE 7-02-CAB13015
DATE 11/26/03
DRWG WITH STD CABLE 15 E ET
-ENG



BRACING GROUP SPECIES AND GRADES:			
GROUP A:		HDL-STR	
SPRUCE-PINE-TR		#1	STD
#1 / #2		STANDARD	
#3		STD	
DOUGLAS FIR-LARCH		#3	STD
STANDARD		STD	
STANDARD		STANDARD	
GROUP B:		HDL-STR	
SOUTHERN PINE		#1	STD
#1		STANDARD	
DOUGLAS FIR-LARCH		#1	STD
STANDARD		STD	
STANDARD		STANDARD	


LIVE LOAD DEFLECTION CRITERIA IS $l/240$.
 PROVIDE WEAP CONNECTIONS FOR 180 PL OVER
 CONTINUOUS BEARING (6 PSF VC DEAD LOAD).
 CABLE END SUPPORTS LOAD FROM 4" 0"
 OUTLOOKERS WITH 2" 0" OVERHANG, OR 12"
 PLTWOOD OVERHANG.

1. BRACING MUST BE A MINIMUM OF 60% OF THE
 MEMBER LENGTH.
 2. BRACING MUST BE 104 INCHES.
 3. FOR (1) 1" BRACE, SPACE MUST BE 8" O.C.
 IN 18" END ZONES AND 4" O.C. BETWEEN ZONES
 4. FOR (2) 1" BRACES, SPACE MUST BE 3" O.C.
 IN 18" END ZONES AND 6" O.C. BETWEEN ZONES


VERTICAL LENGTH	NO. BEAMS
LESS THAN 4' 0"	1X4 OR 2X3
GREATER THAN 4' 0", BUT LESS THAN 11' 0"	2X4
GREATER THAN 11' 0"	2.5X4

+ REFER TO COMMON TRUSS DESIGN FOR
PEAK, SPLICE, AND HEBEL PLATES.


TYPICAL ATTIC TRUSS BRACING



TYPICAL ALTERNATE BRACING DETAIL FOR EXTERIOR FLAT GIRDER TRUSS





CABLE END TRUSS DETAIL



MINIMUM BC BRACING ON CABLE TRUSSES. OTHER PERMANENT BRACING DESIGNS BY ARCHITECT OR BOB

TYPICAL WALL GIRDER VERTICAL WEB BRACING DETAIL



JULIUS LEE'S
CONS. ENGINEERS P.A.
1425 SW 4TH AVENUE
ORLANDO BEACH, FL 32444-2161

No: 34869
STATE OF FLORIDA

TOP CHORD 2x4 #2 OR BETTER
BOT CHORD 2x4 #2 OR BETTER
WEBS 2x4 #8 OR BETTER

PIGGYBACK DETAIL

REFER TO SEALED DESIGN FOR DASHED PLATES.

SPACE PIGGYBACK VERTICALS AT 4' OC MAX.

TOP AND BOTTOM CHORD SPLICES MUST BE STAGGERED SO THAT ONE SPLICE IS NOT DIRECTLY OVER ANOTHER.

PIGGYBACK BOTTOM CHORD MAY BE OMITTED. ATTACH VERTICAL WEBS TO TRUSS TOP CHORD WITH 1.5X3 PLATE.

ATTACH PURLINS TO TOP OF FLAT TOP CHORD. IF PIGGYBACK IS SOLID LUMBER OR THE BOTTOM CHORD IS OMITTED, PURLINS MAY BE APPLIED BENEATH THE TOP CHORD OF SUPPORTING TRUSS.

REFER TO ENGINEER'S SEALED DESIGN FOR REQUIRED PURLIN SPACING.



THIS DETAIL IS APPLICABLE FOR THE FOLLOWING WIND CONDITIONS:

110 MPH WIND, 30' MEAN HGT, ASCE 7-02, CLOSED BLDG, LOCATED ANYWHERE IN ROOF, 1 MI FROM COAST
CAT I, EXP C, WIND TC DL=5 PSF, WIND BC DL=5 PSF

110 MPH WIND, 30' MEAN HGT, ENG ENCLOSED BLDG, LOCATED ANYWHERE IN ROOF
WIND TC DL=5 PSF, WIND BC DL=5 PSF

FRONT FACE (B*) PLATES MAY BE OFFSET FROM BACK FACE PLATES AS LONG AS BOTH FACES ARE SPACED 4' OC MAX.

130 MPH WIND, 30' MEAN HGT, ASCE 7-02, CLOSED BLDG, LOCATED ANYWHERE IN ROOF, CAT II, EXP. C, WIND TC DL=6 PSF, WIND BC DL=6 PSF




SEALING/SHIMMING TRUSSES REQUIRE EXTENSIVE CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO SEALING BUILDING COMPONENT SAFETY DEPARTMENT, FILM ISSUED BY THE TRUSS AND BRACING INSTITUTE, 1000 N. W. 17TH AVE., SUITE 100, MIAMI, FL 33135 FOR SAFETY PRACTICES PERTAINING TO THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

JOINT TYPE	SPANS UP TO		
	30'	36'	62'
A	2x4	2.5x4	3x5
B	4x6	5x6	5x8
C	1.5x3	1.5x4	1.5x4
D	5x4	5x6	5x8
E	4x8 OR 3x6 TRUSS AT 4' OC, ROTATED VERTICALLY		

ATTACH TRUSS PLATES WITH (6) 0.120" X 1.375" NAILS OR EQUAL PER FACE PER PLY. (4) NAILS IN EACH MEMBER TO BE CONNECTED. REFER TO DRAWING 160 TL FOR TRUSS INFORMATION.

WEB LENGTH	WEB BRACING CHART
0' TO 7'9"	NO BRACING
7'9" TO 10'	1x4 "T" BRACE, SAME GRADE, SPECIES AS WEB MEMBER, OR BETTER, AND 80% LENGTH OF WEB MEMBER. ATTACH WITH 8d NAILS AT 4" OC.
10' TO 14'	2x4 "T" BRACE, SAME GRADE, SPECIES AS WEB MEMBER, OR BETTER, AND 80% LENGTH OF WEB MEMBER. ATTACH WITH 16d NAILS AT 4" OC.



THIS DRAWING REPLACES DRAWINGS 634.016 634.017 & 647.045

JULIUS LEE'S
CONS. ENGINEERS P.A.
1460 NW 4th AVENUE
DORSET BEACH, FL 33444-2161

No. 34888
STATE OF FLORIDA

MAX LOADING	55 PSF AT	DATE 09/12/07
	1.33 DUR. FAC.	DRWG/ITEK STD PIGGY
SPACING	50 PSF AT	-ENG JL
	1.25 DUR. FAC.	
SPACING	47 PSF AT	
	1.15 DUR. FAC.	
24.0"		

VALLEY TRUSS DETAIL

TOP CHORD 2X4 SP #2 OR SPF #1/#2 OR BETTER.
BOT CHORD 2X3(*) OR 2X4 SP #2N OR SPF #1/#2 OR BETTER.
WEBS 2X4 SP #3 OR BETTER.

* 2X3 MAY BE RIPPED FROM A 2X6 (PITCHED OR SQUARE).

** ATTACH EACH VALLEY TO EVERY SUPPORTING TRUSS WITH:

- (2) 16d BOX (0.135" X 3.5") NAILS TOE-NAILED FOR FBC 2004 110 MPH, ASCE 7-02 110 MPH WIND OR (3) 16d FOR ASCE 7-02 130 MPH WIND. 15' MEAN HEIGHT, ENCLOSED BUILDING, EXP. C, RESIDENTIAL, WIND TC DL=5 PSF.






UNLESS SPECIFIED ON ENGINEER'S SEALED DESIGN, APPLY 1X4 "I"-BRACE, 80% LENGTH OF WEB, VALLEY WEB, SAME SPECIES AND GRADE OR BETTER, ATTACHED WITH 8d BOX (0.113" X 2.5") NAILS AT 6" OC, OR CONTINUOUS LATERAL BRACING, EQUALLY SPACED, FOR VERTICAL VALLEY WEBS GREATER THAN 7'9".

MAXIMUM VALLEY VERTICAL HEIGHT MAY NOT EXCEED 12'0".



TOP CHORD OF TRUSS BENEATH VALLEY SET MUST BE BRACED WITH: PROPERLY ATTACHED, RATED SHEATHING APPLIED PRIOR TO VALLEY TRUSS INSTALLATION

OR
PURLINS AT 24" OC OR AS OTHERWISE SPECIFIED ON ENGINEERS' SEALED DESIGN
OR
BY VALLEY TRUSSES USED IN LIEU OF PURLIN SPACING AS SPECIFIED ON ENGINEERS' SEALED DESIGN.

*** NOTE THAT THE PURLIN SPACING FOR BRACING THE TOP CHORD OF THE TRUSS BENEATH THE VALLEY IS MEASURED ALONG THE SLOPE OF THE TOP CHORD.
++ LARGER SPANS MAY BE BUILT AS LONG AS THE VERTICAL HEIGHT DOES NOT EXCEED 12'0".
BOTTOM CHORD MAY BE SQUARE OR PITCHED CUT AS SHOWN.



SUPPORTING TRUSSES AT 24" OC MAXIMUM SPACING.



REVIEWING TRUSSES REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, DESTALING AND BRACING. REFER TO NEXT 1-10 BUILDING DEPARTMENT SAFETY INFORMATION, PUBLISHED BY THE TRUSS AND JOINT INSTITUTE, 500 DOWNSIDE DR., SUITE 200, AUSTIN, TX 78709, AND THE TRUSS JOINT INSTITUTE, 500 DOWNSIDE DR., SUITE 200, AUSTIN, TX 78709. THESE FUNCTIONS, UNLESS OTHERWISE INDICATED, TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

JULIUS LEE'S
CONS. ENGINEERS P.A.

1455 SW 4th AVENUE
DEALY BEACH, FL 33444-2801

No. 34898
STATE OF FLORIDA

TC IL	20	PSF	REF	VALLEY DETAIL
TC DL	7	PSF	DATE	11/26/03
BC DL	5	PSF	DRWG	VALTRUSS1103
BC IL	0	PSF	-ENG	JL
TOT. LD.	32	PSF		
DUR.FAC.	1.25			
SPACING	24"			

THIS DRAWING REPLACES DRAWING A105

TOE-NAIL DETAIL

TOE-NAILS TO BE DRIVEN AT AN ANGLE OF APPROXIMATELY THIRTY DEGREES WITH THE PIECE AND STARTED APPROXIMATELY ONE-THIRD THE LENGTH OF THE NAIL FROM THE END OF THE MEMBER.

PER ANSI/AF&PA NDS-2001 SECTION 12.4.1 - EDGE DISTANCE, END DISTANCE, SPACING, EDGE DISTANCES, END DISTANCES AND SPACINGS FOR NAILS AND SPIKES SHALL BE SUFFICIENT TO PREVENT SPLITTING OF THE WOOD.



THE NUMBER OF TOE-NAILS TO BE USED IN A SPECIFIC APPLICATION IS DEPENDENT UPON PROPERTIES FOR THE CHORD SIZE, LUMBER SPECIES, AND NAIL TYPE. PROPER CONSTRUCTION PRACTICES AS WELL AS GOOD JUDGEMENT SHOULD DETERMINE THE NUMBER OF NAILS TO BE USED.

THIS DETAIL DISPLAYS A TOE-NAILED CONNECTION FOR JACK FRAMING INTO A SINGLE OR DOUBLE PLY SUPPORTING GIRDER.

MAXIMUM VERTICAL RESISTANCE OF 16d (0.162"x3.5") COMMON TOE-NAILS

NUMBER OF TOE-NAILS	SOUTHERN PINE		DOUGLAS FIR-LARCH		HEM-FIR		SPRUCE PINE FIR	
	1 PLY	2 PLYS	1 PLY	2 PLYS	1 PLY	2 PLYS	1 PLY	2 PLYS
2	197#	256#	181#	234#	156#	203#	154#	199#
3	296#	383#	271#	351#	234#	304#	230#	298#
4	394#	511#	361#	468#	312#	406#	307#	397#
5	493#	639#	452#	585#	390#	507#	384#	496#

ALL VALUES MAY BE MULTIPLIED BY APPROPRIATE DURATION OF LOAD FACTOR.



ALTERNATIVE CONDITION

THIS DRAWING REPLACES DRAWING 784040

WARNING TRUSSES REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BCST 1-93 CALLING COMPONENT SAFETY INFORMATION, PUBLISHED BY THE TRUSS OF AMERICA, 6800 ENTERPRISE LN, NORTON, VA 22719, FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED ROOF CEILING.

JULIUS LEE'S
CONS. ENGINEERS P.A.

1480 SW 4TH AVENUE
DELRAY BEACH, FL 33444-2181


No. 34689
STATE OF FLORIDA

TC LL	PSF	REF	TOE-NAIL
TC DL	PSF	DATE	09/12/07
BC DL	PSF	DRWG	CNTONAIL1103
BC LL	PSF	-ENG	JL
TOT. LD.	PSF		
DUR. FAC.	1.00		
SPACING			

1/2" DIAMETER BOLT SPACING FOR LOAD APPLIED PARALLEL TO GRAIN.

* GRADE AND SPECIES AS SPECIFIED ON THE ALPINE DESIGN.
BOLT HOLES SHALL BE A MINIMUM OF 1/32" TO A MAXIMUM OF 1/16" LARGER THAN BOLT DIAMETER.

TYPICAL LOCATION OF 1/2" DIAMETER THRU BOLTS. BOLT QUANTITIES AS NOTED ON SEALED DESIGN MUST BE APPLIED IN ONE OF THE PATTERNS SHOWN BELOW.
WASHERS REQUIRED UNDER BOLT HEAD AND NUT



2X6 DETAIL

2X8 DETAIL

THIS DRAWING REPLACES DRAWING A828.016

WARNING: TRUSSES REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BEST 1-800 BUILDING DEPARTMENT SAFETY INFORMATION, PUBLISHED BY THE TRUSS PLATE INSTITUTE, 380 DOWNTOWN DR., SUITE 200, WASHINGTON, VA 22799 AND ALTA CEDD TRUSS COUNCIL OF AMERICA, 6500 ENTERPRISE LN, HANSEN, VA 22729 FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL FIBERS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED ROPE CELLING.

JULIUS LEE'S
CONS. ENGINEERS P.A.
1400 17TH AVE. SW
DELMAR BEACH, FL 33444-2161

No: 34689
STATE OF FLORIDA

TC LL	PSF	REF	BOLT SPACING
TC DL	PSF	DATE	11/26/03
BC DL	PSF	DRWG	CNBOL/SP1103
BC LL	PSF	-ENG	JL
TOT. LD.	PSF		
DUR. FAC.			
SPACING			

TRULOX CONNECTION DETAIL




11 GAUGE (0.120" X 1.375") NAILS REQUIRED FOR TRULOX PLATE ATTACHMENT. FILL ROWS COMPLETELY WHERE SHOWN (Φ).

* NAILS MAY BE OMITTED FROM THESE ROWS.

THIS DETAIL MAY BE USED WITH SO. PINE, DOUGLAS-FIR OR HEM-FIR CHORDS WITH A MINIMUM 1.00 DURATION OF LOAD OR SPRUCE-PINE-FIR CHORDS WITH A MINIMUM 1.15 DURATION OF LOAD. CHORD SIZE OF BOTH TRUSSES MUST EXCEED THE TRULOX PLATE WIDTH.

TRULOX PLATE IS CENTERED ON THE CHORDS AND BENT BETWEEN NAIL ROWS.

REFER TO ENGINEER'S SEALED DESIGN REFERENCING THIS DETAIL FOR LUMBER, PLATES, AND OTHER INFORMATION NOT SHOWN.



TRULOX PLATE SIZE	REQUIRED NAILS PER TRUSS	MAXIMUM LOAD UP OR DOWN
3X6	9	350#
5X6	15	990#

MINIMUM 3X6 TRULOX PLATE

MINIMUM 5X6 TRULOX PLATE

THIS DRAWING REPLACES DRAWINGS 1,158,989 1,158,988/R 1,154,844 1,152,217 1,152,017 1,159,154 & 1,151,524

WARNING: TRUSSES REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO RC31 1-93 (BUILDING DEPARTMENT SAFETY INFORMATION, PUBLISHED BY THE TRUSS PLATE INSTITUTE, 383 EDENFORD DR., SUITE 800, MARIETTA, VA 20157) AND VITA (VED) TRUSS COUNCIL OF AMERICA, 6300 ENTERPRISE LN, MARIETTA, VA 20157 FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

JULIUS LEE'S
CONS. ENGINEERS P.A.

1455 SW 4th AVENUE
DELUPT BEACH, FL 33444-2301

No: 34859
STATE OF FLORIDA


REF TRULOX

DATE 11/26/03


DRWG CNTRULOX1103

-ENG JL

STRONG BACK DETAIL SYSTEM-42 OR FLAT TRUSS



ALTERNATE DETAIL FOR STRONG BACK WITH VERTICAL NOT LINING UP




JULIUS LEE'S
CONS. ENGINEERS P.A.
1426 SW 4th AVENUE
DEERAT BEACH, FL 33444-2161

No. 34669
STATE OF FLORIDA

ASCE 7-02: 130 MPH WIND SPEED, 15' MEAN HEIGHT, ENCLOSED, I = 1.00, EXPOSURE C

MAX GABLE VERTICAL LENGTH														
GABLE VERTICAL SPECIES	2x4 BRACE	NO BRACES	(1) 1x4 "L" BRACE *											
			GROUP A	GROUP B	GROUP A	GROUP B	GROUP A	GROUP B	GROUP A	GROUP B	GROUP A	GROUP B		
24" O.C.	SPF	#1 / #2	3' 4"	6' 10"	6' 0"	6' 11"	7' 1"	8' 3"	8' 6"	10' 10"	11' 2"	12' 11"	13' 3"	
		#3	3' 3"	4' 11"	4' 11"	6' 6"	6' 6"	8' 3"	8' 3"	10' 1"	10' 1"	12' 11"	12' 11"	
	HF	STUD	3' 3"	4' 11"	4' 11"	6' 5"	6' 5"	8' 3"	8' 3"	10' 0"	10' 0"	12' 11"	12' 11"	
		STANDARD	3' 3"	4' 2"	4' 2"	6' 6"	6' 6"	7' 5"	7' 5"	8' 8"	8' 8"	11' 6"	11' 6"	
	SP	#1	3' 8"	5' 10"	6' 3"	6' 11"	7' 5"	8' 3"	8' 11"	10' 10"	11' 8"	12' 11"	13' 11"	
		#2	3' 7"	5' 10"	6' 8"	6' 11"	7' 5"	8' 3"	8' 11"	10' 10"	11' 8"	12' 11"	13' 11"	
	DFL	#3	3' 6"	5' 0"	6' 0"	6' 8"	6' 8"	8' 3"	8' 8"	10' 4"	10' 4"	12' 11"	13' 7"	
		STUD	3' 6"	5' 0"	5' 0"	6' 7"	6' 7"	8' 3"	8' 8"	10' 3"	10' 3"	12' 11"	13' 7"	
	16" O.C.	SPF	STANDARD	3' 4"	4' 3"	4' 3"	5' 8"	6' 8"	7' 8"	8' 8"	10' 3"	10' 3"	12' 11"	13' 7"
			#1 / #2	3' 10"	6' 8"	6' 10"	7' 11"	8' 1"	9' 5"	9' 8"	12' 6"	12' 9"	14' 0"	14' 0"
HF		#3	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		STUD	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
SP		#1	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		#2	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
DFL		#3	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		STUD	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
12" O.C.		SPF	#1 / #2	3' 10"	6' 8"	6' 10"	7' 11"	8' 1"	9' 5"	9' 8"	12' 6"	12' 9"	14' 0"	14' 0"
			#3	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"
	HF	STUD	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		STANDARD	3' 4"	4' 3"	4' 3"	5' 8"	6' 8"	7' 8"	8' 8"	10' 3"	10' 3"	12' 11"	13' 7"	
	SP	#1	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		#2	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
	DFL	#3	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		STUD	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
	12" O.C.	SPF	#1 / #2	3' 10"	6' 8"	6' 10"	7' 11"	8' 1"	9' 5"	9' 8"	12' 6"	12' 9"	14' 0"	14' 0"
			#3	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"
HF		STUD	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		STANDARD	3' 4"	4' 3"	4' 3"	5' 8"	6' 8"	7' 8"	8' 8"	10' 3"	10' 3"	12' 11"	13' 7"	
SP		#1	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		#2	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
DFL		#3	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		STUD	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
12" O.C.		SPF	#1 / #2	3' 10"	6' 8"	6' 10"	7' 11"	8' 1"	9' 5"	9' 8"	12' 6"	12' 9"	14' 0"	14' 0"
			#3	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"
	HF	STUD	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		STANDARD	3' 4"	4' 3"	4' 3"	5' 8"	6' 8"	7' 8"	8' 8"	10' 3"	10' 3"	12' 11"	13' 7"	
	SP	#1	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		#2	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
	DFL	#3	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		STUD	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
	12" O.C.	SPF	#1 / #2	3' 10"	6' 8"	6' 10"	7' 11"	8' 1"	9' 5"	9' 8"	12' 6"	12' 9"	14' 0"	14' 0"
			#3	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"
HF		STUD	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		STANDARD	3' 4"	4' 3"	4' 3"	5' 8"	6' 8"	7' 8"	8' 8"	10' 3"	10' 3"	12' 11"	13' 7"	
SP		#1	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		#2	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
DFL		#3	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		STUD	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
12" O.C.		SPF	#1 / #2	3' 10"	6' 8"	6' 10"	7' 11"	8' 1"	9' 5"	9' 8"	12' 6"	12' 9"	14' 0"	14' 0"
			#3	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"
	HF	STUD	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		STANDARD	3' 4"	4' 3"	4' 3"	5' 8"	6' 8"	7' 8"	8' 8"	10' 3"	10' 3"	12' 11"	13' 7"	
	SP	#1	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		#2	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
	DFL	#3	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		STUD	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
	12" O.C.	SPF	#1 / #2	3' 10"	6' 8"	6' 10"	7' 11"	8' 1"	9' 5"	9' 8"	12' 6"	12' 9"	14' 0"	14' 0"
			#3	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"
HF		STUD	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		STANDARD	3' 4"	4' 3"	4' 3"	5' 8"	6' 8"	7' 8"	8' 8"	10' 3"	10' 3"	12' 11"	13' 7"	
SP		#1	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		#2	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
DFL		#3	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		STUD	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
12" O.C.		SPF	#1 / #2	3' 10"	6' 8"	6' 10"	7' 11"	8' 1"	9' 5"	9' 8"	12' 6"	12' 9"	14' 0"	14' 0"
			#3	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"
	HF	STUD	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		STANDARD	3' 4"	4' 3"	4' 3"	5' 8"	6' 8"	7' 8"	8' 8"	10' 3"	10' 3"	12' 11"	13' 7"	
	SP	#1	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		#2	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
	DFL	#3	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		STUD	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
	12" O.C.	SPF	#1 / #2	3' 10"	6' 8"	6' 10"	7' 11"	8' 1"	9' 5"	9' 8"	12' 6"	12' 9"	14' 0"	14' 0"
			#3	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"
HF		STUD	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		STANDARD	3' 4"	4' 3"	4' 3"	5' 8"	6' 8"	7' 8"	8' 8"	10' 3"	10' 3"	12' 11"	13' 7"	
SP		#1	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		#2	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
DFL		#3	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		STUD	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
12" O.C.		SPF	#1 / #2	3' 10"	6' 8"	6' 10"	7' 11"	8' 1"	9' 5"	9' 8"	12' 6"	12' 9"	14' 0"	14' 0"
			#3	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"
	HF	STUD	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		STANDARD	3' 4"	4' 3"	4' 3"	5' 8"	6' 8"	7' 8"	8' 8"	10' 3"	10' 3"	12' 11"	13' 7"	
	SP	#1	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		#2	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
	DFL	#3	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		STUD	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
	12" O.C.	SPF	#1 / #2	3' 10"	6' 8"	6' 10"	7' 11"	8' 1"	9' 5"	9' 8"	12' 6"	12' 9"	14' 0"	14' 0"
			#3	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"
HF		STUD	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		STANDARD	3' 4"	4' 3"	4' 3"	5' 8"	6' 8"	7' 8"	8' 8"	10' 3"	10' 3"	12' 11"	13' 7"	
SP		#1	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		#2	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
DFL		#3	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		STUD	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
12" O.C.		SPF	#1 / #2	3' 10"	6' 8"	6' 10"	7' 11"	8' 1"	9' 5"	9' 8"	12' 6"	12' 9"	14' 0"	14' 0"
			#3	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"
	HF	STUD	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
		STANDARD	3' 4"	4' 3"	4' 3"	5' 8"	6' 8"	7' 8"	8' 8"	10' 3"	10' 3"			



REFER TO CHART ABOVE FOR MAX GABLE VERTICAL LENGTH.

WARNING TRUSSES REQUIRE EXTENSIVE CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO 3031-1-43 GRADING COMPONENT SAFETY INFORMATION, PUBLISHED BY THE TRUSS PLATE INSTITUTE, 583 DOWNTOWN DR., SUITE 200, MANASSAS, VA 20108 AND VITA (WOOD TRUSS COUNCIL OF AMERICA, 6300 ENTERPRISE LN., WOODBRIDGE, VA 22191) FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, TOP CORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

JULIUS LEE'S
CONS. ENGINEERS P.A.
1455 6TH AVE. AUSTIN
DELRAN BEACH, FL 33444-8161

No. 34866
STATE OF FLORIDA

MAX. TOT. LD. 60 PSF
MAX. SPACING 24.0"

REF ASCE7-02-CAB13015
DATE 11/26/03
DRWG WTKA STD CABLE 15 E HT
-ENG

CABLE VERTICAL PLATE SIZES	
VERTICAL LENGTH	NO BRACE
LESS THAN 4' 0"	1x4 OR 2x3
GREATER THAN 4' 0" BUT LESS THAN 11' 8"	2x4
GREATER THAN 11' 8"	2x6

+ REFER TO COMMON TRUSS DESIGN FOR PLATE, SPACER, AND BRG. PLATES.

ATTACH EACH T" BRACE WITH 104 NUTS.
* FOR (1) T" BRACE, SPACE NUTS AT 8" O.C.
** FOR (2) T" BRACES, SPACE NUTS AT 3" O.C.
IN 18" END ZONES AND 6" O.C. BETWEEN ZONES.
T" BRACING MUST BE A MINIMUM OF 80% OF WEB MEMBER LENGTH.

PROVIDE UPRAIT CONNECTIONS FOR 136 PLG OVER CONTINUOUS BEARING (6 PSF TO DEAD LOAD).
CABLE END SUPPORTS LOAD FROM 4' 0" OUTDOCKERS WITH 8' 0" OVERHANG, OR 12" PLYWOOD OVERHANG.


CABLE TRUSS DETAIL NOTES:

BRACING GROUP SPECIES AND GRADES:	
GROUP A:	
SPRUCE-PINE-YR	RED-PTR
#1 / #2 STANDARD	#2 STUD
#3 STUD	#3 STANDARD
DOUGLAS FIR-LARCH	
#2 STUD	#3 STUD
STANDARD	STANDARD
GROUP B:	
RED-PTR	DOUGLAS FIR-LARCH
#1 & BTR	#1
STANDARD	#2


ASCE 7-02: 130 MPH WIND SPEED, 30' MEAN HEIGHT, ENCLOSED, I = 1.00, EXPOSURE C

MAX GABLE VERTICAL LENGTH														
CABLE VERTICAL SPACING	2x4 SPECIES	BRACE	NO BRACES	(1) 1x4 "L" BRACE *										
				GROUP A	GROUP B	GROUP A	GROUP B	GROUP A	GROUP B	GROUP A	GROUP B	GROUP A	GROUP B	
24" O.C.	SPF	#1 / #2	3' 2"	5' 6"	6' 8"	6' 6"	6' 9"	7' 10"	8' 0"	10' 3"	10' 7"	12' 3"	12' 7"	
		#3	3' 1"	4' 5"	4' 5"	5' 10"	5' 10"	7' 10"	7' 10"	9' 1"	9' 1"	12' 3"	12' 3"	
	HF	STUD	3' 1"	4' 6"	4' 6"	5' 10"	6' 10"	7' 10"	7' 10"	9' 1"	9' 1"	12' 3"	12' 3"	
		STANDARD	2' 11"	3' 9"	3' 9"	5' 0"	5' 0"	6' 9"	6' 9"	7' 10"	7' 10"	10' 7"	10' 7"	
	SP	#1	3' 6"	5' 6"	5' 11"	6' 8"	7' 0"	7' 10"	8' 5"	10' 3"	11' 1"	12' 3"	13' 2"	
		#2	3' 6"	5' 6"	5' 11"	6' 6"	7' 0"	7' 10"	8' 5"	10' 3"	11' 1"	12' 3"	13' 2"	
	DFL	#3	3' 3"	4' 6"	4' 6"	6' 0"	6' 0"	7' 10"	8' 1"	9' 4"	11' 1"	12' 3"	13' 2"	
		STUD	3' 3"	4' 6"	4' 6"	5' 11"	5' 11"	7' 10"	8' 0"	9' 3"	9' 3"	12' 3"	12' 6"	
	16" O.C.	SPF	#1 / #2	3' 0"	3' 10"	3' 10"	5' 1"	5' 1"	6' 11"	6' 11"	8' 0"	8' 0"	10' 10"	10' 10"
			#3	3' 8"	5' 4"	6' 8"	7' 6"	7' 6"	8' 11"	9' 2"	11' 8"	12' 1"	14' 0"	14' 0"
HF		STUD	3' 7"	5' 5"	5' 5"	7' 2"	7' 2"	8' 11"	8' 11"	11' 2"	11' 2"	14' 0"	14' 0"	
		STANDARD	3' 7"	5' 6"	6' 6"	7' 2"	7' 2"	8' 11"	8' 11"	11' 1"	11' 1"	14' 0"	14' 0"	
SP		#1	2' 0"	3' 4"	3' 10"	7' 8"	6' 2"	6' 2"	8' 3"	8' 3"	9' 7"	9' 7"	12' 11"	12' 11"
		#2	3' 11"	5' 4"	6' 10"	7' 8"	8' 1"	8' 11"	9' 7"	11' 9"	12' 8"	14' 0"	14' 0"	
DFL		#3	3' 9"	5' 6"	6' 7"	7' 4"	7' 4"	8' 11"	9' 6"	11' 6"	11' 6"	14' 0"	14' 0"	
		STUD	3' 8"	5' 6"	5' 6"	7' 3"	7' 3"	8' 11"	9' 5"	11' 4"	11' 4"	14' 0"	14' 0"	
12" O.C.		SPF	STANDARD	3' 8"	4' 9"	4' 9"	6' 3"	6' 3"	8' 5"	8' 5"	9' 9"	9' 9"	13' 3"	13' 3"
			#1 / #2	4' 0"	6' 11"	7' 2"	6' 3"	6' 6"	9' 10"	10' 1"	12' 11"	12' 11"	14' 0"	14' 0"
	HF	#3	3' 11"	5' 3"	6' 3"	6' 3"	6' 3"	8' 10"	9' 10"	12' 11"	12' 11"	14' 0"	14' 0"	
		STUD	3' 11"	5' 3"	6' 3"	6' 3"	6' 3"	8' 10"	9' 10"	12' 10"	12' 10"	14' 0"	14' 0"	
	SP	STANDARD	3' 11"	5' 4"	6' 4"	7' 1"	7' 1"	9' 6"	9' 6"	11' 1"	11' 1"	14' 0"	14' 0"	
		#1	4' 5"	6' 11"	7' 8"	8' 3"	8' 11"	9' 10"	10' 7"	12' 11"	13' 11"	14' 0"	14' 0"	
	DFL	#2	4' 4"	6' 11"	7' 6"	8' 3"	8' 11"	9' 10"	10' 7"	12' 11"	13' 11"	14' 0"	14' 0"	
		#3	4' 2"	6' 6"	6' 6"	8' 3"	8' 6"	9' 10"	10' 4"	12' 11"	13' 3"	14' 0"	14' 0"	
	STUD	#1	4' 2"	6' 4"	6' 4"	8' 3"	8' 6"	9' 10"	10' 4"	12' 11"	13' 1"	14' 0"	14' 0"	
		STANDARD	4' 0"	5' 6"	5' 6"	7' 3"	7' 3"	8' 9"	9' 9"	11' 4"	11' 4"	14' 0"	14' 0"	

TYPICAL ATTIC TRUSS BRACING




GABLE END TRUSS DETAIL





MINIMUM BC BRACING ON GABLE TRUSSES. OTHER PERMANENT BRACING DESIGNS BY ARCHITECT OR BOB

TYPICAL ALTERNATE BRACING DETAIL FOR EXTERIOR FLAT GIRDER TRUSS



TYPICAL WALL GIRDER VERTICAL WEB BRACING DETAIL



JULIUS LEE'S
CONS. ENGINEERS P.A.

1455 SW 435 AVENUE
DORRAT BRACE, FL 33444-2161

No. 34869
STATE OF FLORIDA

TOP CHORD 2X4 #2 OR BETTER
BOT CHORD 2X4 #2 OR BETTER
WEBS 2X4 #3 OR BETTER

PIGGYBACK DETAIL

REFER TO SEALED DESIGN FOR DASHED PLATES.

SPACE PIGGYBACK VERTICALS AT 4' OC MAX.

TOP AND BOTTOM CHORD SPLICES MUST BE STAGGERED SO THAT ONE SPLICE IS NOT DIRECTLY OVER ANOTHER.

PIGGYBACK BOTTOM CHORD MAY BE OMITTED. ATTACH VERTICAL WEBS TO TRUSS TOP CHORD WITH 1.5X3 PLATE.



ATTACH PURLINS TO TOP OF FLAT TOP CHORD. IF PIGGYBACK IS SOLID LUMBER OR THE BOTTOM CHORD IS OMITTED, PURLINS MAY BE APPLIED BENEATH THE TOP CHORD OF SUPPORTING TRUSS.

REFER TO ENGINEER'S SEALED DESIGN FOR REQUIRED PURLIN SPACING.

THIS DETAIL IS APPLICABLE FOR THE FOLLOWING WIND CONDITIONS:

110 MPH WIND, 30' MEAN HGT, ASCE 7-02, CLOSED BLDG, LOCATED ANYWHERE IN ROOF, 1 MI FROM COAST
CAT I, EXP C, WIND TC DL=6 PSF, WIND BC DL=6 PSF
110 MPH WIND, 30' MEAN HGT, ENG ENCLOSED BLDG, LOCATED ANYWHERE IN ROOF
WIND TC DL=6 PSF, WIND BC DL=6 PSF
130 MPH WIND, 30' MEAN HGT, ASCE 7-02, CLOSED BLDG, LOCATED ANYWHERE IN ROOF, CAT II, EXP C, WIND TC DL=6 PSF, WIND BC DL=6 PSF

FRONT FACE (B*) PLATES MAY BE OFFSET FROM BACK FACE PLATES AS LONG AS BOTH FACES ARE SPACED 4' OC MAX.




*ATTACH PIGGYBACK WITH 3X6 TRUSSES OR ALPINE PIGGYBACK SPECIAL PLATE.

REMARKS: TRUSSES REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO SEALED DESIGN FOR DASHED COMPONENTS, ERECT, INSPECTION, AND REPAIR. THIS DETAIL IS APPLICABLE FOR TRUSSES OF AMERICA, 630 ENTERPRISE LN, NATION, VT 05750 FOR SAFETY PRACTICES PRIOR TO PROCEEDING WITH THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

JOINT TYPE	SPANS UP TO		
	30'	36'	62'
A	2X4	2.5X4	3X6
B	4X6	5X6	5X6
C	1.5X3	1.5X4	1.5X4
D	5X4	5X5	5X6
E	4X6 OR 3X6 TRUSS AT 4' OC, ROTATED VERTICALLY		

ATTACH TRUSS PLATES WITH (B) 0.120" X 1.375" NAILS OR EQUAL, PER FACE PER PLY. (4) NAILS IN EACH MEMBER TO BE CONNECTED. REFER TO DRAWING 160 TL FOR TRUSS INFORMATION.

WEB LENGTH	WEB BRACING CHART
0' TO 7'9"	NO BRACING
7'9" TO 10'	1X4 "T" BRACE, SAME GRADE, SPECIES AS WEB MEMBER, OR BETTER, AND 80% LENGTH OF WEB MEMBER. ATTACH WITH 6d NAILS AT 4" OC.
10' TO 14'	2X4 "T" BRACE, SAME GRADE, SPECIES AS WEB MEMBER, OR BETTER, AND 80% LENGTH OF WEB MEMBER. ATTACH WITH 16d NAILS AT 4" OC.



THIS DRAWING REPLACES DRAWINGS 634.016 634.017 & 647.045

JULIUS LEE'S
CONS. ENGINEERS P.A.
1450 NW 4TH AVENUE
DEERFIELD BEACH, FL 33441-2161

MAX LOADING	55 PSF AT 1.33 DUR. FAC.	REF PIGGYBACK
	50 PSF AT 1.25 DUR. FAC.	DATE 09/12/07
SPACING	47 PSF AT 1.15 DUR. FAC.	DRG/MTEK STD PIGGY
	24.0"	-ENG JL




No. 34968
STATE OF FLORIDA

VALLEY TRUSS DETAIL


TOP CHORD 2X4 SP #2 OR SPF #1/#2 OR BETTER.
BOT CHORD 2X3(*) OR 2X4 SP #2N OR SPF #1/#2 OR BETTER.
WEBS 2X4 SP #3 OR BETTER.

- * 2X3 MAY BE RIPPED FROM A 2X6 (PITCHED OR SQUARE).
- ** ATTACH EACH VALLEY TO EVERY SUPPORTING TRUSS WITH:
(2) 16d BOX (0.135" X 3.5") NAILS TOE-NAILED FOR
FBC 2004 110 MPH, ASCE 7-02 110 MPH WIND OR (3) 16d FOR
ASCE 7-02 130 MPH WIND. 15' MEAN HEIGHT, ENCLOSED
BUILDING, EXP. C, RESIDENTIAL, WIND TC DL=5 PSF.

CUT FROM 2X6 OR
LARGER AS REQ'D





SUPPORTING TRUSSES AT 24" OC MAXIMUM SPACING.



SQUARE CUT
BOTTOM CHORD
VALLEY

UNLESS SPECIFIED ON ENGINEER'S SEALED DESIGN, APPLY 1X4 "T"-BRACE, 80%
LENGTH OF WEB, VALLEY WEB, SAME SPECIES AND GRADE OR BETTER, ATTACHED
WITH 8d BOX (0.113" X 2.5") NAILS AT 6" OC, OR CONTINUOUS LATERAL BRACING,
EQUALLY SPACED, FOR VERTICAL VALLEY WEBS GREATER THAN 7'9".
MAXIMUM VALLEY VERTICAL HEIGHT MAY NOT EXCEED 12'0".
TOP CHORD OF TRUSS BENEATH VALLEY SET MUST BE BRACED WITH:
PROPERLY ATTACHED, RATED SHEATHING APPLIED PRIOR TO VALLEY TRUSS
INSTALLATION
OR
PURLINS AT 24" OC OR AS OTHERWISE SPECIFIED ON ENGINEERS' SEALED DESIGN
OR
BY VALLEY TRUSSES USED IN LIEU OF PURLIN SPACING AS SPECIFIED ON
ENGINEERS' SEALED DESIGN.
*** NOTE THAT THE PURLIN SPACING FOR BRACING THE TOP CHORD OF THE TRUSS
BENEATH THE VALLEY IS MEASURED ALONG THE SLOPE OF THE TOP CHORD.
++ LARGER SPANS MAY BE BUILT AS LONG AS THE VERTICAL HEIGHT DOES
NOT EXCEED 12'0".
BOTTOM CHORD MAY BE SQUARE OR PITCHED CUT AS SHOWN.



NOTATION: TRUSSES REQUIRE OUTSIDE FACE IN FABRICATING, HANDLING, SUPPORT, INSTALLING AND
BRACING. REFER TO BEST PRACTICES FOR TRUSS DESIGN AND CONSTRUCTION. SEE DETAIL FOR TRUSS
PLATE INSTITUTE, 560 DODD RD., SUITE 200, HANSON, VT 55739 AND VITA CHORD TRUSS COUNCIL
OF AMERICA, 6300 ENTERPRISE LN, HANSON, VT 55739 FOR SAFETY PRACTICES PRIOR TO PERFORMING
THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, TOP CHORD SHALL HAVE PROPERLY ATTACHED
STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

JULIUS LEE'S
CONS. ENGINEERS P.A.

1655 5TH AVE. WIND
DEBART BLDG. FL. 5044-2nd

No. 34868
STATE OF FLORIDA

TC IL	20	20	PSF	REF	VALLEY DETAIL
TC DL	7	15	PSF	DATE	11/26/03
BC DL	5	5	PSF	DRWG	VALTRUSS1103
BC IL	0	0	PSF	-ENG	JL
TOT. LD.	32	40	PSF		
DURFAC.	1.25	1.25			
SPACING	24"				

THIS DRAWING REPLACES DRAWING A105

TOE-NAIL DETAIL

TOE-NAILS TO BE DRIVEN AT AN ANGLE OF APPROXIMATELY THIRTY DEGREES WITH THE PIECE AND STARTED APPROXIMATELY ONE-THIRD THE LENGTH OF THE NAIL FROM THE END OF THE MEMBER.

PER ANSI/AF&PA NDS-2001 SECTION 12.4.1 - EDGE DISTANCE, END DISTANCE, SPACING, EDGE DISTANCES, END DISTANCES AND SPACINGS FOR NAILS AND SPIKES SHALL BE SUFFICIENT TO PREVENT SPLITTING OF THE WOOD.



THE NUMBER OF TOE-NAILS TO BE USED IN A SPECIFIC APPLICATION IS DEPENDENT UPON PROPERTIES FOR THE CHORD SIZE, LUMBER SPECIES AND NAIL TYPE. PROPER CONSTRUCTION PRACTICES AS WELL AS GOOD JUDGEMENT SHOULD DETERMINE THE NUMBER OF NAILS TO BE USED.

THIS DETAIL DISPLAYS A TOE-NAILED CONNECTION FOR JACK FRAMING INTO A SINGLE OR DOUBLE PLY SUPPORTING GIRDER.

MAXIMUM VERTICAL RESISTANCE OF 16d (0.162"x3.5") COMMON TOE-NAILS

NUMBER OF TOE-NAILS	SOUTHERN PINE		DOUGLAS FIR-LARCH		HEM-FIR		SPRUCE PINE FIR	
	1 PLY	2 PILES	1 PLY	2 PILES	1 PLY	2 PILES	1 PLY	2 PILES
2	197#	256#	181#	234#	156#	203#	154#	199#
3	296#	383#	271#	351#	234#	304#	230#	298#
4	394#	511#	361#	468#	312#	406#	307#	397#
5	493#	639#	452#	585#	390#	507#	384#	496#

ALL VALUES MAY BE MULTIPLIED BY APPROPRIATE DURATION OF LOAD FACTOR.



THIS DRAWING REPLACES DRAWING 784040

REMARKS: TRUSSES REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO BEST 1-83 CHAIRING COMPONENT SAFETY INFORMATION, PUBLISHED BY THE TRUSS PLATE INSTITUTE, 388 YOUNGER RD., SUITE 200, MADISON, VT. 05719 AND VTCI (WOOD) TRUSS COUNCIL OF AMERICA, 6800 ENTERPRISE LN, MARIETTA, VT 05759 FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, TOP CHORD SHALL HAVE PERMANENTLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PERMANENTLY ATTACHED ROOF CEILING.

JULIUS LEE'S
CONS. ENGINEERS P.A.
1400 ST 4TH AVENUE
DELRAY BEACH, FL 33444-2161


No. 34868
STATE OF FLORIDA

TC LL	PSF	REF	TOE-NAIL
TC DL	PSF	DATE	09/12/07
BC DL	PSF	DRWG	CNTONALL103
BC LL	PSF	-ENG	JL
TOT. LD.	PSF		
DUR. FAC.	1.00		
SPACING			

1/2" DIAMETER BOLT SPACING FOR LOAD APPLIED PARALLEL TO GRAIN.

* GRADE AND SPECIES AS SPECIFIED ON THE ALPINE DESIGN.
BOLT HOLES SHALL BE A MINIMUM OF 1/32" TO A MAXIMUM OF 1/16" LARGER THAN BOLT DIAMETER.

TYPICAL LOCATION OF 1/2" DIAMETER THRU BOLTS. BOLT QUANTITIES AS NOTED ON SEALED DESIGN MUST BE APPLIED IN ONE OF THE PATTERNS SHOWN BELOW.
WASHERS REQUIRED UNDER BOLT HEAD AND NUT



2X6 DETAIL

2X8 DETAIL

THIS DRAWING REPLACES DRAWING A628.016

WARNING: TRUSSES REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO ACST I-83 BUILDING COMPONENT SAFETY INFORMATION, PUBLISHED BY THE TRUSS PLATE INSTITUTE, 583 DOWNTOWN DR., SUITE 204, MADISON, VA. 22729 AND VITA CYCLO TRUSS COUNCIL OF AMERICA, 6500 ENTERPRISE LN, MADISON, WI 53729 FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

JULIUS LEE'S
CONS. ENGINEERS P.A.
1400 RT 424 AVENUE
DELRAY BEACH, FL 33444-2161

TC LL	PSF	REF	BOLT SPACING
TC DL	PSF	DATE	11/26/03
BC DL	PSF	DRWG	CNBOLTP1103
BC LL	PSF	-ENG	JL
TOT. LD.	PSF		
DUR. FAC.			
SPACING			

No. 34869
STATE OF FLORIDA

TRULOX CONNECTION DETAIL




11 GAUGE (0.120" X 1.375") NAILS REQUIRED FOR TRULOX PLATE ATTACHMENT. FILL ROWS COMPLETELY WHERE SHOWN (Φ).

* NAILS MAY BE OMITTED FROM THESE ROWS.

THIS DETAIL MAY BE USED WITH SO. PINE, DOUGLAS-FIR OR HEM-FIR CHORDS WITH A MINIMUM 1.00 DURATION OF LOAD OR SPRUCE-PINE-FIR CHORDS WITH A MINIMUM 1.15 DURATION OF LOAD. CHORD SIZE OF BOTH TRUSSES MUST EXCEED THE TRULOX PLATE WIDTH.

TRULOX PLATE IS CENTERED ON THE CHORDS AND BENT BETWEEN NAIL ROWS.

REFER TO ENGINEER'S SEALED DESIGN REFERENCING THIS DETAIL FOR LUMBER, PLATES, AND OTHER INFORMATION NOT SHOWN.



TRULOX PLATE SIZE	REQUIRED NAILS PER TRUSS	MAXIMUM LOAD UP OR DOWN
3X6	9	350#
5X6	15	990#

MINIMUM 3X6 TRULOX PLATE

MINIMUM 5X6 TRULOX PLATE

THIS DRAWING REPLACES DRAWINGS 1.158.989 1.158.989/R 1.154.844 1.152.217 1.152.017 1.159.154 & 1.151.524

**WARNING: TRUSSES REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SUPPORTING, INSTALLING AND BRACING. REFER TO ACES 1-63 (BUILDING COMPONENT SAFETY INFORMATION, PUBLISHED BY THE TRUSS PLATE INSTITUTE, 384 JENNIFER DR., SUITE 200, WOODBRIDGE, VA 22192) AND VITA (VEDI TRUSS COUNCIL OF AMERICA, 6300 ENTERPRISE LN, WOODBRIDGE, VA 22192) FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, THE CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

JULIUS LEE'S
CONS. ENGINEERS P.A.

1455 SW 4th AVENUE
DELRAY BEACH, FL 33444-2101

No. 34869
STATE OF FLORIDA


REF TRULOX

DATE 11/26/03


DRWG CNTRULOX1103

-ENG JL

STRONG BACK DETAIL SYSTEM-42 OR FLAT TRUSS




ALTERNATE DETAIL FOR STRONG BACK WITH VERTICAL NOT LINING UP



JULIUS LEE'S
CONS. ENGINEERS P.A.
1456 SW 41st AVENUE
OCEAR BEACH, FL 33444-2161

No: 34869
STATE OF FLORIDA

6/12 PITCH - 2'0" O/H



BEARING HEIGHT SCHEDULE

8'-1 1/8"

ALL
FLAT
CLG'S

NOTES:

- 1) REFER TO THE RECOMMENDATIONS FOR THE INSTALLATION AND TYPICAL BRACKING REFER TO ENGINEERED DRAWINGS FOR PERMANENT BRACKING REQUIRED.
- 2) ALL TRUSSES (INCLUDING TRUSSES UNDER VALLEY FRAMING) MUST BE COMPLETELY DECKED OR REFER TO DETAIL FOR ALTERNATE BRACKING REQUIREMENTS.
- 3) ALL VALLEYS ARE TO BE CONVENTIONALLY FRAMED BY DOUBLE.
- 4) ALL TRUSSES ARE DESIGNED FOR 7' o.c. MAXIMUM SPACING UNLESS OTHERWISE NOTED.
- 5) ALL WALLS SUPPORTING R.A. TRUSSES MUST BE DESIGNED TO BE LOUD BEYOND UNLESS OTHERWISE NOTED.
- 6) TRUSSES MUST BE DETAILLED WITH THE TOP BEAMS UP.
- 7) ALL ROOF TRUSSES UNLESS TO BE SUPPORTED BY WALLS OR OTHER TRUSSES MUST BE SUPPORTED BY WALLS OR OTHER TRUSSES UNLESS OTHERWISE NOTED.
- 8) BEAM/CEILING TRUSSES TO BE SUPPORTED BY WALLS OR OTHER TRUSSES UNLESS OTHERWISE NOTED.

SHOP DRAWING APPROVAL

THIS DRAWING IS THE SOLE SOURCE FOR FABRICATION OF TRUSSES AND RAFTERS. ALL PERMITS, MODIFICATIONS, OR OTHER TRUSSES, LAYOUTS, REVISIONS AND APPROVAL OF THIS LAYOUT MUST BE RECEIVED BEFORE ANY TRUSSES WILL BE BUILT. VERIFY ALL CONDITIONS TO MAKE AGAINST OWNERS THAT WILL RESULT IN EXTRA CHARGES TO YOU.

Approved Drawing Date: _____

Approved By: _____

Builders
FirstSource
Burrell

PHONE: 904-437-3244 FAX: 904-437-3994

JACKSONVILLE

PHONE: 904-772-6100 FAX: 904-772-1873

Lake City

PHONE: 386-755-6844 FAX: 386-755-7873

Sanford

PHONE: 407-322-0094 FAX: 407-322-5993

RICHARD KEEN

COUNTRY CREEK LOT 9

CUSTOM

DATE: 1-23-08

BY: K.L.H.

PROJECT: L266503

Notice of Treatment

Applicator: Florida Pest Control & Chemical Co. (www.flapest.com)

Address: 536 SE BAY AVE

City LAKE CITY **Phone** 750-1703

Site Location: Subdivision _____

Lot # _____ **Block#** _____ **Permit #** 27113

Address _____

Product used

Active Ingredient

% Concentration

☐ Premise Imidacloprid 0.1%

☒ Termidor Fipronil 0.12%

☐ Bora-Care Disodium Octaborate Tetrahydrate 23.0%

Type treatment:

☒ Soil

☐ Wood

Area Treated

Square feet

Linear feet

Gallons Applied

FRONT ENTRY 8x4	128	50	64
BACK PATIO			
DRIVEWAY Apron			

As per Florida Building Code 104.2.6 – If soil chemical barrier method for termite prevention is used, final exterior treatment shall be completed prior to final building approval.

If this notice is for the final exterior treatment, initial this line _____.

10/2/08
Date

1030
Time

F254 GUNNAY
Print Technician's Name

Remarks: _____

Applicator - White

Permit File - Canary

Permit Holder - Pink

10/05



Notice of Treatment

Applicator: Florida Pest Control & Chemical Co. (www.flapest.com)

Address: 536 SE Bora Ave

City LC **Phone** 7521703

Site Location: Subdivision _____

Lot # 9 **Block#** _____ **Permit #** 27113

Address 285 SE Bream Loop

Product used

Active Ingredient

% Concentration

☒ Premise Imidacloprid 0.1%

☐ Termidor Fipronil 0.12%

☐ Bora-Care Disodium Octaborate Tetrahydrate 23.0%

Type treatment:

☒ Soil

☐ Wood

Area Treated

Square feet

Linear feet

Gallons Applied

DWL

1650

174

85

As per Florida Building Code 104.2.6 – If soil chemical barrier method for termite prevention is used, final exterior treatment shall be completed prior to final building approval.

If this notice is for the final exterior treatment, initial this line _____.

9/22/08

Date

1500

Time

F254

Print Technician's Name

Remarks: _____

Applicator - White

Permit File - Canary

Permit Holder - Pink