

FLORIDA ENERGY EFFICIENCY CODE FOR BUILDING CONSTRUCTION

Florida Department of Business and Professional Regulation - Residential Performance Method

Project Name: Carter Residence Street: City, State, Zip: Lake City , FL , Owner: Design Location: FL, Gainesville	Builder Name: Permit Office: Permit Number: Jurisdiction: County: Columbia (Florida Climate Zone 2)
--	---

<table style="width: 100%;"> <tr> <td style="width: 30%;">1. New construction or existing</td> <td style="width: 30%;">New (From Plans)</td> <td style="width: 40%;"></td> </tr> <tr> <td>2. Single family or multiple family</td> <td>Single-family</td> <td></td> </tr> <tr> <td>3. Number of units, if multiple family</td> <td>1</td> <td></td> </tr> <tr> <td>4. Number of Bedrooms</td> <td>3</td> <td></td> </tr> <tr> <td>5. Is this a worst case?</td> <td>No</td> <td></td> </tr> <tr> <td>6. Conditioned floor area above grade (ft²)</td> <td>1314</td> <td></td> </tr> <tr> <td>Conditioned floor area below grade (ft²)</td> <td>0</td> <td></td> </tr> <tr> <td>7. Windows(128.0 sqft.)</td> <td>Description</td> <td>Area</td> </tr> <tr> <td>a. U-Factor:</td> <td>DbI, U=0.33</td> <td>128.00 ft²</td> </tr> <tr> <td>SHGC:</td> <td>SHGC=0.22</td> <td></td> </tr> <tr> <td>b. U-Factor:</td> <td>N/A</td> <td>ft²</td> </tr> <tr> <td>SHGC:</td> <td></td> <td></td> </tr> <tr> <td>c. U-Factor:</td> <td>N/A</td> <td>ft²</td> </tr> <tr> <td>SHGC:</td> <td></td> <td></td> </tr> <tr> <td>d. U-Factor:</td> <td>N/A</td> <td>ft²</td> </tr> <tr> <td>SHGC:</td> <td></td> <td></td> </tr> <tr> <td>Area Weighted Average Overhang Depth:</td> <td>3.469 ft.</td> <td></td> </tr> <tr> <td>Area Weighted Average SHGC:</td> <td>0.220</td> <td></td> </tr> <tr> <td>8. Floor Types (1314.0 sqft.)</td> <td>Insulation</td> <td>Area</td> </tr> <tr> <td>a. Slab-On-Grade Edge Insulation</td> <td>R=0.0</td> <td>1314.00 ft²</td> </tr> <tr> <td>b. N/A</td> <td>R=</td> <td>ft²</td> </tr> <tr> <td>c. N/A</td> <td>R=</td> <td>ft²</td> </tr> </table>	1. New construction or existing	New (From Plans)		2. Single family or multiple family	Single-family		3. Number of units, if multiple family	1		4. Number of Bedrooms	3		5. Is this a worst case?	No		6. Conditioned floor area above grade (ft²)	1314		Conditioned floor area below grade (ft²)	0		7. Windows(128.0 sqft.)	Description	Area	a. U-Factor:	DbI, U=0.33	128.00 ft²	SHGC:	SHGC=0.22		b. U-Factor:	N/A	ft²	SHGC:			c. U-Factor:	N/A	ft²	SHGC:			d. U-Factor:	N/A	ft²	SHGC:			Area Weighted Average Overhang Depth:	3.469 ft.		Area Weighted Average SHGC:	0.220		8. Floor Types (1314.0 sqft.)	Insulation	Area	a. Slab-On-Grade Edge Insulation	R=0.0	1314.00 ft²	b. N/A	R=	ft²	c. N/A	R=	ft²	<table style="width: 100%;"> <tr> <td style="width: 30%;">9. Wall Types (1640.7 sqft.)</td> <td style="width: 30%;">Insulation</td> <td style="width: 40%;">Area</td> </tr> <tr> <td>a. Frame - Wood, Exterior</td> <td>R=13.0</td> <td>1346.70 ft²</td> </tr> <tr> <td>b. Frame - Wood, Adjacent</td> <td>R=13.0</td> <td>294.00 ft²</td> </tr> <tr> <td>c. N/A</td> <td>R=</td> <td>ft²</td> </tr> <tr> <td>d. N/A</td> <td>R=</td> <td>ft²</td> </tr> <tr> <td>10. Ceiling Types (1314.0 sqft.)</td> <td>Insulation</td> <td>Area</td> </tr> <tr> <td>a. Under Attic (Vented)</td> <td>R=30.0</td> <td>1314.00 ft²</td> </tr> <tr> <td>b. N/A</td> <td>R=</td> <td>ft²</td> </tr> <tr> <td>c. N/A</td> <td>R=</td> <td>ft²</td> </tr> <tr> <td>11. Ducts</td> <td></td> <td>R ft²</td> </tr> <tr> <td>a. Sup: Attic, Ret: Attic, AH: Garage</td> <td></td> <td>6 262.8</td> </tr> <tr> <td>12. Cooling systems</td> <td>kBtu/hr</td> <td>Efficiency</td> </tr> <tr> <td>a. Central Unit</td> <td>30.0</td> <td>SEER:15.00</td> </tr> <tr> <td>13. Heating systems</td> <td>kBtu/hr</td> <td>Efficiency</td> </tr> <tr> <td>a. Electric Heat Pump</td> <td>30.0</td> <td>HSPF:8.50</td> </tr> <tr> <td>14. Hot water systems</td> <td></td> <td></td> </tr> <tr> <td>a. Electric</td> <td></td> <td>Cap: 40 gallons</td> </tr> <tr> <td>b. Conservation features</td> <td></td> <td>EF: 0.920</td> </tr> <tr> <td></td> <td></td> <td>None</td> </tr> <tr> <td>15. Credits</td> <td></td> <td>CF, Pstat</td> </tr> </table>	9. Wall Types (1640.7 sqft.)	Insulation	Area	a. Frame - Wood, Exterior	R=13.0	1346.70 ft²	b. Frame - Wood, Adjacent	R=13.0	294.00 ft²	c. N/A	R=	ft²	d. N/A	R=	ft²	10. Ceiling Types (1314.0 sqft.)	Insulation	Area	a. Under Attic (Vented)	R=30.0	1314.00 ft²	b. N/A	R=	ft²	c. N/A	R=	ft²	11. Ducts		R ft²	a. Sup: Attic, Ret: Attic, AH: Garage		6 262.8	12. Cooling systems	kBtu/hr	Efficiency	a. Central Unit	30.0	SEER:15.00	13. Heating systems	kBtu/hr	Efficiency	a. Electric Heat Pump	30.0	HSPF:8.50	14. Hot water systems			a. Electric		Cap: 40 gallons	b. Conservation features		EF: 0.920			None	15. Credits		CF, Pstat
1. New construction or existing	New (From Plans)																																																																																																																														
2. Single family or multiple family	Single-family																																																																																																																														
3. Number of units, if multiple family	1																																																																																																																														
4. Number of Bedrooms	3																																																																																																																														
5. Is this a worst case?	No																																																																																																																														
6. Conditioned floor area above grade (ft²)	1314																																																																																																																														
Conditioned floor area below grade (ft²)	0																																																																																																																														
7. Windows(128.0 sqft.)	Description	Area																																																																																																																													
a. U-Factor:	DbI, U=0.33	128.00 ft²																																																																																																																													
SHGC:	SHGC=0.22																																																																																																																														
b. U-Factor:	N/A	ft²																																																																																																																													
SHGC:																																																																																																																															
c. U-Factor:	N/A	ft²																																																																																																																													
SHGC:																																																																																																																															
d. U-Factor:	N/A	ft²																																																																																																																													
SHGC:																																																																																																																															
Area Weighted Average Overhang Depth:	3.469 ft.																																																																																																																														
Area Weighted Average SHGC:	0.220																																																																																																																														
8. Floor Types (1314.0 sqft.)	Insulation	Area																																																																																																																													
a. Slab-On-Grade Edge Insulation	R=0.0	1314.00 ft²																																																																																																																													
b. N/A	R=	ft²																																																																																																																													
c. N/A	R=	ft²																																																																																																																													
9. Wall Types (1640.7 sqft.)	Insulation	Area																																																																																																																													
a. Frame - Wood, Exterior	R=13.0	1346.70 ft²																																																																																																																													
b. Frame - Wood, Adjacent	R=13.0	294.00 ft²																																																																																																																													
c. N/A	R=	ft²																																																																																																																													
d. N/A	R=	ft²																																																																																																																													
10. Ceiling Types (1314.0 sqft.)	Insulation	Area																																																																																																																													
a. Under Attic (Vented)	R=30.0	1314.00 ft²																																																																																																																													
b. N/A	R=	ft²																																																																																																																													
c. N/A	R=	ft²																																																																																																																													
11. Ducts		R ft²																																																																																																																													
a. Sup: Attic, Ret: Attic, AH: Garage		6 262.8																																																																																																																													
12. Cooling systems	kBtu/hr	Efficiency																																																																																																																													
a. Central Unit	30.0	SEER:15.00																																																																																																																													
13. Heating systems	kBtu/hr	Efficiency																																																																																																																													
a. Electric Heat Pump	30.0	HSPF:8.50																																																																																																																													
14. Hot water systems																																																																																																																															
a. Electric		Cap: 40 gallons																																																																																																																													
b. Conservation features		EF: 0.920																																																																																																																													
		None																																																																																																																													
15. Credits		CF, Pstat																																																																																																																													

Glass/Floor Area: 0.097	Total Proposed Modified Loads: 45.83	PASS
	Total Baseline Loads: 46.95	

I hereby certify that the plans and specifications covered by this calculation are in compliance with the Florida Energy Code. PREPARED BY: _____ DATE: <u>4-9-20</u> I hereby certify that this building, as designed, is in compliance with the Florida Energy Code. OWNER/AGENT: _____ DATE: _____	Review of the plans and specifications covered by this calculation indicates compliance with the Florida Energy Code. Before construction is completed this building will be inspected for compliance with Section 553.908 Florida Statutes.  BUILDING OFFICIAL: _____ DATE: _____
---	---

- Compliance requires certification by the air handler unit manufacturer that the air handler enclosure qualifies as certified factory-sealed in accordance with R403.3.2.1.
- Compliance requires an Air Barrier and Insulation Inspection Checklist in accordance with R402.4.1.1 and this project requires an envelope leakage test report with envelope leakage no greater than 5.00 ACH50 (R402.4.1.2).

INPUT SUMMARY CHECKLIST REPORT

PROJECT

Title:	Carter Residence	Bedrooms:	3	Address Type:	Street Address
Building Type:	User	Conditioned Area:	2922	Lot #	
Owner Name:		Total Stories:	1	Block/Subdivision:	
# of Units:	1	Worst Case:	No	PlatBook:	
Builder Name:		Rotate Angle:	0	Street:	
Permit Office:		Cross Ventilation:		County:	Columbia
Jurisdiction:		Whole House Fan:		City, State, Zip:	Lake City , FL ,
Family Type:	Single-family				
New/Existing:	New (From Plans)				
Comment:					

CLIMATE

✓	Design Location	TMY Site	Design Temp 97.5 %	2.5 %	Int Design Temp Winter	Summer	Heating Degree Days	Design Moisture	Daily Temp Range
_____	FL, Gainesville	FL_GAINESVILLE_REGI	32	92	70	75	1305.5	51	Medium

BLOCKS

Number	Name	Area	Volume
1	Block1	1314	11826

SPACES

Number	Name	Area	Volume	Kitchen	Occupants	Bedrooms	Infil ID	Finished	Cooled	Heated
1	Main	1314	11826	Yes	6	3	1	Yes	Yes	Yes

FLOORS

✓	#	Floor Type	Space	Perimeter	R-Value	Area		Tile	Wood	Carpet
_____	1	Slab-On-Grade Edge Insulatio	Main	182 ft	0	1314 ft²	----	0.33	0.33	0.34

ROOF

✓	#	Type	Materials	Roof Area	Gable Area	Roof Color	Rad Barr	Solar Absor.	SA Tested	Emitt	Emitt Tested	Deck Insul.	Pitch (deg)
_____	1	Gable or shed	Composition shingles	1522 ft²	384 ft²	Medium	N	0.85	No	0.9	No	0	30.3

ATTIC

✓	#	Type	Ventilation	Vent Ratio (1 in)	Area	RBS	IRCC
_____	1	Full attic	Vented	300	1314 ft²	N	N

CEILING

✓	#	Ceiling Type	Space	R-Value	Ins Type	Area	Framing Frac	Truss Type
_____	1	Under Attic (Vented)	Main	30	Blown	1314 ft²	0.11	Wood

INPUT SUMMARY CHECKLIST REPORT

WALLS

✓	#	Ornt	Adjacent To	Wall Type	Space	Cavity R-Value	Width Ft	In	Height Ft	In	Area	Sheathing R-Value	Framing Fraction	Solar Absor.	Below Grade%
___	1	N	Exterior	Frame - Wood	Main	13	20	8	9		186.0 ft²		0.23	0.75	0
___	2	E	Exterior	Frame - Wood	Main	13	6		9		54.0 ft²		0.23	0.75	0
___	3	N	Exterior	Frame - Wood	Main	13	17	8	10		176.7 ft²		0.23	0.75	0
___	4	W	Exterior	Frame - Wood	Main	13	6		9		54.0 ft²		0.23	0.75	0
___	5	N	Exterior	Frame - Wood	Main	13	11	4	9		102.0 ft²		0.23	0.75	0
___	6	E	Exterior	Frame - Wood	Main	13	33	4	9		300.0 ft²		0.23	0.75	0
___	7	S	Exterior	Frame - Wood	Main	13	11	4	9		102.0 ft²		0.23	0.75	0
___	8	S	Exterior	Frame - Wood	Main	13	18		10		180.0 ft²		0.23	0.75	0
___	9	E	Exterior	Frame - Wood	Main	13	21	4	9		192.0 ft²		0.23	0.75	0
___	10	S	Garage	Frame - Wood	Main	13	32	8	9		294.0 ft²		0.23	0.75	0

DOORS

✓	#	Ornt	Door Type	Space	Storms	U-Value	Width Ft	In	Height Ft	In	Area
___	1	N	Insulated	Main	None	.4	6		6	8	40 ft²
___	2	S	Insulated	Main	None	.4	5		8		40 ft²
___	3	S	Insulated	Main	None	.4	3		6	8	20 ft²

WINDOWS

Orientation shown is the entered, Proposed orientation.

✓	#	Ornt	Wall ID	Frame	Panes	NFRC	U-Factor	SHGC	Imp	Area	Overhang Depth	Separation	Int Shade	Screening
___	1	N	1	Vinyl	Low-E Double	Yes	0.33	0.22	N	24.0 ft²	1 ft 6 in	1 ft 4 in	None	None
___	2	N	3	Vinyl	Low-E Double	Yes	0.33	0.22	N	12.0 ft²	7 ft 6 in	1 ft 4 in	None	None
___	3	N	5	Vinyl	Low-E Double	Yes	0.33	0.22	N	18.0 ft²	1 ft 6 in	1 ft 4 in	None	None
___	4	S	7	Vinyl	Low-E Double	Yes	0.33	0.22	N	18.0 ft²	1 ft 6 in	1 ft 4 in	None	None
___	5	S	8	Vinyl	Low-E Double	Yes	0.33	0.22	N	36.0 ft²	6 ft 6 in	1 ft 4 in	None	None
___	6	E	9	Vinyl	Low-E Double	Yes	0.33	0.22	N	8.0 ft²	1 ft 6 in	1 ft 4 in	None	None
___	7	E	9	Vinyl	Low-E Double	Yes	0.33	0.22	N	12.0 ft²	1 ft 6 in	1 ft 4 in	None	None

GARAGE

✓	#	Floor Area	Ceiling Area	Exposed Wall Perimeter	Avg. Wall Height	Exposed Wall Insulation
___	1	516.675 ft²	516.675 ft²	70.667 ft	9 ft	1

INFILTRATION

#	Scope	Method	SLA	CFM 50	ELA	EqLA	ACH	ACH 50
1	Wholehouse	Proposed ACH(50)	.000286	985.5	54.1	101.75	.1128	5

INPUT SUMMARY CHECKLIST REPORT

HEATING SYSTEM

☒	#	System Type	Subtype	Speed	Efficiency	Capacity	Block	Ducts
☐	1	Electric Heat Pump/	None	Singl	HSPF:8.5	30 kBtu/hr	1	sys#1

COOLING SYSTEM

☒	#	System Type	Subtype	Subtype	Efficiency	Capacity	Air Flow	SHR	Block	Ducts
☐	1	Central Unit/	None	Singl	SEER: 15	30 kBtu/hr	900 cfm	0.85	1	sys#1

HOT WATER SYSTEM

☒	#	System Type	SubType	Location	EF	Cap	Use	SetPnt	Conservation
☐	1	Electric	None	Garage	0.92	40 gal	60 gal	120 deg	None

SOLAR HOT WATER SYSTEM

☒	FSEC	Company Name	System Model #	Collector Model #	Collector Area	Storage Volume	FEF
☐	None	None			ft ²		

DUCTS

☒	#	Location	Supply R-Value	Area	Location	Return Area	Leakage Type	Air Handler	CFM 25 TOT	CFM25 OUT	QN	RLF	HVAC # Heat	Coil
☐	1	Attic	6	262.8 ft	Attic	65.7 ft ²	Default Leakage	Garage	(Default)	(Default)			1	1

TEMPERATURES

Programable Thermostat: Y

Ceiling Fans:

Cooling	☐ Jan	☐ Feb	☐ Mar	☐ Apr	☐ May	☒ Jun	☒ Jul	☒ Aug	☒ Sep	☐ Oct	☐ Nov	☐ Dec
Heating	☒ Jan	☒ Feb	☒ Mar	☒ Apr	☐ May	☐ Jun	☐ Jul	☐ Aug	☐ Sep	☒ Oct	☒ Nov	☒ Dec
Venting	☐ Jan	☐ Feb	☒ Mar	☒ Apr	☐ May	☐ Jun	☐ Jul	☐ Aug	☐ Sep	☒ Oct	☒ Nov	☐ Dec

Thermostat Schedule: HERS 2006 Reference

Schedule Type		1	2	3	4	5	6	7	8	9	10	11	12
Cooling (WD)	AM	78	78	78	78	78	78	78	78	80	80	80	80
	PM	80	80	80	80	78	78	78	78	78	78	78	78
Cooling (WEH)	AM	78	78	78	78	78	78	78	78	80	80	80	80
	PM	80	80	80	80	78	78	78	78	78	78	78	78
Heating (WD)	AM	65	65	65	65	65	65	65	68	68	68	68	68
	PM	68	68	68	68	68	68	68	68	68	68	68	68
Heating (WEH)	AM	65	65	65	65	65	65	65	68	68	68	68	68
	PM	68	68	68	68	68	68	68	68	68	68	68	68

MASS

Mass Type	Area	Thickness	Furniture Fraction	Space
Default(8 lbs/sq.ft.	0 ft ²	0 ft	0.3	Main