

Items to Include-



#### COLUMBIA COUNTY BUILDING DEPARTMENT RESIDENTIAL CHECK LIST

MINIMUM PLAN REQUIREMENTS: FLORIDA BUILDING CODE RESIDENTIAL 2014 EFFECTIVE 1 JULY 2015 AND THE NATIONAL ELECTRICAL CODE 2011 EFFECTIVE 1 JULY 2015

ALL REQUIREMENTS ARE SUBJECT TO CHANGE

ALL BUILDING PLANS MUST INDICATE COMPLIANCE WITH THE CURRENT 2014 FLORIDA BUILDING CODES RESIDENTIAL, EFFECTIVE 1 JULY 2015. NATIONAL ELECTRICAL CODE 2011 EFFECTIVE 1 JULY 2015. ALL PLANS OR DRAWINGS SHALL PROVIDE CALCULATIONS AND DETAILS THAT HAVE THE SEAL AND SIGNATURE OF A CERTIFIED ARCHITECT OR ENGINEER REGISTERED IN THE STATE OF FLORIDA, OR ALTERNATE METHODOLOGIES, APPROVED BY THE STATE OF FLORIDA BUILDING COMMISSION FOR ONE-AND-TWO FAMILY DWELLINGS.

FOR DESIGN PURPOSES THE FOLLOWING BASIC WIND SPEEDS ARE PER FLORIDA BUILDING CODE FIGURE 1609-A
THROUGH 1609-C ULTIMATE DESIGN WIND SPEEDS FOR RISK CATEGORY AND BUILDINGS AND OTHER STRUCTURES
Revised 12/2016

GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL		) A	Marked as Applicable	
1	Two (2) complete sets of plans containing the following:		om the Dr	opbox
2 All drawings must be clear, concise, drawn to scale, details that are not used shall be marked void			es	
		-	ye (	
	Condition space (Sq. Ft.) 2157 Total (Sq. Ft.) under roof 3048	YES	, 40	N/A
De	esigners name and signature shall be on all documents and a licensed architect or engineer, signature an affixed to the plans and documents as per the FLORIDA BUILDING CODES RESIDENTIAL R101.2 ite Plan information including:	d official ( 2.1	embossed s	eal shal
4	Dimensions of lot or parcel of land	. 1	lo C	
5	Dimensions of all building set backs	. 1	200	$\dashv$
6	Location of all other structures (include square footage of structures) on parcel, existing or proposed well and septic tank and all utility easements.		Yes	$\exists$
7	Provide a full legal description of property.		Wac	=
W	ind-load Engineering Summary, calculations and any details are required.  GENERAL REQUIREMENTS:	Iten	ns to Includ	e-
	APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL		n Box shall Marked as oplicable	be
8	Plans or specifications must show compliance with FBCR Chapter 3	YES	NO	N/A
	,	Select F	rom the Dr	opbox
9	Basic wind speed (3-second gust), miles per hour	- V	200	
10	(Wind exposure – if more than one wind exposure		1-0	$\neg$
	is used, the wind exposure and applicable wind direction shall be indicated)	I Y	ey	
11	Wind importance factor and nature of occupancy	E	28	
12	The applicable internal pressure coefficient, Components and Cladding	- 1	res	
$\neg$	The design wind pressure in terms of psf (kN/m²), to be used for the design of exterior component,			
13	cladding materials not specifally designed by the registered design professional.		fls	
Ele	vations Drawing including:		4	
14	All side views of the structure	·	Yes	
15	Roof pitch	-	Ves	
16	Overhang dimensions and detail with attic ventilation	-	Vins.	
7	Location, size and height above roof of chimneys	-	VILS	
8	Location and size of skylights with Florida Product Approval	-	1425	
8	Number of stories	-	170	
0A	Building height from the established grade to the roofs highest peak	-	JUS	
JA	Duriding notific from the contract of			

Fl	oor Plan including:	
	Dimensioned area plan showing rooms, attached garage, breeze ways, covered porches, deck,	1 5
20	odicontes	- 497
21	Raised floor surfaces located more than 30 inches above the floor or grade	V
22	All exterior and interior shear walls indicated	144
23	Shear wall opening shown (Windows, Doors and Garage doors)	- 4008
24	Show compliance with Section FBCR 310 Emergency escape and rescue opening shown in each	- 0
	bedroom (net clear eneming shown) and State of the state	
	bedroom (net clear opening shown) and Show compliance with Section FBC 1405.13.2 where the	
	opening of an operable window is located more than 72 inches above the finished grade or surface	
	below, the lowest part of the clear opening of the window shall be a minimum of 24 inches above	- 44
	the finished floor of the room in which the window is located. Glazing between the floor and 24	
-	inches shall be fixed or have openings through which a 4-inch-diameter sphere cannot pass	200
25	Safety glazing of glass where needed	- 1/08
	Fireplaces types (gas appliance) (vented or non-vented) or wood burning with Hearth	
6	(see chapter 10 and chapter 24 of FBCR)	
		· 405
7	Show stairs with dimensions (width, tread and riser and total run) details of guardrails, Handrails	
	and document of guardrains, Italiarians	- Vel
8	Identify accessibility of bathroom (see FBCR SECTION 320)	1//
	, and the state of	
or	proval number and mfg. installation information submitted with the plans (see Fl	
	GENERAL REQUIREMENTS:	Items to Include-
	APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Each Box shall be
		Marked as
_		Applicable
B	CR 403: Foundation Plans	YES / NO / N/A
	*	
	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size	
9	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.	Select From the Dropbo
9	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.  All posts and/or column footing including size and reinforcing	Select From the Dropbo
0	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.  All posts and/or column footing including size and reinforcing  Any special support required by soil analysis such as piling.	Select From the Dropbo
9 0 1 2	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.  All posts and/or column footing including size and reinforcing  Any special support required by soil analysis such as piling.  Assumed load-bearing valve of soil  Pound Per Square Foot	Select From the Dropbo
0 1 2	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.  All posts and/or column footing including size and reinforcing  Any special support required by soil analysis such as piling.  Assumed load-bearing valve of soil  Pound Per Square Foot  Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure	Select From the Dropbo
0 1 2	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.  All posts and/or column footing including size and reinforcing  Any special support required by soil analysis such as piling.  Assumed load-bearing valve of soil Pound Per Square Foot  Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete	Select From the Dropbo
0 1 2	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.  All posts and/or column footing including size and reinforcing  Any special support required by soil analysis such as piling.  Assumed load-bearing valve of soil  Pound Per Square Foot  Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system.	Select From the Dropbo
0 1 2	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.  All posts and/or column footing including size and reinforcing  Any special support required by soil analysis such as piling.  Assumed load-bearing valve of soil Pound Per Square Foot  Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete	Select From the Dropbo
9 0 1 2 3	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.  All posts and/or column footing including size and reinforcing  Any special support required by soil analysis such as piling.  Assumed load-bearing valve of soil Pound Per Square Foot  Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3  CR 506: CONCRETE SLAB ON GRADE	Select From the Dropbox
9 0 1 2 3	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.  All posts and/or column footing including size and reinforcing  Any special support required by soil analysis such as piling.  Assumed load-bearing valve of soil  Pound Per Square Foot  Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3  CR 506: CONCRETE SLAB ON GRADE  Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed)	Select From the Dropbox
9 0 1 2 3	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.  All posts and/or column footing including size and reinforcing  Any special support required by soil analysis such as piling.  Assumed load-bearing valve of soil Pound Per Square Foot  Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3  CR 506: CONCRETE SLAB ON GRADE	Select From the Dropbo
9 0 1 2 3	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.  All posts and/or column footing including size and reinforcing  Any special support required by soil analysis such as piling.  Assumed load-bearing valve of soil  Pound Per Square Foot  Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3  CR 506: CONCRETE SLAB ON GRADE  Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed)  Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports  CR 318: PROTECTION AGAINST TERMITES	Select From the Dropbo
9 0 1 2 3 3 B	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.  All posts and/or column footing including size and reinforcing  Any special support required by soil analysis such as piling.  Assumed load-bearing valve of soil  Pound Per Square Foot  Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3  CR 506: CONCRETE SLAB ON GRADE  Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed)  Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports  CR 318: PROTECTION AGAINST TERMITES  Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or	Select From the Dropbo
9 0 1 2 3 8 4 5	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.  All posts and/or column footing including size and reinforcing  Any special support required by soil analysis such as piling.  Assumed load-bearing valve of soil  Pound Per Square Foot  Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3  CR 506: CONCRETE SLAB ON GRADE  Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed)  Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports  CR 318: PROTECTION AGAINST TERMITES  Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered	Select From the Dropbox
9 0 1 2 3 8 4 5	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.  All posts and/or column footing including size and reinforcing  Any special support required by soil analysis such as piling.  Assumed load-bearing valve of soil  Pound Per Square Foot  Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3  CR 506: CONCRETE SLAB ON GRADE  Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed)  Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports  CR 318: PROTECTION AGAINST TERMITES  Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or	Select From the Dropbo
9 0 1 2 3 8 8 8 8	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.  All posts and/or column footing including size and reinforcing  Any special support required by soil analysis such as piling.  Assumed load-bearing valve of soil  Pound Per Square Foot  Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3  CR 506: CONCRETE SLAB ON GRADE  Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed)  Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports  CR 318: PROTECTION AGAINST TERMITES  Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides  CR 606: Masonry Walls and Stem walls (load bearing & shear Walls)	Select From the Dropbox
9 0 1 2 3 B B 6	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.  All posts and/or column footing including size and reinforcing  Any special support required by soil analysis such as piling.  Assumed load-bearing valve of soil  Pound Per Square Foot  Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3  CR 506: CONCRETE SLAB ON GRADE  Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed)  Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports  CR 318: PROTECTION AGAINST TERMITES  Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides  CR 606: Masonry Walls and Stem walls (load bearing & shear Walls)  Show all materials making up walls, wall height, and Block size, mortar type	Select From the Dropbox
9 0 1 2 3 3 B 4 5	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.  All posts and/or column footing including size and reinforcing  Any special support required by soil analysis such as piling.  Assumed load-bearing valve of soil  Pound Per Square Foot  Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3  CR 506: CONCRETE SLAB ON GRADE  Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed)  Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports  CR 318: PROTECTION AGAINST TERMITES  Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides  CR 606: Masonry Walls and Stem walls (load bearing & shear Walls)  Show all materials making up walls, wall height, and Block size, mortar type	Select From the Dropbox  - 108 - 108 - 109 es - 109 - 110
9 0 1 2 3 8 8 6	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.  All posts and/or column footing including size and reinforcing  Any special support required by soil analysis such as piling.  Assumed load-bearing valve of soil  Pound Per Square Foot  Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3  CR 506: CONCRETE SLAB ON GRADE  Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed)  Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports  CR 318: PROTECTION AGAINST TERMITES  Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides  CR 606: Masonry Walls and Stem walls (load bearing & shear Walls)  Show all materials making up walls, wall height, and Block size, mortar type	Select From the Dropbo
19 10 11 12 13 13 14 15 15 16 17 18 18 18 18 18 18 18 18 18 18 18 18 18	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.  All posts and/or column footing including size and reinforcing  Any special support required by soil analysis such as piling.  Assumed load-bearing valve of soil  Pound Per Square Foot  Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3  CR 506: CONCRETE SLAB ON GRADE  Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed)  Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports  CR 318: PROTECTION AGAINST TERMITES  Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides  CR 606: Masonry Walls and Stem walls (load bearing & shear Walls)  Show all materials making up walls, wall height, and Block size, mortar type  Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement tal frame shear wall and roof systems shall be designed, signed and sealed by Florida Protor Framing System: First and/or second story	Select From the Dropbo
29 30 31 32 33 33 FB 34 35 FB 37 38 Me	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.  All posts and/or column footing including size and reinforcing  Any special support required by soil analysis such as piling.  Assumed load-bearing valve of soil  Pound Per Square Foot  Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3  CR 506: CONCRETE SLAB ON GRADE  Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed)  Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports  CR 318: PROTECTION AGAINST TERMITES  Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides  CR 606: Masonry Walls and Stem walls (load bearing & shear Walls)  Show all materials making up walls, wall height, and Block size, mortar type  Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement tal frame shear wall and roof systems shall be designed, signed and sealed by Florida Pro	Select From the Dropbox  - Jes - Jes - Jes - Jes - Jes

MF.		
	Show conventional floor joist type, size, span, spacing and attachment to load bearing walls,	T
40	Stell waits and of priers	· yes
41	Girder type, size and spacing to load bearing walls, stem wall and/or priers Attachment of joist to girder	- 498
43	Wind load requirements where applicable	- 1/08
44	Show required under-floor crawl space	- Km5
45		· Kes
46	Show required covering of ventilation opening	· FNI
47	Show the required access opening to access to under-floor spaces	1 48
•	Show the sub-floor structural panel sheathing type, thickness and fastener schedule on the edges &	1. 99
48	intermediate of the areas structural panel sheathing	· AA
49		
50		195
51	Provide live and dead load rating of floor framing systems (psf).	· Mas
		YES / NO / N/A
FB	CR CHAPTER 6 WOOD WALL FRAMING CONSTRUCTION	TES PNO PNA
	GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Items to Include- Each Box shall be Marked as Applicable
		elect From the Dropbo
52	Stud type, grade, size, wall height and oc spacing for all load bearing or shear walls	· yes
53	Fastener schedule for structural members per table IRC 602.3 are to be shown	- 48
- 4	Show Wood structural panel's sheathing attachment to studs, joist, trusses, rafters and structural	
54	members, showing fastener schedule attachment on the edges & intermediate of the areas structural	- 40
	panel sheathing	V
55	Show all required connectors with a max uplift rating and required number of connectors and oc spacing for continuous connection of structural walls to foundation and roof trusses or rafter systems	· 105
56	Show sizes, type, span lengths and required number of support jack studs, king studs for shear wall opening and girder or header per IRC Table 502.5 (1)	- 48
57	Indicate where pressure treated wood will be placed	· yes
	Show all wall structural panel sheathing, grade, thickness and show fastener schedule for structural	1/05
58	panel sheathing edges & intermediate areas	100
59	A detail showing gable truss bracing, wall balloon framing details or/ and wall hinge bracing detail	- ya
	CD POOR CHEEPING	<i>V</i>
r I	BCR :ROOF SYSTEMS:	- 005
	Truss design drawing shall meet section FBCR 802.1.6.1 Wood trusses	1 105
61	. It' I I '-t well'A entine for all tempere and reflere	· 1/0 (
62	t '	- 1,05
53	Show gable ends with rake bealths showing reinforcement of gaste trade and hard lead rating of trusses	· 42)
64	Provide dead load rating of trusses	-
F	BCR 802:Conventional Roof Framing Layout	
65	Paffer and ridge beams sizes, span, species and spacing	· Ves
66		- 1/98
67		· Kel
68	Provide dead load rating of rafter system	Ves
		N-
FI	BCR 803 ROOF SHEATHING	
69	Include all materials which will make up the roof decking, identification of structural paner	418
70	Show fastener Size and schedule for structural panel sheathing on the edges & intermediate areas	· Vas
		V .
R	OOF ASSEMBLIES FRC Chapter 9	1. 108
	t t t t t t t t t t t t t t t t t t t	110
72	Submit Florida Product Approval numbers for each component of the roof assembles covering	(4/4)

## FBCR Chapter 11 Energy Efficiency Code for residential building

Residential construction shall comply with this code by using the following compliance methods in the FBCR chapter 11 Residential buildings compliance methods. Two of the required forms are to be submitted, N1100.1.1.1 As an alternative to the computerized requirements specific to this calculation are located in Sub appendix C to Appendix G. Buildings complying by this alternative shall meet all mandatory requirements of this chapter. Computerized versions of the Alternate Residential Point System Method shall not be acceptable for code compliance.

YES / NO / N/A Items to Include-GENERAL REQUIREMENTS: APPLICANT - PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL Each Box shall be Marked as Applicable Select From the Dropbox 73 Show the insulation R value for the following areas of the structure 401 74 Attic space 75 Exterior wall cavity 76 Crawl space HVAC information 77 Submit two copies of a Manual J sizing equipment or equivalent computation study 78 Exhaust fans shown in bathrooms Mechanical exhaust capacity of 50 cfm intermittent or 20 cfm continuous required Show clothes dryer route and total run of exhaust duct Plumbing Fixture layout shown 80 All fixtures waste water lines shall be shown on the foundation plan Show the location of water heater Private Potable Water 82 Pump motor horse power 83 Reservoir pressure tank gallon capacity 84 Rating of cycle stop valve if used Electrical layout shown including 85 Show Switches, receptacles outlets, lighting fixtures and Ceiling fans Show all 120-volt, single phase, 15- and 20-ampere branch circuits outlets required to be protected by Ground-Fault Circuit Interrupter (GFCI) Article 210.8 A Show the location of smoke detectors & Carbon monoxide detectors 87 88 Show service panel, sub-panel, location(s) and total ampere ratings On the electrical plans identify the electrical service overcurrent protection device for the main electrical service. This device shall be installed on the exterior of structures to serve as a disconnecting means for the utility company electrical service. Conductors used from the exterior 89 disconnecting means to a panel or sub panel shall have four-wire conductors, of which one conductor shall be used as an equipment ground. Indicate if the utility company service entrance cable will be of the overhead or underground type. For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an Grounding electrode system. Per the National Electrical Code article 250.52.3 Appliances and HVAC equipment and disconnects Show all 120-volt, single phase, 15- and 20-ampere branch circuits supplying outlets installed in dwelling unit family rooms, dining rooms, living rooms, parlors, libraries, dens, bedrooms, sunrooms, recreation rooms, closets, hallways, or similar rooms or areas shall be protected by a listed Combination arc-fault circuit interrupter, Protection device.

### GENERAL REQUIREMENTS: APPLICANT - PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL

Items to Include-Each Box shall be Circled as Applicable

# THE FOLLOWING ITEMS MUST BE SUBMITTED WITH BUILDING PLANS

92	Ruilding Pormit Annilland	YES	NO	N/A
	Building Permit Application A current Building Permit Application is to be completed, by following the Checklist all supporting documents must be submitted.  There is a \$15.00 application fee. The completed application with attached documents and application fee can be mailed.	(R)		
93	Parcel Number The parcel number (Tax ID number) from the Property Appraisers Office (386) 758-1083 is required. A copy of property deed is also required. www.columbiacountyfla.com	B		
94	<b>Town of Fort White</b> (386) 497-2321 If the parcel in the application for building permit is within the Corporate city limits of Fort White, an approval land use development letter issued by the Town of Fort is required to be submitted with the application for a building permit.	NA		
***	BELOW ITEMS ONLY NEEDED AFTER ZONING APPROVAL HAS GIVEN.	****	***	***
95	Environmental Health Permit or Sewer Tap Approval A copy of a approved Columbia County Environmental Health (386) 758-1058	A STATE OF THE PROPERTY OF THE		
96	City of Lake City A City Water and/or Sewer letter. Call 386-752-2031	100	JA	
97	Flood Information: All projects within the Floodway of the Suwannee or Santa Fe Rivers shall require permitting through the Suwannee River Water Management District, before submitting a application to this office. Any project located within a flood zone where the base flood elevation (100 year flood) has been established shall meet the requirements of Section 8.5.2 of the Columbia County Land Development Regulations. Any project located within a flood zone where the base flood elevation has not been established (Zone A) shall meet the requirements of Section 8.5.3 of the Columbia County Land Development Regulations	400,	NA	
98	CERTIFIED FINISHED FLOOR ELEVATIONS will be required on any project where the approved FIRM Flood Maps show the property is in a AE, Floodway, and AH flood zones. Additionally One Foot Rise letters are required for AE and AH zones. In the Floodway Flood zones a Zero Rise letter is required.	yles		
99	A Flood development permit is also required for AE, Floodway & AH. Development permit cost is \$50.00			
100	<b>Driveway Connection:</b> If the property does not have an existing access to a public road, then an application for a culvert permit (\$25.00) must be made. County Public Works Dept. determines the size and length of every culvert before instillation and completes a final inspection before permanent power is granted. If the applicant feels that a culvert is not needed, they may apply for a culvert waiver (\$50.00) Separate Check when issued. If the project is to be located on an F.D.O.T. maintained road, then an F.D.O.T. access permit is required.	100		
101	911 Address: An application for a 911address must be applied for and received through the Columbia County Emergency Management Office of 911 Addressing Department (386) 758-1125.	W.	1	1

## TOILET FACILITIES SHALL BE PROVIDED FOR ALL CONSTRUCTION SITES. NO

Disclosure Statement for Owner Builders If you as the applicant will be acting as an owner/builder under section 489.103(7) of the Florida Statutes, submit the required owner builder disclosure statement form.

### Notice Of Commencement

A notice of commencement form recorded in the Columbia County Clerk Office is required to be filed with the building department Before Any Inspections can be preformed.

Section R101.2.1 of the Florida Building Code Residential:

The provisions of Chapter 1, Florida Building Code shall govern the administration and enforcement of the Florida Building Code, Residential.