



Lumber design values are in accordance with ANSI/TPI 1 section 6.3  
These truss designs rely on lumber values established by others.

RE: 1552-A - Deen Residence

MiTek, Inc.  
16023 Swingley Ridge Rd.  
Chesterfield, MO 63017  
314.434.1200

**Site Information:**

Customer Info: Parrish Builders Group Project Name: Deen Residence Model: .  
Lot/Block: . Subdivision: .  
Address: 2938 SW County Road 778, .  
City: Fort White State: FL

**Name Address and License # of Structural Engineer of Record, If there is one, for the building.**

Name: License #:  
Address:  
City: State:

**General Truss Engineering Criteria & Design Loads (Individual Truss Design Drawings Show Special Loading Conditions):**


Design Code: FBC2023/TPI2014 Design Program: MiTek 20/20 8.7  
Wind Code: ASCE 7-22 Wind Speed: 130 mph  
Roof Load: 40.0 psf Floor Load: N/A psf

This package includes 6 individual, Truss Design Drawings and 0 Additional Drawings.  
With my seal affixed to this sheet, I hereby certify that I am the Truss Design Engineer and this index sheet conforms to 61G15-31.003, section 5 of the Florida Board of Professional Engineers Rules.

No.	Seal#	Truss Name	Date
1	T34287602	G1	6/27/24
2	T34287603	G2	6/27/24
3	T34287604	T1	6/27/24
4	T34287605	T2	6/27/24
5	T34287606	T3	6/27/24
6	T34287607	T4	6/27/24



Review for Code Compliance  
Universal Engineering Science


  
Examiner-License No.

PX2707 07/15/2024

The truss drawing(s) referenced above have been prepared by MiTek USA, Inc.  
under my direct supervision based on the parameters  
provided by 19 Lumber, Inc..

Truss Design Engineer's Name: Velez, Joaquin  
My license renewal date for the state of Florida is February 28, 2025.

**IMPORTANT NOTE:** The seal on these truss component designs is a certification that the engineer named is licensed in the jurisdiction(s) identified and that the designs comply with ANSI/TPI 1. These designs are based upon parameters shown (e.g., loads, supports, dimensions, shapes and design codes), which were given to MiTek or TRENCO. Any project specific information included is for MiTek's or TRENCO's customers file reference purpose only, and was not taken into account in the preparation of these designs. MiTek or TRENCO has not independently verified the applicability of the design parameters or the designs for any particular building. Before use, the building designer should verify applicability of design parameters and properly incorporate these designs into the overall building design per ANSI/TPI 1, Chapter 2.



Joaquin Velez PE No.68182  
MiTek Inc. DBA MiTek USA FL Cert 6634  
16023 Swingley Ridge Rd. Chesterfield, MO 63017  
Date:

June 27,2024

Velez, Joaquin


1 of 1

Job	Truss	Truss Type	Qty	Ply	Deen Residence
1552-A	G1	Common Supported Gable	2	1	T34287602
Job Reference (optional)					

19 Lumber, Inc., Old Town, FL - 32680,

Run: 8.73 S Jun 13 2024 Print: 8.730 S Jun 13 2024 MiTek Industries, Inc. Wed Jun 26 11:51:31  
ID:2TRI6tffejwtp6rg7TC6yz9yg1-RfC?PsB70Hq3NSgPqnL8w3uITXbGKwRCDoi7J4zJC?i

Page: 1



Scale = 1:60.3

Plate Offsets (X, Y): [2:0-3-8,Edge], [2:0-2-8,Edge], [18:0-3-8,Edge], [18:0-2-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.25	TC	0.21	Vert(LL)	n/a	-	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.25	BC	0.15	Vert(CT)	n/a	-	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.17	Horz(CT)	0.01	18	n/a		
BCDL	10.0	Code	FBC2023/TPI2014	Matrix-MS							
Weight: 173 lb FT = 20%											

#### LUMBER

TOP CHORD	2x4 SP No.2
BOT CHORD	2x4 SP No.2
OTHERS	2x4 SP No.2

#### BRACING

TOP CHORD	Structural wood sheathing directly applied or 10-0-0 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 6-0-0 oc bracing.

#### REACTIONS

(size)	2=30-0-0, 18=30-0-0, 20=30-0-0, 21=30-0-0, 22=30-0-0, 23=30-0-0, 24=30-0-0, 25=30-0-0, 27=30-0-0, 28=30-0-0, 29=30-0-0, 30=30-0-0, 31=30-0-0, 32=30-0-0, 35=30-0-0
Max Horiz	2=133 (LC 13), 32=133 (LC 13)
Max Uplift	2=28 (LC 12), 18=48 (LC 13), 20=113 (LC 13), 21=31 (LC 13), 22=62 (LC 13), 23=57 (LC 13), 24=56 (LC 13), 27=58 (LC 12), 28=56 (LC 12), 29=62 (LC 12), 30=34 (LC 12), 31=107 (LC 12), 32=28 (LC 12), 35=48 (LC 13)
Max Grav	2=258 (LC 25), 18=258 (LC 26), 20=374 (LC 26), 21=61 (LC 1), 22=185 (LC 26), 23=152 (LC 26), 24=172 (LC 26), 25=223 (LC 22), 27=172 (LC 25), 28=152 (LC 25), 29=185 (LC 25), 30=61 (LC 1), 31=374 (LC 25), 32=258 (LC 25), 35=258 (LC 26)

#### FORCES

(lb) - Maximum Compression/Maximum Tension	
TOP CHORD	1-2=0/42, 2-4=144/150, 4-6=66/114, 6-7=32/141, 7-8=12/146, 8-9=30/162, 9-10=49/212, 10-11=49/212, 11-12=30/162, 12-13=12/111, 13-14=0/101, 14-16=11/73, 16-18=93/131, 18-19=0/42

#### BOT CHORD

2-31=85/168, 30-31=85/168, 29-30=85/168, 28-29=85/168, 27-28=85/168, 25-27=85/168, 24-25=85/168, 23-24=85/168, 22-23=85/168, 21-22=85/168, 20-21=85/168, 18-20=85/168, 10-25=183/0, 9-27=131/92, 8-28=115/96, 7-29=134/101, 6-30=63/69, 4-31=250/166, 11-24=131/92, 12-23=115/96, 13-22=134/101, 14-21=63/69, 16-20=250/165

#### WEBS

#### NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-22; Vult=130mph (3-second gust) Vasd=101mph; TCDL=5.0psf; BCDL=5.0psf; n=30; II; Exp B; Enclosed; MWFRS (envelope) exterior (2) zone and C-C Zone3 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SP No.2.

- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 28 lb uplift at joint 2, 48 lb uplift at joint 18, 58 lb uplift at joint 27, 56 lb uplift at joint 28, 62 lb uplift at joint 29, 34 lb uplift at joint 30, 107 lb uplift at joint 31, 56 lb uplift at joint 24, 57 lb uplift at joint 23, 62 lb uplift at joint 22, 31 lb uplift at joint 21, 113 lb uplift at joint 20, 28 lb uplift at joint 2 and 48 lb uplift at joint 18.

LOAD CASE(S) Standard


Review for Code Compliance  
Universal Engineering Science



Examiner-License No.

PX2707

07/15/2024



Joaquin Velez PE No.68182  
MiTek Inc. DBA MiTek USA FL Cert 6634  
16023 Swingley Ridge Rd. Chesterfield, MO 63017  
Date:

June 27, 2024

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

**MiTek®**


16023 Swingley Ridge Rd.  
Chesterfield, MO 63017  
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Deen Residence	T34287603
1552-A	G2	Common Supported Gable	1	1	Job Reference (optional)	

19 Lumber, Inc., Old Town, FL - 32680,

Run: 8.73 S Jun 13 2024 Print: 8.730 S Jun 13 2024 MiTek Industries, Inc. Wed Jun 26 11:51:32  
ID:6dresi8jFzApyk9UPUQF761z2U17-RfC?PsB70Hq3NSgPqnL8w3uITXbGKWRcDoi7J4zJC?f

Page: 1



Scale = 1:33.4

Plate Offsets (X, Y): [2:0-3-8,Edge], [2:0-2-8,Edge], [8:0-3-8,Edge], [8:0-2-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.25	TC	0.17	Vert(LL)	n/a	-	n/a	999	MT20
TCDL	10.0	Lumber DOL	1.25	BC	0.11	Vert(CT)	n/a	-	n/a	999	244/190
BCLL	0.0*	Rep Stress Incr	YES	WB	0.04	Horz(CT)	0.00	8	n/a	n/a	
BCDL	10.0	Code	FBC2023/TPI2014	Matrix-MS							Weight: 60 lb FT = 20%

#### LUMBER

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
OTHERS 2x4 SP No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or 10-0-0 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

#### REACTIONS

(size) 2=13-0-0, 8=13-0-0, 10=13-0-0, 11=13-0-0, 12=13-0-0, 13=13-0-0, 16=13-0-0  
Max Horiz 2=62 (LC 12), 13=62 (LC 12)  
Max Uplift 2=59 (LC 12), 8=68 (LC 13), 10=105 (LC 13), 12=102 (LC 12), 13=59 (LC 12), 16=68 (LC 13)  
Max Grav 2=233 (LC 25), 8=233 (LC 26), 10=330 (LC 26), 11=123 (LC 1), 12=330 (LC 25), 13=233 (LC 25), 16=233 (LC 26)

#### FORCES

(lb) - Maximum Compression/Maximum Tension  
TOP CHORD 1-2=0/42, 2-4=-85/163, 4-5=0/120, 5-6=0/117, 6-8=-81/163, 8-9=0/42  
BOT CHORD 2-12=-107/153, 11-12=-107/153, 10-11=-107/153, 8-10=-107/153  
WEBS 5-11=-141/4, 4-12=-223/200, 6-10=-2

#### NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-22; Vult=130mph (3-second gust) Vasd=101mph; TCDL=5.0psf; BCDL=5.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior (2) zone and C-C Zone3 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60

- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SP No.2 .
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 59 lb uplift at joint 2, 68 lb uplift at joint 8, 102 lb uplift at joint 12, 105 lb uplift at joint 10, 59 lb uplift at joint 2 and 68 lb uplift at joint 8.

LOAD CASE(S) Standard


Review for Code Compliance  
Universal Engineering Science



*Lawrence Parnell*  
Examiner-License No.

PX2707

07/15/2024



Joaquin Velez PE No.68182  
MiTek Inc. DBA MiTek USA FL Cert 6634  
16023 Swingley Ridge Rd. Chesterfield, MO 63017  
Date:

June 27,2024

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of the design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

**MiTek®**


16023 Swingley Ridge Rd.  
Chesterfield, MO 63017  
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Deen Residence
1552-A	T1	Common	32	1	T34287604
Job Reference (optional)					

19 Lumber, Inc., Old Town, FL - 32680,

Run: 8.73 S Jun 13 2024 Print: 8.730 S Jun 13 2024 MiTek Industries, Inc. Wed Jun 26 11:51:32  
ID:2TRiT6ffejwtP6rg7TC6yz9yg1-RfC?PsB70Hq3NSgPqnL8w3uTXbGKwRCDoi7J4zJC?i

Page: 1



Scale = 1:58.3

Plate Offsets (X, Y): [3:0-3-8,0-3-0], [7:0-3-8,0-3-0], [11:0-4-0,0-3-0]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.25	TC	0.68	Vert(LL)	0.10	12-15	>999	240	MT20	244/190
TCDL	10.0	Lumber DOL	1.25	BC	0.71	Vert(CT)	-0.23	12-15	>999	180		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.24	Horz(CT)	0.09	8	n/a	n/a		
BCDL	10.0	Code	FBC2023/TPI2014	Matrix-MS							Weight: 145 lb	FT = 20%

#### LUMBER

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
WEBS 2x4 SP No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or 3-3-10 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 9-11-1 oc bracing.

WEBS 1 Row at midpt 7-11, 3-11

REACTIONS (size) 2=0-4-0, 8=0-4-0  
Max Horiz 2=-138 (LC 13)  
Max Uplift 2=-238 (LC 12), 8=-238 (LC 13)  
Max Grav 2=1294 (LC 1), 8=1294 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/42, 2-3=-2170/346, 3-5=-1467/277,  
5-7=-1467/277, 7-8=-2170/346, 8-9=0/42  
BOT CHORD 2-12=-336/1870, 10-12=-336/1870,  
8-10=-198/1870

WEBS 5-11=-81/817, 7-11=-753/278, 7-10=0/318,  
3-11=-753/277, 3-12=0/318

#### NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-22; Vult=130mph (3-second gust)  
Vasd=101mph; TCDL=5.0psf; BCDL=5.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Zone3 -1-6-13 to 1-5-3, Zone1 15-0-0, Zone2 15-0-0 to 19-2-15, Zone1 19-2-15 to 31-6-13 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.

- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SP No.2 .
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 238 lb uplift at joint 2 and 238 lb uplift at joint 8.

LOAD CASE(S) Standard



Review for Code Compliance  
Universal Engineering Science

*Joaquin Velez*  
Examiner-License No.

PX2707

07/15/2024



Joaquin Velez PE No.68182  
MiTek Inc. DBA MiTek USA FL Cert 6634  
16023 Swingley Ridge Rd. Chesterfield, MO 63017  
Date:

June 27,2024

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

**MiTek®**

16023 Swingley Ridge Rd.  
Chesterfield, MO 63017  
314.434.1200 / MiTek-US.com




Job	Truss	Truss Type	Qty	Ply	Deen Residence	T34287605
1552-A	T2	Common	7	1	Job Reference (optional)	

19 Lumber, Inc., Old Town, FL - 32680,

Run: 8.73 S Jun 13 2024 Print: 8.730 S Jun 13 2024 MiTek Industries, Inc. Wed Jun 26 11:51:32  
ID:2TRiT6fiejwT6rg7TC6yz9yg1-RfC?PsB70Hq3NSgPqnL8w3uTXbGKWRCDoi7J4zJC?i

Page: 1



Scale = 1:56  
Plate Offsets (X, Y): [2:0-3-4,0-3-0], [6:0-3-8,0-3-0], [10:0-4-0,0-3-0]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.25	TC	0.70	Vert(LL)	0.12	11-14	>999	240	MT20	244/190
TCDL	10.0	Lumber DOL	1.25	BC	0.76	Vert(CT)	-0.26	11-14	>999	180		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.25	Horz(CT)	0.09	7	n/a	n/a		
BCDL	10.0	Code	FBC2023/TPI2014	Matrix-MS							Weight: 143 lb	FT = 20%

#### LUMBER

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
WEBS 2x4 SP No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or 3-1-11 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 9-8-5 oc bracing.

WEBS 1 Row at midpt 6-10, 2-10

REACTIONS (size) 1=0-4-0, 7=0-4-0  
Max Horiz 1=151 (LC 13)  
Max Uplift 1=200 (LC 12), 7=238 (LC 13)  
Max Grav 1=1198 (LC 1), 7=1296 (LC 1)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=2170/355, 2-4=1473/289,  
4-6=1472/279, 6-7=2175/347, 7-8=0/42  
BOT CHORD 1-11=345/1889, 9-11=345/1889,  
7-9=199/1875

WEBS 4-10=-84/822, 6-10=-753/278, 6-9=0/318,  
2-10=-769/286, 2-11=0/320

#### NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-22; Vult=130mph (3-second gust)  
Vasd=101mph; TCDL=5.0psf; BCDL=5.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior (2) zone and C-C Zone3 0-0-0 to 3-0-0, Zone1 3-0-0 to 15-0-0, Zone2 15-0-0 to 19-2-15, Zone1 19-2-15 to 31-6-13 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.

- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- All bearings are assumed to be SP No.2.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 200 lb uplift at joint 1 and 238 lb uplift at joint 7.

LOAD CASE(S) Standard




Review for Code Compliance  
Universal Engineering Science

*Lawrence Parnell*  
Examiner-License No.

PX2707

07/15/2024



Joaquin Velez PE No.68182  
MiTek Inc. DBA MiTek USA FL Cert 6634  
16023 Swingley Ridge Rd. Chesterfield, MO 63017  
Date:

June 27, 2024

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

**MiTek®**


16023 Swingley Ridge Rd.  
Chesterfield, MO 63017  
314.434.1200 / MiTek-US.com

Job	Truss	Truss Type	Qty	Ply	Deen Residence
1552-A	T3	Common	3	1	T34287606
Job Reference (optional)					

19 Lumber, Inc., Old Town, FL - 32680,

Run: 8.73 S Jun 13 2024 Print: 8.730 S Jun 13 2024 MiTek Industries, Inc. Wed Jun 26 11:51:32  
ID:HTUbS5eUNK2p0E1F898jtmz2U1D-RfC?PsB70Hq3NSgPqnL8w3ulTXbGKWrCdoi7J4zJC?f

Page: 1



Scale = 1:32.7

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.25	TC	0.48	Vert(LL)	0.05	6-9	>999	240	244/190
TCDL	10.0	Lumber DOL	1.25	BC	0.46	Vert(CT)	-0.10	6-9	>999	180	
BCLL	0.0*	Rep Stress Incr	YES	WB	0.07	Horz(CT)	0.01	4	n/a	n/a	
BCDL	10.0	Code	FBC2023/TPI2014	Matrix-MS							
Weight: 51 lb FT = 20%											

#### LUMBER

TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
WEBS 2x4 SP No.2

#### BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

#### REACTIONS (size)

2=0-3-0, 4=0-3-0  
Max Horiz 2=67 (LC 12)  
Max Uplift 2=-125 (LC 12), 4=-125 (LC 13)  
Max Grav 2=614 (LC 1), 4=614 (LC 1)

#### FORCES

(lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/42, 2-3=-719/201, 3-4=-719/201, 4-5=0/42

BOT CHORD 2-6=-51/575, 4-6=-51/575  
WEBS 3-6=0/304

#### NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-22; Vult=130mph (3-second gust)  
Vasd=101mph; TCDL=5.0psf; BCDL=5.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior (2) zone and C-C Zone3 -1-6-13 to 1-5-3, Zone1 1-5-3 to 6-6-0, Zone2 6-6-0 to 10-8-15, Zone1 10-8-15 to 14-6-13 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.




Review for Code Compliance  
Universal Engineering Science

*Lawrence Parnell*  
Examiner-License No.

PX2707

07/15/2024



Joaquin Velez PE No.68182  
MiTek Inc. DBA MiTek USA FL Cert 6634  
16023 Swingley Ridge Rd. Chesterfield, MO 63017  
Date:

June 27, 2024


**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 1/2/2023 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria and DSB-22** available from Truss Plate Institute (www.tpinst.org) and **BCSI Building Component Safety Information** available from the Structural Building Component Association (www.sbcsccomponents.com)

**MiTek®**

16023 Swingley Ridge Rd.  
Chesterfield, MO 63017  
314.434.1200 / MiTek-US.com


19 Lumber, Inc., Old Town, FL - 32680, Run: 8.73 S Jun 13 2024 Print: 8.730 S Jun 13 2024 MiTek Industries, Inc. Wed Jun 26 11:51:32 Page: 1  
ID:apPEwUjtjUxpMJ3b27mMfFz2U16-RfC?PsB70Hq3NSgPqnL8w3uITxbGKWRCDoi7J4zJC?f



<b>LUMBER</b>		5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
TOP CHORD	2x4 SP No.2	6) All bearings are assumed to be SP No.2 .
BOT CHORD	2x4 SP No.2	
WEBS	2x4 SP No.2	
<b>BRACING</b>		7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 87 lb uplift at joint 1 and 87 lb uplift at joint 3.
TOP CHORD	Structural wood sheathing directly applied or 5-10-10 oc purlins.	<b>LOAD CASE(S)</b> Standard
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.	

**NOTES**

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-22; Vult=130mph (3-second gust)  
Vasd=101mph; TCDL=5.0psf; BCDL=5.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior (2) zone and C-C Zone3 0-0-0 to 3-0-0, Zone1 3-0-0 to 6-6-0, Zone2 6-6-0 to 10-8-15, Zone1 10-8-15 to 13-0-0 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.




**Review for Code Compliance**  
**Universal Engineering Science**

---

PX2707 07/15/2024

*Examiner License No.*




Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria and DSB-22** available from Truss Plate Institute ([www.tpinst.org](http://www.tpinst.org)) and **BCSI Building Component Safety Information** available from the Structural Building Components Association ([www.sbsccomponents.com](http://www.sbsccomponents.com))

**MiTek®**  
16023 Swingley Ridge Rd.  
Chesterfield, MO 63017  
314.434.1200 / MiTek-US.com

# Symbols

## PLATE LOCATION AND ORIENTATION




For 4 x 2 orientation, locate plates 0- 1/16" from outside edge of truss.

This symbol indicates the required direction of slots in connector plates.

## PLATE SIZE


The first dimension is the plate width measured perpendicular to slots. Second dimension is the length parallel to slots.

## LATERAL BRACING LOCATION



Indicated by symbol shown and/or by text in the bracing section of the output. Use T or I bracing if indicated.


## BEARING



Indicates location where bearings (supports) occur. Icons vary but reaction section indicates joint number/letter where bearings occur. Min size shown is for crushing only.

**Industry Standards:**  
ANSI/TP1: National Design Specification for Metal Plate Connected Wood Truss Construction.  
DSB-22: Design Standard for Bracing.  
BCSI: Building Component Safety Information, Guide to Good Practice for Handling, Installing, Restraining & Bracing of Metal Plate Connected Wood Trusses.

# Numbering System



JOINTS ARE GENERALLY NUMBERED/LETTERED CLOCKWISE AROUND THE TRUSS STARTING AT THE JOINT FARTHEST TO THE LEFT.

CHORDS AND WEBS ARE IDENTIFIED BY END JOINT NUMBERS/LETTERS.

## Product Code Approvals

ICC-ES Reports:  
ESR-1988, ESR-2362, ESR-2685, ESR-3282  
ESR-4722, ESL-1388

## Design General Notes

Trusses are designed for wind loads in the plane of the truss unless otherwise shown.

Lumber design values are in accordance with ANSI/TP1 section 6.3. These truss designs rely on lumber values established by others.

© 2023 MITek® All Rights Reserved



MITek Engineering Reference Sheet: MII-7473 rev. 1/2/2023

# General Safety Notes

Failure to Follow Could Cause Property Damage or Personal Injury

1. Additional stability bracing for truss system, e.g. diagonal or X-bracing, is always required. See BCSI.
2. Truss bracing must be designed by an engineer. For wide truss spacing, individual lateral braces themselves may require bracing, or alternative Tor I bracing should be considered.
3. Never exceed the design loading shown and never stack materials on inadequately braced trusses.
4. Provide copies of this truss design to the building designer, erection supervisor, property owner and all other interested parties.
5. Cut members to bear tightly against each other.
6. Place plates on each face of truss at each joint and embed fully. Knots and wane at joint locations are regulated by ANSI/TP1 1.
7. Design assumes trusses will be suitably protected from the environment in accord with ANSI/TP1 1.
8. Unless otherwise noted, moisture content of lumber shall not exceed 19% at time of fabrication.
9. Unless expressly noted, this design is not applicable for use with fire retardant, preservative treated, or green lumber.
10. Camber is a non-structural consideration and is the responsibility of truss fabricator. General practice is to camber for dead load deflection.
11. Plate type, size, orientation and location dimensions indicated are minimum plating requirements.
12. Lumber used shall be of the species and size, and all respects, equal to or better than that specified.
13. Top chords must be sheathed or purlins provided at spacing indicated on design.
14. Bottom chords require lateral bracing at 10 ft. spacing, or less, if no ceiling is installed, unless otherwise noted.
15. Connections not shown are the responsibility of others.
16. Do not cut or alter truss member or plate without prior approval of an engineer.
17. Install and load vertically unless indicated otherwise.
18. Use of green or treated lumber may pose unacceptable environmental, health or performance risks. Consult with project engineer before use.
19. Review all portions of this design (front, back, words and pictures) before use. Reviewing pictures alone is not sufficient.
20. Design assumes manufacture in accordance with ANSI/TP1 1 Quality Criteria.
21. The design does not take into account any dynamic or other loads other than those expressly stated.






Review for Code Compliance  
Universal Engineering Science

*Lawrence Parnell*  
Examiner-License No.

PX2707

07/15/2024



JOB NAME: Deen Residence

CUSTOMER NAME: Parrish  
Builders Group

ADDRESS: 2938 SW County  
Road 778  
Fort White FL 32038

DATE: 6/26/2024  
JOB#1552

PITCH: 6/12  
OVERHANG: 1'-06"-00"  
ROOF SPACING: 24"

WALL HEIGHT: 10'

\*The General Contractor is  
Responsible For All  
Connections Other Than Truss  
to Truss, unless specified  
otherwise.

**FBC 2023**  
**Roof loading**  
TCLL: 20.0 lb/ft<sup>2</sup>  
TCCL: 10.0 lb/ft<sup>2</sup>  
BCCL: 10.0 lb/ft<sup>2</sup>  
**Floor Loading**  
TCLL: 10.0 lb/ft<sup>2</sup>  
TCCL: 10.0 lb/ft<sup>2</sup>  
BCCL: 5.0 lb/ft<sup>2</sup>

**\*THIS DRAWING MUST  
BE APPROVED AND  
RETURNED BEFORE  
FABRICATION WILL  
BEGIN. For Your  
Protection Check All  
Dimensions and  
Conditions Prior to  
Approval Of Plan**

**\*SIGNATURE BELOW  
INDICATES ALL NOTES  
AND DEMENSIONS  
HAVE BEEN ACCEPTED**

By: \_\_\_\_\_

Date: \_\_\_\_\_

**NOTES:**  
\*ALL DEMENSIONS ARE FEET-  
INCHES- SIXTEENTHS  
\*DO NOT CUT OR ALTER  
TRUSSES IN ANY WAY  
\*ONLY TRUSS TO TRUSS  
CONNECTIONS SUPPLIED  
WITH TRUSS PACKAGES

\*NO BACKCHARGES will be  
accepted



25221 SE Hwy 19  
Old Town, FL 32680  
P: (352) 469-5008  
19Lumberinc@gmail.com

HANGER LIST