Envelope Leakage Test Report (Blower Door Test) Residential Prescriptive, Performance or ERI Method Compliance 2020 Florida Building Code, Energy Conservation, 7th Edition

Jurisdiction:	Permit #: 44252
Job Information	44232
Builder: Community:	Lot: NA
Address: 2054 SW Salem Rd	
City: Lake City State	: FL Zip: 32024
Air Leakage Test Results Passing results must meet	either the Performance, Prescriptive, or ERI Method
PRESCRIPTIVE METHOD-The building or dwelling unit shall be tested and verified as having an air leakage rate of not exceeding 7 air changes per hour at a pressure of 0.2 inch w.g. (50 Pascals) in Climate Zones 1 and 2. PERFORMANCE or ERI METHOD-The building or dwelling unit shall be tested and verified as having an air leakage rate of not exceeding the selected ACH(50) value, as shown on Form R405-2020 (Performance) or R406-2020 (ERI), section labeled as infiltration, sub-section ACH50. ACH(50) specified on Form R405-2020-Energy Calc (Performance) or R406-2020 (ERI): 5.00	
2,912 x 60 ÷ 48000 = 3.64 CFM(50) Building Volume ACH(50) PASS When ACH(50) is less than 3, Mechanical Ventilation in must be verified by building department.	Method for calculating building volume: ☐ Retrieved from architectural plans ☐ Code software calculated ☐ Field measured and calculated
R402.4.1.2 Testing. Testing shall be conducted in accordance with ANSI/RESNET/ICC 380 and reported at a pressure of 0.2 inch w.g. (50 Pascals). Testing shall be conducted by either individuals as defined in Section 553.993(5) or (7), Florida Statues or individuals licensed as set forth in Section 489.105(3)(f), (g), or (i) or an approved third party. A written report of the results of the test shall be signed by the party conducting the test and provided to thecode official. Testing shall be performed at any time after creation of all penetrations of the building thermal envelope. During testing: 1. Exterior windows and doors, fireplace and stove doors shall be closed, but not sealed, beyond the intended weatherstripping or other infiltration control measures. 2. Dampers including exhaust, intake, makeup air, back draft and flue dampers shall be closed, but not sealed beyond intended infiltration control measures. 3. Interior doors, if installed at the time of the test, shall be open. 4. Exterior doors for continuous ventilation systems and heat recovery ventilators shall be closed and sealed. 5. Heating and cooling systems, if installed at the time of the test, shall be fully open.	
Testing Company	
Company Name: E-Calcs Plus, Inc. I hereby verify that the above Air Leakage results are in accordant Energy Conservation requirements according to the compliance report of Tester: Eric Struble Date: 2022.10.04 1 Printed Name of Tester: Eric Struble License/Certification #: HERS Rater ID# 0757810	nethod selected above. Eric Struble