



INNOVATIONS FOR LIVING®

29722

This home has been professionally insulated with

Owens Corning

PROPINK® L77 PINK Fiberglas™ Unbonded Loosefill Insulation

Home Earon Simgue Const (Job Site Address)
 Address 2153 Old Wine Rd
 City Lake City State FL Zip _____

Owens Corning PROPINK® L77 PINK Fiberglas™ Unbonded Loosefill Insulation

Owens Corning will accept no responsibility when the product is not installed in accordance with the product label. Stated R-value is provided by installing the required number of bags at a thickness not less than the labeled minimum thickness. Installation of the required number of bags may yield more than the specified minimum thickness. Failure by the installer to provide both the required bags and at least the minimum thickness will result in lower insulation R-value.

Specification for Open Blow AtticsNew Construction ☒ Retrofit ☐

Number of bags used

22

Estimated R-value of previous insulation

Ø

Area of coverage (sq. ft.)

1458

Other type(s) of insulation in attic

Ø

Thickness of insulation

10 3/4

Depth of previous insulation

Ø

Attics

R-value	Bags Per 1000 Sq. Ft.	Maximum Net Coverage	Minimum Weight Sq. Ft.	Minimum Thickness (in)	Minimum Settled Thickness
R-12	9.5	182.9	3.80	4.75	4.75
R-19	9.7	241.2	0.266	6.75	6.75
R-24	9.4	196.3	0.311	7.75	7.75
R-26	11.2	296.6	0.368	9.00	9.00
R-30	13.0	77.0	0.458	10.25	10.25
R-36	16.6	59.5	0.553	12.75	12.75
R-44	20.1	49.8	0.652	14.75	14.75
R-49	23.6	44.3	0.747	16.25	16.25
R-60	28.5	35.1	0.940	19.50	19.50

Walls

R-value	Minimum Thickness	Installed Density lbs. Per Cu. Ft.	Maximum Coverage Per Bag	Bags Per 1000 Sq. Ft.	Minimum weight lbs. Per Sq. Ft.
13	3.5 (2x4)	1.3	87.2	1.5	0.379
15	3.5 (2x4)	1.5	75.4	13.3	0.438
20	5.5 (2x6)	1.3	55.4	18.1	0.596
24	5.5 (2x6)	1.8	40.0	25.0	0.825

Floors

R-value	Minimum Thickness	Installed Density lbs. Per Cu. Ft.	Maximum Coverage Per Bag	Bags Per 1000 Sq. Ft.	Minimum weight lbs. Per Sq. Ft.
31	2x8	1.4	35.3	25.4	0.846
34	2x10	1.4	30.6	32.7	1.071
46	2x12	1.3	23.5	42.6	1.406

Cathedral Ceiling

R-value	Minimum Thickness	Installed Density lbs. Per Cu. Ft.	Maximum Coverage Per Bag	Bags Per 1000 Sq. Ft.	Minimum weight lbs. Per Sq. Ft.
38	2x8	1.4	42.0	23.2	0.785
39	2x10	1.3	32.9	30.4	1.002
44	2x12	1.3	27.1	36.9	1.219

The product shows negligible settling.

Loosefill insulation varies in thermal performance due to factors such as aging, mean temperature, settlement, convection, moisture absorption and installation variation. Convection in glass loosefill insulation installed in open attics can reduce its thermal performance in extreme winter temperatures during the heating season.

Contractor Moran Insulation Date 2/27/12 Builder _____ Date _____
 Company S. Moran Company _____
 Address _____ Address _____
 Phone _____ Phone _____



INNOVATIONS FOR LIVING®

OWENS CORNING INSULATING SYSTEMS, LLC
 ONE OWENS CORNING PARKWAY
 TOLEDO, OHIO, USA 43659

1-800-GET-PINK®
 www.owenscorning.com

Pub. No. 45145-E Printed in U.S.A., January 2010.
 The color PINK is a registered trademark of Owens Corning. ©2010 Owens Corning.