



Project Information for: L260952

Builder: GIEBEIG HOMES
 Lot : 47
 Subdivision: MAY-FAIR
 County: COLUMBIA
 Truss Count: 32
 Design Program: MiTek 20/20 6.3
 Building Code: FBC2004/TPI2002

Truss Design Load Information:

Gravity: **Wind:**

Roof (psf): 42.0 Wind Standard: ASCE 7-02 Wind Exposure: B
 Floor (psf): N/A Wind Speed (mph): 110

Note: See the individual truss drawings for special loading conditions.

Contractor of Record, responsible for structural engineering:

Brian T. Giebeig Florida Registered Residential Contractor License No. RR282811523

Address: Trent Giebeig Construction, Inc. 462 Southwest Fairlington Court Lake City, Florida 32025


Truss Design Engineer: Julius Lee, PE Florida P.E. License No. 34869

Address: 1109 Coastal Bay Blvd. Boynton Beach, FL 33435

Notes:

1. Determination as to the suitability of these truss components for the structure is the responsibility of the building designer/engineer of record, as defined in ANSI/TPI 1-2002 Section 2.2
2. The seal date shown on the individual truss component drawings must match the seal date on this index sheet.
3. The Truss Design Engineer's responsibility relative to this structure consists solely of the design of the individual truss components and does not include the design of any additional structural elements including but not limited to continuous lateral bracing elements in the web and chord planes. See Florida Administrative Code 61G15-31.003 sections 3 c) & 5 and Chapter 2 of the National Design Standard for Metal Plate Connected Wood Truss Construction ANSI/TPI 1-2002 for additional information on the responsibilities of the delegated "Truss Design Engineer". Builders FirstSource and Julius Lee, PE do not accept any additional delegations beyond the scope of work described in the referenced documents above.


No.	Drwg. #	Truss ID	Date	No.	Drwg. #	Truss ID	Date
1	J1910545	CJ1	11/16/07	29	J1910573	T18	11/16/07
2	J1910546	CJ3	11/16/07	30	J1910574	T19	11/16/07
3	J1910547	CJ3A	11/16/07	31	J1910575	T20	11/16/07
4	J1910548	CJ5	11/16/07	32	J1910576	T21	11/16/07
5	J1910549	CJ5A	11/16/07				
6	J1910550	EJ3	11/16/07				
7	J1910551	EJ7	11/16/07				
8	J1910552	EJ7A	11/16/07				
9	J1910553	HJ4	11/16/07				
10	J1910554	HJ9	11/16/07				
11	J1910555	HJ9A	11/16/07				
12	J1910556	T01	11/16/07				
13	J1910557	T02	11/16/07				
14	J1910558	T03	11/16/07				
15	J1910559	T04	11/16/07				
16	J1910560	T05	11/16/07				
17	J1910561	T06	11/16/07				
18	J1910562	T07	11/16/07				
19	J1910563	T08	11/16/07				
20	J1910564	T09	11/16/07				
21	J1910565	T10	11/16/07				
22	J1910566	T11	11/16/07				
23	J1910567	T12	11/16/07				
24	J1910568	T13	11/16/07				
25	J1910569	T14	11/16/07				
26	J1910570	T15	11/16/07				
27	J1910571	T16	11/16/07				
28	J1910572	T17	11/16/07				



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - MAY-FAIR LOT 47
L260952	CJ1	ROOF TRUSS	18	1	J1910545
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MITek Industries, Inc. Thu Nov 15 16:44:12 2007 Page 1



LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.28	Vert(LL)	-0.00	2	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.01	Vert(TL)	-0.00	2	>999	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.00	Horz(TL)	0.00	3	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
									Weight: 7 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or
1-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc
bracing.

REACTIONS (lb/size) 2=256/0-3-8, 4=5/Mechanical, 3=-90/Mechanical
Max Horz 2=87(load case 6)
Max Uplift 2=-286(load case 6), 4=-9(load case 4), 3=-90(load case 1)
Max Grav 2=256(load case 1), 4=14(load case 2), 3=127(load case 6)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-69/75
BOT CHORD 2-4=0/0

JOINT STRESS INDEX

2 = 0.14

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS gable end zone and C-C Exterior(2) zone; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- 2) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 286 lb uplift at joint 2, 9 lb uplift at joint 4 and 90 lb uplift at joint 3.

Continued on page 2

Julian Lee
Truss Design Engineer
Florida Registered Professional Engineer
1100 Coastal Way Blvd
Boynton Beach, FL 33435

November 16, 2007

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with Mitek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Oroff Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - MAY-FAIR LOT 47
L260952	CJ1	ROOF TRUSS	18	1	J1910545
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Thu Nov 15 16:44:12 2007 Page 2

LOAD CASE(S) Standard

John Lee
Truss Design Engineer
Florida PG No. 34888
1100 Coastal Bay Blvd
Gwynn Beach, FL 33436

November 16, 2007

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE


This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TP1 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - MAY-FAIR LOT 47
L260952	CJ3	ROOF TRUSS	10	1	J1910546
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Thu Nov 15 16:44:12 2007 Page 1



Scale = 1:12.5

LOADING (psf)	SPACING		CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	2-0-0	TC 0.29	Vert(LL)	-0.00	2-4	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.06	Vert(TL)	-0.01	2-4	>999	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.00	Horz(TL)	-0.00	3	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)						Weight: 13 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or
3-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc
bracing.

REACTIONS (lb/size) 3=31/Mechanical, 2=250/0-3-8, 4=14/Mechanical
Max Horz 2=132(load case 6)
Max Uplift 3=-28(load case 7), 2=-203(load case 6)
Max Grav 3=31(load case 1), 2=250(load case 1), 4=42(load case 2)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-57/7
BOT CHORD 2-4=0/0

JOINT STRESS INDEX

2 = 0.13

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS gable end zone and C-C Exterior(2) zone; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- 2) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 28 lb uplift at joint 3 and 203 lb uplift at joint 2.

Continued on page 2

Julius Lee
Truss Design Engineer
Florida ME No. 31888
1100 Coastal Bay Blvd
Denville, DE 19842

November 16, 2007

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCS1-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onotio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - MAY-FAIR LOT 47
L260952	CJ3	ROOF TRUSS	10	1	J1910546
					Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MITek Industries, Inc. Thu Nov 15 16:44:12 2007 Page 2

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida PE No. 24866
1100 Coastal Bay Blvd
Boynton Beach, FL 33435

November 16, 2007

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE


This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MITek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - MAY-FAIR LOT 47
L260952	CJ3A	ROOF TRUSS	4	1	J1910547
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Thu Nov 15 16:44:13 2007 Page 1



LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.29	Vert(LL)	0.01	2-4	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.08	Vert(TL)	-0.01	2-4	>999	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.00	Horz(TL)	-0.00	3	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
										Weight: 13 lb

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 3-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 3=31/Mechanical, 2=250/0-3-8, 4=14/Mechanical
Max Horz 2=132(load case 6)
Max Uplift 3=-28(load case 7), 2=-238(load case 6), 4=-27(load case 4)
Max Grav 3=31(load case 1), 2=250(load case 1), 4=42(load case 2)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-57/7
BOT CHORD 2-4=0/0

JOINT STRESS INDEX

2 = 0.13

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS gable end zone and C-C Exterior(2) zone; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- 2) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 28 lb uplift at joint 3, 238 lb uplift at joint 2 and 27 lb uplift at joint 4.

Continued on page 2

Julius Lee
Truss Design Engineer
Florida PE No. 31886
1100 Central Bay Blvd
Boynton Beach, FL 33435

November 16, 2007

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 563 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - MAY-FAIR LOT 47 J1910547
L260952	CJ3A	ROOF TRUSS	4	1	Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MITek Industries, Inc. Thu Nov 15 16:44:13 2007 Page 2

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida PE No. 24888
1100 Coastal Way Blvd
Boynton Beach, FL 33435

November 16, 2007

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE


This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MITek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - MAY-FAIR LOT 47
L260952	CJ5	ROOF TRUSS	10	1	J1910548
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Thu Nov 15 16:44:14 2007 Page 1



LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.29	Vert(LL)	-0.03	2-4	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.16	Vert(TL)	-0.05	2-4	>999	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.00	Horz(TL)	-0.00	3	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
Weight: 19 lb										

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or
5-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc
bracing.

REACTIONS (lb/size) 3=103/Mechanical, 2=295/0-3-8, 4=24/Mechanical
Max Horz 2=178(load case 6)
Max Uplift 3=-87(load case 6), 2=-199(load case 6)
Max Grav 3=103(load case 1), 2=295(load case 1), 4=72(load case 2)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-88/36
BOT CHORD 2-4=0/0

JOINT STRESS INDEX

2 = 0.14

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS gable end zone and C-C Exterior(2) zone; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- 2) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 87 lb uplift at joint 3 and 199 lb uplift at joint 2.

Continued on page 2

John A. Lee
Truss Design Engineer
Florida PE No. 34888
1100 Coastal Pkwy NW
Covington, GA 30045

November 16, 2007

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - MAY-FAIR LOT 47
L260952	CJ5	ROOF TRUSS	10	1	J1910548
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Thu Nov 15 16:44:14 2007 Page 2

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida PE No. 24880
1100 Coastal Bay Blvd
Dayton Beach, FL 32009

November 16, 2007

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE


This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TP1 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - MAY-FAIR LOT 47
L260952	CJ5A	ROOF TRUSS	4	1	J1910549
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Thu Nov 15 16:44:14 2007 Page 1



LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.29	Vert(LL)	-0.03	2-4	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.16	Vert(TL)	-0.05	2-4	>999	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.00	Horz(TL)	-0.00	3	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
										Weight: 19 lb

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or
5-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc
bracing.

REACTIONS (lb/size) 3=103/Mechanical, 2=295/0-3-8, 4=24/Mechanical
Max Horz 2=178(load case 6)
Max Uplift 3=-87(load case 6), 2=-199(load case 6)
Max Grav 3=103(load case 1), 2=295(load case 1), 4=72(load case 2)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-88/36
BOT CHORD 2-4=0/0

JOINT STRESS INDEX

2 = 0.14

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS gable end zone and C-C Exterior(2) zone; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- 2) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 87 lb uplift at joint 3 and 199 lb uplift at joint 2.

Continued on page 2

Johns Lee
Truss Design Engineer
Florida PE No. 31888
1100 Coastal Bay Blvd
Gwynn Beach, FL 32038

November 16, 2007

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - MAY-FAIR LOT 47
L260952	CJ5A	ROOF TRUSS	4	1	J1910549
					Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Thu Nov 15 16:44:14 2007 Page 2

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida P.E. No. 34881B
1480 Coastal Way Blvd
Boynton Beach, FL 33435

November 16, 2007

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE


This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - MAY-FAIR LOT 47
L260952	EJ3	ROOF TRUSS	3	1	J1910550
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Thu Nov 15 16:44:15 2007 Page 1



LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in (loc)	I/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.29	Vert(LL)	0.01	2-4	>999	360	MT20
TCDL 7.0	Lumber Increase	1.25	BC 0.08	Vert(TL)	-0.01	2-4	>999	240	244/190
BCLL 10.0	* Rep Stress Incr	YES	WB 0.00	Horz(TL)	-0.00	3	n/a	n/a	
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)						Weight: 13 lb

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 3-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 3=31/Mechanical, 2=250/0-3-8, 4=14/Mechanical

Max Horz 2=132(load case 6)

Max Uplift 3=-28(load case 7), 2=-238(load case 6), 4=-27(load case 4)

Max Grav 3=31(load case 1), 2=250(load case 1), 4=42(load case 2)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-57/7

BOT CHORD 2-4=0/0

JOINT STRESS INDEX

2 = 0.13

NOTES

1) Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS gable end zone and C-C Exterior(2) zone; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.

2) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

3) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi

4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 28 lb uplift at joint 3, 238 lb uplift at joint 2 and 27 lb uplift at joint 4.

Continued on page 2

John Lee
Truss Design Engineer
Florida No. 34880
1100 Coastal Bay Blvd
Boynton Beach, FL 33435

November 16, 2007

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Oonofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - MAY-FAIR LOT 47
L260952	EJ3	ROOF TRUSS	3	1	J1910550
					Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Thu Nov 15 16:44:15 2007 Page 2

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida PE No. 34888
1100 Coastal Hwy Blvd
Boynton Beach, FL 33435


November 16, 2007

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



6.300 s Feb 15 2006 MiTek Industries, Inc. Thu Nov 15 16:44:15 2007 Page 1



LUMBER

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 3=154/Mechanical, 2=352/0-3-8, 4=45/Mechanical
 Max Horz 2=161(load case 6)
 Max Uplift 3=-84(load case 6), 2=-139(load case 6)
 Max Grav 3=154(load case 1), 2=352(load case 1), 4=94(load case 2)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-119/54
BOT CHORD 2-4=0/0

JOINT STRESS INDEX
2 = 0.77

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS and C-C Exterior(2) zone; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- 2) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 84 lb uplift at joint 3 and 139 lb uplift at joint 2.

Julius Lee
True Design Engineer
Florida PD No. 2-1000
4100 Central Hwy North
Davenport FL 33415

November 16, 2007

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - MAY-FAIR LOT 47
L260952	EJ7	ROOF TRUSS	25	1	J1910551
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Thu Nov 15 16:44:15 2007 Page 2

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida P.E. No. 34888
1100 Coastal Bay Blvd
Boynton Beach, FL 33435

November 16, 2007

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE


This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling, Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GEIBEIG HOMES - CANNON CREEK PL LOT 11 J1910552
L260952	EJ7A	ROOF TRUSS	2	1	Job Reference (optional)

Builders FirstSource, Bunnell, FL. 32110

6.300 s Apr 19 2006 MiTek Industries, Inc. Fri Nov 16 10:14:20 2007 Page 1



LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.50	Vert(LL)	0.33	B-D	>250	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.45	Vert(TL)	-0.16	B-D	>501	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.00	Horz(TL)	-0.00	C	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
									Weight: 26 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) C=154/Mechanical, B=352/0-3-8, D=45/Mechanical

Max Horz B=161(load case 6)
Max Uplift C=-94(load case 6), B=-224(load case 6), D=-65(load case 5)
Max Grav C=154(load case 1), B=352(load case 1), D=94(load case 2)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD A-B=0/47, B-C=-131/54
BOT CHORD B-D=0/0

JOINT STRESS INDEX

B = 0.58

NOTES

1) Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS and C-C Exterior(2) zone; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.

Julius Lee
Truss Design Engineer
Florida PE No. 24888
1850 Central Expressway
Boynton Beach, FL 33426

November 16, 2007

Continued on page 2

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GEIBEIG HOMES - CANNON CREEK PL LOT 11 J1910552
L260952	EJ7A	ROOF TRUSS	2	1	Job Reference (optional)

Builders FirstSource, Bunnell, FL. 32110

6.300 s Apr 19 2006 MiTek Industries, Inc. Fri Nov 16 10:14:20 2007 Page 2

NOTES

- 2) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 94 lb uplift at joint C, 224 lb uplift at joint B and 65 lb uplift at joint D.

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida PE No. 34888
1100 Coastal Way West
Boynton Beach, FL 33426

November 16,2007

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE


This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - MAY-FAIR LOT 47
L260952	HJ4	ROOF TRUSS	2	1	J1910553
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Thu Nov 15 16:44:16 2007 Page 1



LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.53	Vert(LL)	0.02	2-4	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.10	Vert(TL)	-0.02	2-4	>999	240		
BCLL 10.0	* Rep Stress Incr	NO	WB 0.00	Horz(TL)	-0.00	3	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
									Weight: 18 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or
4-2-15 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc
bracing.

REACTIONS (lb/size) 3=15/Mechanical, 2=275/0-4-15, 4=14/Mechanical

Max Horz 2=98(load case 3)

Max Uplift 3=-6(load case 6), 2=-302(load case 3), 4=-41(load case 3)

Max Grav 3=32(load case 7), 2=275(load case 1), 4=54(load case 2)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/50, 2-3=-37/10

BOT CHORD 2-4=0/0

JOINT STRESS INDEX

2 = 0.11

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS gable end zone; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60.
- 2) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 6 lb uplift at joint 3, 302 lb uplift at joint 2 and 41 lb uplift at joint 4.

John A. Lee
Truss Design Engineer
Florida PE No. 31836
1100 Coastal Highway
Boynton Beach, FL 33435

Continued on page 2

November 16, 2007

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onotio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - MAY-FAIR LOT 47
L260952	HJ4	ROOF TRUSS	2	1	J1910553
					Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Thu Nov 15 16:44:16 2007 Page 2

NOTES

5) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

1) Regular: Lumber Increase=1.25, Plate Increase=1.25

Uniform Loads (plf)

Vert: 1-2=-54

Trapezoidal Loads (plf)

Vert: 2=-3(F=26, B=26)-to-3=-57(F=-2, B=-2), 2=-0(F=5, B=5)-to-4=-11(F=-0, B=-0)

Julius Lee
Truss Design Engineer
Florida P.E. No. 31833
1190 Coastal Bay Blvd
Dayton Beach, FL 32117

November 16, 2007

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE


This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - MAY-FAIR LOT 47
L260952	HJ9	ROOF TRUSS	5	1	J1910554
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Thu Nov 15 16:44:17 2007 Page 1



LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.60	Vert(LL)	-0.04	6-7	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.40	Vert(TL)	-0.11	6-7	>999	240		
BCLL 10.0	* Rep Stress Incr	NO	WB 0.36	Horz(TL)	0.01	5	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
										Weight: 45 lb

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 4=267/Mechanical, 2=453/0-4-15, 5=220/Mechanical
Max Horz 2=269(load case 3)
Max Uplift 4=-231(load case 3), 2=-278(load case 3), 5=-63(load case 3)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/50, 2-3=-650/121, 3-4=-105/65
BOT CHORD 2-7=-309/603, 6-7=-309/603, 5-6=0/0
WEBS 3-7=0/186, 3-6=-627/322

JOINT STRESS INDEX

2 = 0.76, 3 = 0.16, 6 = 0.17 and 7 = 0.13

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS gable end zone; Lumber DOL=1.60 plate grip DOL=1.60.
- 2) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 231 lb uplift at joint 4, 278 lb uplift at joint 2 and 63 lb uplift at joint 5.
- 5) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

Continued on page 2

Julius Lee
Truss Design Engineer
Florida PE No. 34886
1100 Coastal Hwy Blvd
Gwynn Beach, FL 33435

November 16, 2007

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITTEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - MAY-FAIR LOT 47
L260952	HJ9	ROOF TRUSS	5	1	J1910554
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Thu Nov 15 16:44:17 2007 Page 2

LOAD CASE(S) Standard

1) Regular: Lumber Increase=1.25, Plate Increase=1.25

Uniform Loads (plf)

Vert: 1-2=-54

Trapezoidal Loads (plf)

Vert: 2=-3(F=26, B=26)-to-4=-134(F=-40, B=-40), 2=-0(F=5, B=5)-to-5=-25(F=-7, B=-7)

Julius Lee
Truss Design Engineer
Florida P.E. No. 34828
1100 Coastal Bay Blvd
Daytona Beach, FL 32115

November 16, 2007

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE


This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - MAY-FAIR LOT 47
L260952	HJ9A	ROOF TRUSS	2	1	J1910555
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Thu Nov 15 16:44:17 2007 Page 1



LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.60	Vert(LL)	0.09	6-7	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.40	Vert(TL)	-0.11	6-7	>999	240		
BCLL 10.0	* Rep Stress Incr	NO	WB 0.36	Horz(TL)	0.01	5	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
									Weight: 45 lb	

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 7-11-7 oc bracing.

REACTIONS (lb/size) 4=267/Mechanical, 2=453/0-4-15, 5=220/Mechanical
Max Horz 2=269(load case 3)
Max Uplift 4=-233(load case 3), 2=-399(load case 3), 5=-183(load case 3)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/50, 2-3=-650/365, 3-4=-105/65
BOT CHORD 2-7=-538/603, 6-7=-538/603, 5-6=0/0
WEBS 3-7=-89/186, 3-6=-627/559

JOINT STRESS INDEX

2 = 0.76, 3 = 0.22, 6 = 0.17 and 7 = 0.13

NOTES

- 1) Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS gable end zone; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60.
- 2) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 233 lb uplift at joint 4, 399 lb uplift at joint 2 and 183 lb uplift at joint 5.

Julius Lee
Truss Design Engineer
Florida PE No. 34888
1190 Coastal Bay Blvd
Gwynn Beach, FL 32435

November 16, 2007

Continued on page 2

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Oonofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - MAY-FAIR LOT 47
L260952	HJ9A	ROOF TRUSS	2	1	J1910555
					Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Thu Nov 15 16:44:17 2007 Page 2

NOTES

5) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

1) Regular: Lumber Increase=1.25, Plate Increase=1.25

Uniform Loads (plf)

Vert: 1-2=-54

Trapezoidal Loads (plf)

Vert: 2=-3(F=26, B=26)-to-4=-134(F=-40, B=-40), 2=-0(F=5, B=5)-to-5=-25(F=-7, B=-7)

Julius Lee
Truss Design Engineer
Florida P.E. No. 34888
1100 Coastal Hwy Blvd
Boynton Beach, FL 33435

November 16, 2007

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - MAY-FAIR LOT 47
L260952	T01	ROOF TRUSS	1	1	J1910556
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Thu Nov 15 16:44:18 2007 Page 1




Plate Offsets (X,Y): [2:0-8-0,0-0-6], [4:0-4-3,Edge], [5:0-8-0,0-0-6]

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.53	Vert(LL)	-0.09	7-9	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.48	Vert(TL)	-0.19	7-9	>999	240		
BCLL 10.0	* Rep Stress Incr	NO	WB 0.18	Horz(TL)	0.07	5	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
Weight: 88 lb										

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 3-8-5 oc purlins.
BOT CHORD Rigid ceiling directly applied or 8-0-10 oc bracing.

REACTIONS (lb/size) 2=1381/0-3-8, 5=1381/0-3-8
Max Horz 2=77(load case 5)
Max Uplift 2=-474(load case 5), 5=-474(load case 6)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-2416/730, 3-4=-2101/687, 4-5=-2415/730, 5-6=0/47
BOT CHORD 2-9=-619/2080, 8-9=-590/2100, 7-8=-590/2100, 5-7=-586/2079
WEBS 3-9=-125/568, 4-9=-124/126, 4-7=-108/516

JOINT STRESS INDEX

2 = 0.74, 3 = 0.82, 4 = 0.85, 5 = 0.74, 7 = 0.37, 8 = 0.77 and 9 = 0.36

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS; Lumber DOL=1.60 plate grip DOL=1.60.
- Provide adequate drainage to prevent water ponding.
- *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi

Continued on page 2

Julius Lee
Truss Design Engineer
Florida Reg No. 21000
1100 Coastal Bay Blvd
Boynton Beach, FL 33435

November 16,2007

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE
This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - MAY-FAIR LOT 47
L260952	T01	ROOF TRUSS	1	1	J1910556
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Thu Nov 15 16:44:18 2007 Page 2

NOTES

- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 474 lb uplift at joint 2 and 474 lb uplift at joint 5.
- 7) Girder carries hip end with 7-0-0 end setback.
- 8) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- 1) Regular: Lumber Increase=1.25, Plate Increase=1.25

Uniform Loads (plf)

Vert: 1-3=-54, 3-4=-118(F=-64), 4-6=-54, 2-9=-10, 7-9=-22(F=-12), 5-7=-10

Concentrated Loads (lb)

Vert: 9=-411(F) 7=-411(F)

John A. Lane
Truss Design Engineer
Provides the following
1100 Coastal Bay Blvd
Gwynn Beach, FL 33410

November 16, 2007

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - MAY-FAIR LOT 47
L260952	T02	ROOF TRUSS	1	1	J1910557
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Thu Nov 15 16:44:19 2007 Page 1




Plate Offsets (X,Y): [2:0-1-5,0-0-7], [7:0-1-5,0-0-7]

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.29	Vert(LL)	-0.13 2-11	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.42	Vert(TL)	-0.25 2-11	>965	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.12	Horz(TL)	0.03 7	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)						
Weight: 104 lb									

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 2=747/0-3-8, 7=747/0-3-8
Max Horz 2=-89(load case 7)
Max Uplift 2=-229(load case 6), 7=-229(load case 7)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-1067/567, 3-4=-805/447, 4-5=-675/453, 5-6=-806/448, 6-7=-1067/567, 7-8=0/47
BOT CHORD 2-11=-346/898, 10-11=-143/674, 9-10=-143/674, 7-9=-346/898
WEBS 3-11=-258/229, 4-11=-61/210, 5-9=-61/209, 6-9=-257/228, 4-9=-104/109

JOINT STRESS INDEX

2 = 0.85, 3 = 0.33, 4 = 0.45, 5 = 0.37, 6 = 0.33, 7 = 0.85, 9 = 0.64, 10 = 0.59 and 11 = 0.34

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS and C-C Exterior(2) zone; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- Provide adequate drainage to prevent water ponding.
- *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

Continued on page 2

Julius Lee
Truss Design Engineer
Florida P.E. No. 31886
1100 Coastal Hwy Blvd
Boynton Beach, FL 33435

November 16, 2007

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - MAY-FAIR LOT 47
L260952	T02	ROOF TRUSS	1	1	J1910557
					Job Reference (optional)

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Thu Nov 15 16:44:19 2007 Page 2

NOTES

- 5) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 229 lb uplift at joint 2 and 229 lb uplift at joint 7.

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida PE No. 34888
1170 Coastal Hwy Blvd
Boynton Beach, FL 33426

November 16, 2007

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE


This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - MAY-FAIR LOT 47
L260952	T03	ROOF TRUSS	5	1	J1910558
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Thu Nov 15 16:44:20 2007 Page 1



LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.36	Vert(LL)	0.24	8-10	>989	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.66	Vert(TL)	-0.37	8-10	>640	240		
BCLL 10.0	* Rep Stress Incr	NO	WB 0.18	Horz(TL)	0.04	6	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
										Weight: 97 lb

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-9-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 7-9-10 oc bracing.

REACTIONS (lb/size) 2=960/0-3-8, 6=960/0-3-8
Max Horz 2=-95(load case 7)
Max Uplift 2=-292(load case 6), 6=-292(load case 7)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-1609/870, 3-4=-1438/813, 4-5=-1438/813, 5-6=-1609/870, 6-7=0/47
BOT CHORD 2-10=-621/1374, 9-10=-316/925, 8-9=-316/925, 6-8=-621/1374
WEBS 3-10=-216/200, 4-10=-263/547, 4-8=-263/547, 5-8=-216/200

JOINT STRESS INDEX

2 = 0.69, 3 = 0.33, 4 = 0.82, 5 = 0.33, 6 = 0.69, 8 = 0.40, 9 = 0.53 and 10 = 0.40

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS and C-C Exterior(2) zone; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- 3) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 292 lb uplift at joint 2 and 292 lb uplift at joint 6.

Continued on page 2

Julius Lee
Truss Design Engineer
Florida PE No. 24188
1100 Coastal Way North
Boynton Beach, FL 33435

November 16, 2007

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITTEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - MAY-FAIR LOT 47
L260952	T03	ROOF TRUSS	5	1	J1910558
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Thu Nov 15 16:44:20 2007 Page 2

NOTES

6) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

1) Regular: Lumber Increase=1.25, Plate Increase=1.25

Uniform Loads (plf)

Vert: 1-4=-54, 4-7=-54, 2-10=-10, 8-10=-70(F=-60), 6-8=-10

Julius Lee
Truss Design Engineer
Florida P.E. No. 34888
11100 Central Bay Blvd
Boynton Beach, FL 33435

November 16, 2007

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



6.300 s Feb 15 2006 MiTek Industries, Inc. Thu Nov 15 16:44:21 2007 Page 1



TOP CHORD	Structural wood sheathing directly applied or 2-6-7 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 5-2-2 oc bracing.

November 16, 2007

Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - MAY-FAIR LOT 47
L260952	T04	ROOF TRUSS	1	1	J1910559
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Thu Nov 15 16:44:21 2007 Page 2

NOTES

- 4) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 660 lb uplift at joint 2 and 660 lb uplift at joint 7.
- 7) Girder carries hip end with 7-0-0 end setback.
- 8) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- 1) Regular: Lumber Increase=1.25, Plate Increase=1.25

Uniform Loads (plf)

Vert: 1-3=-54, 3-6=-118(F=-64), 6-8=-54, 2-11=-10, 9-11=-22(F=-12), 7-9=-10

Concentrated Loads (lb)

Vert: 11=-411(F) 9=-411(F)

John A. Lee
Truss Design Engineer
Florida PE No. 31888
1100 Coastal Hwy Blvd
Boynton Beach, FL 33435

November 16, 2007

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - MAY-FAIR LOT 47
L260952	T05	ROOF TRUSS	1	1	J1910560
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Thu Nov 15 16:44:22 2007 Page 1




Plate Offsets (X,Y): [2:0-1-5,0-0-7], [8:0-1-5,0-0-7], [11:0-3-0,0-3-0]

LOADING (psf)	SPACING	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP
TCLL 20.0	Plates Increase	1.25	TC 0.31	Vert(LL)	-0.15	2-12	>999	360	MT20	244/190
TCDL 7.0	Lumber Increase	1.25	BC 0.52	Vert(TL)	-0.29	2-12	>999	240		
BCLL 10.0	* Rep Stress Incr	YES	WB 0.38	Horz(TL)	0.08	8	n/a	n/a		
BCDL 5.0	Code FBC2004/TPI2002		(Matrix)							
										Weight: 154 lb

LUMBER

TOP CHORD 2 X 4 SYP No.2
BOT CHORD 2 X 4 SYP No.2
WEBS 2 X 4 SYP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-8-4 oc purlins.
BOT CHORD Rigid ceiling directly applied or 7-8-15 oc bracing.

REACTIONS (lb/size) 2=1069/0-3-8, 8=1069/0-3-8
Max Horz 2=89(load case 6)
Max Uplift 2=-267(load case 6), 8=-267(load case 7)

FORCES (lb) - Maximum Compression/Maximum Tension

TOP CHORD 1-2=0/47, 2-3=-1745/913, 3-4=-1515/815, 4-5=-1325/788, 5-6=-1325/788,
6-7=-1515/815, 7-8=-1745/913, 8-9=0/47
BOT CHORD 2-12=-649/1494, 11-12=-617/1570, 10-11=-617/1570, 8-10=-650/1494
WEBS 3-12=-208/198, 4-12=-138/397, 5-12=-401/176, 5-11=0/128, 5-10=-401/176,
6-10=-138/397, 7-10=-208/198

JOINT STRESS INDEX

2 = 0.82, 3 = 0.33, 4 = 0.60, 5 = 0.56, 6 = 0.60, 7 = 0.33, 8 = 0.82, 10 = 0.56, 11 = 0.37 and 12 = 0.56

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-02; 110mph (3-second gust); h=13ft; TCDL=4.2psf; BCDL=3.0psf; Category II; Exp B; enclosed; MWFRS and C-C Exterior(2) zone; Lumber DOL=1.60 plate grip DOL=1.60. This truss is designed for C-C for members and forces, and for MWFRS for reactions specified.
- Provide adequate drainage to prevent water ponding.

Continued on page 2

Julius Lee
Truss Design Engineer
Florida PE No. 34888
1100 Coastal Hwy NW
Boynton Beach, FL 33435

November 16, 2007

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719



Job	Truss	Truss Type	Qty	Ply	GIEBEIG HOMES - MAY-FAIR LOT 47
L260952	T05	ROOF TRUSS	1	1	J1910560
Job Reference (optional)					

Builders FirstSource, Lake City, FL 32055

6.300 s Feb 15 2006 MiTek Industries, Inc. Thu Nov 15 16:44:22 2007 Page 2

NOTES

- 4) *This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) All bearings are assumed to be SYP No.2 crushing capacity of 565.00 psi
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 267 lb uplift at joint 2 and 267 lb uplift at joint 8.

LOAD CASE(S) Standard

Julius Lee
Truss Design Engineer
Florida P.E. No. 34886
1100 Coastal Bay Blvd
Boynton Beach, FL 33426

November 16, 2007

Warning - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 BEFORE USE

This design is based only upon the parameters shown for an individual building component that is installed and loaded vertically and fabricated with MiTek connectors. Applicability of design parameters and proper incorporation of component into the overall building structure, including all temporary and permanent bracing, is the responsibility of building designer and / or contractor per ANSI / TPI 1 as referenced by the building code. For general guidance regarding storage, delivery, erection and bracing, consult BCSI-1 or HIB-91 Handling Installing and Bracing Recommendation available from the Wood Truss Council of America, 1 WTCA Center, 6300 Enterprise Lane, Madison, WI 53719 or the Truss Plate Institute, 583 D'Onofrio Drive, Madison, WI 53719

