### FLORIDA ENERGY EFFICIENCY CODE FOR BUILDING CONSTRUCTION

Florida Department of Business and Professional Regulation - Residential Performance Method

Project Name: New Millennium - Guard House	Builder Name:							
Street: City, State, Zip: , FL,	Permit Office: Permit Number:							
Owner:	Jurisdiction:							
Design Location: FL, Gainesville	County: columbia(Florida Climate Zone 2)							
New construction or existing     New (From Plans)	10. Wall Types(648.0 sqft.) Insulation Area							
Single family or multiple family  Detached	a. Frame - Wood, Exterior R=13.0 522.00 ft <sup>2</sup> b. Frame - Wood, Adjacent R=13.0 126.00 ft <sup>2</sup>							
Number of units, if multiple family	c. N/A							
4. Number of Bedrooms 0	d. N/A							
5. Is this a worst case?	11. Ceiling Types(310.0 sqft.) Insulation Area a. Flat ceiling under att (Vented) R=30.0 310.00 ft <sup>2</sup>							
6. Conditioned floor area above grade (ft²) 310 Conditioned floor area below grade (ft²) 0	b. N/A c. N/A							
7. Windows(75.3 sqft.) Description Area a. U-Factor: Dbl, U=0.26 75.25 ft <sup>2</sup>	<ul> <li>12. Roof(Comp. Shingles, Vented) Deck R=0.0 320 ft<sup>2</sup></li> <li>13. Ducts, location &amp; insulation level R ft<sup>2</sup></li> </ul>							
SHGC: SHGC=0.20 b. U-Factor: N/A ft <sup>2</sup> SHGC:	a. b. c.							
c. U-Factor: N/A ft <sup>2</sup> SHGC:	14. Cooling Systems kBtu/hr Efficiency a. Central Unit 12.0 SEER2:21.00							
Area Weighted Average Overhang Depth: 1.500 ft Area Weighted Average SHGC: 0.200								
8. Skylights Description Area U-Factor:(AVG) N/A N/A ft <sup>2</sup> SHGC(AVG): N/A	15. Heating Systems kBtu/hr Efficiency a. Electric Heat Pump 12.0 HSPF2:12.00							
9. Floor Types Insulation Area a. Slab-On-Grade Edge Insulation R= 0.0 310.00 ft <sup>2</sup> b. N/A R= ft <sup>2</sup>	16. Hot Water Systems a.							
c. N/A R= $\text{ft}^2$	b. Conservation features							
	17. Credits CF, Pstat							
Glass/Floor Area: 0.243 Total Proposed Modif Total Basel	117 C.C.							
NOTE: Proposed residence must have annual total normalized Modified Loads that are less than or	or equal to 95 percent of the annual total loads of the standard reference design in order to comply.							
I hereby certify that the plans and specifications covered by this calculation are in compliance with the Florida Energy Code.  PREPARED BY:  8-7-24	Review of the plans and specifications covered by this calculation indicates compliance with the Florida Energy Code. Before construction is completed this building will be inspected for compliance with Section 553.908							
I hereby certify that this building, as designed, is in compliance with the Florida Energy Code  OWNER/AGENT:  DATE: 8-7-2024	BUILDING OFFICIAL:  DATE:							

- Compliance requires certification by the air handler unit manufacturer that the air handler enclosure qualifies as certified factory-sealed in accordance with R403.3.2.1.
- Homes without ducts do not require duct testing.
- Compliance requires an Air Barrier and Insulation Inspection Checklist in accordance with R402.4.1.1 and this project requires a PERFORMANCE envelope leakage test report with envelope leakage no greater than 5.24 ACH50 (R402.4.1.2).

# **INPUT SUMMARY CHECKLIST REPORT**

				PROJE	СТ						
Title: Building Type: Owner: Builder Home ID: Builder Name: Permit Office: Jurisdiction: Family Type: New/Existing: Year Construct: Comment:	New Millennium - User  Detached New (From Plans 2024	)	Bedrooms Condition Total Stor Worst Ca: Rotate An Cross Ver Whole Ho Terrain: Shielding:	ed Area: ies: se: gle: ntilation: use Fan:	0 310 1 No 0 Suburban Suburban	Lot : Bloc Plat Stre Cou	:k/SubDivisi Book: et:		Address		
				CLIMA	TE						
Design Location		Tmy Site		Desigr 97.5%	Temp 2.5%		gn Temp Summer	Heating Degree Day	Desi ys Moistu		ily temp inge
FL, Gainesville		FL_GAINESVILLE_F	REGIONA	32	92	70	75	1305.5	51	Medi	ium
				BLOC	KS						
√ Number	Name	Area	Volu	ume							
1	Block1	310	279	0 cu ft							
				SPAC	ES						
√ Number	Name	Area	Volume	Kitchen	Occupants	s Bed	rooms	Finished	Co	oled I	Heated
1	office	310	2790	Yes	1			Yes	Y	'es	Yes
				FLOO	RS		(Total E	xposed	Area =	310 sc	μ.ft.)
# Floor Typ	e	Space	Expos Perim			Value m. Joist	U-Factor	Slab Insu Vert/Horiz	ıl. Tile	Wood	Carpet
1 Slab-On-G	ade Edge Ins	office	72	310	sqft 0		0.710	0 (ft)/0	(ft) 1.00	0.00	0.00
				ROO	F						
√# Type		Materials			able Roof Area Colo			SA E Tested	mitt Emitt Tested	Deck I Insul.	
1 Hip		Composition shingles	32	20 ft² (	) ft <sup>2</sup> Mediu	m N	0.96	No (	).9 No	0	14.04
				ATTI	С						
√# Type		Ventilation		Vent Rat	io (1 in)	Area	RBS	IR	CC		
1 Full attic		Vented		30	0	310 ft <sup>2</sup>	N		N		
				CEILII	NG		(Total E	xposed	Area =	310 sc	ı.ft.)
√# Ceiling T	уре	S	pace	R-Valu	e Ins. Ty	pe Ar	ea U-F	actor Frar	ning Frac.	Trus	s Type
1 Flat ceiling	under attic(Vented	١	office	30.0	Blowi	n 310	Oft2 O (	030	0.11	14	/ood

# **INPUT SUMMARY CHECKLIST REPORT**

								WA	LLS	}		(To	tal Ex	oosed	Area	a = 64	l8 sq.	ft.)
<b>\</b> #	Ornt		icent o	Wall Type		Space			vity Value	Width Ft In		Height Ft In	Area sq.ft.	U- Factor	Sheatl R-Valu		Solar . Absor	Below . Grade
1 2 3 4	E S		Exterior Exterior Garage Exterior	Frame - Woo Frame - Woo Frame - Woo Frame - Woo	od od	of of	fice fice fice fice	1 1	3.0  3.0  3.0  3.0	14.0 (22.0 (14.0 (22.0 (14.0 (	) 9	9.0 0 9.0 0 9.0 0	126.0 198.0 126.0 198.0	0.084 0.084		0.23 0.23 0.23 0.23	0.75 0.75 0.75 0.75	0 % 0 % 0 % 0 %
<b>DOORS</b> (Total Exposed Area = 40 sq.ft.)																		
<b>/</b> #	Ornt		Adjacent	To Door Type	e	Space			Storr	ms	U	l-Value		/idth <sup>-</sup> t In		eight t In	Ar	ea
1 2	E S		Exterio Garage			office office			No No			0.46 0.46	3.00 3.00		6.00 6.00		20. 20.	
							W	/INI	DOW	IS		T)	otal E	xpose	ed Are	ea = 7	'5 sq.	ft.)
<b>/</b> #	Ornt	Wall ID	Frame	Panes	NFRC	U-Factor	SHGC	Imp	Storm	Total Area (ft²)	Same Units	Width (ft)	Height (ft)	Overh Depth (ft)		Interior	Shade	Screen
1 2 3	E	1 2 4	Vinyl Vinyl Vinyl	Low-E Double Low-E Double Low-E Double	Y Y Y	0.26 0.26 0.26	0.20 0.20 0.20	N N N	N N N	33.3 21.0 21.0	1 1 1	9.50 6.00 6.00	3.50 3.50 3.50	1.5 1.5 1.5	1.3 1.3 1.3	No No No	ne	None None None
							INF	ILT	RAT	ION								
<b>\</b> #	Scope	е	Ме	ethod	S	SLA C	CFM50	E	ELΑ	EqLA	١	ACH	ACH5	0 Spac	e(s)	Infiltra	tion Tes	t Volume
1	Wh	olehou	ise Prop	oosed ACH(50)	0.0	0030	244	1	3.37	25.10	) (	0.1076	5.2	Al	I	2790 (	cu ft	
							C	<b>SAF</b>	RAGI	E								
<b>/</b> #		F	loor Area	ı	Roof Are	ea	Exp	osed	Wall Po	erimeter		Avg	ı. Wall He	ight	Exp	osed Wa	all Insula	ition
1			112 ft²		112 ft <sup>2</sup>	!			30 ft				8 ft			1		
								M	ASS									
<b>/</b> #	Ma	ss Typ	е		А	rea		Т	hicknes	S	Furr	niture Fra	action	5	Space			
1	Def	ault(8	lbs/sq.ft.)		C	) ft²			0 ft			0.30			office			
						ŀ	HEAT	INC	3 SY	STE	VI							
<b>/</b> #	Sys	stem Ty	ype		Subtype/	Speed .	AHRI	#	Effici	ency	Capa kBtu/	-	Geoth ntry Po		eatPum Volt C		Oucts	Block
1	Ele	ctric H	eat Pump	Small	Duct Hig	gh Velocity	/S		HSPF2	2: 12.00	12.0	0	C	0.00	0.00	0.00 s	ys#0	1
						C	COOL	IN	G SY	STE	M							
<b>/</b> #	Sys	stem Ty	ype		Subtype/	Speed	АН	RI#	Eff	iciency		Capacit kBtu/hı	,	Air Flow cfm	S	HR I	Duct	Block

# **INPUT SUMMARY CHECKLIST REPORT**

		СО	OLIN	G SYS	TEM(	Continu	ued)					
1 Central Unit		Sm. Duct Hi Ve	lo/Single		SEER	2:21.0 12	2.0	3	360	0.75	Ductless	s 1
HOT WATER SYSTEM												
# System Type	Subtype	Locatio	n	EF(UEF)	Сар	Use	SetPnt	Fixture	Flow I	Pipe Ins.	Pipe	length
Recirculation System	Recirc Co Type	ntrol	Loop length	Branch length	Pump power	DWHR	Facilitie Connect	-		DWHR Eff	Other	Credits
				DU	ICTS							
	upply R-Value Area	Re Location	turn R-Value		Leakage <sup>-</sup>	Гуре	Air Handler	CFM 25 TOT	CFM 25 OUT			HVAC # eat Cool
			TI	EMPE	RATU	RES						
Programable Thermond Cooling [] Jan Heating [X] Jan Venting [] Jan	[] Feb [] [X] Feb [X]	Mar [] Apr   Mar [] Apr   Mar [X] Apr	/ [ ] / [ ]	/lay [		[X] Jul [ ] Jul [ ] Jul	[X] Aug [] Aug [] Aug	[X] Sep [] Sep [] Sep	[] Oc [] Oc [X] Oc	t [X]	Nov Nov Nov	[] Dec [X] Dec [] Dec
Thermostat Sched Schedule Type	ule: HERS 2006 1		3	4	5	Hou 6	ırs 7	8	9	10	11	12
Cooling (WD)	AM 7 PM 8	78 78 80 80	78 80	78 80	78 78	78 78	78 78	78 78	80 78	80 78	80 78	80 78
Cooling (WEH)	AM 7 PM 8	78 78 30 80	78 80	78 80	78 78	78 78	78 78	78 78	80 78	80 78	80 78	80 78
Heating (WD)	AM 6	65 68 68	65 68	65 68	65 68	65 68	65 68	68 68	68 68	68 68	68 68	68 68
Heating (WEH)	AM 6	65 65 68 68	65 68	65 68	65 68	65 68	65 68	68 68	68 68	68 68	68 68	68 68

### **ENERGY PERFORMANCE LEVEL (EPL) DISPLAY CARD ESTIMATED ENERGY PERFORMANCE INDEX\* = 58**

The lower the EnergyPerformance Index, the more efficient the home.

"FL,

1. New construction or e	xisting	New (From Plan	s) 1	0. Wall Types(648.0 sqft.)	Insulation	
2. Single family or multip	2. Single family or multiple family		ed	a. Frame - Wood, Exterior	R=13.0	522.00 ft <sup>2</sup>
3. Number of units, if mu	3. Number of units, if multiple family			b. Frame - Wood, Adjacent c. N/A	R=13.0	126.00 ft <sup>2</sup>
4. Number of Bedrooms			0	d. N/A		
5. Is this a worst case?		١	No 1	1. Ceiling Types(310.0 sqft.)	Insulation	2
<ol><li>Conditioned floor area Conditioned floor area</li></ol>		•	10 0	a. Flat ceiling under att (Vented) b. N/A c. N/A	R=30.0	310.00 ft <sup>2</sup>
7. Windows** a. U-Factor: SHGC: b. U-Factor:	Description Dbl, U=0.26 SHGC=0.20 N/A	Arc 75.25		<ol> <li>Roof(Comp. Shingles, Vented) I</li> <li>Ducts, location &amp; insulation level         <ul> <li>b.</li> </ul> </li> </ol>	Deck R=0.0	320 ft <sup>2</sup> R ft <sup>2</sup>
SHGC: c. U-Factor: SHGC: Area Weighted Average Area Weighted Average	• •	th: 1.500	ft	c. 4. Cooling Systems a. Central Unit	kBtu/hr 12.0 SE	Efficiency ER2:21.00
8. Skylights U-Factor:(AVG) SHGC(AVG):	Description N/A N/A	Are N/A	ea 1	5. Heating Systems a. Electric Heat Pump	kBtu/hr 12.0 HS	Efficiency SPF2:12.00
<ol> <li>Floor Types</li> <li>a. Slab-On-Grade Edge</li> <li>b. N/A</li> </ol>	==	nsulation Are = 0.0 310.0 =	0 ft <sup>2</sup>	6. Hot Water Systems a.		
c. N/A	R:	=	ft <sup>2</sup>	b. Conservation features		
			1	7. Credits		CF, Pstat

I certify that this home has complied with the Florida Energy Efficiency Code for Building Construction through the above energy saving features which will be installed (or exceeded) in this home before final inspection. Otherwise, a new EPL Display Card will be completed based on installed Code compliant features.

8-7-2024 Builder Signature: Date:

Address of New Home: City/FL Zip: ,FL,

\*Note: This is not a Building Energy Rating. If your Index is below 70, your home may qualify for energy efficient mortgage (EEM) incentives if you obtain a Florida Energy Rating. For information about the Florida Building Code, Energy Conservation, contact the Florida Building Commission's support staff.

\*\*Label required by Section R303.1.3 of the Florida Building Code, Energy Conservation, if not DEFAULT.

