


| COLUMN DIMENSIONS |     |     |     |
|-------------------|-----|-----|-----|
| Size              | W   | D   | H   |
| CU1               | 18" | 18" | 10' |
| CU3               | 18" | 18" | 10' |
| CU5               | 18" | 18" | 10' |
| CU7               | 18" | 18" | 10' |
| CU9               | 18" | 18" | 10' |



BEARING HEIGHT SCHEDULE

10'0"

8/12

PITCH

18"

OH

NOTES:

- 1) REFER TO THE RECOMMENDATIONS FOR THE INSTALLATION AND TYPICAL BEARING HEIGHTS FOR THE TRUSSES FOR THE RECOMMENDED BEARING HEIGHTS.
- 2) ALL TRUSSES INCLUDING TRUSSES USED FOR THE ROOF SHALL BE INSTALLED AT THE BEARING HEIGHTS SHOWN UNLESS OTHERWISE NOTED.
- 3) ALL WALLS ARE TO BE CONVENTIONALLY FINISHED BY THE OWNER.
- 4) ALL TRUSSES ARE TO BE DESIGNED FOR 7' OC SPACING UNLESS OTHERWISE NOTED.
- 5) ALL WALLS SHOWN ON THIS PLAN SHALL BE CONSIDERED TO BE CONVENTIONALLY FINISHED BY THE OWNER UNLESS OTHERWISE NOTED.
- 6) STAIR TRUSSES MUST BE INSTALLED WITH THE TOP CHORD UP.
- 7) ALL ROOF TRUSSES HANGERS TO BE SUPPLIED BY THE OWNER UNLESS OTHERWISE NOTED. ALL TRUSSES SHALL BE INSTALLED UNLESS OTHERWISE NOTED.
- 8) REFER TO THE RECOMMENDATIONS FOR THE INSTALLATION AND TYPICAL BEARING HEIGHTS FOR THE TRUSSES FOR THE RECOMMENDED BEARING HEIGHTS.

SHOP DRAWING APPROVAL

THIS LAYOUT IS THE SOLE SOURCE FOR INFORMATION OF THE TRUSSES AND JOBS. ALL TRUSSES AND JOBS MUST BE REVIEWED AND APPROVED BY THE TRUSS MANUFACTURER BEFORE ANY TRUSSES WILL BE DELIVERED TO THE JOB SITE. ALL TRUSSES MUST BE INSTALLED IN EXACT DIMENSIONS TO THE TRUSS MANUFACTURER'S DRAWINGS.

Approved By: \_\_\_\_\_  
**Builders FirstSource**  
 Dumfries  
 PHONE: 904.437.5349 FAX: 904.437.5994  
 JACKSONVILLE  
 PHONE: 904.772.6000 FAX: 904.772.1973  
 LAKE CITY  
 PHONE: 386.755.6984 FAX: 386.755.7873  
 SANFORD  
 PHONE: 407.327.0098 FAX: 407.322.9993

DATE: \_\_\_\_\_  
 DRAWN BY: E.W.P.L.  
 CHECKED BY: \_\_\_\_\_  
 TITLE: \_\_\_\_\_  
 PROJECT: HAKKER RESIDENCE  
 SCALE: NT5  
 SHEET: 11/7106 JOE | 217950