

Business & Professional Regulation







Product Approval Menu > Product or Application Search > Application List > Application Detail

FL5414-R28 Application Type Affirmation Code Version 2020 Application Status Approved

> *Approved by DBPR. Approvals by DBPR shall be reviewed and ratified by the POC and/or the Commission if necessary.

Archived

Product Manufacturer Address/Phone/Email

Simonton/Ply Gem Windows 5020 Weston Parkway Suite 300 Cary, NC 27513 (800) 542-9118 Ext 413596 luanne.harris@cornerstone-bb.com

Authorized Signature

Luanne Harris luanne.harris@cornerstone-bb.com

Technical Representative Address/Phone/Email

Luanne Harris 3948 Townsfair Way Suite 200 Columbus, OH 43219 (614) 532-3596 luanne.harris@simonton.com

Quality Assurance Representative Address/Phone/Email

AAMA 1827 Walden Office Square Suite 550 Schaumburg, IL 60173 (847) 303-5664 webmaster@aamanet.org

Category Subcategory

Windows Single Hung

Compliance Method

Certification Mark or Listing

Certification Agency Validated By

American Architectural Manufacturers Association American Architectural Manufacturers Association

Referenced Standard and Year (of Standard)

Year AAMA/WDMA/CSA 101/I.S 2/A440 2008 AAMA/WDMA/CSA 101/I.S 2/A440 2011

Equivalence of Product Standards Certified By

> I affirm that there are no changes in the new Florida Building Code which affect my product(s) and my product(s) are in

compliance with the new Florida Building Code.

Documentation from approved Evaluation or Validation Entity

Yes No N/A

FL5414 R28 COC 7thEdFBC-FL5414.pdf

Product Approval Method

Method 1 Option A

Date Submitted

12/14/2020

Date Validated

12/14/2020

Date Pending FBC Approval

Date Approved

12/21/2020

Design Pressure: N/A

FL#	Model, Number or Name	Description
5414.1	41-18	ProFinish Brickmould 300, PerfeXion BM 300 Vinyl Single Hung
Impact Resista Design Pressur Other: 48x80 (+	se outside HVHZ: Yes nt: No e: N/A -/-25 PSF), 53x71 (+/-30 PSF), 44x63 (+/-35 40 PSF), 36x63 (+/-45 PSF), 44x63 (+/-45	Certification Agency Certificate FL5414 R28 C CAC 41-18 SH 36x63 R-PG45.pdf FL5414 R28 C CAC 41-18 SH 36x76 R-PG50.pdf FL5414 R28 C CAC 41-18 SH 44x63 R45.pdf FL5414 R28 C CAC 41-18 SH 44x63 R-PG35.pdf FL5414 R28 C CAC 41-18 SH 44x63 R-PG35.pdf FL5414 R28 C CAC 41-18 SH 48x72 R40.pdf FL5414 R28 C CAC 41-18 SH 48x80 R-PG25.pdf FL5414 R28 C CAC 41-18 SH 53x71 R-PG30.pdf Quality Assurance Contract Expiration Date 05/24/2021 Installation Instructions FL5414 R28 II IN0228 41-18 SH 2X.pdf FL5414 R28 II IN0285-R2 41-18 SH 1X.pdf Verified By: American Architectural Manufacturers Association Created by Independent Third Party: Evaluation Reports FL5414 R28 AE EvalReport-IN0285-R2-2017.pdf Created by Independent Third Party: Yes
5414.2	41-18	ProFinish Brickmould 300, PerfeXion BM 300 Vinyl Twin Single Hung
Impact Resista Design Pressur	se outside HVHZ: Yes int: No re: N/A -/-25 PSF), 89x63 (+/-30 PSF), 73x74 (+/-45	Certification Agency Certificate FL5414 R28 C CAC 41-18 SH Twin 73x74 R PG50.pdf FL5414 R28 C CAC 41-18 SH Twin 73x74 R-PG45.pdf FL5414 R28 C CAC 41-18 SH Twin 89x63 R30.pdf FL5414 R28 C CAC 41-18 SH Twin 96x80 R25.pdf Quality Assurance Contract Expiration Date 06/11/2021 Installation Instructions FL5414 R28 II IN0230 41-18 SH T-Mulled Twin 2X.pdf Verified By: American Architectural Manufacturers Association Created by Independent Third Party: Evaluation Reports Created by Independent Third Party:
5414.3	41-18	ProFinish Brickmould 300, PerfeXion BM 300 Vinyl Triple Single Hung
Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: No Design Pressure: N/A Other: 109x63 (+/-35 PSF) or 109x72 (+/-45 PSF)		Certification Agency Certificate FL5414 R28 C CAC 41-18 SH Triple 109x63 R35 (ext.).pdf FL5414 R28 C CAC 41-18 SH Twin 109x72 R PG45.pdf Quality Assurance Contract Expiration Date 03/08/2021 Installation Instructions FL5414 R28 II IN0232 41-18 SH T-Mull Triple 2X.pdf Verified By: American Architectural Manufacturers Association Created by Independent Third Party: Evaluation Reports Created by Independent Third Party:
5414.4	43-06 / 43-17	6060 VantagePointe, ProFinish Builder, ProFinish Contractor, ProFinish Master, PerfeXion Contractor Vinyl Single Hung
Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: No Design Pressure: N/A		Certification Agency Certificate FL5414 R28 C CAC 43-06 SH (Fin - Finless) 36x84 R50.pdf FL5414 R28 C CAC 43-06 SH (Fin - Finless) 48x72 R PG40.pdf FL5414 R28 C CAC 43-06 SH (Fin) 32x62 R50 (ext.).pdf

Other: 36x72 (+/-25 PSF), 48x80 (+/-25 PSF), 36x63 (+/- 45 PSF) 44x63 (+/-35 PSF), 36x74 (+/-35 PSF), 53x71 (+/-35

FL5414 R28 C CAC 43-06 SH (Fin) 32x62 R50 (ext.).pdf

FL5414 R28 C CAC 43-06 SH (Fin) 36x63 R45 (ext.),pdf FL5414 R28 C CAC 43-06 SH (Fin) 36x72 R25 (ext.),pdf

		Florida Building	Code Online
	PSF), 48x72 (+/-40 PSF), 44x63 (+/-45 PSF), 36x84 (+/-50 PSF), 36x74 (+/-50 PSF), 32x62 (+/-50 PSF), 44x75 (+/-30)		FL5414 R28 C CAC 43-06 SH (Fin) 36x74 H R35.pdf FL5414 R28 C CAC 43-06 SH (Fin) 36x74 H R50.pdf FL5414 R28 C CAC 43-06 SH (Fin) 44x63 H R35.pdf FL5414 R28 C CAC 43-06 SH (Fin) 44x63 H R45.pdf FL5414 R28 C CAC 43-06 SH (Fin) 44x65 H R45.pdf FL5414 R28 C CAC 43-06 SH (Fin) 48x80 LC25.pdf FL5414 R28 C CAC 43-06 SH (Fin) 48x80 LC25.pdf FL5414 R28 C CAC 43-06 SH (Finless) 36x74 R50.pdf FL5414 R28 C CAC 43-06 SH (Finless) 48x80 R25.pdf FL5414 R28 C CAC 43-17 SH (Finless) 48x80 R25.pdf FL5414 R28 C CAC 43-17 SH (Finless) 48x80 R25.pdf FL5414 R28 C CAC 43-17 SH (Finless) 48x80 R25.pdf FL5414 R28 C CAC 43-17 SH (Finless) 48x80 R25.pdf FL5414 R28 C CAC 43-17 SH (Finless) 48x80 R25.pdf FL5414 R28 II IN0160 43-06 43-17 SH 2X.pdf FL5414 R28 II IN0242-R6 43-06 43-17 SH 1X.pdf Verified By: American Architectural Manufacturers Association Created by Independent Third Party: Evaluation Reports FL5414 R28 AE EvalReport-IN0242-R6.pdf Created by Independent Third Party: Yes
	5414.5	43-17	ProFinish Contractor, ProFinish Master, PerfeXion Contractor Vinyl Single Hung
	Limits of Use Approved for use in H Approved for use outs Impact Resistant: No Design Pressure: N/A Other: 48x80 (+/-25 PS PSF), 36x96 (+/-50 PSF)	side HVHZ: Yes SF), 44x63 (+/-35 PSF), 36x76 (+/-50	Certification Agency Certificate FL5414 R28 C CAC 43-17 SH 36x76 R50.pdf FL5414 R28 C CAC 43-17 SH 36x96 R PG50.pdf FL5414 R28 C CAC 43-17 SH 44x63 R35.pdf FL5414 R28 C CAC 43-17 SH 44x96 R PG20.pdf FL5414 R28 C CAC 43-17 SH 48x80 R PG25.pdf Quality Assurance Contract Expiration Date 07/11/2021 Installation Instructions FL5414 R28 II IN0162 43-17 SH 2X.pdf FL5414 R28 II IN0244-R5 43-17 SH 1X.pdf Verified By: American Architectural Manufacturers Association Created by Independent Third Party: Evaluation Reports FL5414 R28 AE EvalReport-IN0244-R5.pdf Created by Independent Third Party: Yes
	5414.6	43-17	ProFinish Contractor, ProFinish Master, PerfeXion Contractor Vinyl Twin Single Hung
	Limits of Use Approved for use in H Approved for use outs Impact Resistant: No Design Pressure: N/A Other: 89x63 (+/-30 PS PSF)		Certification Agency Certificate FL5414 R28 C CAC 43-17 SH Twin 73x63 R35.pdf FL5414 R28 C CAC 43-17 SH Twin 73x74 R PG45.pdf FL5414 R28 C CAC 43-17 SH Twin 89x63 R30.pdf Quality Assurance Contract Expiration Date 07/10/2021 Installation Instructions FL5414 R28 II IN0161 43-17 SH T-Mull Twin 2X.pdf FL5414 R28 II IN0246-R3 43-17 SH T-Mull 1X.pdf Verified By: American Architectural Manufacturers Association Created by Independent Third Party: Evaluation Reports FL5414 R28 AE EvalReport-IN0246-R3.pdf Created by Independent Third Party: Yes
	5414.7	43-17	ProFinish Contractor, ProFinish Master, PerfeXion Contractor Vinyl Triple Single Hung
	Limits of Use Approved for use in H Approved for use outs Impact Resistant: No Design Pressure: +35/ Other: 109" x 63"	ide HVHZ: Yes	Certification Agency Certificate FL5414 R28 C CAC 43-17 SH Triple 109x63 H R35.pdf FL5414 R28 C CAC 43-17 SH Triple 109x63 R PG35.pdf Quality Assurance Contract Expiration Date 04/04/2021 Installation Instructions FL5414 R28 II IN0248-R3 43-17 SH T-Mull Triple 1X.pdf Verified By: American Architectural Manufacturers Association Created by Independent Third Party: Evaluation Reports FL5414 R28 AE EvalReport-IN0248-R3.pdf Created by Independent Third Party: Yes
	5414.8	43-17 (Sunroom)	ProFinish Contractor, PerfeXion Contractor Vinyl Single Hung for Sunrooms
	Limits of Use Approved for use in H Approved for use outs Impact Resistant: No Design Pressure: N/A		Certification Agency Certificate FL5414 R28 C CAC 43-17 SH 36x96 R PG50.pdf FL5414 R28 C CAC 43-17 SH 44x63 R35.pdf FL5414 R28 C CAC 43-17 SH 48x80 R PG25.pdf Quality Assurance Contract Expiration Date 07/11/2021

Other: 36x96 (+/-50 PSF), 44x63 (+/-35 PSF), 48x80 (+/-25

Installation Instructions

FL5414 R28 II IN0528 43-17 SH SUNROOM.pdf

Verified By: American Architectural Manufacturers Association

Created by Independent Third Party:

Evaluation Reports FL5414 R28 AE PER5926.pdf

Created by Independent Third Party: Yes

Contact Us:: 2601 Blair Stone Road, Tallahassee FL 32399 Phone: 850-487-1824

The State of Florida is an AA/EEO employer. Copyright 2007-2013 State of Florida. :: Privacy Statement :: Accessibility Statement :: Refund Statement

Under Florida law, email addresses are public records. If you do not want your e-mail address released in response to a public-records request, do not send electronic mail to this entity. Instead, contact the office by phone or by traditional mail. If you have any questions, please contact 850.487.1395. *Pursuant to Section 455.275(1), Florida Statutes, effective October 1, 2012, licensees licensed under Chapter 455, F.S. must provide the Department with an email address if they have one. The emails provided may be used for official communication with the licensee. However email addresses are public record. If you do not wish to supply a personal address, please provide the Department with an email address which can be made available to the public. To determine if you are a licensee under Chapter 455, F.S., please click <a href="https://example.com/html/personal-address-new-mai

Product Approval Accepts:











Credit Card Safe securitymetrics