

COLUMBIA COUNTY BUILDING DEPARTMENT RESIDENTIAL CHECK LIST

MINIMUM PLAN REQUIREMENTS: FLORIDA BUILDING CODE RESIDENTIAL 2014 EFFECTIVE 1 JULY 2015 AND THE NATIONAL ELECTRICAL CODE 2014 EFFECTIVE 1 JULY 2015

ALL REQUIREMENTS ARE SUBJECT TO CHANGE

ALL BUILDING PLANS MUST INDICATE COMPLIANCE WITH THE CURRENT 2014 FLORIDA BUILDING CODES RESIDENTIAL, EFFECTIVE 1 JULY 2015. NATIONAL ELECTRICAL CODE 2011 EFFECTIVE 1 JULY 2015. ALL PLANS OR DRAWINGS SHALL PROVIDE CALCULATIONS AND DETAILS THAT HAVE THE SEAL AND SIGNATURE OF A CERTIFIED ARCHITECT OR ENGINEER REGISTERED IN THE STATE OF FLORIDA, OR ALTERNATE METHODOLOGIES, APPROVED BY THE STATE OF FLORIDA BUILDING COMMISSION FOR ONE-AND-TWO FAMILY DWELLINGS.

FOR DESIGN PURPOSES THE FOLLOWING BASIC WIND SPEEDS ARE PER FLORIDA BUILDING CODE FIGURE 1609-A THROUGH 1609-C ULTIMATE DESIGN WIND SPEEDS FOR RISK CATEGORY AND BUILDINGS AND OTHER STRUCTURES Revised 12/2016

	GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Each Box shall be Marked as Applicable		
	m (M) 1	Select From the Dropbox		
1	Two (2) complete sets of plans containing the following:	- 1152		
2	All drawings must be clear, concise, drawn to scale, details that are not used shall be marked void	- 1100		
3	Condition space (Sq. Ft.) 60 Total (Sq. Ft.) under roof 2697	YES NO N/A		
be	esigners name and signature shall be on all documents and a licensed architect or engineer, signature an affixed to the plans and documents as per the FLORIDA BUILDING CODES RESIDENTIAL R101. Ite Plan information including: Dimensions of lot or parcel of land Dimensions of all building set backs Location of all other structures (include square footage of structures) on parcel, existing or proposed well and septic tank and all utility easements.	ad official embossed seal shall 2.1		
7	Provide a full legal description of property.	- UPC		
W	ind-load Engineering Summary, calculations and any details are required. GENERAL REQUIREMENTS:	Items to Include-		
APPLICANT - PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL		Each Box shall be Marked as Applicable		
8	Plans or specifications must show compliance with FBCR Chapter 3	(YES) NO N/A		
-		Select From the Dropbox		
9	Basic wind speed (3-second gust), miles per hour	- UPS		
10	(Wind exposure – if more than one wind exposure			
	is used, the wind exposure and applicable wind direction shall be indicated)	- yes		
11	Wind importance factor and nature of occupancy	- Ves		
12	The applicable internal pressure coefficient, Components and Cladding	-1145		
	The design wind pressure in terms of psf (kN/m²), to be used for the design of exterior component,			
13	cladding materials not specifally designed by the registered design professional.	·UES		
Ele	evations Drawing including:			
14	All side views of the structure	I- Yes		
15	Roof pitch	- 425		
16	Overhang dimensions and detail with attic ventilation	- 425		
17	Location, size and height above roof of chimneys	1. 463		
18	Location and size of skylights with Florida Product Approval	- 1167		
18	Number of stories	1- 162		
20A		- 1100		

Flo	or Plan including:	
••	Dimensioned area plan showing rooms, attached garage, breeze ways, covered porches, deck,	- yec
20	balconies	
21	Raised floor surfaces located more than 30 inches above the floor or grade	- hla
22	All exterior and interior shear walls indicated	- yes
23	Shear wall opening shown (Windows, Doors and Garage doors)	- yes
4	Show compliance with Section FBCR 310 Emergency escape and rescue opening shown in each	· · ·
	bedroom (net clear opening shown) and Show compliance with Section FBC 1405.13.2 where the	
	opening of an operable window is located more than 72 inches above the finished grade or surface	
	below, the lowest part of the clear opening of the window shall be a minimum of 24 inches above	- yes
	the finished floor of the room in which the window is located. Glazing between the floor and 24	
	inches shall be fixed or have openings through which a 4-inch-diameter sphere cannot pass.	
5	Safety glazing of glass where needed	- nla
	Fireplaces types (gas appliance) (vented or non-vented) or wood burning with Hearth	975
6	(see chapter 10 and chapter 24 of FBCR)	799
		-
7	Show stairs with dimensions (width, tread and riser and total run) details of guardrails, Handrails	
	(,,	- n 2
8	Identify accessibility of bathroom (see FBCR SECTION 320)	- Mra
	GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Items to Include- Each Box shall be Marked as
		Applicable
9	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.	elect From the Dropbo
0	All posts and/or column footing including size and reinforcing	- Yes
	Any special support required by soil analysis such as piling.	- hla
	Assumed load-bearing valve of soil Pound Per Square Foot	r Wie
	Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures	
3	with foundation which establish new electrical utility companies service connection a Concrete	
	Encased Electrode will be required within the foundation to serve as an grounding electrode system.	- Wa
1	Per the National Electrical Code article 250.52.3	
	rei the ivational electrical code article 230.32.3	
B		
	CR 506: CONCRETE SLAB ON GRADE	
	CR 506: CONCRETE SLAB ON GRADE Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed)	1-
5 I	Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed)	-
5		-
	Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports	-
В	Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES	-
ВС	Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or	
ВС	Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered	- URS
ВС	Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or	- yrs
ВС	Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides CR 606: Masonry Walls and Stem walls (load bearing & shear Walls)	
BC	Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides CR 606: Masonry Walls and Stem walls (load bearing & shear Walls) Show all materials making up walls, wall height, and Block size, mortar type	- yes
B(Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides CR 606: Masonry Walls and Stem walls (load bearing & shear Walls)	
BC 7 8	Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides CR 606: Masonry Walls and Stem walls (load bearing & shear Walls) Show all materials making up walls, wall height, and Block size, mortar type	- yes
BO 7 8	Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides CR 606: Masonry Walls and Stem walls (load bearing & shear Walls) Show all materials making up walls, wall height, and Block size, mortar type Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement al frame shear wall and roof systems shall be designed, signed and sealed by Florida Prof	- yes
BC 7 8 Met	Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides CR 606: Masonry Walls and Stem walls (load bearing & shear Walls) Show all materials making up walls, wall height, and Block size, mortar type Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement	f. Engineer or Archit
BC 7 8 Met	Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides CR 606: Masonry Walls and Stem walls (load bearing & shear Walls) Show all materials making up walls, wall height, and Block size, mortar type Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement al frame shear wall and roof systems shall be designed, signed and sealed by Florida Protection of Framing System: First and/or second story	- yes

	Show conventional floor joint time airs area area and a state of the s	
40	Show conventional floor joist type, size, span, spacing and attachment to load bearing walls, stem walls and/or priers	- 400
41		
42		- 1185
43		1 - 467
44		- UPI
45		- nla
46		- Wa
47	Show the required access opening to access to under-floor spaces	- hila
7,	Show the required access opening to access to under-noor spaces Show the sub-floor structural panel sheathing type, thickness and fastener schedule on the edges &	-
48	intermediate of the areas structural panel sheathing	- Unes
49		
50	Show fireproofing requirements for garages attached to living spaces, per FBCR section 302.6	15-11
51	Provide live and dead load rating of floor framing systems (psf).	11-03
		- yes
FB	CR CHAPTER 6 WOOD WALL FRAMING CONSTRUCTION	YES / NO / N
	GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Items to Include- Each Box shall be Marked as Applicable
- 2	Secret processing to the secret secre	elect From the Drop
52	Stud type, grade, size, wall height and oc spacing for all load bearing or shear walls	- 4 2 5
3	Fastener schedule for structural members per table IRC 602.3 are to be shown	- 465
	Show Wood structural panel's sheathing attachment to studs, joist, trusses, rafters and structural	2 7 ****
4	members, showing fastener schedule attachment on the edges & intermediate of the areas structural panel sheathing	- yes
	Show all required connectors with a max uplift rating and required number of connectors and	
5	oc spacing for continuous connection of structural walls to foundation and roof trusses or rafter systems	- 425
	Show sizes, type, span lengths and required number of support jack studs, king studs for shear	1.400
6	wall opening and girder or header per IRC Table 502.5 (1)	- Lies
7	Indicate where pressure treated wood will be placed	- U-es
	Show all wall structural panel sheathing, grade, thickness and show fastener schedule for structural	- ues
8 9	panel sheathing edges & intermediate areas	
9	A detail showing gable truss bracing, wall balloon framing details or/ and wall hinge bracing detail	- yes
	CR :ROOF SYSTEMS:	
0	Truss design drawing shall meet section FBCR 802.1.6.1 Wood trusses	- 4-05
1	Include a layout and truss details, signed and sealed by Florida Professional Engineer	- 1123
2	Show types of connector's assemblies' and resistance uplift rating for all trusses and rafters	. 400
3	Show gable ends with rake beams showing reinforcement or gable truss and wall bracing details	- 1101
1	Provide dead load rating of trusses	. 925
B	CR 802:Conventional Roof Framing Layout	
Ĩ	Rafter and ridge beams sizes, span, species and spacing	1 . 4.4
	Connectors to wall assemblies' include assemblies' resistance to uplift rating	- 100
	Valley framing and support details	· Hes
	Provide dead load rating of rafter system	- 48
		1 6/23
B	CR 803 ROOF SHEATHING	
	include all materials which will make up the roof decking, identification of structural panel	. 1185
	sheathing, grade, thickness	L 14.4.2
	Show fastener Size and schedule for structural panel sheathing on the edges & intermediate areas	- URS
13		
00	OF ASSEMBLIES FRC Chapter 9	
00	OF ASSEMBLIES FRC Chapter 9 Include all materials which will make up the roof assembles covering Submit Florida Product Approval numbers for each component of the roof assembles covering	- 4-62

FBCR Chapter 11 Energy Efficiency Code for residential building

Residential construction shall comply with this code by using the following compliance methods in the FBCR chapter 11 Residential buildings compliance methods. Two of the required forms are to be submitted, N1100.1.1.1 As an alternative to the computerized Compliance Method A, the Alternate Residential Point System Method hand calculation, Alternate Form 600A, may be used. All requirements specific to this calculation are located in Sub appendix C to Appendix G. Buildings complying by this alternative shall meet all mandatory requirements of this chapter. Computerized versions of the Alternate Residential Point System Method shall not be acceptable for code compliance.

YES / NO / N/A

	GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Items to Include- Each Box shall be Marked as Applicable
		Select From the Dropbox
73	Show the insulation R value for the following areas of the structure	142
	Attic space	I LIPC
75	Exterior wall cavity	125
76	Crawl space	- W-14
H	VAC information	7,
77	Submit two copies of a Manual J sizing equipment or equivalent computation study	1-485
78		- 40
	20 cfm continuous required	- 17-6 -
79	Show clothes dryer route and total run of exhaust duct	- 1125
PI	umbing Fixture layout shown	
	All fixtures waste water lines shall be shown on the foundation plan	- C15.2
-	Show the location of water heater	- 11-62
Pr 82	ivate Potable Water Pump motor horse power	,
	Reservoir pressure tank gallon capacity	-
84		<u> </u>
04	Raining of cycle stop valve if used	<u> </u>
	ectrical layout shown including	
85	Show Switches, receptacles outlets, lighting fixtures and Ceiling fans	- Ues
86	Show all 120-volt, single phase, 15- and 20-ampere branch circuits outlets required to be protected	- 4-62
	by Ground-Fault Circuit Interrupter (GFCI) Article 210.8 A	
87	Show the location of smoke detectors & Carbon monoxide detectors	- 4-7
88	Show service panel, sub-panel, location(s) and total ampere ratings	- 442
89	On the electrical plans identify the electrical service overcurrent protection device for the main electrical service. This device shall be installed on the exterior of structures to serve as a disconnecting means for the utility company electrical service. Conductors used from the exterior disconnecting means to a panel or sub panel shall have four-wire conductors, of which one conductor shall be used as an equipment ground. Indicate if the utility company service entrance cable will be of the overhead or underground type.	- 425
00	For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an Grounding electrode system. Per the National Electrical Code article 250.52.3	1.75
90	Appliances and HVAC equipment and disconnects	
91	Show all 120-volt, single phase, 15- and 20-ampere branch circuits supplying outlets installed in dwelling unit family rooms, dining rooms, living rooms, parlors, libraries, dens, bedrooms, sunrooms, recreation rooms, closets, hallways, or similar rooms or areas shall be protected by a listed Combination arc-fault circuit interrupter , Protection device.	: Lites

GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL

Items to Include-Each Box shall be Circled as Applicable

THE FOLLOWING ITEMS MUST BE SUBMITTED WITH BUILDING PLANS

		YES	NO	N/A
92	Building Permit Application A current Building Permit Application is to be completed, by following the Checklist all supporting documents must be submitted. There is a \$15.00 application fee. The completed application with attached documents and application fee can be mailed.	NO		
93	Parcel Number The parcel number (Tax ID number) from the Property Appraisers Office (386) 758-1083 is required. A copy of property deed is also required. www.columbiacountyfla.com	NÓ	U/A	\$
94	Town of Fort White (386) 497-2321 If the parcel in the application for building permit is within the Corporate city limits of Fort White, an approval land use development letter issued by the Town of Fort is required to be submitted with the application for a building permit.	NO		
***	BELOW ITEMS ONLY NEEDED AFTER ZONING APPROVAL HAS GIVEN.	****	***	***
95	Environmental Health Permit or Sewer Tap Approval A copy of a approved Columbia County Environmental Health (386) 758-1058	NO	ries	
96	City of Lake City A City Water and/or Sewer letter. Call 386-752-2031 Flood Information: All projects within the Floodway of the Suwannee or Santa Fe Rivers shall require permitting through the Suwannee River Water Management District, before submitting	NO		
	a application to this office. Any project located within a flood zone where the base flood elevation (100 year flood) has been established shall meet the requirements of Section 8.5.2 of the Columbia County Land Development Regulations. Any project located within a flood zone where the base flood elevation has not been established (Zone A) shall meet the requirements of Section 8.5.3 of the Columbia County Land Development Regulations	NO		
98	CERTIFIED FINISHED FLOOR ELEVATIONS will be required on any project where the approved FIRM Flood Maps show the property is in a AE, Floodway, and AH flood zones. Additionally One Foot Rise letters are required for AE and AH zones. In the Floodway Flood zones a Zero Rise letter is required. A Flood development permit is also required for AE, Floodway & AH. Development permit cost is \$50.00			
100	Driveway Connection: If the property does not have an existing access to a public road, then an application for a culvert permit (\$25.00) must be made. County Public Works Dept. determines the size and length of every culvert before instillation and completes a final inspection before permanent power is granted. If the applicant feels that a culvert is not needed, they may apply for a culvert waiver (\$50.00) Separate Check when issued. If the project is to be located on an F.D.O.T. maintained road, then an F.D.O.T. access permit is required.	NO		
101	911 Address: An application for a 911 address must be applied for and received through the Columbia County Emergency Management Office of 911 Addressing Department (386) 758-1125.	No		

TOILET FACILITIES SHALL BE PROVIDED FOR ALL CONSTRUCTION SITES. NO

<u>Disclosure Statement for Owner Builders</u> If you as the applicant will be acting as an owner/builder under section 489.103(7) of the Florida Statutes, submit the required owner builder disclosure statement form.

Notice Of Commencement

A notice of commencement form recorded in the Columbia County Clerk Office is required to be filed with the building department Before Any Inspections can be preformed.

Section R101.2.1 of the Florida Building Code Residential:

The provisions of Chapter 1, Florida Building Code shall govern the administration and enforcement of the Florida Building Code, Residential.