



5/12 PITCH

1'6" OVERHANGS

NOTES:

1) REFER TO HB 91 (RECONMENDATIONS FOR HAVELING INSTALLATION AND TEMPORARY BRACING) REFER TO ENGNEED DRAWINGS FOR PERMANENT BRACING REQUIRED

- 2) ALL TRUSSES (INCLUDING TRUSSES UNDER VALLEY FRANKING) MUST DE COMPLETELY DECKED OR REFER TO DETAIL VOS FOR ALTERNATE BRACING RECRIREMENTS 3) ALL VALLEYS ARE TO BE CONVENTIONALLY FRAMED BY BUILDER.
- 4.) ALL TRUSSES ARE DESIGNED FOR Z' a c MAXIMUM SPACING, UNLESS OTHERWISE NOTED
- 5) ALL WALLS SHOWN ON PLACEMENT PLAN ARE CONSIDERED TO BE LOAD BEARING, UNLESS OTHERWISE NOTED.

- T) ALL ROOF TRUSS HANGERS TO BE SIMPSON HTU26 UNLESS OTHERWISE NOTED ALL PLOOR TRUSS HANGERS TO BE SIMPSON THA 422 UNLESS OTHERWISE NOTED 6) 5742 TRUSSES MUST BE INSTALLED WITH THE TOP BEING UP
- 8.) BEAMHEADER/LINTEL (HDR) TO BE FURNISHED BY BUILDER

SHOP DRAWING APPROVAL

THS LAYOUT IS THE SOLE SOURCE FOR FABRICATION OF TRUSSES AND YOURS ALL PREVIOUS ARCHITECTURAL OR OTHER TRUSS LAYOUTS. REVIEW AND APPROVAL OF THIS LAYOUT AUST BE RECEIVED DEFORE ANY TRUSSES WILL BE DULT. VERBY ALL CONDITIONS TO INSURE AGAINST CHANGES THAT WILL RESULT. IN EXTRA CHARGES TO YOU

Requested Delivery Date

	by	
Builders FirstSource	Date:	

|--|

PHONE: 904-437-3349 FAX: 904-437-3994 Jacksonville

WIREGRASS

LOT 17 HEIGHT ASHBURY

CUSTOM

SLN 31W75

03-27-06

RAL

L157178

BEARING HEIGHT SCHEDULE