


1405-216

ITW Building Components Group, Inc.

2400 Lake Orange Drive suite 150 Orlando FL 32837
Florida Engineering Certificate of Authorization Number 0 278
Florida Certificate of Product Approval # FL1999
Page 1 of 1 Document ID 1V6E487-Z0115100241

Truss Fabricator **Anderson Truss Company**
Job Identification **14-071-Affinity Construction /Carpenter Add. -- 3643**
Truss Count **2**
Model Code **Florida Building Code 2010**
Truss Criteria **FBC2010Res/TPI-2007(STD)**
Engineering Software **Alpine Software, Version 13.02.**
Structural Engineer of Record **The identity of the structural EOR did not exist as of**
Address **the seal date per section 61G15-31.003(5a) of the FAC**
Minimum Design Loads
Roof - 37.0 PSF @ 1.25 Duration
Floor - N/A
Wind - 120 MPH ASCE 7-10 -Closed

05/15/2014



Walter P. Finn
-Truss Design Engineer-


1. Determination as to the suitability of these truss components for the structure is the responsibility of the building designer/engineer of record, as defined in ANSI/TPI 1
2. The drawing date shown on this index sheet must match the date shown on the individual truss component drawing.
3. As shown on attached drawings; the drawing number is preceded by: HCUSR9114

1950 Marley Drive
Haines City, FL 33844

Details: 12015EC1-GBLLETIN-GABRST10-

#	Ref	Description	Drawing#	Date
1	38786--A	27' Common	14135001	05/15/14
2	38787--ADC	27' Gable	14135002	05/15/14

ALPINE





Gable Detail

For Let-in Verticals

Gable Truss Plate Sizes
Refer to appropriate ITW gable detail for minimum plate sizes for vertical studs

(+) Refer to Engineered truss design for peak splice web and heel plates

(*) If gable vertical plates overlap use a single plate that covers the total area of the overlapped plates to span the web



Provide connections for uplift specified on the engineered truss design

Attach each "T" reinforcing member with

End-Driven Nails

10d Common (0.118" x 3" m) Nails at 4" o.c. plus

10d Nails in the top and bottom chords

Toenailed Nails 10d Common (0.118" x 3" m) Toenails at 4" o.c. plus

(4) toenails in the top and bottom chords

This detail to be used with the appropriate ITW gable detail for ASCE wind load

ASCE 7-98 Gable Detail Drawings

A13015980109 A12015980109 A10015980109 A10015980109

A13030980109 A12030980109 A1030980109 A1030980109

ASCE 7-12 Gable Detail Drawings A1030980109 A1030980109

A13015020109 A12015020109 A10015020109 A14015020109

A1303020109 A1203020109 A1003020109 A10303020109 A1403020109

ASCE 7-05 Gable Detail Drawings A1301550109 A1201550109 A1001550109 A1401550109

A1303050109 A1203050109 A1003050109 A10303050109 A1403050109

ASCE 7-10 Gable Detail Drawings A1031505102 A14031505102 A1401505102

A180150510212 A200150510212 A200150510212 A15050610212

A15050610212 A120150610212 A10030610212 A20030610212

A18030610212 A20030610212 A20030610212 A20030610212

See appropriate ITW gable detail for maximum unreinforced gable vertical length

To convert from "L" to "T" reinforcing members multiply "T" increase by length (based on appropriate ITW gable detail)


Maximum allowable "T" reinforced gable vertical length is 14' from top to bottom chord.

"T" reinforcing member material must match size specie and grade of the "L" reinforcing member

Web Length Increase w/ "T" Brace

"T" Reinf Mbr Size	"T" Increase
2x4	30 %
2x6	20 %

Example ASCE 7-10 Wind Speed = 120 mph
Mean Roof Height = 30 ft Kzt = 100
Gable Vertical = 24 o.c. SP #3
"T" Reinforcing Member Size = 2x4
"T" Brace Increase (From Above) = 30% = 1.30
(1) 2x4 "L" Brace Length = 8' 7" (130 x 8' 7" = 11' 2")
Maximum "T" Reinforced Gable Vertical Length



T Reinforcement Attachment Detail
"T" Reinforcing Member
"T" Reinforcing Member




Building Components Group Inc.

Earth City MO 63045

WARNING READ AND FOLLOW ALL NOTES ON THIS DRAWING! FURNISH THIS DRAWING TO ALL CONTRACTORS, INCLUDING THE INSTALLERS.

Trusses require extreme care in fabrication, handling, shipping, installing, and bracing. Refer to end follow the tests, BESI Building Components Safety Manual for specific information. It is the responsibility of the professional engineer to perform these functions. Unless noted otherwise, chord shall have a properly attached rigid ceiling. Locations shown for permanent lateral restraint of webs shall have bracing installed per BESI sections B3, B7 or B10 as applicable. Apply plates to each face of truss and position as shown above and on the joint details, unless noted otherwise. Refer to drawings 1504-10 for standard plate positions.

ITW Building Components Group Inc. shall not be responsible for any deviation from these drawings, any failure to follow the tests, BESI Building Components Safety Manual or any other code or standard for which the professional engineer is responsible. The safety of any structure is the responsibility of the professional engineer. A seal on this drawing or cover drawing, or any engineering drawing, does not constitute a waiver of responsibility for any structure. For any structure, the responsibility is the responsibility of the Building Designer per ANSI/ATI Sec 2. For more information see this job's general notes page and these websites: ITWBCG (www.itwbcg.com), ITW (www.itw.com), TDS (www.tdst.org), ASCE (www.asce.org) and ICC (www.iccsafe.org).



REF	LET-IN VERT
DATE	2/16/12
DRWG	GBLLETIN0212
MAX TOT LD	60 PSF
DUR FAC	ANY
MAX SPACING	24 0"

