

8'0"

DUAL

PITCH

18"

O.H.

NOTES:

- 1) REFER TO HB 91 (RECOMMENDATIONS FOR HANDBLING INSTALLATION AND TEMPORARY BRACING) REFER TO ENGINEERED DRAWINGS FOR PERMANENT BRACING REQUIRED
- 2) ALL TRUSSES, INCLUDING TRUSSES UNDER VALLEY FRAMING MUST BE CORR ECTLY DECIDED OR REFER TO DETAIL V09 FOR ALTERNATE BRACING REQUIREMENTS
- 3) ALL VALLEYS ARE TO BE CONVENTIONALLY FRAMED BY BUILDER
- 4) ALL TRUSSES ARE DESIGNED FOR 2 0 c MAXIMUM SPACING, UNLESS OTHERWISE NOTED
- 5) ALL WALLS SHOWN ON PLACEMENT PLAN ARE CONSIDERED TO BE LOAD BEARING, UNLESS OTHERWISE NOTED
- 6) 5"x42 TRUSSES MUST BE INSTALLED WITH THE TOP BEARING UP
- 7) ALL ROOF TRUSSES HANGERS TO BE SIMPSON HUS26, UNLESS OTHERWISE NOTED. ALL FLOOR TRUSSES HANGERS TO BE SIMPSON TH4422 UNLESS OTHERWISE NOTED
- 8) BEAM/HEADER/INTEL (HXR) TO BE FURNISHED BY BUILDER

SHOP DRAWING APPROVAL

THIS LAYOUT IS THE SOLE SOURCE FOR FABRICATION OF TRUSSES AND VIDS. ALL PREVIOUS ARCHITECTURAL OR OTHER TRUSS LAYOUTS, REVIEW AND APPROVAL OF THIS LAYOUT MUST BE RECEIVED BEFORE ANY TRUSSES WILL BE BUILT. VERIFY ALL CONDITIONS TO INSURE AGAINST CHANGES THAT WILL RESULT IN EXTRA CHARGES TO YOU.

Accepted Drawing Date: _____

Approved by: _____ Date: _____



PHONE: 904.437.3349 FAX: 904.437.3904

PHONE: 904.772.6100 FAX: 904.772.1073

PHONE: 904.755.6894 FAX: 904.755.7975

PHONE: 407.322.0094 FAX: 407.322.5553

PRUDENTIAL BLDGS

LOT 44-PRICE CREEK LANDING

WESTON

6/19/06 JOE L169928

DATE: 6/19/06

