

24562

BEARING HEIGHT SCHEDULE

8'-0"

6/12 PITCH
2' OVERHANGS

NOTES:

- 1) REFER TO THE SPECIFICATIONS FOR FRAMING DETAILING AND TEMPORARY BRACING. REFER TO ENGINEER DRAWINGS FOR TEMPORARY BRACING REQUIRED.
- 2) ALL TRUSSES INCLUDING TRUSSES UNDER VALLEY FRAMING MUST BE COMPLETELY DECIDED OR REFER TO DETAIL VIDS FOR ALTERNATE BRACING REQUIREMENTS.
- 3) ALL VALLEYS ARE TO BE CONVENTIONALLY FRAMED BY BUILDER.
- 4) ALL TRUSSES ARE DESIGNED FOR 2.0 Cc MAXIMUM SPACING, UNLESS OTHERWISE NOTED.
- 5) ALL WALLS SHOWN ON PLACEMENT PLAN ARE CONSIDERED TO BE LOAD BEARING, UNLESS OTHERWISE NOTED.
- 6) 5"x42" TRUSSES MUST BE INSTALLED WITH THE TOP BEING UP.
- 7) ALL ROOF TRUSSES HANGERS TO BE SHIM/ON FLOOR UNLESS OTHERWISE NOTED. ALL FLOOR TRUSSES HANGERS TO BE SHIM/ON TH4422 UNLESS OTHERWISE NOTED.
- 8) DEBRAND/DEBRAND/INTEL (HKS) TO BE FINISHED BY BUILDER.

SHOP DRAWING APPROVAL

THIS LAYOUT IS THE SOLE SOURCE FOR FABRICATION OF TRUSSES AND VIDS. ALL PREVIOUS ARCHITECTURAL OR OTHER TRUSS LAYOUTS, REVIEW AND APPROVAL OF THIS LAYOUT MUST BE RECEIVED BEFORE ANY TRUSSES WILL BE BUILT. VERIFY ALL CONDITIONS TO INSURE AGAINST CHANGES THAT WILL RESULT IN EXTRA CHARGES TO YOU.

Expenditure Safety Data _____

Approved By _____ Date _____



Bunnell

PHONE: 904-437-3349 FAX: 904-437-3994

Jacksonville

PHONE: 904-772-6100 FAX: 904-772-1973

Lake City

PHONE: 386-755-6894 FAX: 386-755-7973

Sanford

PHONE: 407-322-0059 FAX: 407-322-5553

BUILDER

RICHARD J. KEEN

LOT #11 CENTURY OAKS

CUSTOM SCALE NTS

DATE 04-27-06 DRAWN BY RAL L162012

