

## Force Engineering & Testing

19530 Ramblewood Drive  
Humble, Texas 77338  
Phone: (281) 540-6603 FAX: (281) 540-9966  
Website: [www.forceengineeringtesting.com](http://www.forceengineeringtesting.com)

### Product Evaluation Report CAPITAL METAL SUPPLY, INC.

#### *Min. 29 Ga. Capital Rib Roof Panel over 7/16" OSB*

#### Florida Product Approval # 17992.2 R4

Florida Building Code 2023

Per Rule 61G20-3

Method: 1 -D

Category: Roofing

Subcategory: Metal Roofing

Compliance Method: 61G20-3.005(1)(d)

NON HVHZ

#### Product Manufacturer:

**Capital Metal Supply**

3845 S. US HWY 441

Lake City, Florida 32025

**Capital Metal Supply**

629 SE Industrial Circle

Lake City, Florida 32025

#### Engineer Evaluator:


**Johnathan Green, P.E. #88223**

Florida Evaluation ANE ID: 12901

#### Contents:


**Evaluation Report: Page 1 - 4**

**Installation Detail: Page 5**



THIS DOCUMENT HAS  
BEEN DIGITALLY SIGNED  
AND SEALED BY  
JOHNATHAN GREEN ON  
THE DATE ADJACENT TO  
THE SEAL.

PRINTED COPIES OF THIS  
DOCUMENT ARE NOT  
CONSIDERED SIGNED  
AND SEALED AND THE  
SIGNATURE MUST BE  
VERIFIED ON ANY  
ELECTRONIC COPIES.



**Compliance Statement:** The product as described in this report has demonstrated compliance with the Florida Building Code 2023, Sections 1504.3.2, 1504.7.

**Product Description:** Capital Rib Roof Panel, Min. 29 Ga. Steel, 36" Wide, through fastened roof panel over minimum 7/16" OSB decking. Non-structural Application.

**Panel Material/Standards:** Material: Min. 29 Ga. Steel, ASTM A792 or ASTM A653 G90 conforming to Florida Building Code 2023 Section 1507.4.3. Paint finish optional.  
 Yield Strength: Min. 80.0 ksi  
 Corrosion Resistance: Panel Material shall comply with Florida Building Code 2023, Section 1507.4.3.

**Panel Dimension(s):** Thickness: 0.0160" Min. coated thickness  
 Width: 36" Maximum Coverage  
 Rib Height: ¾" major rib at 9" O.C.  
 Panel Rollformer: MRS Metal Rollforming Systems

**Panel Fastener:** #10-15 x 1-1/2" Woodgrip HiLo dual thread with sealing washing or approved equal.  
 ¼" minimum penetration through plywood  
 Corrosion Resistance: Per Florida Building Code 2023, Section 1507.4.4.


**Substrate Description:** (1) layer of asphalt composition shingles (optional) over (1) layer of 30# felt paper (optional) over minimum 7/16" OSB (or 15/32" APA Rated Plywood) over Southern Yellow Pine wood rafters at 24" O.C. OSB must be inspected and able to withstand the wind loading induced by the wood purlins. Substrate must be designed in accordance w/ Florida Building Code.

**Allowable Design Uplift Pressures:**

**Table "A"**

<b>Maximum Total Uplift Design Pressure:</b>	22.7 psf	78.5 psf
<b>Fastener Pattern:</b>	9"-9"-9"-9"	9"-9"-9"-9"
<b>Pattern Spacing:</b>	24" O.C.	6" O.C.

\*Design Pressure includes a Safety Factor = 2.0.



## **Force Engineering & Testing**


19530 Ramblewood Drive

Humble, Texas 77338

Phone: (281) 540-6603 FAX: (281) 540-9966

Website: [www.forceengineeringtesting.com](http://www.forceengineeringtesting.com)

<b>Code Compliance:</b>	The product described herein has demonstrated compliance with The Florida Building Code 2023, Section 1504.3.2, 1504.7.
<b>Evaluation Report Scope:</b>	The product evaluation is limited to compliance with the structural wind load requirements of the Florida Building Code 2023, as relates to Rule 61G20-3.
<b>Performance Standards:</b>	<p>The product described herein has demonstrated compliance with:</p> <ul style="list-style-type: none"><li>▪ UL 580-06 - Test for Uplift Resistance of Roof Assemblies</li><li>▪ UL 1897-2015 - Uplift Test for Roof Covering Systems</li><li>▪ FM 4471-92 - Foot Traffic Resistance Test</li></ul>
<b>Reference Data:</b>	<ol style="list-style-type: none"><li>1. UL 580-06 / 1897-04 Uplift Test Force Engineering &amp; Testing, Inc. (FBC Organization # TST-5328) Report No. 587-0125T-16A, B</li><li>2. FM 4471-10, Section 4.4 Foot Traffic Resistance Test Force Engineering &amp; Testing, Inc. (FBC Organization # TST-5328) Report No. 587-0169T-15C</li><li>3. Certificate of Independence By Johnathan Green, P.E. (No. 88223) @ Force Engineering &amp; Testing (FBC Organization # ANE ID: 12901)</li></ol>
<b>Test Standard Equivalency:</b>	<ol style="list-style-type: none"><li>1. The UL 1897-04 test standard is equivalent to the UL 1897-2015 test standard.</li><li>2. The FM 4471-10, Foot Traffic Resistance test standard is equivalent to the FM 4471-92, Foot Traffic Resistance test standard</li></ol>
<b>Quality Assurance Entity:</b>	The manufacturer has established compliance of roof panel products in accordance with the Florida Building Code and Rule 61G20-3.005 (3) for manufacturing under a quality assurance program audited by an approved quality assurance entity.



## **Force Engineering & Testing**


19530 Ramblewood Drive

Humble, Texas 77338

Phone: (281) 540-6603 FAX: (281) 540-9966

Website: [www.forceengineeringtesting.com](http://www.forceengineeringtesting.com)

<b>Minimum Slope Range:</b>	Minimum Slope shall comply with Florida Building Code 2023, including Section 1507.4.2 and in accordance with Manufacturers recommendations. For slopes less than 3:12, lap sealant must be used in the panel side laps.
<b>Installation:</b>	Install per manufacturer's recommended details.
<b>Underlayment:</b>	Per Florida Building Code 2023, Section 1507.1 and manufacturer's installation guidelines.
<b>Roof Panel Fire Classification:</b>	Fire classification is not part of this acceptance.
<b>Shear Diaphragm:</b>	Shear diaphragm values are outside the scope of this report.
<b>Design Procedure:</b>	Based on the dimensions of the structure, appropriate wind loads are determined using Chapter 16 of the Florida Building Code 2023 for roof cladding wind loads. These component wind loads for roof cladding are compared to the allowable pressure listed above. The design professional shall select the appropriate erection details to reference in his drawings for proper fastener attachment to his structure and analyze the panel fasteners for pullout and pullover. Support framing must be in compliance with Florida Building Code 2023 Chapter 22 for steel, Chapter 23 for wood and Chapter 16 for structural loading.



## Force Engineering & Testing


19530 Ramblewood Drive

Humble, Texas 77338


Phone: (281) 540-6603 FAX: (281) 540-9966

Website: [www.forceengineeringtesting.com](http://www.forceengineeringtesting.com)

### MIN. 29 GA. CAPITAL RIB PANEL FASTENER PATTERN AT 24" O.C.



### MIN. 29 GA. CAPITAL RIB PANEL FASTENER PATTERN AT 6" O.C.



### PANEL ENDS

