



COLUMBIA COUNTY BUILDING DEPARTMENT RESIDENTIAL CHECK LIST

MINIMUM PLAN REQUIREMENTS: FLORIDA BUILDING CODE RESIDENTIAL 2023 EFFECTIVE 1 JANUARY 2024 AND THE NATIONAL ELECTRICAL 2020 EFFECTIVE 1 JANUARY 2024

ALL REQUIREMENTS ARE SUBJECT TO CHANGE

ALL BUILDING PLANS MUST INDICATE COMPLIANCE WITH THE CURRENT FLORIDA BUILDING CODES RESIDENTIAL AND THE NATIONAL ELECTRICAL CODE. ALL PLANS OR DRAWINGS SHALL PROVIDE CALCULATIONS AND DETAILS THAT HAVE THE SEAL AND SIGNATURE OF A CERTIFIED ARCHITECT OR ENGINEER REGISTERED IN THE STATE OF FLORIDA, OR ALTERNATE METHODOLOGIES, APPROVED BY THE STATE OF FLORIDA BUILDING COMMISSION FOR ONE-AND-TWO FAMILY DWELLINGS, FBC 1609.1 THRU 1609.6.

FOR DESIGN PURPOSES THE FOLLOWING BASIC WIND SPEEDS ARE PER FLORIDA BUILDING CODE FIGURE 1609.3(1)
THROUGH 1609.3(4) ULTIMATE DESIGN WIND SPEEDS FOR RISK CATEGORY AND BUILDINGS AND OTHER
STRUCTURES Revised 7/1/20

S	ubmit Online at- http://www.columbiacountyfla.com/BuildingandZoning.a	JU	s to Inclu Box sha	
	GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	A	Circled as	e
		Select Fro	m Drop	down
1	Two (2) complete sets of plans containing the following:	4		-
	All drawings must be clear, concise, drawn to scale, details that are not used shall be marked void			274
3	Condition space (Sq. Ft.) 1694 Total (Sq. Ft.) under roof 2334	Yes	No	NA
sha	signers name and signature shall be on all documents and a licensed architect or engineer, signature and libe affixed to the plans and documents as per the FLORIDA BUILDING CODES BUILDING 107.1 Te Plan information including:	d official e	embossed	seal
4	Dimensions of lot or parcel of land	. /		
5	Dimensions of all building set backs	-/		
6	Location of all other structures (include square footage of structures) on parcel, existing or proposed well and septic tank and all utility easements.	-/		
7	Provide a full legal description of property.	- /		
	APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	C Ap	Box sha ircled as plicable	
8	Plans or specifications must show compliance with FBCR Chapter 3	Yes	No	NA NA
		Select Fro	om Drop	down
9	Basic wind speed (3-second gust), miles per hour			-
10	(Wind exposure – if more than one wind exposure	-/		
	is used, the wind exposure and applicable wind direction shall be indicated)	-		+
11	Wind importance factor and nature of occupancy	-/		
12	The applicable internal pressure coefficient, Components and Cladding	- /		
	The design wind pressure in terms of psf (kN/m²), to be used for the design of exterior component,			
13	cladding materials not specifally designed by the registered design professional.	-/		
El	evations Drawing including:			
14		- /,	-	-
15	Roofpitch	- /	/	-
16	Overhang dimensions and detail with attic ventilation		_	1
17	Location, size and height above roof of chimneys	ļ- ·	+	/
18	Location and size of skylights with Florida Product Approval	-	+	/
19	Number of stories	- /	+	-
20	Building height from the established grade to the roofs highest peak	-/		

Raised floor surfaces located more than 30 inches above the floor or grade All exterior and interior shear walls indicated Shear wall opening shown (Windows, Doors and Garage doors) Show compliance with Section FBCR 310 Emergency escape and rescue opening shown in each bedroom (net clear opening shown) and Show compliance with Section FBCR 312.2.1 where the opening of an operable window is located more than 72 inches above the finished grade or surface below, the lowest part of the clear opening of the window shall be a minimum of 24 inches above the finished floor of the room in which the window is located. Glazing between the floor and 24 inches shall be fixed or have openings through which a 4-inch-diameter sphere cannot pass. Safety glazing of glass where needed Fireplaces types (gas appliance) (vented or non-vented) or wood burning with Hearth (see chapter 10 and chapter 24 of FBCR) Show stairs with dimensions (width, tread and riser and total run) details of guardrails, Handrails Identify accessibility of bathroom (see FBCR SECTION 320) Ill materials placed within opening or onto/into exterior walls, soffits or roofs shall have Florida proproval number and mfg. installation information submitted with the plans ee Florida product approval form) GENERAL REQUIREMENTS: APPLICANT - PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL GENERAL REQUIREMENTS: APPLICANT - PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL Items to Include Each Box shall be Circled as Applicable BCR 403: Foundation Plans Select From Drop Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Any special support required by soil analysis such as piling. Ansumed load-bearing valve of soil Pound	22 23 24				
All exterior and interior shear walls indicated Shear wall opening shown (Windows, Doors and Garage doors) Show compliance with Section FBCR 310 Emergency escape and rescue opening shown in each bedroom (net clear opening shown) and Show compliance with Section FBCR 312.2.1 where the opening of an operable window is located more than 72 inches above the finished grade or surface below, the lowest part of the clear opening of the window shall be a minimum of 24 inches above the finished floor of the room in which the window is located. Glazing between the floor and 24 inches shall be fixed or have openings through which a 4-inch-diameter sphere cannot pass. Safety glazing of glass where needed Fireplaces types (gas appliance) (vented or non-vented) or wood burning with Hearth (see chapter 10 and chapter 24 of FBCR) Show stairs with dimensions (width, tread and riser and total run) details of guardrails, Handrails Identify accessibility of bathroom (see FBCR SECTION 320) Ill materials placed within opening or onto/into exterior walls, soffits or roofs shall have Florida propoval number and mfg. installation information submitted with the plans GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL Items to Include Each Box shall be Circled as Applicable Circled as Applicable Circled as Applicable Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pow Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrod	23		-/		
Shear wall opening shown (Windows, Doors and Garage doors) Show compliance with Section FBCR 310 Emergency escape and rescue opening shown in each bedroom (net clear opening shown) and Show compliance with Section FBCR 312.2.1 where the opening of an operable window is located more than 72 inches above the finished grade or surface below, the lowest part of the clear opening of the window shall be a minimum of 24 inches above the finished floor of the room in which the window is located. Glazing between the floor and 24 inches shall be fixed or have openings through which a 4-inch-diameter sphere cannot pass. Safety glazing of glass where needed Fireplaces types (gas appliance) (vented or non-vented) or wood burning with Hearth (see chapter 10 and chapter 24 of FBCR) Show stairs with dimensions (width, tread and riser and total run) details of guardrails, Handrails Identify accessibility of bathroom (see FBCR SECTION 320) Il materials placed within opening or onto/into exterior walls, soffits or roofs shall have Florida proproval number and mfg. installation information submitted with the plans ee Florida product approval form) GENERAL REQUIREMENTS: APPLICANT - PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL BCR 403: Foundation Plans Select From Drop Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Door Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 BCR 506: CONCRETE SLAB ON GRADE Show Va per retarder (6mil. Polyethylene with joints overpla	-	Raised floor surfaces located more than 30 inches above the floor or grade	- /		_
Show compliance with Section FBCR 310 Emergency escape and rescue opening shown in each bedroom (net clear opening shown) and Show compliance with Section FBCR 312.2.1 where the opening of an operable window is located more than 72 inches above the finished floor of the room in which the window shall be a minimum of 24 inches above the finished floor of the room in which the window is located. Glazing between the floor and 24 inches shall be fixed or have openings through which a 4-inch-diameter sphere cannot pass. Safety glazing of glass where needed Fireplaces types (gas appliance) (vented or non-vented) or wood burning with Hearth (see chapter 10 and chapter 24 of FBCR) Show stairs with dimensions (width, tread and riser and total run) details of guardrails, Handrails Identify accessibility of bathroom (see FBCR SECTION 320) Il materials placed within opening or onto/into exterior walls, soffits or roofs shall have Florida proproval number and mfg. installation information submitted with the plans GENERAL REQUIREMENTS: APPLICANT - PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL GENERAL REQUIREMENTS: APPLICANT - PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing AN special support required by soil analysis such as piling. Ansyspecial support required by soil analysis such as piling. Assumed load-bearing valve of soil Power Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3	4		- /		
bedroom (net clear opening shown) and Show compliance with Section FBCR 312.2.1 where the opening of an operable window is located more than 72 inches above the finished grade or surface below, the lowest part of the clear opening of the window shall be a minimum of 24 inches above the finished floor of the room in which the window is located. Glazing between the floor and 24 inches shall be fixed or have opening sthrough which a 4-inch-diameter sphere cannot pass. Safety glazing of glass where needed Fireplaces types (gas appliance) (vented or non-vented) or wood burning with Hearth (see chapter 10 and chapter 24 of FBCR) Show stairs with dimensions (width, tread and riser and total run) details of guardrails, Handrails Identify accessibility of bathroom (see FBCR SECTION 320) Il materials placed within opening or onto/into exterior walls, soffits or roofs shall have Florida proproval number and mfg. installation information submitted with the plans to Florida product approval form) GENERAL REQUIREMENTS: APPLICANT - PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL Items to Include Each Box shall be Circled as Applicable BCR 403: Foundation Plans Select From Drop Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pown Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 BCR 506: CONCRETE SLAB ON GRADE Show Va pr retarder (6mil. Polyethylene with joints overplaid 6 inches and sealed)	-		-		
opening of an operable window is located more than 72 inches above the finished grade or surface below, the lowest part of the clear opening of the window shall be a minimum of 24 inches above the finished floor of the room in which the window is located. Glazing between the floor and 24 inches shall be fixed or have openings through which a 4-inch-diameter sphere cannot pass. Safety glazing of glass where needed Fireplaces types (gas appliance) (vented or non-vented) or wood burning with Hearth (see chapter 10 and chapter 24 of FBCR) Show stairs with dimensions (width, tread and riser and total run) details of guardrails, Handrails Identify accessibility of bathroom (see FBCR SECTION 320) Il materials placed within opening or onto/into exterior walls, soffits or roofs shall have Florida proproval number and mfg. installation information submitted with the plans to proproval number and mfg. installation information submitted with the plans to proproval number and mfg. installation information submitted with the plans to proproval form) GENERAL REQUIREMENTS: APPLICANT - PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL GENERAL REQUIREMENTS: APPLICANT - PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. BCR 506: CONCRETE SLAB ON GRADE Show Va pr retarder (6mil. Polyethylene with joints overland 6 inches and sealed)	5	Show compliance with Section FBCR 310 Emergency escape and rescue opening shown in each			
Safety glazing of glass where needed Fireplaces types (gas appliance) (vented or non-vented) or wood burning with Hearth (see chapter 10 and chapter 24 of FBCR) -		opening of an operable window is located more than 72 inches above the finished grade or surface below, the lowest part of the clear opening of the window shall be a minimum of 24 inches above the finished floor of the room in which the window is located. Glazing between the floor and 24			
Fireplaces types (gas appliance) (vented or non-vented) or wood burning with Hearth (see chapter 10 and chapter 24 of FBCR) - Show stairs with dimensions (width, tread and riser and total run) details of guardrails, Handrails - Identify accessibility of bathroom (see FBCR SECTION 320) - Identify accessibility accessibility accessibility accessibility accessibility accessibility accessible accessibility accessible accessible accessibility accessibility accessibility accessibility accessible a	6		- 1/	-	
Show stairs with dimensions (width, tread and riser and total run) details of guardrails, Handrails Identify accessibility of bathroom (see FBCR SECTION 320) Il materials placed within opening or onto/into exterior walls, soffits or roofs shall have Florida proproval number and mfg. installation information submitted with the plans EFlorida product approval form) GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL Circled as Applicable BCR 403: Foundation Plans Select From Drop Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Ansumed load-bearing valve of soil Assumed load-bearing valve of soil Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 BCR 506: CONCRETE SLAB ON GRADE Show Va pr retarder (6mil. Polyethylene with joints overplaid 6 inches and sealed)			- /	-	
Identify accessibility of bathroom (see FBCR SECTION 320) -	7		-		C
Il materials placed within opening or onto/into exterior walls, soffits or roofs shall have Florida proposed number and mfg. installation information submitted with the plans see Florida product approval form) GENERAL REQUIREMENTS:	8	Show stairs with dimensions (width, tread and riser and total run) details of guardrails, Handrails	-		-
Il materials placed within opening or onto/into exterior walls, soffits or roofs shall have Florida proposed number and mfg. installation information submitted with the plans see Florida product approval form) GENERAL REQUIREMENTS:	9	Identify accessibility of bathroom (see FBCR SECTION 320)	- /		
Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 BCR 506: CONCRETE SLAB ON GRADE Show Va per retarder (6mil. Polyethylene with joints overlaid 6 inches and sealed)		APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Circ	led as	
Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 BCR 506: CONCRETE SLAB ON GRADE Show Va per retarder (6mil. Polyethylene with joints overhaid 6 inches and sealed)			Circ	led as	
Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pour Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 BCR 506: CONCRETE SLAB ON GRADE Show Va per retarder (6mil. Polyethylene with joints overhaid 6 inches and sealed)	В		Circ App	led as licable	oe.
Assumed load-bearing valve of soil Pour Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 BCR 506: CONCRETE SLAB ON GRADE Show Va per retarder (6mil. Polyethylene with joints overlaid 6 inches and sealed)	Be	CR 403: Foundation Plans Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size	Circ App	led as licable	e e
Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 BCR 506: CONCRETE SLAB ON GRADE Show Va per retarder (6mil. Polyethylene with joints overplaid 6 inches and sealed)	0	CR 403: Foundation Plans Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.	Circ App	led as licable	oe.
with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 BCR 506: CONCRETE SLAB ON GRADE Show Va per retarder (6mil. Polyethylene with joints overlaid 6 inches and sealed))	CR 403: Foundation Plans Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling.	Circ App	led as licable	be
Show Va per retarder (6mil. Polyethylene with joints overstaid 6 inches and sealed))	CR 403: Foundation Plans Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Torro Pound Per Square Foot	Select Fro	led as licable	be
	2	CR 403: Foundation Plans Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pour Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system.	Select Fro	led as licable	be
Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports -) 1 2 3 1	CR 403: Foundation Plans Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE	Select Fro	led as licable	oe.
	0 1 2 3 4 4 FB	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pow Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structur with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Va per retarder (6mil. Polyethylene with joints overlaid 6 inches and sealed)	Select Fro	led as licable	e e
Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered	B B	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pow Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structur with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Va per retarder (6mil. Polyethylene with joints overlaid 6 inches and sealed)	Select Fro	led as licable	be
/ washing and a property of the second statement of	B(5)	CR 403: Foundation Plans Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pour Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Va per retarder (6mil. Polyethylene with joints overlaid 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES	Select Fro	led as licable	be

Metal frame shear wall and roof systems shall be designed, signed and sealed by Florida Prof. Engineer or Architect

39 Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement

FR	oor Framing System: First and/or second story		
40	Floor truss package shall including layout and details, signed and sealed by Florida Registered	-	
40	Professional Engineer		
41	Show conventional floor joist type, size, span, spacing and attachment to load bearing walls,	-	
41	stem walls and/or priers Girder type, size and spacing to load bearing walls, stem wall and/or priers		
43	Attachment of joist to girder		-
44	Wind load requirements where applicable		-
-			1
45 46	Show required under-floor crawl space		
	Show required amount of ventilation opening for under-floor spaces		-
47	Show required covering of ventilation opening		
48	Show the required access opening to access to under-floor spaces		
40	Show the sub-floor structural panel sheathing type, thickness and fastener schedule on the edges &	-	/
49	intermediate of the areas structural panel sheathing	\rightarrow	
50	Show Draftstopping, Fire caulking and Fire blocking		
51	Show fireproofing requirements for garages attached to living spaces, per FBCR section 302.6		
52	Provide live and dead load rating of floor framing systems (psf).	- 1	
FB	CR CHAPTER 6 WOOD WALL FRAMING CONSTRUCTION		
Personal		Items to	Include-
	GENERAL REQUIREMENTS:	Each Bo	x shall be
	APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Circ	led as
		Appl	icable
	Science	elect from	Drop down
53	Stud type, grade, size, wall height and oc spacing for all load bearing or shear walls	- /	Ĩ
54	Fastener schedule for structural members per table FBC 2304.10.1 are to be shown	- /	
	Show wood structural panel's sheathing attachment to studs, joist, trusses, rafters and structural		
55	members, showing fastener schedule attachment on the edges & intermediate of the areas structural	- /	
	panel sheathing		
	Show all required connectors with a max uplift rating and required number of connectors and	/	
56	oc spacing for continuous connection of structural walls to foundation and roof trusses or	- /	
	rafter systems		
	Show sizes, type, span lengths and required number of support jack studs, king studs	. /	
57	for shear wall opening and girder or header per FBC 2304.3.		
58	Indicate where pressure treated wood will be placed	- /	
	Show all wall structural panel sheathing, grade, thickness and show fastener schedule for structural	- /	
59	panel sheathing edges & intermediate areas		
60	A detail showing gable truss bracing, wall balloon framing details or/and wall hinge bracing detail	- /	
F	BC :ROOF SYSTEMS:		
61	Truss design drawing shall meet section FBC 2303.1 Wood trusses	- //	
62	Include a layout and truss details, signed and sealed by Florida Professional Engineer	- /	
63	Show types of connector's assemblies' and resistance uplift rating for all trusses and rafters	- /	
64	Show gable ends with rake beams showing reinforcement or gable truss and wall bracing details	- /	
65	Provide dead load rating of trusses	- /	
F	BC 2304.4:Conventional Roof Framing Layout		
66	Rafter and ridge beams sizes, span, species and spacing	-	
67	Connectors to wall assemblies' include assemblies' resistance to uplift rating	-	
68	Valley framing and support details	1	
69	Provide dead load rating of rafter system	-	/
FI	BC 2304.8 ROOF SHEATHING		
70	Include all materials which will make up the roof decking, identification of structural panel		
6550	sheathing, grade, thickness	-1/	
71	Show fastener Size and schedule for structural panel sheathing on the edges & intermediate areas	- 1	

ROOF ASSEMBLIES FRC Chapter 9			
Include all materials which will make up the roof assembles covering	- /		
Submit Florida Product Approval numbers for each component of the roof assembles covering		/	
Residential construction shall comply with this code by using the following compliance methods in the buildings compliance methods. Two of the required forms are to be submitted, N1100.1.1.1 As an all Compliance Method A, the Alternate Residential Point System Method hand calculation, Alternate For equirements specific to this calculation are located in Sub appendix C to Appendix G. Buildings complete all mandatory requirements of this chapter. Computerized versions of the Alternate Residential For eacceptable for code compliance.	lternative to rm 600A, m plying by th	the con ay be us is altern	puterized ed. All ative shall
GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Items to Include- Each Box shall be Circled as Applicable Select from Drop Do		hall be as able
Characteristic Daylor Cartha Callerian areas of the atmostrate	Select Jr	om Di	op Down
74 Show the insulation R value for the following areas of the structure		/	-
75 Attic space	- 1		-
76 Exterior wall cavity 77 Crawl space	- /		/
77 Crawi space	ļ-		
HVAC information			
78 Submit two copies of a Manual J sizing equipment or equivalent computation study	- /		
79 Exhaust fans shown in bathrooms Mechanical exhaust capacity of 50 cfm intermittent or		/	
20 cfm continuous required			
80 Show clothes dryer route and total run of exhaust duct			
Plumbing Fixture layout shown			
81 All fixtures waste water lines shall be shown on the foundationslan	-/	1	1
82 Show the location of water heater	-		
52 Show the location of water heater	/		
Private Potable Water			
83 Pump motor horse power	- /		
84 Reservoir pressure tank gallon capacity	- /		

Electrical layout shown including 86 Show Switches, receptacles outlets, lighting fixtures and Ceiling fans Show all 120-volt, single phase, 15- and 20-ampere branch circuits outlets required to be protected by Ground-Fault Circuit Interrupter (GFCI) Article 210.8 A Show the location of smoke detectors & Carbon monoxide detectors 89 Show service panel, sub-panel, location(s) and total ampere ratings On the electrical plans identify the electrical service overcurrent protection device for the main electrical service. This device shall be installed on the exterior of structures to serve as a disconnecting means for the utility company electrical service. Conductors used from the exterior disconnecting means to a panel or sub panel shall have four-wire conductors, of which one conductor shall be used as an equipment ground. Indicate if the utility company service entrance cable will be of the overhead or underground type. For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an Grounding electrode system. Per the National Electrical Code article 250.52.3 91 Appliances and HVAC equipment and disconnects Show all 120-volt, single phase, 15- and 20-ampere branch circuits supplying outlets installed in dwelling unit family rooms, dining rooms, living rooms, parlors, libraries, dens, bedrooms, sunrooms, recreation rooms, closets, hallways, or similar rooms or areas shall be protected by a listed Combination arc-fault circuit interrupter, Protection device.

Notice Of Commencement:

A notice of commencement form RECORDED in the Columbia County Clerk Office is required to be filed with the Building Department BEFORE ANY INSPECTIONS can be performed.

GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Items to Include- Each Box shall be Circled as
	Applicable

ITEMS 95, 96, & 98 Are Required After APPROVAL from the ZONING DEPT. Select from Drop down 93 Building Permit Application A current Building Permit Application is to be completed, by following the Checklist all supporting documents must be submitted. 94 Parcel Number The parcel number (Tax ID number) from the Property Appraisers Office (386) 758-1083 is required. A copy of property deed is also required. www.columbiacountyfla.com 95 Environmental Health Permit or Sewer Tap Approval A copy of a approved Columbia County Environmental Health (386) 758-1058 City of Lake City A City Water and/or Sewer letter. Call 386-752-2031 96 Toilet facilities shall be provided for all construction sites 97 98 Town of Fort White (386) 497-2321 If the parcel in the application for building permit is within the Corporate city limits of Fort White, an approval land use development letter issued by the Town of Fort is required to be submitted with the application for a building permit. Flood Information: All projects within the Floodway of the Suwannee or Santa Fe Rivers shall require permitting through the Suwannee River Water Management District, before submitting a application to this office. Any project located within a flood zone where the base flood elevation (100 year flood) has been established shall meet the requirements of Section 8.5.2 of the Columbia County Land Development Regulations. Any project located within a flood zone where the base flood elevation has not been established (Zone A) shall meet the requirements of Section 8.5.3 of the Columbia County Land Development Regulations (Municode.com) CERTIFIED FINISHED FLOOR ELEVATIONS will be required on any project where the approved FIRM Flood Maps show the property is in a AE, Floodway, and AH flood zones. Additionally One Foot Rise letters are required for AE and AH zones. In the Floodway Flood zones a Zero Rise letter is required. A Flood development permit is also required for AE, Floodway & AH. Development permit cost is \$50.00 |-101 Driveway Connection: If the property does not have an existing access to a public road, then an application for a culvert permit (\$25.00) must be made. County Public Works Dept. determines the size 102 and length of every culvert before instillation and completes a final inspection before permanent power is granted. If the applicant feels that a culvert is not needed, they may apply for a culvert waiver (\$50.00) Separate Check when issued. If the project is to be located on an F.D.O.T. maintained road, then an F.D.O.T. access permit is required. 911 Address: An application for a 911 address must be applied for and received through the Columbia County Office of 911 Addressing Department online.

Ordinance Sec. 90-75. - Construction debris. (e) It shall be unlawful for any person to dispose of or discard solid waste, including construction or demolition debris at any place within the county other than on an authorized disposal site or at the county's solid waste facilities. The temporary storage, not to exceed seven days of solid waste (excluding construction and demolition debris) on the premises where generated or vegetative trash pending disposition as authorized by law or ordinance, shall not be deemed a violation of this section. The temporary storage of construction and demolition debris on the premises where generated or vegetative trash pending disposition as authorized by law or ordinance shall not be deemed in violation of this section; provided, however, such construction and demolition debris must be disposed of in accordance with this article prior to the county's issuance of a certificate of occupancy for the premises. The burning of lumber from a construction or demolition project or vegetative trash when done so with legal and proper permits from the authorized agencies and in accordance with such agencies' rules and regulations, shall not be deemed a violation of this section. No person shall bury, throw, place, or deposit, or cause to be buried, thrown, placed, or deposited, any solid waste, special waste, or debris of any kind into or on any of the public streets, road right-of-way, highways, bridges, alleys, lanes, thoroughfares, waters, canals, or vacant lots or lands within the county. No person shall bury any vegetative trash on any of the public streets, road right-of-way, highways, bridges, lanes, thoroughfares, waters, canals, or lots less than ten acres in size within the county.