


MODEL DESIGNATION: Simonton Double Hung Series 43-40 / 43-45 Vinyl Window

MAXIMUM OVERALL NOMINAL SIZE: See Size Chart

DESIGN PRESSURE RATING: See Size Chart

USABLE CONFIGURATIONS: X  
X

GENERAL DESCRIPTION: The head, sill, and side jambs are extruded PVC. The wall thickness through which the anchor screw penetrates is a minimum of 0.070".






| SIZE CHART   |            |           |
|--------------|------------|-----------|
| OVERALL SIZE |            | DP RATING |
| WIDTH "W"    | HEIGHT "H" |           |
| 46"          | 84"        | ±25 PSF   |
| 36"          | 72"        | ±30 PSF   |
| 44"          | 63"        | ±35 PSF   |
| 48"          | 80"        |           |
| 52"          | 71"        |           |
| 36"          | 63"        | ±45 PSF   |
| 44"          | 63"        |           |
| 32"          | 62"        | ±50 PSF   |
| 36"          | 74"        |           |

NOTES:

- THIS INSTALLATION HAS BEEN EVALUATED FOR USE IN LOCATIONS ADHERING TO THE FLORIDA BUILDING CODES AND WHERE PRESSURE REQUIREMENTS AS DETERMINED BY ASCE 7 MINIMUM DESIGN LOADS FOR BUILDINGS AND OTHER STRUCTURES DO NOT EXCEED THE DESIGN PRESSURE RATINGS HEREIN, FOR USE OUTSIDE THE H.V.H.Z.
- ALL INTERIOR AND EXTERIOR PERIMETER SURFACES OF THE WINDOW MUST BE CAULKED.
- ANCHORS SHALL BE AS SPECIFIED AND SPACED AS SHOWN. ANCHOR EMBEDMENT TO BASE MATERIAL SHALL BE BEYOND WALL DRESSING OR STUCCO AND INTO WOOD.
- THE RESPONSIBILITY FOR SELECTION OF SIMONTON PRODUCTS TO MEET ANY APPLICABLE LOCAL LAWS, BUILDING CODES, ORDINANCES, OR OTHER SAFETY REQUIREMENTS RESTS SOLELY WITH THE ARCHITECT, BUILDING OWNER, OR CONTRACTOR.
- SHIMS ARE OPTIONAL. MAX. SHIM STACK IS 1/4".
- WOOD BUCKS (BY OTHERS) MUST BE ENGINEERED AND ANCHORED PROPERLY TO TRANSFER LOADS TO THE STRUCTURE.
- SCREWS SHOULD BE A MINIMUM OF 3/4" FROM THE EDGE OF THE WOOD.
- WHEN USED IN AREAS REQUIRING IMPACT PROTECTION, THIS PRODUCT REQUIRES THE USE OF APPROVED IMPACT RESISTANT SHUTTERS OR OTHER EXTERNAL PROTECTION.
- FLASHING SHOULD BE APPLIED USING THE ASTM E 2112 METHOD APPROPRIATE FOR THE OPENING INTO WHICH THE WINDOW IS BEING INSTALLED.
- INSTALLATION SCREWS MUST BE AT LEAST 3/4" FROM THE EDGE OF THE WOOD..
- GLAZING SHALL COMPLY WITH ASTM E 1300.
- DESIGNATION "X" IS FOR OPERABLE PANEL AND "O" IS FOR FIXED PANEL
- USE 100% PURE SILICONE CAULK COMPLIANT WITH AAMA 800 SECTION I - SEALANT SPECIFICATIONS FOR USE WITH ARCHITECTURAL FENESTRATION PRODUCTS. FOR MORE DETAILS VISIT SIMONTON.COM.
- USE A BACKER ROD ON ALL JOINTS >3/4" DEEP AND/OR WIDER THAN 1/4". FINISHED CAULK JOINT SHOULD BE A MINIMUM OF 3/8" DEEP.

NO P.E. SEAL REQUIRED  
INSTALLATION SUPPORTED  
BY AAMA TEST REPORTS



| REV. #: | REVISIONS:                      | REVISED BY: | DATE:    |
|---------|---------------------------------|-------------|----------|
| 2       | ADDED MIN. EDGE DIST. NOTE.     | B.J.S.      | 06/17/15 |
| 3       | ADDED NOTES 12 & 13 - AAMA 800  | LMH         | 08/15/16 |
| 4       | ADDITION TO SIZE CHART.         | LMH         | 12/01/17 |
| 5       | CORRECTED SIZE CHART DIMENSION. | LMH         | 07/11/19 |
| 6       | ADDED DP25 TO SIZE CHART        | LMH         | 09/25/19 |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                 |            |                                                                                                                                              |                                                                                                                                                                                                                         |                                      |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|------------|----------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|
| <div>DISCLOSURE STATEMENT</div> <div>This document is the property of Simonton Windows, which retains all proprietary and other rights to its subject matter. This document is provided to the recipient on the expressed condition that it is not to be disclosed, reproduced in whole or part, nor used in conjunction with the design, manufacture or repair of goods for anyone other than Simonton Windows without its consent. This restriction does not limit the recipient's rights to utilize information contained in this document which is properly obtained from another source.</div> <div>FILE: FL 5167</div> | MATERIAL:       |            | <div>Dimensional Tolerances<br/>Unless Otherwise Specified</div> <div>DecimalsAngles</div> <div>.X ± .03<br/>.XX ± .01<br/>.XXX ± .005</div> | <div>SIMONTON®<br/>W I N D O W S<br/>1 Cochrane Avenue<br/>Pennsboro, WV 26415</div> <div>SCALE: FITSHEET: 1 of 1</div> <div>SERIES: 43-40 / 43-45 DOUBLE HUNG</div> <div>TITLE: 2X BUCK INSTALLATION (AS TESTED)</div> | SIZE: B DRAWING NO.: IN0432b REV.: 6 |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | RMS FINISH:     |            |                                                                                                                                              |                                                                                                                                                                                                                         | DRAWN BY: T.D.D. DATE: 09/04/09      |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | ALLOY & TEMPER: |            |                                                                                                                                              |                                                                                                                                                                                                                         | CHECKED BY: DATE:                    |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | WEIGHT:         | VOLUME:    |                                                                                                                                              |                                                                                                                                                                                                                         | APPR'V'D BY: DATE:                   |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | SURFACE AREA:   | PERIMETER: |                                                                                                                                              |                                                                                                                                                                                                                         |                                      |
| FINISH TREATMENT:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                 |            |                                                                                                                                              |                                                                                                                                                                                                                         |                                      |