



Lumber design values are in accordance with ANSI/TPI 1 section 6.3
These truss designs rely on lumber values established by others.

RE: 2874271 - EXCEPTIONS REALITY - LOT 10 CRP

MiTek USA, Inc.
6904 Parke East Blvd.
Tampa, FL 33610-4115

Site Information:

Customer Info: Exceptions Reality Project Name: Spec Hse Model: Custom
Lot/Block: 10 Subdivision: Creek Run Plantation
Address: TBD, TBD
City: Columbia Cty State: FL

Name Address and License # of Structural Engineer of Record, If there is one, for the building.

Name: License #:
Address:
City: State:

General Truss Engineering Criteria & Design Loads (Individual Truss Design Drawings Show Special Loading Conditions):

Design Code: FBC2020/TPI2014 Design Program: MiTek 20/20 8.4
Wind Code: ASCE 7-16 Wind Speed: 130 mph
Roof Load: 37.0 psf Floor Load: N/A psf

This package includes 30 individual, Truss Design Drawings and 0 Additional Drawings.

With my seal affixed to this sheet, I hereby certify that I am the Truss Design Engineer and this index sheet conforms to 61G15-31.003, section 5 of the Florida Board of Professional Engineers Rules.


No.	Seal#	Truss Name	Date	No.	Seal#	Truss Name	Date
1	T25045006	CJ01	8/17/21	23	T25045028	T14	8/17/21
2	T25045007	CJ03	8/17/21	24	T25045029	T15	8/17/21
3	T25045008	CJ05	8/17/21	25	T25045030	T17	8/17/21
4	T25045009	EJ01	8/17/21	26	T25045031	T18	8/17/21
5	T25045010	HJ09	8/17/21	27	T25045032	T19	8/17/21
6	T25045011	HJ10	8/17/21	28	T25045033	T20	8/17/21
7	T25045012	PB01	8/17/21	29	T25045034	T21	8/17/21
8	T25045013	PB02	8/17/21	30	T25045035	T22	8/17/21
9	T25045014	T01	8/17/21				
10	T25045015	T01A	8/17/21				
11	T25045016	T02	8/17/21				
12	T25045017	T03	8/17/21				
13	T25045018	T04	8/17/21				
14	T25045019	T05	8/17/21				
15	T25045020	T06	8/17/21				
16	T25045021	T07	8/17/21				
17	T25045022	T08	8/17/21				
18	T25045023	T09	8/17/21				
19	T25045024	T10	8/17/21				
20	T25045025	T11	8/17/21				
21	T25045026	T12	8/17/21				
22	T25045027	T13	8/17/21				

The truss drawing(s) referenced above have been prepared by MiTek USA, Inc. under my direct supervision based on the parameters provided by Builders FirstSource-Lake City, FL.

Truss Design Engineer's Name: O'Regan, Philip

My license renewal date for the state of Florida is February 28, 2023.

IMPORTANT NOTE: The seal on these truss component designs is a certification that the engineer named is licensed in the jurisdiction(s) identified and that the designs comply with ANSI/TPI 1. These designs are based upon parameters shown (e.g., loads, supports, dimensions, shapes and design codes), which were given to MiTek or TRENCO. Any project specific information included is for MiTek's or TRENCO's customers file reference purpose only, and was not taken into account in the preparation of these designs. MiTek or TRENCO has not independently verified the applicability of the design parameters or the designs for any particular building. Before use, the building designer should verify applicability of design parameters and properly incorporate these designs into the overall building design per ANSI/TPI 1, Chapter 2.




Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17, 2021

Job 2874271	Truss CJ01	Truss Type Jack-Open	Qty 12	Ply 1	EXCEPTIONS REALITY - LOT 10 CRP T25045006
----------------	---------------	-------------------------	-----------	----------	--

Builders FirstSource (Lake City,FL), Lake City, FL - 32055, 8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:16 2021 Page 1
ID:krMvx1mH9U?wf6?cKU0X49yy8lb-SKPMoaxpuTc06IX071P5iokZ1ivANL9zOIL_MZynCTz



Scale = 1:10.5

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.19	Vert(LL)	0.00	7	>999	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.05	Vert(CT)	0.00	7	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	0.00	2	n/a	n/a		
BCDL 10.0	Code FBC2020/TPI2014		Matrix-MP						Weight: 6 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 1-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.


REACTIONS.

(size) 3=Mechanical, 2=0-8-0, 4=Mechanical
Max Horz 2=52(LC 12)
Max Uplift 3=-5(LC 1), 2=-69(LC 12), 4=-20(LC 1)
Max Grav 3=7(LC 8), 2=179(LC 1), 4=21(LC 16)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; porch left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 5 lb uplift at joint 3, 69 lb uplift at joint 2 and 20 lb uplift at joint 4.



Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17,2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601
ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component



6904 Parke East Blvd.
Tampa, FL 36610

Job 2874271	Truss CJ03	Truss Type Jack-Open	Qty 12	Ply 1	EXCEPTIONS REALITY - LOT 10 CRP	T25045007
----------------	---------------	-------------------------	-----------	----------	---------------------------------	-----------


Builders FirstSource (Lake City,FL),

Lake City, FL - 32055,

8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:16 2021 Page 1
ID:krMvx1mH9U?wf6?cKU0X49yy8lb-SKPMoaxpuTc06IX071P5iokZ81uMNL9zOIL_MZynCTz



Scale = 1:17.3



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.16	in (loc) l/defl L/d	MT20	244/190
TCDL 7.0	Plate Grip DOL 1.25	BC 0.10	Vert(LL) 0.01 4-7 >999 240		
BCLL 0.0 *	Lumber DOL 1.25	WB 0.00	Vert(CT) -0.01 4-7 >999 180		
BCDL 10.0	Rep Stress Incr YES	Matrix-MP	Horz(CT) -0.00 3 n/a n/a		
	Code FBC2020/TPI2014			Weight: 13 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 3-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.


REACTIONS.

(size) 3=Mechanical, 2=0-8-0, 4=Mechanical
Max Horz 2=97(LC 12)
Max Uplift 3=-44(LC 12), 2=-49(LC 12), 4=-16(LC 9)
Max Grav 3=62(LC 19), 2=210(LC 1), 4=51(LC 3)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2E) -1-6-0 to 1-6-0, Interior(1) 1-6-0 to 2-11-4 zone; porch left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 44 lb uplift at joint 3, 49 lb uplift at joint 2 and 16 lb uplift at joint 4.



Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17,2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601
ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component



6904 Parke East Blvd.
Tampa, FL 36610

Job 2874271	Truss CJ05	Truss Type Jack-Open	Qty 12	Ply 1	EXCEPTIONS REALITY - LOT 10 CRP Job Reference (optional)	T25045008
----------------	---------------	-------------------------	-----------	----------	---	-----------

Builders FirstSource (Lake City, FL),


Lake City, FL - 32055,

8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:17 2021 Page 1

ID:krMvx1mH9U?wf6?cKU0X49yy8lb-wWYk0wxSfntjv5DhlwKF?Gi_QCN6oP6cy5Xv0ynCTy



Scale: 1/2"=1'



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.28	Vert(LL)	0.03	4-7	>999	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.24	Vert(CT)	-0.06	4-7	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	0.00	3	n/a	n/a		
BCDL 10.0	Code FBC2020/TPI2014		Matrix-MP						Weight: 19 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 5-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.


REACTIONS.

(size) 3=Mechanical, 2=0-8-0, 4=Mechanical
Max Horz 2=143(LC 12)
Max Uplift 3=-81(LC 12), 2=-49(LC 12), 4=-1(LC 12)
Max Grav 3=120(LC 19), 2=276(LC 1), 4=89(LC 3)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2E) -1-6-0 to 1-6-0, Interior(1) 1-6-0 to 4-11-4 zone; porch right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 81 lb uplift at joint 3, 49 lb uplift at joint 2 and 1 lb uplift at joint 4.



Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17, 2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component



6904 Parke East Blvd.
Tampa, FL 36610

Builders FirstSource (Lake City,FL), Lake City, FL - 32055, 8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:18 2021 Page 1
ID:krMvx1mH9U?wf6?cKU0X49yy8lb-PIW7DGy4Q4skL3gPESSZoDpsiqVYrESGrqc4RSynCTx




Plate Offsets (X,Y)-- [2:0-1-9,0-2-5]

LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc)	L/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.25	TC 0.35	Vert(LL) -0.08 6-9	>999	240	MT20	244/190
TCDL 7.0	Lumber DOL 1.25	BC 0.44	Vert(CT) -0.16 6-9	>529	180		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.08	Horz(CT) 0.00 2	n/a	n/a		
BCDL 10.0	Code FBC2020/TPI2014	Matrix-MS				Weight: 32 lb	FT = 20%

LUMBER-

TOP CHORD	2x4 SP No.2
BOT CHORD	2x4 SP No.2
WEBS	2x4 SP No.3

BRACING-

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.


REACTIONS.

(size) 4=Mechanical, 2=0-8-0, 5=Mechanical
 Max Horz 2=182(LC 12)
 Max Uplift 4=-48(LC 12), 2=-55(LC 12), 5=-58(LC 12)
 Max Grav 4=77(LC 19), 2=346(LC 1), 5=184(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2E) -1-6-0 to 1-6-0, Interior(1) 1-6-0 to 6-11-4 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 48 lb uplift at joint 4, 55 lb uplift at joint 2 and 58 lb uplift at joint 5.



Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17, 2021

 WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE


WARNING – verify design parameters and NOTES ON THIS AND INCLUDED WITHIN REFERENCE TO AISC MH-143 (Rev. 3/25/2020) BEFORE USE.
Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for the building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI 1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601.



6904 Parke East Blvd.
Tampa, FL 36610

Job	Truss	Truss Type	Qty	Ply	EXCEPTIONS REALITY - LOT 10 CRP	T25045010
2874271	HJ09	Roof Special Girder	1	1	Job Reference (optional)	

Builders FirstSource (Lake City, FL), Lake City, FL - 32055, 8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:19 2021 Page 1
ID:krMvx1mH9U?wf6?ckU0X49yy8lb-tv4VRcziBO_bzCFbo9zoKQL2AEt2ag_P4GaezuynCTw



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.30	in (loc) l/defl L/d	MT20	244/190
TCDL 7.0	Plate Grip DOL 1.25	BC 0.30	Vert(LL) 0.02 7-10 >999 240		
BCLL 0.0 *	Lumber DOL 1.25	WB 0.19	Vert(CT) -0.03 7-10 >999 180		
BCDL 10.0	Rep Stress Incr NO	Matrix-MS	Horz(CT) 0.01 6 n/a n/a		
	Code FBC2020/TPI2014			Weight: 48 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS.

(size) 2=0-4-9, 6=0-10-9
Max Horz 2=175(LC 8)
Max Uplift 2=-202(LC 4), 6=-261(LC 5)
Max Grav 2=483(LC 1), 6=447(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


TOP CHORD 2-3=-498/210
BOT CHORD 2-7=-255/395, 6-7=-255/395
WEBS 3-6=-445/289

NOTES-

- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 202 lb uplift at joint 2 and 261 lb uplift at joint 6.
- 6) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 62 lb down and 73 lb up at 1-6-1, 62 lb down and 73 lb up at 1-6-1, 76 lb down and 46 lb up at 4-4-0, 76 lb down and 46 lb up at 4-4-0, and 109 lb down and 92 lb up at 7-1-15, and 109 lb down and 92 lb up at 7-1-15 on top chord, and 44 lb down and 45 lb up at 1-6-1, 44 lb down and 45 lb up at 1-6-1, 19 lb down and 24 lb up at 4-4-0, 19 lb down and 24 lb up at 4-4-0, and 70 lb down and 16 lb up at 7-1-15, and 70 lb down and 16 lb up at 7-1-15 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- 7) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- 1) Dead + Roof Live (balanced): Lumber Increase=1.25, Plate Increase=1.25
Uniform Loads (plf)
Vert: 1-4=-54, 4-5=-54, 6-8=-20
Concentrated Loads (lb)
Vert: 13=-73(F=-36, B=-36) 16=-4(F=-2, B=-2) 17=-59(F=-29, B=-29)



Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17, 2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.


Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.
Tampa, FL 36610

Job 2874271	Truss HJ10	Truss Type Diagonal Hip Girder	Qty 5	Ply 1	EXCEPTIONS REALITY - LOT 10 CRP T25045011
----------------	---------------	-----------------------------------	----------	----------	--

Builders FirstSource (Lake City, FL), Lake City, FL - 32055, 8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:20 2021 Page 1
ID:krMvx1mH9U?wf6?cKU0X49yy8lb-L5etey_Kyi6SaMqoMtU1teu9ke9eJ3CYJwJBVLynCTv



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.57	in (loc) l/defl L/d	MT20	244/190
TCDL 7.0	Plate Grip DOL 1.25	BC 0.53	Vert(LL) -0.04 6-7 >999 240		
BCLL 0.0 *	Lumber DOL 1.25	WB 0.38	Vert(CT) -0.09 6-7 >999 180		
BCDL 10.0	Rep Stress Incr NO	Matrix-MS	Horz(CT) 0.01 6 n/a n/a		
	Code FBC2020/TPI2014			Weight: 46 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS.

(size) 4=Mechanical, 2=0-10-15, 6=Mechanical
Max Horz 2=182(LC 8)
Max Uplift 4=-93(LC 8), 2=-217(LC 8), 6=-136(LC 8)
Max Grav 4=147(LC 1), 2=524(LC 1), 6=304(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


TOP CHORD 2-3=-639/261
BOT CHORD 2-7=-333/545, 6-7=-333/545
WEBS 3-7=-28/270, 3-6=-592/361

NOTES-

- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone; Lumber DOL=1.60 plate grip DOL=1.60
- Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
- N/A
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 93 lb uplift at joint 4, 217 lb uplift at joint 2 and 136 lb uplift at joint 6.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 62 lb down and 73 lb up at 1-6-1, 62 lb down and 73 lb up at 1-6-1, 76 lb down and 46 lb up at 4-4-0, 76 lb down and 46 lb up at 4-4-0, and 109 lb down and 92 lb up at 7-1-15, and 109 lb down and 92 lb up at 7-1-15 on top chord, and 21 lb down and 45 lb up at 1-6-1, 21 lb down and 45 lb up at 1-6-1, 18 lb down and 24 lb up at 4-4-0, 18 lb down and 24 lb up at 4-4-0, and 47 lb down and 16 lb up at 7-1-15, and 47 lb down and 16 lb up at 7-1-15 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- Dead + Roof Live (balanced): Lumber Increase=1.25, Plate Increase=1.25
Uniform Loads (plf)
Vert: 1-4=-54, 5-8=-20
Concentrated Loads (lb)
Vert: 7=-4(F=-2, B=-2) 12=-73(F=-36, B=-36) 15=-59(F=-29, B=-29)



Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17, 2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




6904 Parke East Blvd.
Tampa, FL 36610

Job 2874271	Truss PB01	Truss Type Piggyback	Qty 8	Ply 1	EXCEPTIONS REALITY - LOT 10 CRP T25045012
----------------	---------------	-------------------------	----------	----------	--

Builders FirstSource (Lake City, FL), Lake City, FL - 32055, 8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:21 2021 Page 1
ID:krMvx1mH9U?wf6?ckU0X49yy8lb-pHCFsl_yj?EJCWP_wa?GPrRPB2ce2b?iXa3l2nynCTu

3-10-0 7-8-0
3-10-0 3-10-0

Scale = 1:16.9



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.14	in (loc) l/defl L/d	MT20	244/190
TCDL 7.0	Plate Grip DOL 1.25	BC 0.10	Vert(LL) 0.00 5 n/r 120		
BCLL 0.0 *	Lumber DOL 1.25	WB 0.03	Vert(CT) 0.01 5 n/r 120		
BCDL 10.0	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 4 n/a n/a		
	Code FBC2020/TPI2014			Weight: 25 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.


REACTIONS.

(size) 2=6-1-12, 4=6-1-12, 6=6-1-12
Max Horz 2=-52(LC 10)
Max Uplift 2=-48(LC 12), 4=-55(LC 13), 6=-15(LC 12)
Max Grav 2=150(LC 1), 4=150(LC 1), 6=207(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2E) 0-3-5 to 3-3-5, Interior(1) 3-3-5 to 3-10-0, Exterior(2R) 3-10-0 to 6-10-14, Interior(1) 6-10-14 to 7-4-11 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 48 lb uplift at joint 2, 55 lb uplift at joint 4 and 15 lb uplift at joint 6.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.



Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17, 2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601
ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component




6904 Parke East Blvd.
Tampa, FL 36610

Job 2874271	Truss PB02	Truss Type Piggyback	Qty 2	Ply 1	EXCEPTIONS REALITY - LOT 10 CRP T25045013
Builders FirstSource (Lake City, FL), Lake City, FL - 32055, 8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:21 2021 Page 1 ID:krMvx1mH9U?wf6?cKU0X49yy8lb-pHCFsl_yj?EJCWP_wa?GPrROD2c72b2IXa3l2nynCTu					
Job Reference (optional)					

7-8-0
7-8-0

Scale = 1:15.0



7-8-0
7-8-0

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.21	in (loc) l/defl L/d	MT20	244/190
TCDL 7.0	Plate Grip DOL 1.25	BC 0.06	Vert(LL) 0.00 5 n/r 120		
BCLL 0.0 *	Lumber DOL 1.25	WB 0.02	Vert(CT) 0.00 5 n/r 120		
BCDL 10.0	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 5 n/a n/a		
	Code FBC2020/TPI2014			Weight: 23 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.


REACTIONS.

All bearings 6-1-12.
(lb) - Max Horz 2=-26(LC 10)
Max Uplift All uplift 100 lb or less at joint(s) 2, 5, 8, 7
Max Grav All reactions 250 lb or less at joint(s) 2, 5, 8, 7

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2E) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
- Provide adequate drainage to prevent water ponding.
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 5, 8, 7.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.



Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17, 2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601
ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component



6904 Parke East Blvd.
Tampa, FL 36610

Job 2874271	Truss T01	Truss Type Hip Girder	Qty 1	Ply 1	EXCEPTIONS REALITY - LOT 10 CRP T25045014
Builders FirstSource (Lake City, FL), Lake City, FL - 32055, 8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:23 2021 Page 1 ID:krMvx1mH9U?wf6?cKU0X49yy8lb-IgK?G_0CFdU0RqZN1?1kVGWkGrBIWPO??uYr6fynCTs					
Job Reference (optional)					




Plate Offsets (X,Y)-- [2:0-6-0,0-0-11], [8:0-6-0,0-0-12]							
LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d
TCLL 20.0	Plate Grip DOL	1.25	TC 0.23	Vert(LL)	-0.08 10	>999	240
TCDL 7.0	Lumber DOL	1.25	BC 0.50	Vert(CT)	-0.14 10	>999	180
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.42	Horz(CT)	0.05 8	n/a	n/a
BCDL 10.0	Code FBC2020/TPI2014		Matrix-MS				
						PLATES	GRIP
						MT20	244/190
						Weight: 139 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 3-6 oc purlins.
BOT CHORD 2x6 SP No.2	BOT CHORD Rigid ceiling directly applied or 7-10-14 oc bracing.
WEBS 2x4 SP No.3	


REACTIONS.	(size) 8=0-8-0, 2=0-8-0
	Max Horz 2=118(LC 26)
	Max Uplift 8=583(LC 9), 2=604(LC 8)
	Max Grav 8=1570(LC 1), 2=1631(LC 1)

FORCES.	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	2-3=-2528/977, 3-4=-2379/953, 4-5=-1967/833, 5-6=-2010/858, 6-7=-2434/986, 7-8=-2576/1011
BOT CHORD	2-12=-824/2065, 10-12=-867/2255, 9-10=-867/2255, 8-9=-785/2115
WEBS	4-12=-414/1092, 5-12=-505/266, 5-10=-146/377, 5-9=-431/204, 6-9=-371/1054

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
 - 4) Provide adequate drainage to prevent water ponding.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 8=583, 2=604.
 - 8) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 66 lb down and 51 lb up at 7-0-0, 66 lb down and 49 lb up at 9-0-12, 66 lb down and 41 lb up at 11-0-0, and 66 lb down and 49 lb up at 12-11-4, and 171 lb down and 155 lb up at 15-0-0 on top chord, and 431 lb down and 243 lb up at 7-0-0, 156 lb down and 78 lb up at 9-0-12, 156 lb down and 78 lb up at 11-0-0, and 156 lb down and 78 lb up at 12-11-4, and 431 lb down and 243 lb up at 14-11-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
 - 9) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard
1) Dead + Roof Live (balanced): Lumber Increase=1.25, Plate Increase=1.25
Uniform Loads (plf)
Vert: 1-4=-54, 4-6=-54, 6-8=-54, 2-8=-20

Continued on page 2



Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17,2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.
Tampa, FL 36610

Job	Truss	Truss Type	Qty	Ply	EXCEPTIONS REALITY - LOT 10 CRP
2874271	T01	Hip Girder	1	1	T25045014
Job Reference (optional)					

LOAD CASE(S) Standard
Concentrated Loads (lb)
Vert: 4=-18(F) 6=-89(F) 12=-431(F) 10=-156(F) 5=-18(F) 9=-431(F) 17=-18(F) 18=-18(F) 19=-156(F) 20=-156(F)

Job	Truss	Truss Type	Qty	Ply	EXCEPTIONS REALITY - LOT 10 CRP	T25045015
2874271	T01A	Hip	1	1	Job Reference (optional)	

Builders FirstSource (Lake City,FL), Lake City, FL - 32055,

8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:24 2021 Page 1

ID:krMvx1mH9U?wf6?cKU0X49yy8lb-DsuOUK1r0wdt3_8ZbjYz1U3rfFUJFwW8DYHPf6ynCTr



Scale = 1:42.1




Plate Offsets (X,Y)-- [2:0-8-0,0-0-12], [5:0-5-12,0-2-0], [7:0-8-0,0-0-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.45	Vert(LL)	-0.16	8-13	>999	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.67	Vert(CT)	-0.33	8-13	>808	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.17	Horz(CT)	0.03	7	n/a	n/a		
BCDL 10.0	Code FBC2020/TPI2014		Matrix-MS						Weight: 117 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 5-1-6 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS.


(size) 7=0-8-0, 2=0-8-0
Max Horz 2=147(LC 11)
Max Uplift 7=-166(LC 13), 2=-200(LC 12)
Max Grav 7=811(LC 1), 2=898(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-1154/254, 3-4=-944/211, 4-5=-727/213, 5-6=-949/215, 6-7=-1163/261
BOT CHORD 2-10=-237/933, 8-10=-65/730, 7-8=-157/946
WEBS 3-10=-280/171, 4-10=-55/322, 5-8=-68/324, 6-8=-292/179

NOTES-

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2E) -1-6-0 to 1-6-0, Interior(1) 1-6-0 to 9-0-0, Exterior(2E) 9-0-0 to 13-0-0, Exterior(2R) 13-0-0 to 17-5-6, Interior(1) 17-5-6 to 22-0-0 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
- 4) Provide adequate drainage to prevent water ponding.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 7=166, 2=200.



Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17,2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component



6904 Parke East Blvd.
Tampa, FL 36610

Job 2874271	Truss T02	Truss Type Common	Qty 2	Ply 1	EXCEPTIONS REALITY - LOT 10 CRP	T25045016
----------------	--------------	----------------------	----------	----------	---------------------------------	-----------

Builders FirstSource (Lake City,FL), Lake City, FL - 32055, 8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:24 2021 Page 1
ID:krMvx1mH9U?wf6?cKU0X49yy8lb-DsuOUK1r0wdt3_8ZbjYz1U3t9FYTFuL8DYHPf6ynCTR



4x6 ||

Scale: 1/4"=1'




Plate Offsets (X,Y)--		[6:0-2-3,Edge]									
LOADING (psf)		SPACING-	2-0-0	CSI.		DEFL.	in	(loc)	l/defl	L/d	
TCLL	20.0	Plate Grip DOL	1.25	TC	0.35	Vert(LL)	-0.15	7-9	>999	240	
TCDL	7.0	Lumber DOL	1.25	BC	0.41	Vert(CT)	-0.28	7-9	>938	180	
BCLL	0.0 *	Rep Stress Incr	NO	WB	0.31	Horz(CT)	0.03	6	n/a	n/a	
BCDL	10.0	Code FBC2020/TPI2014		Matrix-MS							
											PLATES
											MT20
											GRIP
											244/190
											Weight: 111 lb
											FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP M 31
WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-4-3 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS.

(size) 6=0-8-0, 2=0-8-0
Max Horz 2=176(LC 9)
Max Uplift 6=-217(LC 13), 2=-251(LC 12)
Max Grav 6=1137(LC 20), 2=1216(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


TOP CHORD 2-3=-1691/337, 3-4=-1601/389, 4-5=-1612/396, 5-6=-1701/344
BOT CHORD 2-9=-314/1463, 7-9=-128/967, 6-7=-219/1356
WEBS 4-7=-237/882, 5-7=-289/205, 4-9=-228/867, 3-9=-283/201

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2E) -1-6-0 to 1-6-0, Interior(1) 1-6-0 to 11-0-0, Exterior(2R) 11-0-0 to 14-0-0, Interior(1) 14-0-0 to 22-0-0 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 6=217, 2=251.
- In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- Dead + Roof Live (balanced): Lumber Increase=1.25, Plate Increase=1.25
Uniform Loads (plf)
Vert: 1-4=-54, 4-6=-54, 9-13=-20, 7-9=-80(F=-60), 7-10=-20



Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17,2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.
Tampa, FL 36610

Job 2874271	Truss T03	Truss Type Common	Qty 4	Ply 1	EXCEPTIONS REALITY - LOT 10 CRP	T25045017
----------------	--------------	----------------------	----------	----------	---------------------------------	-----------

Builders FirstSource (Lake City, FL), Lake City, FL - 32055,

8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:25 2021 Page 1

ID:krMvx1mH9U?wf6?cKU0X49yy8lb-h3Rmhf2TnElkh7ji9Q4Cahb1WfnC_LkISC1yBYnCTq



4x6 ||

Scale: 1/4"=1'




Plate Offsets (X,Y)-- [7:0-3-8,Edge]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.44	Vert(LL)	-0.17	8-10	>999	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.89	Vert(CT)	-0.31	8-10	>846	180		
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.30	Horz(CT)	0.03	7	n/a	n/a		
BCDL 10.0	Code FBC2020/TPI2014		Matrix-MS						Weight: 112 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2 *Except*
2-9: 2x4 SP M 31
WEBS 2x4 SP No.3
SLIDER Right 2x4 SP No.3 1-11-8

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-4-6 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS.

(size) 7=0-3-8, 2=0-8-0
Max Horz 2=176(LC 9)
Max Uplift 7=-214(LC 13), 2=-248(LC 12)
Max Grav 7=1124(LC 20), 2=1198(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


TOP CHORD 2-3=-1662/332, 3-4=-1572/384, 4-5=-1513/378, 5-7=-1575/327
BOT CHORD 2-10=-314/1437, 8-10=-128/935, 7-8=-207/1257
WEBS 3-10=-280/201, 4-10=-230/883, 4-8=-218/776

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2E) -1-6-0 to 1-6-0, Interior(1) 1-6-0 to 11-0-0, Exterior(2R) 11-0-0 to 14-0-0, Interior(1) 14-0-0 to 21-7-8 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 7=214, 2=248.
- In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- Dead + Roof Live (balanced): Lumber Increase=1.25, Plate Increase=1.25
Uniform Loads (plf)
Vert: 1-4=-54, 4-7=-54, 10-15=-20, 8-10=-80(F=-60), 8-11=-20



Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17, 2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see



ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.
Tampa, FL 36610

Job 2874271	Truss T04	Truss Type Hip Girder	Qty 1	Ply 1	EXCEPTIONS REALITY - LOT 10 CRP	T25045018
Builders FirstSource (Lake City, FL), Lake City, FL - 32055, 8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:27 2021 Page 1						
ID:krMvx1mH9U?wf6?cKU0X49yy8lb-eRZW6L3jr?SwRs8Gr6gf6hM3SRAS4WawVW3FRynCTo						
Job Reference (optional)						



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.50	Vert(LL)	0.23 16-17	>999	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.98	Vert(CT)	-0.41 13-14	>917	180		
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.98	Horz(CT)	0.12 11	n/a	n/a		
BCDL 10.0	Code FBC2020/TPI2014		Matrix-MS					Weight: 202 lb	FT = 20%


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 2-6-6 oc purlins.
BOT CHORD 2x6 SP No.2	BOT CHORD Rigid ceiling directly applied or 5-8-4 oc bracing.
WEBS 2x4 SP No.3	

REACTIONS.	(size) 2=0-8-0, 11=0-8-0
	Max Horz 2=-125(LC 6)
	Max Uplift 2=-880(LC 8), 11=-906(LC 9)
	Max Grav 2=2413(LC 1), 11=2453(LC 1)

FORCES.	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	2-3=-3953/1479, 3-4=-3799/1457, 4-5=-3181/1261, 5-6=-4414/1712, 6-8=-4430/1711, 8-9=-3239/1300, 9-10=-3869/1505, 10-11=-4023/1527
BOT CHORD	2-17=-1224/3241, 16-17=-1542/4045, 14-16=-1709/4499, 13-14=-1534/4076, 11-13=-1179/3300
WEBS	4-17=-689/1881, 5-17=-1373/601, 5-16=-321/850, 8-14=-287/808, 8-13=-1325/559, 9-13=-660/1850

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone; Lumber DOL=1.60 plate grip DOL=1.60
 - Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=880, 11=906.
 - Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 66 lb down and 51 lb up at 7-0-0, 66 lb down and 49 lb up at 9-0-12, 66 lb down and 49 lb up at 11-0-12, 66 lb down and 49 lb up at 13-0-12, 66 lb down and 47 lb up at 15-0-12, 66 lb down and 47 lb up at 16-7-4, 66 lb down and 49 lb up at 18-7-4, 66 lb down and 49 lb up at 20-7-4, and 66 lb down and 49 lb up at 22-7-4, and 171 lb down and 155 lb up at 24-8-0 on top chord, and 431 lb down and 220 lb up at 7-0-0, 156 lb down and 78 lb up at 9-0-12, 156 lb down and 78 lb up at 11-0-12, 156 lb down and 78 lb up at 13-0-12, 156 lb down and 78 lb up at 15-0-12, 156 lb down and 78 lb up at 16-7-4, 156 lb down and 78 lb up at 18-7-4, 156 lb down and 78 lb up at 20-7-4, and 156 lb down and 78 lb up at 22-7-4, and 431 lb down and 220 lb up at 24-7-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
 - In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard
Continued on page 2



Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17,2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.
Tampa, FL 36610

Job	Truss	Truss Type	Qty	Ply	EXCEPTIONS REALITY - LOT 10 CRP
2874271	T04	Hip Girder	1	1	T25045018
Job Reference (optional)					

LOAD CASE(S)
Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.25, Plate Increase=1.25

Uniform Loads (plf)

Vert: 1-4=-54, 4-9=-54, 9-12=-54, 2-11=-20

Concentrated Loads (lb)

Vert: 4=-18(F) 9=-89(F) 17=-431(F) 5=-18(F) 8=-18(F) 13=-431(F) 22=-18(F) 23=-18(F) 24=-18(F) 25=-18(F) 26=-18(F) 27=-18(F) 28=-156(F) 29=-156(F) 30=-156(F) 31=-156(F) 32=-156(F) 33=-156(F) 34=-156(F) 35=-156(F)

Job	Truss	Truss Type	Qty	Ply	EXCEPTIONS REALITY - LOT 10 CRP	T25045019
2874271	T05	Hip	1	1	Job Reference (optional)	

Builders FirstSource (Lake City, FL), Lake City, FL - 32055,

8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:28 2021 Page 1
ID:krMvx1mH9U?wf6?cKU0X49yy8lb-6e7uKh4L397JYbRKqYdvCKDW0SpQBink89FcotynCTn

-1-6-0	4-10-4	9-0-0	15-10-0	22-8-0	26-9-12	31-8-0	33-2-0
1-6-0	4-10-4	4-1-12	6-10-0	6-10-0	4-1-12	4-10-4	1-6-0

Scale = 1:56.5




Plate Offsets (X,Y)-- [2:0-1-5,0-1-8], [4:0-2-4,0-2-4], [6:0-2-4,0-2-4], [8:0-1-5,0-1-8], [11:0-3-0,0-3-0]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.53	Vert(LL)	-0.15 12-15	>999	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.79	Vert(CT)	-0.31 12-15	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.28	Horz(CT)	0.08 8	n/a	n/a		
BCDL 10.0	Code FBC2020/TPI2014		Matrix-MS					Weight: 173 lb	FT = 20%


LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 3-10-8 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 5-12, 5-10

REACTIONS. (size) 2=0-8-0, 8=0-8-0
Max Horz 2=-155(LC 10)
Max Uplift 2=-282(LC 12), 8=-282(LC 13)
Max Grav 2=1354(LC 2), 8=1354(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1918/392, 3-4=-1749/357, 4-5=-1422/337, 5-6=-1422/337, 6-7=-1749/357, 7-8=-1918/392
BOT CHORD 2-12=-334/1577, 11-12=-289/1756, 10-11=-289/1756, 8-10=-229/1577
WEBS 3-12=-283/161, 4-12=-94/730, 5-12=-510/192, 5-11=0/315, 5-10=-510/192, 6-10=-94/730, 7-10=-283/162

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2E) -1-6-0 to 1-8-0, Interior(1) 1-8-0 to 9-0-0, Exterior(2R) 9-0-0 to 13-5-12, Interior(1) 13-5-12 to 22-8-0, Exterior(2R) 22-8-0 to 26-11-4, Interior(1) 26-11-4 to 33-2-0 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=282, 8=282.



Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17,2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601
ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component



6904 Parke East Blvd.
Tampa, FL 33610

Job	Truss	Truss Type	Qty	Ply	EXCEPTIONS REALITY - LOT 10 CRP	T25045020
2874271	T06	Hip	1	1	Job Reference (optional)	

Builders FirstSource (Lake City,FL), Lake City, FL - 32055,

8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:29 2021 Page 1

ID:krMvx1mH9U?wf6?cKU0X49yy8lb-aqhHX15zqTFA9I0WOG88kXmiUG6gw8qtNp?AKJynCTm

-1-6-0	6-1-1	11-0-0	15-10-0	20-8-0	25-6-15	31-8-0	33-2-0
1-6-0	6-1-1	4-10-15	4-10-0	4-10-0	4-10-15	6-1-1	1-6-0

Scale = 1:56.5




Plate Offsets (X,Y)--		[8:0-2-3,Edge]									
LOADING (psf)		SPACING-	2-0-0	CSI.		DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL	20.0	Plate Grip DOL	1.25	TC	0.31	Vert(LL)	-0.33 11-13	>999	240	MT20	244/190
TCDL	7.0	Lumber DOL	1.25	BC	0.98	Vert(CT)	-0.55 11-13	>688	180		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.36	Horz(CT)	0.07 8	n/a	n/a		
BCDL	10.0	Code FBC2020/TPI2014		Matrix-MS						Weight: 183 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 3-11-11 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:
WEBS 2-2-0 oc bracing: 11-13.
1 Row at midpt 5-13, 5-11

REACTIONS.


(size) 2=0-8-0, 8=0-8-0
Max Horz 2=-184(LC 10)
Max Uplift 2=-277(LC 12), 8=-277(LC 13)
Max Grav 2=1349(LC 2), 8=1349(LC 2)

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1941/367, 3-4=-1614/340, 4-5=-1295/323, 5-6=-1295/323, 6-7=-1614/340,
7-8=-1941/367
BOT CHORD 2-14=-318/1599, 13-14=-318/1599, 11-13=-180/1369, 10-11=-194/1563, 8-10=-194/1563
WEBS 3-13=-444/201, 4-13=-107/675, 5-13=-265/161, 5-11=-265/161, 6-11=-107/675,
7-11=-444/201

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2E) -1-6-0 to 1-8-0, Interior(1) 1-8-0 to 11-0-0, Exterior(2R) 11-0-0 to 15-5-12, Interior(1) 15-5-12 to 20-8-0, Exterior(2R) 20-8-0 to 25-1-12, Interior(1) 25-1-12 to 33-2-0 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=277, 8=277.



Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17,2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




6904 Parke East Blvd.
Tampa, FL 33610

Job 2874271	Truss T07	Truss Type Hip	Qty 1	Ply 1	EXCEPTIONS REALITY - LOT 10 CRP T25045021
----------------	--------------	-------------------	----------	----------	--

Builders FirstSource (Lake City, FL), Lake City, FL - 32055,

8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:30 2021 Page 1

ID:krMvx1mH9U?wf6?cKU0X49yy8lb-20FfkN5bbmN1nvbjxzfnHJJuGgYofV61cTkjsynCTI



Scale = 1:59.6

Plate Offsets (X,Y)-- [3:0-3-0,0-3-0], [4:0-5-12,0-2-0], [5:0-3-12,0-2-0], [7:0-2-3,Edge]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.44	Vert(LL)	-0.10 11-12	>999	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.60	Vert(CT)	-0.19 11-12	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.74	Horz(CT)	0.07 7	n/a	n/a		
BCDL 10.0	Code FBC2020/TPI2014		Matrix-MS					Weight: 180 lb	FT = 20%


LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 3-10-11 oc purlins.
BOT CHORD Rigid ceiling directly applied or 9-10-14 oc bracing.
WEBS 1 Row at midpt 4-9

REACTIONS. (size) 7=0-8-0, 2=0-8-0
Max Horz 2=206(LC 9)
Max Uplift 7=240(LC 13), 2=273(LC 12)
Max Grav 7=1273(LC 20), 2=1353(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1938/358, 3-4=-1458/312, 4-5=-1141/316, 5-6=-1452/315, 6-7=-1939/365
BOT CHORD 2-12=-345/1661, 11-12=-345/1665, 9-11=-146/1166, 8-9=-222/1562, 7-8=-222/1562
WEBS 3-12=0/277, 3-11=-606/239, 4-11=-93/567, 5-9=-87/540, 6-9=-615/247, 6-8=0/279

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2E) -1-6-0 to 1-8-0, Interior(1) 1-8-0 to 13-0-0, Exterior(2R) 13-0-0 to 17-5-12, Interior(1) 17-5-12 to 18-8-0, Exterior(2R) 18-8-0 to 23-1-12, Interior(1) 23-1-12 to 31-8-0 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
 - 4) Provide adequate drainage to prevent water ponding.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 7=240, 2=273.



Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17,2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




6904 Parke East Blvd.
Tampa, FL 36610

Job	Truss	Truss Type	Qty	Ply	EXCEPTIONS REALITY - LOT 10 CRP	T25045022
2874271	T08	Hip	1	1	Job Reference (optional)	

Builders FirstSource (Lake City, FL), Lake City, FL - 32055,

8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:31 2021 Page 1

ID:krMvx1mH9U?wf6?cKU0X49yy8lb-WDp1yj6EM4VuP2AvVhAcpyr0C4tK03bAq7UGOCynCTk



Scale = 1:72.9




Plate Offsets (X,Y)-- [3:0-4-0,0-3-0], [4:0-5-12,0-2-0], [5:0-3-12,0-2-0], [6:0-4-0,0-3-0], [7:0-2-3,Edge]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.62	Vert(LL)	0.10	8-18	>999	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.65	Vert(CT)	-0.19	8-18	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.27	Horz(CT)	0.06	7	n/a	n/a		
BCDL 10.0	Code FBC2020/TPI2014		Matrix-MS						Weight: 191 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 3-8-3 oc purlins.
BOT CHORD Rigid ceiling directly applied or 9-10-10 oc bracing.
WEBS 1 Row at midpt 3-11, 4-9, 6-9

REACTIONS.


(size) 2=0-8-0, 7=0-8-0
Max Horz 2=236(LC 9)
Max Uplift 2=-267(LC 12), 7=-234(LC 13)
Max Grav 2=1255(LC 1), 7=1170(LC 1)

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1762/339, 3-4=-1236/308, 4-5=-930/301, 5-6=-1239/307, 6-7=-1769/346
BOT CHORD 2-12=-334/1388, 11-12=-334/1391, 9-11=-105/927, 8-9=-192/1399, 7-8=-192/1396
WEBS 3-12=0/329, 3-11=-598/279, 4-11=-117/396, 5-9=-139/423, 6-9=-606/286, 6-8=0/327

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2E) -1-6-0 to 1-8-0, Interior(1) 1-8-0 to 15-0-0, Exterior(2E) 15-0-0 to 16-8-0, Exterior(2R) 16-8-0 to 21-1-12, Interior(1) 21-1-12 to 31-8-0 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=267, 7=234.



Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17, 2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component



6904 Parke East Blvd.
Tampa, FL 36610

Job 2874271	Truss T09	Truss Type Common	Qty 1	Ply 1	EXCEPTIONS REALITY - LOT 10 CRP	T25045023
Builders FirstSource (Lake City,FL), Lake City, FL - 32055, 8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:32 2021 Page 1 ID:krMvx1mH9U?wf6?ckU0X49yy8lb-_PMP937s7OdI0CI53OirMAO9wTcQ7VFK3nDqkeynCTJ						




Plate Offsets (X,Y)-- [2:0-6-0,0-0-3], [3:0-4-0,0-3-0], [5:0-4-0,0-3-0], [6:0-6-0,0-0-3], [8:0-4-0,0-3-0]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.75	Vert(LL)	-0.14	8-9	>999	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.76	Vert(CT)	-0.25	8-9	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.38	Horz(CT)	0.07	6	n/a	n/a		
BCDL 10.0	Code FBC2020/TPI2014		Matrix-MS						Weight: 165 lb	FT = 20%


LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied or 9-9-11 oc bracing.
WEBS 1 Row at midpt 5-8, 3-8

REACTIONS. (size) 2=0-8-0, 6=0-8-0
Max Horz 2=247(LC 11)
Max Uplift 2=-264(LC 12), 6=-231(LC 13)
Max Grav 2=1412(LC 19), 6=1335(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1968/338, 3-4=-1338/312, 4-5=-1337/312, 5-6=-1978/345
BOT CHORD 2-9=-344/1733, 8-9=-343/1737, 7-8=-205/1573, 6-7=-205/1568
WEBS 4-8=-167/1003, 5-8=-784/307, 5-7=0/372, 3-8=-773/300, 3-9=0/371

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2E) -1-6-0 to 1-8-0, Interior(1) 1-8-0 to 15-10-0, Exterior(2R) 15-10-0 to 19-0-0, Interior(1) 19-0-0 to 31-8-0 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=264, 6=231.





Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17,2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.
Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

MiTek
6904 Parke East Blvd.
Tampa, FL 36610

Job 2874271	Truss T10	Truss Type Half Hip Girder	Qty 1	Ply 1	EXCEPTIONS REALITY - LOT 10 CRP T25045024
Builders FirstSource (Lake City, FL), Lake City, FL - 32055, 8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:33 2021 Page 1 ID:krMvx1mH9U?wf6?cKU0X49yy8lb-SbwnNP8UuhiceMKId6D4uNxHWta7sqmTIRzNT4ynCTi					
Job Reference (optional)					



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.95	Vert(LL)	0.10 11-13	>999	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.63	Vert(CT)	-0.17 11-13	>999	180		
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.87	Horz(CT)	0.04 9	n/a	n/a		
BCDL 10.0	Code FBC2020/TPI2014		Matrix-MS					Weight: 155 lb	FT = 20%

LUMBER-			BRACING-	
TOP CHORD	2x4 SP No.2		TOP CHORD	Structural wood sheathing directly applied or 3-6-6 oc purlins, except end verticals.
BOT CHORD	2x6 SP No.2		BOT CHORD	Rigid ceiling directly applied or 7-6-6 oc bracing.
WEBS	2x4 SP No.3			

REACTIONS.	(size) 9=0-3-8, 2=0-8-0
	Max Horz 2=191(LC 8)
	Max Uplift 9=-770(LC 5), 2=-594(LC 8)
	Max Grav 9=1971(LC 1), 2=1681(LC 1)

FORCES.	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	2-3=-2629/965, 3-4=-2483/940, 4-5=-2057/825, 5-7=-1741/673, 7-8=-1741/673, 8-9=-1677/682
BOT CHORD	2-13=-907/2148, 11-13=-944/2402, 10-11=-944/2402
WEBS	4-13=-372/1097, 5-13=-459/256, 5-11=-151/560, 5-10=-879/381, 7-10=-356/210, 8-10=-881/2285

- NOTES-**
- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
 - 3) Provide adequate drainage to prevent water ponding.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 9=770, 2=594.
 - 7) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 66 lb down and 51 lb up at 7-0-0, 66 lb down and 49 lb up at 9-0-12, 66 lb down and 49 lb up at 11-0-12, 66 lb down and 49 lb up at 13-0-12, 66 lb down and 41 lb up at 15-0-12, 66 lb down and 49 lb up at 17-0-12, 66 lb down and 49 lb up at 19-0-12, and 66 lb down and 49 lb up at 21-0-12, and 60 lb down and 51 lb up at 22-7-4 on top chord, and 431 lb down and 220 lb up at 7-0-0, 156 lb down and 78 lb up at 9-0-12, 156 lb down and 78 lb up at 11-0-12, 156 lb down and 78 lb up at 13-0-12, 156 lb down and 78 lb up at 15-0-12, 156 lb down and 78 lb up at 17-0-12, 156 lb down and 78 lb up at 19-0-12, and 156 lb down and 78 lb up at 21-0-12, and 160 lb down and 73 lb up at 22-7-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
 - 8) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S)	Standard
1) Dead + Roof Live (balanced):	Lumber Increase=1.25, Plate Increase=1.25

Continued on page 2

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date: August 17,2021

MiTek
6904 Parke East Blvd.
Tampa, FL 36610

Job	Truss	Truss Type	Qty	Ply	EXCEPTIONS REALITY - LOT 10 CRP
2874271	T10	Half Hip Girder	1	1	T25045024
Job Reference (optional)					

LOAD CASE(S)
Standard

Uniform Loads (plf)

Vert: 1-4=-54, 4-8=-54, 2-9=-20

Concentrated Loads (lb)

Vert: 4=-18(B) 6=-18(B) 13=-431(B) 16=-18(B) 17=-18(B) 18=-18(B) 19=-18(B) 20=-18(B) 21=-18(B) 22=-31(B) 23=-156(B) 24=-156(B) 25=-156(B) 26=-156(B) 27=-156(B) 28=-156(B) 29=-156(B) 30=-160(B)

Job	Truss	Truss Type	Qty	Ply	EXCEPTIONS REALITY - LOT 10 CRP	T25045025
2874271	T11	Half Hip	1	1	Job Reference (optional)	

Builders FirstSource (Lake City, FL), Lake City, FL - 32055,

8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:34 2021 Page 1

ID:krMvx1mH9U?wf6?ckU0X49yy8lb-xnUAak96f?iTGWvUApkJRbTX8HvRbNrcX5ix?XynCTh

-1-6-0	4-8-3	9-0-0	16-1-12	23-3-8
1-6-0	4-8-3	4-3-13	7-1-12	7-1-12

Scale = 1:42.4




Plate Offsets (X,Y)-- [2:0-1-5,0-1-8], [4:0-2-4,0-2-4]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.58	Vert(LL)	-0.14	10-13	>999	240	MT20
TCDL 7.0	Lumber DOL	1.25	BC 0.69	Vert(CT)	-0.29	10-13	>950	180	
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.50	Horz(CT)	0.04	7	n/a	n/a	
BCDL 10.0	Code FBC2020/TPI2014		Matrix-MS						
								Weight: 135 lb	FT = 20%


LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 4-8-2 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 9-6-0 oc bracing.
WEBS 1 Row at midpt 5-10, 5-7

REACTIONS. (size) 7=0-3-8, 2=0-8-0
Max Horz 2=237(LC 12)
Max Uplift 7=-221(LC 9), 2=-221(LC 12)
Max Grav 7=966(LC 2), 2=1006(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1310/289, 3-4=-1134/248, 4-5=-901/248
BOT CHORD 2-10=-383/1078, 8-10=-192/850, 7-8=-192/850
WEBS 3-10=-295/163, 4-10=-4/377, 5-8=0/382, 5-7=-1105/250

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2E) -1-6-0 to 1-6-0, Interior(1) 1-6-0 to 9-0-0, Exterior(2R) 9-0-0 to 13-2-15, Interior(1) 13-2-15 to 23-1-12 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
 - 4) Provide adequate drainage to prevent water ponding.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 7=221, 2=221.



Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17, 2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component




6904 Parke East Blvd.
Tampa, FL 33610

Job 2874271	Truss T12	Truss Type Half Hip	Qty 1	Ply 1	EXCEPTIONS REALITY - LOT 10 CRP	T25045026
----------------	--------------	------------------------	----------	----------	---------------------------------	-----------

Builders FirstSource (Lake City,FL), Lake City, FL - 32055,

8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:35 2021 Page 1

ID:krMvx1mH9U?wf6?ckU0X49yy8lb-P_2Yo49kQJ?JtgTgkWFY_o0lGhHEKrNmllSUXzynCTg



Scale = 1:48.7




Plate Offsets (X,Y)-- [4:0-5-12,0-2-0]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.42	Vert(LL)	-0.06	8-10	>999	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.46	Vert(CT)	-0.10	7-8	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.42	Horz(CT)	0.03	7	n/a	n/a		
BCDL 10.0	Code FBC2020/TPI2014		Matrix-MS						Weight: 149 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

REACTIONS.


(size) 7=0-3-8, 2=0-8-0
Max Horz 2=283(LC 12)
Max Uplift 7=-216(LC 9), 2=-212(LC 12)
Max Grav 7=976(LC 2), 2=1022(LC 19)

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1367/254, 3-4=-980/222, 4-5=-612/150, 5-6=-612/150, 6-7=-856/230
BOT CHORD 2-11=-390/1127, 10-11=-390/1127, 8-10=-231/763
WEBS 3-10=-495/196, 4-10=-78/513, 4-8=-300/127, 5-8=-386/190, 6-8=-239/959

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2E) -1-6-0 to 1-6-0, Interior(1) 1-6-0 to 11-0-0, Exterior(2R) 11-0-0 to 15-2-15, Interior(1) 15-2-15 to 23-1-12 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 7=216, 2=212.



Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17,2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component



6904 Parke East Blvd.
Tampa, FL 36610

Job 2874271	Truss T13	Truss Type Half Hip	Qty 1	Ply 1	EXCEPTIONS REALITY - LOT 10 CRP	T25045027
Builders FirstSource (Lake City,FL), Lake City, FL - 32055, 8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:36 2021 Page 1 ID:krMvx1mH9U?wf6?cKU0X49yy8lb-tAcw?QAMBC7AVq2slEmnW0Zvg5dr3DZv_PB14PynCTf						




Plate Offsets (X,Y)-- [3:0-3-0,0-3-0], [4:0-5-12,0-2-0]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.45	Vert(LL)	-0.06 10-11	>999	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.50	Vert(CT)	-0.12 10-11	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.74	Horz(CT)	0.03 7	n/a	n/a		
BCDL 10.0	Code FBC2020/TPI2014		Matrix-MS					Weight: 160 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

REACTIONS.


(size) 7=0-3-8, 2=0-8-0
Max Horz 2=329(LC 12)
Max Uplift 7=-221(LC 12), 2=-200(LC 12)
Max Grav 7=977(LC 2), 2=1039(LC 19)

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1354/229, 3-4=-851/181, 4-5=-451/122, 5-6=-451/122, 6-7=-873/233
BOT CHORD 2-11=-408/1140, 10-11=-408/1144, 8-10=-207/640
WEBS 3-11=0/282, 3-10=-616/240, 4-10=-93/564, 4-8=-437/169, 5-8=-322/162, 6-8=-246/899

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2E) -1-6-0 to 1-6-0, Interior(1) 1-6-0 to 13-0-0, Exterior(2R) 13-0-0 to 17-2-15, Interior(1) 17-2-15 to 23-1-12 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 7=221, 2=200.



Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17,2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see


Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component



6904 Parke East Blvd.
Tampa, FL 36610

Job 2874271	Truss T14	Truss Type Hip	Qty 1	Ply 1	EXCEPTIONS REALITY - LOT 10 CRP T25045028
Builders FirstSource (Lake City,FL), Lake City, FL - 32055, 8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:37 2021 Page 1 ID:krMvx1mH9U?wf6?cKU0X49yy8lb-LMAICmB_ywF17zd3sxH03D5?xUvkogw3D3xbcrnCTe					



Scale = 1:62.8

Plate Offsets (X,Y)-- [3:0-3-0,0-3-4], [4:0-3-12,0-2-0], [5:0-3-12,0-2-0]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.73	Vert(LL)	-0.22	7-8	>999	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.71	Vert(CT)	-0.35	7-8	>803	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.73	Horz(CT)	0.02	7	n/a	n/a		
BCDL 10.0	Code FBC2020/TPI2014		Matrix-MS						Weight: 159 lb	FT = 20%


LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3 *Except*
5-8: 2x4 SP No.2

BRACING-
TOP CHORD Structural wood sheathing directly applied or 4-8-1 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 8-11-13 oc bracing.
WEBS 1 Row at midpt 3-8, 4-8, 6-7, 5-7

REACTIONS. (size) 2=0-8-0, 7=0-3-8
Max Horz 2=368(LC 12)
Max Uplift 2=-186(LC 12), 7=-245(LC 12)
Max Grav 2=1048(LC 19), 7=973(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1308/196, 3-4=-723/140, 4-5=-532/177
BOT CHORD 2-10=-405/1098, 8-10=-404/1102
WEBS 3-10=0/309, 3-8=-695/281, 5-8=-260/806, 5-7=-966/331

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2E) -1-6-0 to 1-6-0, Interior(1) 1-6-0 to 15-0-0, Exterior(2R) 15-0-0 to 19-2-15, Interior(1) 19-2-15 to 22-8-0, Exterior(2E) 22-8-0 to 23-1-12 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=186, 7=245.



Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17,2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




6904 Parke East Blvd.
Tampa, FL 33610

Job 2874271	Truss T15	Truss Type Piggyback Base	Qty 3	Ply 1	EXCEPTIONS REALITY - LOT 10 CRP Job Reference (optional)	T25045029
----------------	--------------	------------------------------	----------	----------	---	-----------

Builders FirstSource (Lake City,FL), Lake City, FL - 32055,

8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:38 2021 Page 1

ID:krMvx1mH9U?wf6?cKU0X49yy8lb-pZkgQ6CdJENuk7CFPfoFbRe9vuFzX7ACRjg88lynCTd



Scale = 1:62.8

Plate Offsets (X,Y)-- [3:0-3-0,0-3-4], [4:0-3-12,0-2-0], [5:0-3-12,0-2-0]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.78	Vert(LL)	-0.22	7-8	>999	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.71	Vert(CT)	-0.35	7-8	>803	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.73	Horz(CT)	0.02	7	n/a	n/a		
BCDL 10.0	Code FBC2020/TPI2014		Matrix-MS						Weight: 159 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3 *Except*
5-8: 2x4 SP No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-8-3 oc purlins, except end verticals, and 2-0-0 oc purlins (5-5-3 max.): 4-5.
BOT CHORD Rigid ceiling directly applied or 8-11-13 oc bracing.
WEBS 1 Row at midpt 3-8, 4-8, 6-7, 5-7

REACTIONS.


(size) 2=0-8-0, 7=0-3-8
Max Horz 2=368(LC 12)
Max Uplift 2=-186(LC 12), 7=-245(LC 12)
Max Grav 2=1046(LC 19), 7=973(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-1303/196, 3-4=-723/140, 4-5=-528/177
BOT CHORD 2-10=-405/1100, 8-10=-404/1104
WEBS 3-10=0/309, 3-8=-695/281, 5-8=-260/810, 5-7=-966/331

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2E) -1-6-0 to 1-6-0, Interior(1) 1-6-0 to 15-0-0, Exterior(2R) 15-0-0 to 19-2-15, Interior(1) 19-2-15 to 22-8-0, Exterior(2E) 22-8-0 to 23-1-12 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=186, 7=245.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17,2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




6904 Parke East Blvd.
Tampa, FL 36610

Job 2874271	Truss T17	Truss Type Roof Special	Qty 1	Ply 1	EXCEPTIONS REALITY - LOT 10 CRP	T25045030
Builders FirstSource (Lake City,FL), Lake City, FL - 32055,						8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:39 2021 Page 1
ID:krMvx1mH9U?wf6?cKU0X49yy8lb-HII3dSCFUXVIMHnRzMKU8eALNIZjGY3LgNQigkymCTc						Job Reference (optional)

1-6-0 7-8-0 15-10-0 20-3-0 24-8-0 30-8-0 37-8-0 39-2-0
1-6-0 7-8-0 8-2-0 4-5-0 4-5-0 6-0-0 7-0-0 1-6-0

5x6 =

Scale = 1:78.7



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.74	Vert(LL)	0.12 10-21	>636	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.87	Vert(CT)	-0.45 12-13	>840	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.82	Horz(CT)	0.04 10	n/a	n/a		
BCDL 10.0	Code FBC2020/TPI2014		Matrix-MS					Weight: 214 lb	FT = 20%


LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 1 Row at midpt 3-13, 5-13, 5-12

REACTIONS. (size) 2=0-8-0, 10=0-8-0, 8=0-3-8
Max Horz 2=-255(LC 10)
Max Uplift 2=-248(LC 12), 10=-365(LC 13), 8=-269(LC 19)
Max Grav 2=1310(LC 19), 10=2124(LC 2), 8=45(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1783/317, 3-4=-1143/296, 4-5=-1088/316, 5-6=-1212/353, 6-7=-942/240,
7-8=-132/947
BOT CHORD 2-15=-306/1591, 13-15=-305/1595, 12-13=-77/997, 10-12=-420/141, 8-10=-686/194
WEBS 3-15=0/353, 3-13=-765/302, 4-13=-200/876, 5-13=-276/219, 6-12=-853/310,
7-12=-236/1782, 7-10=-1882/371

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2E) -1-6-0 to 2-3-3, Interior(1) 2-3-3 to 15-10-0, Exterior(2R) 15-10-0 to 19-7-3, Interior(1) 19-7-3 to 30-8-0, Exterior(2R) 30-8-0 to 34-5-3, Interior(1) 34-5-3 to 39-2-0 zone; porch right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=248, 10=365, 8=269.



Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17,2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.
Tampa, FL 33610

Job 2874271	Truss T18	Truss Type Roof Special	Qty 1	Ply 1	EXCEPTIONS REALITY - LOT 10 CRP	T25045031
Builders FirstSource (Lake City, FL), Lake City, FL - 32055,						8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:40 2021 Page 1
ID:krMvx1mH9U?w6?cKU0X49yy8lb-lxrRroDtErec_RMeX4rjhsjW3ixF?4aVv19FDAYnCTb						Job Reference (optional)

-1-6-0 1-6-0	7-8-0 7-8-0	15-10-0 8-2-0	22-8-0 6-10-0	28-8-0 6-0-0	32-11-13 4-3-13	37-8-0 4-8-3	39-2-0 1-6-0
-----------------	----------------	------------------	------------------	-----------------	--------------------	-----------------	-----------------

Scale = 1:75.3





Plate Offsets (X,Y)--		[3:0-4-0,0-3-0], [6:0-3-12,0-2-0], [8:0-6-0,0-0-3]									
LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP		
TCLL 20.0	Plate Grip DOL	1.25	TC 0.74	Vert(LL)	-0.13 14-16	>999	240	MT20	244/190		
TCDL 7.0	Lumber DOL	1.25	BC 0.72	Vert(CT)	-0.24 14-16	>999	180				
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.48	Horz(CT)	0.06 10	n/a	n/a				
BCDL 10.0	Code FBC2020/TPI2014		Matrix-MS								
										Weight: 221 lb	FT = 20%

LUMBER-	BRACING-		
TOP CHORD 2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 2-2-0 oc purlins.	
BOT CHORD 2x4 SP No.2	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing, Except:	
WEBS 2x4 SP No.3	WEBS	6-0-0 oc bracing: 8-10. 1 Row at midpt 3-14, 5-14, 5-11, 6-10	

REACTIONS.	(size) 2=0-8-0, 10=0-8-0, 8=0-3-8		
	Max Horz 2=-255(LC 10)		
	Max Uplift 2=-248(LC 12), 10=-359(LC 13), 8=-132(LC 10)		
	Max Grav 2=1325(LC 19), 10=1934(LC 2), 8=99(LC 24)		

FORCES.	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.		
TOP CHORD	2-3=-1816/310, 3-4=-1142/289, 4-5=-1146/296, 6-7=-75/674, 7-8=-100/576		
BOT CHORD	2-16=-306/1617, 14-16=-305/1622, 13-14=-81/1115, 11-13=-80/1122, 8-10=-400/120		
WEBS	3-16=0/376, 3-14=-778/299, 4-14=-149/829, 5-14=-343/200, 5-13=0/307, 5-11=-1307/227, 6-11=-125/1047, 6-10=-1711/254, 7-10=-255/167		

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2E) -1-6-0 to 2-3-3, Interior(1) 2-3-3 to 15-10-0, Exterior(2R) 15-10-0 to 19-7-3, Interior(1) 19-7-3 to 28-8-0, Exterior(2R) 28-8-0 to 32-5-3, Interior(1) 32-5-3 to 39-2-0 zone; porch right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
 - 4) Provide adequate drainage to prevent water ponding.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=248, 10=359, 8=132.



Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17,2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.
Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.
Tampa, FL 33610

Job 2874271	Truss T19	Truss Type Roof Special	Qty 1	Ply 1	EXCEPTIONS REALITY - LOT 10 CRP	T25045032
Builders FirstSource (Lake City, FL), Lake City, FL - 32055,						8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:41 2021 Page 1
ID:krMvx1mH9U?wf6?cKU0X49yy8lb-E8Pp28EV?9mTcbxq5nMyD3Ght6G2kVZe8hvoldynCTa						Job Reference (optional)

1-6-0	7-8-0	15-10-0	20-8-0	26-8-0	31-4-0	37-8-0	39-2-0
1-6-0	7-8-0	8-2-0	4-10-0	6-0-0	4-8-0	6-4-0	1-6-0

5x6 =

Scale = 1:78.7




Plate Offsets (X,Y)-- [3:0-4-0,0-3-0], [6:0-4-4,0-2-4], [8:0-2-3,Edge]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.74	Vert(LL)	0.09 10-22	>870	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.75	Vert(CT)	-0.27 14-16	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.63	Horz(CT)	0.05 10	n/a	n/a		
BCDL 10.0	Code FBC2020/TPI2014		Matrix-MS					Weight: 227 lb	FT = 20%


LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 1 Row at midpt 3-14, 5-14, 5-11

REACTIONS. (size) 2=0-8-0, 10=0-8-0, 8=0-3-8
Max Horz 2=-255(LC 10)
Max Uplift 2=-253(LC 12), 10=-320(LC 13), 8=-127(LC 10)
Max Grav 2=1351(LC 19), 10=1898(LC 2), 8=152(LC 24)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1863/328, 3-4=-1188/308, 4-5=-1151/327, 5-6=-516/224, 6-7=-688/226,
7-8=-84/583
BOT CHORD 2-16=-312/1657, 14-16=-311/1661, 13-14=-85/1150, 11-13=-85/1155, 10-11=-389/115,
8-10=-389/115
WEBS 3-16=0/383, 3-14=-785/299, 4-14=-199/912, 5-14=-417/216, 5-13=0/279, 5-11=-995/174,
7-11=-123/1240, 7-10=-1659/331

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2E) -1-6-0 to 2-3-3, Interior(1) 2-3-3 to 15-10-0, Exterior(2R) 15-10-0 to 19-7-3, Interior(1) 19-7-3 to 26-8-0, Exterior(2R) 26-8-0 to 30-5-3, Interior(1) 30-5-3 to 39-2-0 zone; porch right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=253, 10=320, 8=127.



Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17, 2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




6904 Parke East Blvd.
Tampa, FL 36610

Job 2874271	Truss T20	Truss Type Roof Special	Qty 1	Ply 1	EXCEPTIONS REALITY - LOT 10 CRP	T25045033
Builders FirstSource (Lake City, FL), Lake City, FL - 32055, 8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:42 2021 Page 1						

ID:krMvx1mH9U?w6?cKU0X49yy8lb-iKzBGTf7mSuKDIW0eVtBmHosmVaqTyJoMLeMH3ynCTZ

Scale = 1:78.7




LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.73	Vert(LL)	0.09 11-22	>864	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.85	Vert(CT)	-0.38 13-14	>995	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.59	Horz(CT)	0.05 11	n/a	n/a		
BCDL 10.0	Code FBC2020/TPI2014		Matrix-MS					Weight: 223 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3	WEBS 1 Row at midpt 3-14, 5-14, 5-13

REACTIONS. (size) 2=0-8-0, 11=0-8-0, 9=0-3-8
Max Horz 2=-255(LC 10)
Max Uplift 2=-254(LC 12), 11=-325(LC 13), 9=-110(LC 8)
Max Grav 2=1364(LC 19), 11=1820(LC 2), 9=182(LC 24)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1880/331, 3-4=-1223/303, 4-5=-1146/340, 5-6=-688/258, 6-8=-916/249, 8-9=-71/462
BOT CHORD 2-16=-314/1671, 14-16=-313/1675, 13-14=-106/1090, 11-13=-285/110, 9-11=-285/110
WEBS 3-16=0/355, 3-14=-764/300, 4-14=-231/978, 5-14=-370/232, 5-13=-654/154, 6-13=-20/254, 8-13=-110/1192, 8-11=-1576/349

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2E) -1-6-0 to 2-3-3, Interior(1) 2-3-3 to 15-10-0, Exterior(2E) 15-10-0 to 18-8-0, Interior(1) 18-8-0 to 24-8-0, Exterior(2R) 24-8-0 to 28-5-3, Interior(1) 28-5-3 to 39-2-0 zone; porch right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=254, 11=325, 9=110.



Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17, 2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component




6904 Parke East Blvd.
Tampa, FL 33610

Job 2874271	Truss T21	Truss Type Hip	Qty 1	Ply 1	EXCEPTIONS REALITY - LOT 10 CRP T25045034
----------------	--------------	-------------------	----------	----------	--

Builders FirstSource (Lake City, FL), Lake City, FL - 32055,

8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:43 2021 Page 1

ID:krMvx1mH9U?w6?cKU0X49yy8lb-AWXZTpGIXm0Bru5DCCOQIUL0uvx1CMzxb?OvqVynCTY



Scale = 1:70.2




Plate Offsets (X,Y)-- [3:0-3-0,0-3-4], [4:0-4-4,0-2-4], [5:0-6-4,0-2-4], [6:0-4-0,0-3-0], [7:0-2-3,Edge]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.83	Vert(LL)	0.09 9-20	>859	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.78	Vert(CT)	-0.32 12-14	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.82	Horz(CT)	0.05 9	n/a	n/a		
BCDL 10.0	Code FBC2020/TPI2014		Matrix-MS					Weight: 215 lb	FT = 20%


LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3 *Except*
5-12: 2x4 SP No.2

BRACING-
TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 1 Row at midpt 3-12, 5-11

REACTIONS. (size) 2=0-8-0, 9=0-8-0, 7=0-3-8
Max Horz 2=-243(LC 10)
Max Uplift 2=-283(LC 12), 9=-241(LC 13), 7=-122(LC 8)
Max Grav 2=1339(LC 19), 9=1770(LC 2), 7=246(LC 24)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1917/364, 3-4=-1284/315, 4-5=-990/323, 5-6=-1037/272, 6-7=-26/370
BOT CHORD 2-14=-340/1664, 12-14=-348/1581, 11-12=-84/777
WEBS 3-14=0/373, 3-12=-673/284, 4-12=-55/385, 5-12=-144/433, 6-11=-107/758, 6-9=-1467/275

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2E) -1-6-0 to 2-3-3, Interior(1) 2-3-3 to 15-0-0, Exterior(2R) 15-0-0 to 20-3-15, Interior(1) 20-3-15 to 22-8-0, Exterior(2R) 22-8-0 to 27-11-15, Interior(1) 27-11-15 to 39-2-0 zone; porch right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=283, 9=241, 7=122.



Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17,2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.
Tampa, FL 33610

Job 2874271	Truss T22	Truss Type Piggyback Base	Qty 7	Ply 1	EXCEPTIONS REALITY - LOT 10 CRP T25045035
----------------	--------------	------------------------------	----------	----------	--

Builders FirstSource (Lake City, FL), Lake City, FL - 32055,

8.430 s Jun 2 2021 MiTek Industries, Inc. Mon Aug 16 17:28:44 2021 Page 1

ID:krMvx1mH9U?wf6?cKU0X49yy8lb-ej5yg9GNI482T2gPmvvfrui9CJHGxpD5qf7SMxynCTX

Job Reference (optional)

1-6-0 1-6-0	7-8-0 7-8-0	15-0-0 7-4-0	22-8-0 7-8-0	30-0-0 7-4-0	37-8-0 7-8-0	39-2-0 1-6-0
----------------	----------------	-----------------	-----------------	-----------------	-----------------	-----------------

Scale = 1:70.2




Plate Offsets (X,Y)-- [3:0-3-0,0-3-4], [4:0-4-4,0-2-4], [5:0-6-4,0-2-4], [6:0-4-0,0-3-0], [7:0-2-3,Edge]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.25	TC 0.92	Vert(LL)	0.09 9-20	>859	240	MT20	244/190
TCDL 7.0	Lumber DOL	1.25	BC 0.78	Vert(CT)	-0.32 12-14	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.82	Horz(CT)	0.05 9	n/a	n/a		
BCDL 10.0	Code FBC2020/TPI2014		Matrix-MS					Weight: 215 lb	FT = 20%


LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3 *Except*
5-12: 2x4 SP No.2

BRACING-
TOP CHORD Structural wood sheathing directly applied or 3-10-6 oc purlins, except
2-0-0 oc purlins (2-2-0 max.): 4-5.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 1 Row at midpt 3-12, 5-11

REACTIONS. (size) 2=0-8-0, 9=0-8-0, 7=0-3-8
Max Horz 2=-243(LC 10)
Max Uplift 2=-283(LC 12), 9=-241(LC 13), 7=-122(LC 8)
Max Grav 2=1339(LC 19), 9=1770(LC 2), 7=246(LC 24)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1917/364, 3-4=-1284/315, 4-5=-990/323, 5-6=-1037/272, 6-7=-26/370
BOT CHORD 2-14=-340/1664, 12-14=-348/1581, 11-12=-84/777
WEBS 3-14=0/373, 3-12=-673/284, 4-12=-55/385, 5-12=-144/433, 6-11=-107/758, 6-9=-1467/275

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=101mph; TCDL=4.2psf; BCDL=3.0psf; h=20ft; Cat. II; Exp B; Encl., GCpi=0.18; MWFRS (envelope) gable end zone and C-C Exterior(2E) -1-6-0 to 2-3-3, Interior(1) 2-3-3 to 15-0-0, Exterior(2R) 15-0-0 to 20-3-15, Interior(1) 20-3-15 to 22-8-0, Exterior(2R) 22-8-0 to 27-11-15, Interior(1) 27-11-15 to 39-2-0 zone; porch right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Building Designer / Project engineer responsible for verifying applied roof live load shown covers rain loading requirements specific to the use of this truss component.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=283, 9=241, 7=122.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



Philip J. O'Regan PE No.58126
MiTek USA, Inc. FL Cert 6634
6904 Parke East Blvd. Tampa FL 33610
Date:

August 17,2021

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component



Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



6904 Parke East Blvd.
Tampa, FL 33610

Symbols

PLATE LOCATION AND ORIENTATION




For 4 x 2 orientation, locate plates 0- 3/16" from outside edge of truss.

This symbol indicates the required direction of slots in connector plates.


PLATE SIZE

The first dimension is the plate width measured perpendicular to slots. Second dimension is the length parallel to slots.

LATERAL BRACING LOCATION




BEARING



Industry Standards:
ANSI/TP1.1: National Design Specification for Metal Plate Connected Wood Truss Construction.
DSB-89: Building Component Safety Information, Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses.

Numbering System



JOINTS ARE GENERALLY NUMBERED/LETTERED CLOCKWISE AROUND THE TRUSS STARTING AT THE JOINT FARTHEST TO THE LEFT.

CHORDS AND WEBS ARE IDENTIFIED BY END JOINT NUMBERS/LETTERS.

PRODUCT CODE APPROVALS

ICC-ES Reports:
ESR-1311, ESR-1352, ESR1988
ER-3907, ESR-2362, ESR-1397, ESR-3282

Trusses are designed for wind loads in the plane of the truss unless otherwise shown.

Lumber design values are in accordance with ANSI/TP1 1 section 6.3 These truss designs rely on lumber values established by others.

© 2012 MITek® All Rights Reserved



Mitek Engineering Reference Sheet: MII-7473 rev. 5/19/2020

General Safety Notes

Failure to Follow Could Cause Property Damage or Personal Injury

1. Additional stability bracing for truss system, e.g. diagonal or X-bracing, is always required. See BCSI.
2. Truss bracing must be designed by an engineer. For wide truss spacing, individual lateral braces themselves may require bracing, or alternative T or I bracing should be considered.
3. Never exceed the design loading shown and never stack materials on inadequately braced trusses.
4. Provide copies of this truss design to the building designer, erection supervisor, property owner and all other interested parties.
5. Cut members to bear tightly against each other.
6. Place plates on each face of truss at each joint and embed fully. Knots and wane at joint locations are regulated by ANSI/TP1 1.
7. Design assumes trusses will be suitably protected from the environment in accord with ANSI/TP1 1.
8. Unless otherwise noted, moisture content of lumber shall not exceed 19% at time of fabrication.
9. Unless expressly noted, this design is not applicable for use with fire retardant, preservative treated, or green lumber.
10. Camber is a non-structural consideration and is the responsibility of truss fabricator. General practice is to camber for dead load deflection.
11. Plate type, size, orientation and location dimensions indicated are minimum plating requirements.
12. Lumber used shall be of the species and size, and in all respects, equal to or better than that specified.
13. Top chords must be sheathed or purlins provided at spacing indicated on design.
14. Bottom chords require lateral bracing at 10 ft. spacing, or less, if no ceiling is installed, unless otherwise noted.
15. Connections not shown are the responsibility of others.
16. Do not cut or alter truss member or plate without prior approval of an engineer.
17. Install and load vertically unless indicated otherwise.
18. Use of green or treated lumber may pose unacceptable environmental, health or performance risks. Consult with project engineer before use.
19. Review all portions of this design (front, back, words and pictures) before use. Reviewing pictures alone is not sufficient.
20. Design assumes manufacture in accordance with ANSI/TP1 1 Quality Criteria.
21. The design does not take into account any dynamic or other loads other than those expressly stated.