



This document has been electronically signed and sealed using a Digital Signature. Printed copies without an original signature must be verified using the original electronic version.



COA #0 278
06/25/2020

Alpine, an ITW Company
6750 Forum Drive, Suite 305
Orlando, FL 32821
Phone: (800)755-6001
www.alpineitw.com


73

Site Information:	Page 1:
Customer: Seminole Trusses, Inc.	Job Number: B51561a
Job Description: -KRAMER RESIDENCE America's Home Place	
Address: COLONEY DR., LAKE CITY, FL 32024	

Job Engineering Criteria:			
Design Code: FBC 2017 RES		IntelliVIEW Version: 18.02.01A	
		JRef #: 1WWf8570002	
Wind Standard: ASCE 7-10	Wind Speed (mph): 130	Roof Load (psf): 20.00- 7.00- 0.00-10.00	
Building Type: Closed		Floor Load (psf): None	

This package contains general notes pages, 10 truss drawing(s) and 7 detail(s).

Item	Drawing Number	Truss	Item	Drawing Number	Truss
1	177.20.1023.09570	A1-G 54' Gable	2	177.20.1023.10997	A2a 54' Common
3	177.20.1023.12117	A2b 54' Common	4	177.20.1023.13263	A2c 54' Common
5	177.20.1023.14340	B1-G 13' Gable	6	177.20.1023.16737	B2 13' Common Girder
7	177.20.1023.43033	V1-G 26'2"8 Valley	8	177.20.1023.57700	V2-G 18'0"8 Valley
9	177.20.1023.39290	PB1-G 18' Gable	10	177.20.1023.41797	PB2 18' Common
11	A14015ENC101014		12	GBLLETIN0118	
13	PB160160118		14	PB180160118	
15	REPCHRD1014		16	CNNAILSP1014	
17	A14030ENC101014				



General Notes

Truss Design Engineer Scope of Work, Design Assumptions and Design Responsibilities:

The design responsibilities assumed in the preparation of these design drawings are those specified in ANSI/TPI 1, Chapter 2; and the National Design Standard for Metal Plate Connected Wood Truss Construction, by the Truss Plate Institute. The truss component designs conform to the applicable provisions of ANSI/TPI 1 and NDS, the National Design Specification for Wood Construction by AWC. The truss component designs are based on the specified loading and dimension information furnished by others to the Truss Design Engineer. The Truss Design Engineer has no duty to independently verify the accuracy or completeness of the information provided by others and may rely on that information without liability. The responsibility for verification of that information remains with others neither employed nor controlled by the Truss Design Engineer. The Truss Design Engineer's seal and signature on the attached drawings, or cover page listing these drawings, indicates acceptance of professional engineering responsibility solely for the truss component designs and not for the technical information furnished by others which technical information and consequences thereof remain their sole responsibility.

The suitability and use of these drawings for any particular structure is the responsibility of the Building Designer in accordance with ANSI/TPI 1 Chapter 2. The Building Designer is responsible for determining that the dimensions and loads for each truss component match those required by the plans and by the actual use of the individual component, and for ascertaining that the loads shown on the drawings meet or exceed applicable building code requirements and any additional factors required in the particular application. Truss components using metal connector plates with integral teeth shall not be placed in environments that will cause the moisture content of the wood in which plates are embedded to exceed 19% and/or cause corrosion of connector plates and other metal fasteners.

The Truss Design Engineer shall not be responsible for items beyond the specific scope of the agreed contracted work set forth herein, including but not limited to: verifying the dimensions of the truss component, calculation of any of the truss component design loads, inspection of the truss components before or after installation, the design of temporary or permanent bracing and their attachment required in the roof and/or floor systems, the design of diaphragms or shear walls, the design of load transfer connections to and from diaphragms and shear walls, the design of load transfer to the foundation, the design of connections for truss components to their bearing supports, the design of the bearing supports, installation of the truss components, observation of the truss component installation process, review of truss assembly procedures, sequencing of the truss component installation, construction means and methods, site and/or worker safety in the installation of the truss components and/or its connections.

This document may be a high quality facsimile of the original engineering document which is a digitally signed electronic file with third party authentication. A wet or embossed seal copy of this engineering document is available upon request.

Temporary Lateral Restraint and Bracing:

Temporary lateral restraint and diagonal bracing shall be installed according to the provisions of BCSI chapters B1, B2, B7 and/or B10 (Building Component Safety Information, by TPI and SBCA), or as specified by the Building Designer or other Registered Design Professional. The required locations for lateral restraint and/or bracing depicted on these drawings are only for the permanent lateral support of the truss members to reduce buckling lengths, and do not apply to and may not be relied upon for the temporary stability of the truss components during their installation.

Permanent Lateral Restraint and Bracing:

The required locations for lateral restraint or bracing depicted on these drawings are for the permanent lateral support of the truss members to reduce buckling lengths. Permanent lateral support shall be installed according to the provisions of BCSI chapters B3, B7 and/or B10, or as specified by the Building Designer or other Registered Design Professional. These drawings do not depict or specify installation/erection bracing, wind bracing, portal bracing or similar building stability bracing which are parts of the overall building design to be specified, designed and detailed by the Building Designer.

Connector Plate Information:

Alpine connector plates are made of ASTM A653 or ASTM A1063 galvanized steel with the following designations, gauges and grades: W=Wave, 20ga, grade 40; H=High Strength, 20ga, grade 60; S=Super Strength, 18ga, grade 60. Information on model code compliance is contained in the ICC Evaluation Service report ESR-1118, available on-line at www.icc-es.org.

Fire Retardant Treated Lumber:

Fire retardant treated lumber must be properly re-dried and maintained below 19% or less moisture level through all stages of construction and usage. Fire retardant treated lumber may be more brittle than untreated lumber. Special handling care must be taken to prevent breakage during all handling activities.

General Notes (continued)

Key to Terms:

Information provided on drawings reflects a summary of the pertinent information required for the truss design. Detailed information on load cases, reactions, member lengths, forces and members requiring permanent lateral support may be found in calculation sheets available upon written request.

BCDL = Bottom Chord standard design Dead Load in pounds per square foot.

BCLL = Bottom Chord standard design Live Load in pounds per square foot.

CL = Certified lumber.

Des Ld = total of TCLL, TCDL, BCLL and BCDL Design Load in pounds per square foot.

FRT = Fire Retardant Treated lumber.

FRT-DB = D-Blaze Fire Retardant Treated lumber.

FRT-DC = Dricon Fire Retardant Treated lumber.

FRT-FP = FirePRO Fire Retardant Treated lumber.

FRT-FL = FlamePRO Fire Retardant Treated lumber.

FRT-FT = FlameTech Fire Retardant Treated lumber.

FRT-PG = PYRO-GUARD Fire Retardant Treated lumber.

g = green lumber.

HORZ(LL) = maximum Horizontal panel point deflection due to Live Load, in inches.

HORZ(TL) = maximum Horizontal panel point long term deflection in inches, due to Total Load, including creep adjustment.

HPL = additional Horizontal Load added to a truss Piece in pounds per linear foot or pounds.

Ic = Incised lumber.

FJ = Finger Jointed lumber.

L/# = user specified divisor for limiting span/deflection ratio for evaluation of actual L/defl value.

L/defl = ratio of Length between bearings, in inches, divided by the vertical Deflection due to creep, in inches, at the referenced panel point. Reported as 999 if greater than or equal to 999.

Loc = Location, starting location of left end of bearing or panel point (joint) location of deflection.

Max BC CSI = Maximum bending and axial Combined Stress Index for Bottom Chords for of all load cases.

Max TC CSI = Maximum bending and axial Combined Stress Index for Top Chords for of all load cases.

Max Web CSI = Maximum bending and axial Combined Stress Index for Webs for of all load cases.

NCBCLL = Non-Concurrent Bottom Chord design Live Load in pounds per square foot.

PL = additional Load applied at a user specified angle on a truss Piece in pounds per linear foot or pounds.

PLB = additional vertical load added to a Bottom chord Piece of a truss in pounds per linear foot or pounds

PLT = additional vertical load added to a Top chord Piece of a truss in pounds per linear foot or pounds.

PP = Panel Point.

R = maximum downward design Reaction, in pounds, from all specified gravity load cases, at the indicated location (Loc).

-R = maximum upward design Reaction, in pounds, from all specified gravity load cases, at the identified location (Loc).

Rh = maximum horizontal design Reaction in either direction, in pounds, from all specified gravity load cases, at the indicated location (Loc).

RL = maximum horizontal design Reaction in either direction, in pounds, from all specified non-gravity (wind or seismic) load cases, at the indicated location (Loc).

Rw = maximum downward design Reaction, in pounds, from all specified non-gravity (wind or seismic) load cases, at the identified location (Loc).

TCDL = Top Chord standard design Dead Load in pounds per square foot.

TCLL = Top Chord standard design Live Load in pounds per square foot.

U = maximum Upward design reaction, in pounds, from all specified non-gravity (wind or seismic) load cases, at the indicated location (Loc).

VERT(CL) = maximum Vertical panel point deflection in inches due to Live Load and Creep Component of Dead Load in inches.

VERT(CTL) = maximum Vertical panel point deflection ratios due to Live Load and Creep Component of Dead Load, and maximum long term Vertical panel point deflection in inches due to Total load, including creep adjustment.

VERT(LL) = maximum Vertical panel point deflection in inches due to Live Load.

VERT(TL) = maximum Vertical panel point long term deflection in inches due to Total load, including creep adjustment.

W = Width of non-hanger bearing, in inches.


Refer to ASCE-7 for Wind and Seismic abbreviations.

Uppercase Acronyms not explained above are as defined in TPI 1.

References:

1. AWC: American Wood Council; 222 Catoctin Circle SE, Suite 201; Leesburg, VA 20175; www.awc.org.
2. ICC: International Code Council; www.iccsafe.org.
3. Alpine, a division of ITW Building Components Group Inc.: 13723 Riverport Drive, Suite 200, Maryland Heights, MO 63043; www.alpineitw.com.
4. TPI: Truss Plate Institute, 2670 Crain Highway, Suite 203, Waldorf, MD 20601; www.tpinst.org.
5. SBCA: Wood Truss Council of America, 6300 Enterprise Lane, Madison, WI 53719; www.sbcindustry.com.

SEQN: 973046 FROM: RJL	GABL Ply: 1 Qty: 2	Job Number: B51561a -KRAMER RESIDENCE America's Home Place Truss Label: A1-G 54' Gable	Cust: R 857 JRef: 1WWF8570002 T2 DrwNo: 177.20.1023.09570 SSB / DF 06/25/2020
---------------------------	--------------------------	--	---



Loading Criteria (psf)	Wind Criteria	Snow Criteria (Pg, Pf in PSF)	Defl/CSI Criteria	▲ Maximum Reactions (lbs), or *PLF
TCLL: 20.00 TCDL: 7.00 BCLL: 0.00 BCDL: 10.00 Des Ld: 37.00 NCBCLL: 10.00 Soffit: 0.00 Load Duration: 1.25 Spacing: 24.0"	Wind Std: ASCE 7-10 Speed: 130 mph Enclosure: Closed Risk Category: II EXP: B Kzt: NA Mean Height: 15.00 ft TCDL: 4.2 psf BCDL: 5.2 psf MWFRS Parallel Dist: 0 to h/2 C&C Dist a: 5.40 ft Loc. from endwall: Any GCpi: 0.18 Wind Duration: 1.60	Pg: NA Ct: NA CAT: NA Pf: NA Ce: NA Lu: NA Cs: NA Snow Duration: NA Building Code: FBC 2017 RES TPI Std: 2014 Rep Fac: No FT/RT:20(0)/10(0) Plate Type(s): WAVE, HS	PP Deflection in loc L/defl L/# VERT(LL): 0.002 W 999 360 VERT(CL): 0.006 W 999 240 HORZ(LL): 0.004 AD - - HORZ(TL): 0.007 Z - - Creep Factor: 2.0 Max TC CSI: 0.140 Max BC CSI: 0.058 Max Web CSI: 0.108 VIEW Ver: 18.02.01A.0205.19	Gravity Non-Gravity Loc R+ / R- / Rh / Rw / U / RL AG*114 /- /- /39 /7 /5 Wind reactions based on MWFRS AG Brg Width = 648 Min Req = - Bearing B is a rigid surface. Members not listed have forces less than 375#

Lumber

Top chord: 2x4 SP #1; T3,T4 2x6 SP #1;
Bot chord: 2x4 SP #1;
Webs: 2x4 SP #1;

Bracing

(a) 1x4 #3SRB SPF-S or better "L" reinforcement.
80% length of web member. Attach with 8d Box or
Gun (0.113"x2.5", min.) nails @ 6" oc.

Plating Notes

All plates are 2X4 except as noted.

Loading

Truss designed to support 1-0-0 top chord outlookers
and cladding load not to exceed 5.00 PSF one face
and 24.0" span opposite face. Top chord must not be
cut or notched, unless specified otherwise.


Wind

Wind loads based on MWFRS with additional C&C
member design.

Additional Notes

See DWGS A14015ENC101014 & GBLLETIN0118 for
gable wind bracing and other requirements.

WARNING: Furnish a copy of this DWG to the
installation contractor. Special care must be taken
during handling, shipping and installation of trusses.
See "WARNING" note below.



COA #0298
06/25/2020

****WARNING**** READ AND FOLLOW ALL NOTES ON THIS DRAWING!
****IMPORTANT**** FURNISH THIS DRAWING TO ALL CONTRACTORS INCLUDING THE INSTALLERS


Trusses require extreme care in fabricating, handling, shipping, installing and bracing. Refer to and follow the latest edition of BCSI (Building Component Safety Information, by TPI and SBCEA) for safety practices prior to performing these functions. Installers shall provide temporary bracing per BCSI. Unless noted otherwise, top chord shall have properly attached structural sheathing and bottom chord shall have a properly attached rigid ceiling. Locations shown for permanent lateral restraint of webs shall have bracing installed per BCSI sections B3, B7, or B10, as applicable. Apply plates to each face of truss and position as shown above and on the Joint Details, unless noted otherwise. Refer to drawings 160A-Z for standard plate positions. Refer to job's General Notes page for additional information.

Alpine, a division of ITW Building Components Group Inc. shall not be responsible for any deviation from this drawing, any failure to build the truss in conformance with ANSI/TPI 1, or for handling, shipping, installation and bracing of trusses. A seal on this drawing or cover page listing this drawing, indicates acceptance of professional engineering responsibility solely for the design shown. The suitability and use of this drawing for any structure is the responsibility of the Building Designer per ANSI/TPI 1 Sec.2.

For more information see these web sites: Alpine: www.alpineitw.com; TPI: www.tpinet.org; SBCEA: www.sbcindustry.com; ICC: www.iccsafe.org

ALPINE
AN ITW COMPANY
6750 Forum Drive
Suite 305
Orlando FL, 32821

SEQN: 973047 FROM: RJL	COMN Ply: 1 Qty: 19	Job Number: B51561a -KRAMER RESIDENCE America's Home Place Truss Label: A2a 54' Common	Cust: R 857 JRef: 1WW8570002 T12 DrwNo: 177.20.1023.10997 SSB / DF 06/25/2020
---------------------------	------------------------	--	---



Loading Criteria (psf)	Wind Criteria	Snow Criteria (Pg, Pf in PSF)	Defl/CSI Criteria	Maximum Reactions (lbs)
TCLL: 20.00 TCDL: 7.00 BCLL: 0.00 BCDL: 10.00 Des Ld: 37.00 NCBCLL: 10.00 Soffit: 0.00 Load Duration: 1.25 Spacing: 24.0 "	Wind Std: ASCE 7-10 Speed: 130 mph Enclosure: Closed Risk Category: II EXP: B Kzt: NA Mean Height: 15.00 ft TCDL: 4.2 psf BCDL: 5.2 psf MWFRS Parallel Dist: h to 2h C&C Dist a: 5.40 ft Loc. from endwall: not in 13.00 ft GCpi: 0.18 Wind Duration: 1.60	Pg: NA Ct: NA CAT: NA Pf: NA Ce: NA Lu: NA Cs: NA Snow Duration: NA Building Code: FBC 2017 RES TPI Std: 2014 Rep Fac: No FT/RT: 20(0)/10(0) Plate Type(s): WAVE, HS	PP Deflection in loc L/defl L/# VERT(LL): 0.311 F 999 360 VERT(CL): 0.514 F 999 240 HORZ(LL): 0.147 M - - HORZ(TL): 0.243 M - - Creep Factor: 2.0 Max TC CSI: 0.920 Max BC CSI: 0.765 Max Web CSI: 0.407 VIEW Ver: 18.02.01A.0205.19	Gravity Non-Gravity Loc R+ / R- / Rh / Rw / U / RL B 2539 /- /- /1144 /- /235 K 2540 /- /- /1144 /- /- Wind reactions based on MWFRS B Brg Width = 3.5 Min Req = 2.6 K Brg Width = - Min Req = - Bearing B is a rigid surface. Members not listed have forces less than 375# Maximum Top Chord Forces Per Ply (lbs) Chords Tens.Comp. Chords Tens. Comp. B - C 603 -4191 G - H 595 -3102 C - D 665 -4045 H - I 632 -3621 D - E 632 -3620 I - J 666 -4047 E - F 595 -3102 J - K 604 -4193 F - G 595 -3102

Lumber
Top chord: 2x4 SP SS Dense; T2, T5 2x4 SP #1; T3, T4 2x6 SP #1;
Bot chord: 2x4 SP SS Dense; B3 2x8 SP SS Dense;
Webs: 2x4 SP #1;
Lt Wedge: 2x4 SP #3; Rt Wedge: 2x4 SP #3;

Bracing

(a) Continuous lateral restraint equally spaced on member. Or 1x4 #3SRB SPF-S or better "T" reinforcement. 80% length of web member. Attached with 8d Box or Gun (0.113"x2.5", min.) nails @ 6" oc.
(b) Continuous lateral restraint equally spaced on member. Or 2x6 #3 or better "T" reinforcement. 80% length of web member. Attached with 10d Box or Gun (0.128"x3", min.) nails @ 6" oc.

Hangers / Ties

(J) Hanger Support Required, by others

Loading

Truss passed check for 20 psf additional bottom chord live load in areas with 42"-high x 24"-wide clearance.

Purlins


In lieu of structural panels use purlins to brace all flat TC @ 24" oc.

Wind

Wind loads based on MWFRS with additional C&C member design.

Additional Notes

WARNING: Furnish a copy of this DWG to the installation contractor. Special care must be taken during handling, shipping and installation of trusses. See "WARNING" note below.



COA #0 248
06/25/2020

Maximum Bot Chord Forces Per Ply (lbs)

Chords	Tens.Comp.	Chords	Tens. Comp.
B - T	3494 -412	P - O	2907 -281
T - S	3362 -383	O - N	3363 -404
S - R	3362 -383	N - M	3363 -404
R - Q	2907 -272	M - K	3496 -425
Q - P	3256 -346		

Maximum Web Forces Per Ply (lbs)

Webs	Tens.Comp.	Webs	Tens. Comp.
D - R	159 -488	P - H	721 -63
R - E	622 -90	H - O	623 -89
E - Q	722 -63	O - I	159 -489

****WARNING**** READ AND FOLLOW ALL NOTES ON THIS DRAWING!
****IMPORTANT**** FURNISH THIS DRAWING TO ALL CONTRACTORS INCLUDING THE INSTALLERS


Trusses require extreme care in fabricating, handling, shipping, installing and bracing. Refer to and follow the latest edition of BCSI (Building Component Safety Information, by TPI and SBCE) for safety practices prior to performing these functions. Installers shall provide temporary bracing per BCSI. Unless noted otherwise, top chord shall have properly attached structural sheathing and bottom chord shall have a properly attached rigid ceiling. Locations shown for permanent lateral restraint of webs shall have bracing installed per BCSI sections B3, B7, or B10, as applicable. Apply plates to each face of truss and position as shown above and on the Joint Details, unless noted otherwise. Refer to drawings 160A-Z for standard plate positions. Refer to job's General Notes page for additional information.

Alpine, a division of ITW Building Components Group Inc, shall not be responsible for any deviation from this drawing, any failure to build the truss in conformance with ANSI/TPI 1, or for handling, shipping, installation and bracing of trusses. A seal on this drawing or cover page listing this drawing, indicates acceptance of professional engineering responsibility solely for the design shown. The suitability and use of this drawing for any structure is the responsibility of the Building Designer per ANSI/TPI 1 Sec.2.

For more information see these web sites: Alpine: www.alpineitw.com; TPI: www.tpinet.org; SBCE: www.sbceindustry.com; ICC: www.iccsafe.org

ALPINE
AN ITW COMPANY
6750 Forum Drive
Suite 305
Orlando FL, 32821

SEQN: 973048 FROM: RJL	COMN Qty: 1	Ply: 1 Job Number: B51561a -KRAMER RESIDENCE America's Home Place Truss Label: A2b 54' Common	Cust: R 857 JRef: 1WWF8570002 T8 DrwNo: 177.20.1023.12117 SSB / DF 06/25/2020
---------------------------	----------------	--	---



Loading Criteria (psf)	Wind Criteria	Snow Criteria (Pg, Pf in PSF)	Defl/CSI Criteria	Maximum Reactions (lbs)
TCLL: 20.00 TCDL: 7.00 BCLL: 0.00 BCDL: 10.00 Des Ld: 37.00 NCBCLL: 10.00 Soffit: 0.00 Load Duration: 1.25 Spacing: 24.0 "	Wind Std: ASCE 7-10 Speed: 130 mph Enclosure: Closed Risk Category: II EXP: B Kzt: NA Mean Height: 15.00 ft TCDL: 4.2 psf BCDL: 5.2 psf MWFRS Parallel Dist: h to 2h C&C Dist a: 5.40 ft Loc. from endwall: not in 13.00 ft GCpi: 0.18 Wind Duration: 1.60	Pg: NA Ct: NA CAT: NA Pf: NA Ce: NA Lu: NA Cs: NA Snow Duration: NA Building Code: FBC 2017 RES TPI Std: 2014 Rep Fac: No FT/RT: 20(0)/10(0) Plate Type(s): WAVE, HS	PP Deflection in loc L/defl L/# VERT(LL): 0.159 O 999 360 VERT(CL): 0.267 O 999 240 HORZ(LL): 0.060 M - - HORZ(TL): 0.101 M - - Creep Factor: 2.0 Max TC CSI: 0.801 Max BC CSI: 0.728 Max Web CSI: 0.977 VIEW Ver: 18.02.01A.0205.19	Gravity Non-Gravity Loc R+ / R- / Rh / Rw / U / RL B 348 / -49 / - / 164 / 1 / 235 T 2761 / - / - / 1201 / - / - K 1928 / - / - / 959 / - / - Wind reactions based on MWFRS B Brg Width = 3.5 Min Req = 1.5 T Brg Width = 3.5 Min Req = 2.4 K Brg Width = 3.5 Min Req = 1.9 Bearings B, T, & K are a rigid surface. Members not listed have forces less than 375# Maximum Top Chord Forces Per Ply (lbs) Chords Tens.Comp. Chords Tens. Comp.

Lumber
Top chord: 2x4 SP #1; T3, T4 2x6 SP #1;
Bot chord: 2x4 SP SS Dense; B2, B4 2x4 SP #1;
B3 2x8 SP SS Dense;
Webs: 2x4 SP #1;
Lt Wedge: 2x4 SP #3; Rt Wedge: 2x4 SP #3;

Bracing
(c) Continuous lateral restraint equally spaced on member. Or 1x4 #3SRB SPF-S or better "T" reinforcement. 80% length of web member. Attached with 8d Box or Gun (0.113"x2.5", min.) nails @ 6" oc.
(a) Continuous lateral restraint equally spaced on member. Or 2x4 #3 or better "T" reinforcement. 80% length of web member. Attached with 10d Box or Gun (0.128"x3", min.) nails @ 6" oc.
(b) Continuous lateral restraint equally spaced on member. Or 2x6 #3 or better "T" reinforcement. 80% length of web member. Attached with 10d Box or Gun (0.128"x3", min.) nails @ 6" oc.

Loading
Truss passed check for 20 psf additional bottom chord live load in areas with 42"-high x 24"-wide clearance.


Purlins
In lieu of structural panels use purlins to brace all flat TC @ 24" oc.

Wind
Wind loads based on MWFRS with additional C&C member design.

Additional Notes
WARNING: Furnish a copy of this DWG to the installation contractor. Special care must be taken during handling, shipping and installation of trusses. See "WARNING" note below.

Chords	Tens.Comp.	Chords	Tens. Comp.
R - Q	1128 -34	O - N	2383 -288
Q - P	1891 -166	N - M	2383 -288
P - O	1959 -163	M - K	2521 -315


Webs	Tens.Comp.	Webs	Tens. Comp.
C - T	98 -421	E - Q	1238 -131
T - D	322 -2307	Q - F	195 -878
D - R	1751 -177	H - O	540 -92
R - E	164 -1201	O - I	161 -469



****WARNING**** READ AND FOLLOW ALL NOTES ON THIS DRAWING!
****IMPORTANT**** FURNISH THIS DRAWING TO ALL CONTRACTORS INCLUDING THE INSTALLERS
Trusses require extreme care in fabricating, handling, shipping, installing and bracing. Refer to and follow the latest edition of BCS (Building Component Safety Information, by TPI and SBCEA) for safety practices prior to performing these functions. Installers shall provide temporary bracing per BCS. Unless noted otherwise, top chord shall have properly attached structural sheathing and bottom chord shall have a properly attached rigid ceiling. Locations shown for permanent lateral restraint of webs shall have bracing installed per BCS sections B3, B7, or B10, as applicable. Apply plates to each face of truss and position as shown above and on the Joint Details, unless noted otherwise. Refer to drawings 160A-Z for standard plate positions. Refer to job's General Notes page for additional information.
Alpine, a division of ITW Building Components Group Inc. shall not be responsible for any deviation from this drawing, any failure to build the truss in conformance with ANSI/TPI 1, or for handling, shipping, installation and bracing of trusses. A seal on this drawing or cover page listing this drawing, indicates acceptance of professional engineering responsibility solely for the design shown. The suitability and use of this drawing for any structure is the responsibility of the Building Designer per ANSI/TPI 1 Sec.2.
For more information see these web sites: Alpine: www.alpineitw.com; TPI: www.tpinet.org; SBCEA: www.sbceaindustry.com; ICC: www.iccsafe.org

ALPINE
AN ITW COMPANY
6750 Forum Drive
Suite 305
Orlando FL, 32821

SEQN: 973049 FROM: RJL	COMN Ply: 1 Qty: 11	Job Number: B51561a -KRAMER RESIDENCE America's Home Place Truss Label: A2c 54' Common	Cust: R 857 JRef: 1WWF8570002 T7 DrwNo: 177.20.1023.13263 SSB / DF 06/25/2020
---------------------------	------------------------	--	---



Loading Criteria (psf)	Wind Criteria	Snow Criteria (Pg. Pf in PSF)	Defl/CSI Criteria	Maximum Reactions (lbs)
TCLL: 20.00 TCCL: 7.00 BCLL: 0.00 BCDL: 10.00 Des Ld: 37.00 NCBCLL: 10.00 Soffit: 0.00 Load Duration: 1.25 Spacing: 24.0 "	Wind Std: ASCE 7-10 Speed: 130 mph Enclosure: Closed Risk Category: II EXP: B Kzt: NA Mean Height: 15.00 ft TCDL: 4.2 psf BCDL: 5.2 psf MWFRS Parallel Dist: h to 2h C&C Dist a: 5.40 ft Loc. from endwall: not in 13.00 ft GCpi: 0.18 Wind Duration: 1.60	Pg: NA Ct: NA CAT: NA Pf: NA Ce: NA Lu: NA Cs: NA Snow Duration: NA Building Code: FBC 2017 RES TPI Std: 2014 Rep Fac: No FT/RT: 20(0)/10(0) Plate Type(s): WAVE, HS	PP Deflection in loc L/defl L/# VERT(LL): 0.058 F 999 360 VERT(CL): 0.096 F 999 240 HORZ(LL): 0.023 O - - HORZ(TL): 0.038 O - - Creep Factor: 2.0 Max TC CSI: 0.520 Max BC CSI: 0.612 Max Web CSI: 0.995 VIEW Ver: 18.02.01A.0205.19	Gravity Non-Gravity Loc R+ / R- / Rh / Rw / U / RL B 487 /- /- /258 /- /235 V 2133 /- /- /964 /- /- O 2179 /- /- /953 /- /- L 289 /- /- /186 /8 /- Wind reactions based on MWFRS B Brg Width = 3.5 Min Req = 1.5 V Brg Width = 3.5 Min Req = 2.1 O Brg Width = 3.5 Min Req = 2.2 L Brg Width = 3.5 Min Req = 1.5 Bearings B, V, O, & L are a rigid surface. Members not listed have forces less than 375#

Lumber
Top chord: 2x4 SP #1; T3, T4 2x6 SP #1;
Bot chord: 2x4 SP #1; B3 2x8 SP SS Dense;
Webs: 2x4 SP #1;
Lt Wedge: 2x4 SP #3; Rt Wedge: 2x4 SP #3;

Bracing

- (a) Continuous lateral restraint equally spaced on member. Or 1x4 #3SRB SPF-S or better "T" reinforcement. 80% length of web member. Attached with 8d Box or Gun (0.113"x2.5", min.) nails @ 6" oc.
- (c) Continuous lateral restraint equally spaced on member. Or 2x4 #3 or better "T" reinforcement. 80% length of web member. Attached with 10d Box or Gun (0.128"x3", min.) nails @ 6" oc.
- (b) Continuous lateral restraint equally spaced on member. Or 2x6 #3 or better "T" reinforcement. 80% length of web member. Attached with 10d Box or Gun (0.128"x3", min.) nails @ 6" oc.

Loading

Truss passed check for 20 psf additional bottom chord live load in areas with 42"-high x 24"-wide clearance.

Purlins


In lieu of structural panels use purlins to brace all flat TC @ 24" oc.

Wind

Wind loads based on MWFRS with additional C&C member design.

Additional Notes

WARNING: Furnish a copy of this DWG to the installation contractor. Special care must be taken during handling, shipping and installation of trusses. See "WARNING" note below.



COA #0 218
06/25/2020

Chords	Tens. Comp.	Chords	Tens. Comp.
B - C	107 -393	F - G	365 -1426
D - E	306 -1141	G - H	365 -1426
E - F	355 -1300	H - I	338 -1482


Chords	Tens. Comp.	Chords	Tens. Comp.
T - S	1073 -23	Q - P	705 -35
S - R	1514 -107	P - O	705 -35
R - Q	1270 -55		

Webs	Tens. Comp.	Webs	Tens. Comp.
C - V	94 -405	S - F	130 -441
V - D	232 -1700	R - H	579 -50
D - T	1221 -100	Q - I	750 -30
T - E	104 -788	I - O	301 -1895
E - S	841 -72		

****WARNING**** READ AND FOLLOW ALL NOTES ON THIS DRAWING!
****IMPORTANT**** FURNISH THIS DRAWING TO ALL CONTRACTORS INCLUDING THE INSTALLERS
Trusses require extreme care in fabricating, handling, shipping, installing and bracing. Refer to and follow the latest edition of BCSI (Building Component Safety Information, by TPI and SBCA) for safety practices prior to performing these functions. Installers shall provide temporary bracing per BCSI. Unless noted otherwise, top chord shall have properly attached structural sheathing and bottom chord shall have a properly attached rigid ceiling. Locations shown for permanent lateral restraint of webs shall have bracing installed per BCSI sections B3, B7, or B10, as applicable. Apply plates to each face of truss and position as shown above and on the Joint Details, unless noted otherwise. Refer to drawings 160A-Z for standard plate positions. Refer to job's General Notes page for additional information.
Alpine, a division of ITW Building Components Group Inc, shall not be responsible for any deviation from this drawing, any failure to build the truss in conformance with ANSI/TPI 1, or for handling, shipping, installation and bracing of trusses. A seal on this drawing or cover page listing this drawing, indicates acceptance of professional engineering responsibility solely for the design shown. The suitability and use of this drawing for any structure is the responsibility of the Building Designer per ANSI/TPI 1 Sec.2.
For more information see these web sites: Alpine: www.alpineitw.com; TPI: www.tpinet.org; SBCA: www.sbcindustry.com; ICC: www.iccsafe.org

ALPINE
AN ITW COMPANY
6750 Forum Drive
Suite 305
Orlando FL, 32821

SEQN: 973050 FROM: RJL	GABL Ply: 1 Qty: 1	Job Number: B51561a -KRAMER RESIDENCE America's Home Place Truss Label: B1-G 13' Gable	Cust: R 857 JRef: 1WW/8570002 T3 DrwNo: 177.20.1023.14340 SSB / DF 06/25/2020
---------------------------	--------------------------	--	---



Loading Criteria (psf)	Wind Criteria	Snow Criteria (Pg, Pf in PSF)	Defl/CSI Criteria	▲ Maximum Reactions (lbs), or *PLF
TCLL: 20.00 TCCL: 7.00 BCLL: 0.00 BCDL: 10.00 Des Ld: 37.00 NCBCLL: 10.00 Soffit: 0.00 Load Duration: 1.25 Spacing: 24.0 "	Wind Std: ASCE 7-10 Speed: 130 mph Enclosure: Closed Risk Category: II EXP: B Kzt: NA Mean Height: 15.00 ft TCDL: 4.2 psf BCDL: 5.2 psf MWFRS Parallel Dist: 0 to h/2 C&C Dist a: 3.00 ft Loc. from endwall: Any GCpi: 0.18 Wind Duration: 1.60	Pg: NA Ct: NA CAT: NA Pf: NA Ce: NA Lu: NA Cs: NA Snow Duration: NA Building Code: FBC 2017 RES TPI Std: 2014 Rep Fac: No FT/RT: 20(0)/10(0) Plate Type(s): WAVE	PP Deflection in loc L/defl L/# VERT(LL): -0.001 I 999 360 VERT(CL): -0.002 I 999 240 HORZ(LL): -0.002 P - - HORZ(TL): 0.002 P - - Creep Factor: 2.0 Max TC CSI: 0.161 Max BC CSI: 0.036 Max Web CSI: 0.044 VIEW Ver: 18.02.01A.0205.19	Gravity Loc R+ /R- /Rh /Rw /U /RL Non-Gravity J* 106 /- /- /47 /23 /12 Wind reactions based on MWFRS J Brg Width = 156 Min Req = - Bearing B is a rigid surface. Members not listed have forces less than 375#

Lumber

Top chord: 2x4 SP #1;
Bot chord: 2x4 SP #1;
Webs: 2x4 SP #1;
Lt Slider: 2x4 SP #1; block length = 1.500'
Rt Slider: 2x4 SP #1; block length = 1.500'

Plating Notes

All plates are 1.5X3 except as noted.

Loading


Truss designed to support 1-0-0 top chord outlookers and cladding load not to exceed 5.00 PSF one face and 24.0" span opposite face. Top chord must not be cut or notched, unless specified otherwise.

Wind

Wind loads based on MWFRS with additional C&C member design.

Additional Notes

See DWGS A14015ENC101014 & GBLLETIN0118 for gable wind bracing and other requirements.



****WARNING**** READ AND FOLLOW ALL NOTES ON THIS DRAWING!

****IMPORTANT**** FURNISH THIS DRAWING TO ALL CONTRACTORS INCLUDING THE INSTALLERS

Trusses require extreme care in fabricating, handling, shipping, installing and bracing. Refer to and follow the latest edition of BCSI (Building Component Safety Information, by TPI and SBCEA) for safety practices prior to performing these functions. Installers shall provide temporary bracing per BCSI. Unless noted otherwise, top chord shall have properly attached structural sheathing and bottom chord shall have a properly attached rigid ceiling. Locations shown for permanent lateral restraint of webs shall have bracing installed per BCSI sections B3, B7, or B10, as applicable. Apply plates to each face of truss and position as shown above and on the Joint Details, unless noted otherwise. Refer to drawings 160A-Z for standard plate positions. Refer to job's General Notes page for additional information.


Alpine, a division of ITW Building Components Group Inc, shall not be responsible for any deviation from this drawing, any failure to build the truss in conformance with ANSI/TPI 1, or for handling, shipping, installation and bracing of trusses. A seal on this drawing or cover page listing this drawing, indicates acceptance of professional engineering responsibility solely for the design shown. The suitability and use of this drawing for any structure is the responsibility of the Building Designer per ANSI/TPI 1 Sec.2.

For more information see these web sites: Alpine: www.alpineitw.com; TPI: www.tpinst.org; SBCEA: www.sbcindustry.com; ICC: www.iccsafe.org

ALPINE
AN ITW COMPANY
6750 Forum Drive
Suite 305
Orlando FL, 32821

SEQN: 973051 FROM: RJL	COMN Ply: 2 Qty: 1	Job Number: B51561a -KRAMER RESIDENCE America's Home Place Truss Label: B2 13' Common Girder	Cust: R 857 JRef: 1WW8570002 T13 DrwNo: 177.20.1023.16737 SSB / DF 06/25/2020
---------------------------	--------------------------	--	---

2 Complete Trusses Required



Loading Criteria (psf)	Wind Criteria	Snow Criteria (Pg, Pf in PSF)	Defl/CSI Criteria	Maximum Reactions (lbs)
TCLL: 20.00 TCDL: 7.00 BCLL: 0.00 BCDL: 10.00 Des Ld: 37.00 NCBCLL: 0.00 Soffit: 0.00 Load Duration: 1.25 Spacing: 24.0 "	Wind Std: ASCE 7-10 Speed: 130 mph Enclosure: Closed Risk Category: II EXP: B Kzt: NA Mean Height: 15.00 ft TCDL: 4.2 psf BCDL: 5.2 psf MWFRS Parallel Dist: 0 to h/2 C&C Dist a: 3.00 ft Loc. from endwall: Any GCpi: 0.18 Wind Duration: 1.60	Pg: NA Ct: NA CAT: NA Pf: NA Ce: NA Lu: NA Cs: NA Snow Duration: NA Building Code: FBC 2017 RES TPI Std: 2014 Rep Fac: No FT/RT: 20(0)/10(0) Plate Type(s): WAVE	PP Deflection in loc L/defl L/# VERT(LL): 0.075 F 999 360 VERT(CL): 0.138 F 999 240 HORZ(LL): 0.025 B - - HORZ(TL): 0.045 B - - Creep Factor: 2.0 Max TC CSI: 0.718 Max BC CSI: 0.466 Max Web CSI: 0.420 VIEW Ver: 18.02.01A.0205.19	Gravity Non-Gravity Loc R+ / R- / Rh / Rw / U / RL H 7537 /- /- /240 /- /- I 8583 /- /- /285 /- /- Wind reactions based on MWFRS H Brg Width = 3.5 Min Req = - I Brg Width = 3.5 Min Req = - Bearings H & I are a rigid surface. Members not listed have forces less than 375# Maximum Top Chord Forces Per Ply (lbs) Chords Tens.Comp. Chords Tens. Comp. A - B 0 - 4423 C - D 0 - 4383 B - C 0 - 4345 D - E 0 - 4460

Lumber

Top chord: 2x4 SP #1;
Bot chord: 2x8 SP SS Dense;
Webs: 2x4 SP #1;

Nailnote

Nail Schedule: 0.128"x3", min. nails
Top Chord: 1 Row @ 12.00" o.c.
Bot Chord: 3 Rows @ 3.75" o.c. (Each Row)
Webs : 1 Row @ 4" o.c.
Use equal spacing between rows and stagger nails in each row to avoid splitting.

Special Loads

---(Lumber Dur.Fac.=1.25 / Plate Dur.Fac.=1.25)
TC: From 58 plf at 0.00 to 58 plf at 13.00
BC: From 10 plf at 0.00 to 10 plf at 13.00
BC: 2540 lb Conc. Load at 1.94, 3.94, 5.94, 7.94, 9.94, 11.94

Plating Notes

(I) - plates so marked were sized using 0% Fabrication Tolerance, 0 degrees Rotational Tolerance, and/or zero Positioning Tolerance.

Wind

Wind loads and reactions based on MWFRS.

Blocking

Full Height Blocking reinforcement required to prevent buckling of members over the bearings:
bearing 1 located at 0.0'
bearing 2 located at 12.7'

Bearing Block(s)


Brg blocks: 0.128"x3", min. nails
brg x-loc #blocks length/blk #nails/blk wall plate
1 0.000' 1 12" 5 Rigid Surface
2 12.709' 1 12" 14 Rigid Surface
Brg block to be same size and species as chord.
Refer to drawing CNNAILSP1014 for more information.

Maximum Bot Chord Forces Per Ply (lbs)

Chords	Tens.Comp.	Chords	Tens. Comp.
A - G 3441	0	F - E 3472	0
G - F 2451	0		

Maximum Web Forces Per Ply (lbs)

Webs	Tens.Comp.	Webs	Tens. Comp.
G - C 2680	0	C - F 2757	0



COA #0 278
06/25/2020

****WARNING**** READ AND FOLLOW ALL NOTES ON THIS DRAWING!
****IMPORTANT**** FURNISH THIS DRAWING TO ALL CONTRACTORS INCLUDING THE INSTALLERS


Trusses require extreme care in fabricating, handling, shipping, installing and bracing. Refer to and follow the latest edition of BCSI (Building Component Safety Information, by TPI and SBCEA) for safety practices prior to performing these functions. Installers shall provide temporary bracing per BCSI. Unless noted otherwise, top chord shall have properly attached structural sheathing and bottom chord shall have a properly attached rigid ceiling. Locations shown for permanent lateral restraint of webs shall have bracing installed per BCSI sections B3, B7, or B10, as applicable. Apply plates to each face of truss and position as shown above and on the Joint Details, unless noted otherwise. Refer to drawings 160A-Z for standard plate positions. Refer to job's General Notes page for additional information.

Alpine, a division of ITW Building Components Group Inc. shall not be responsible for any deviation from this drawing, any failure to build the truss in conformance with ANSI/TPI 1, or for handling, shipping, installation and bracing of trusses. A seal on this drawing or cover page listing this drawing, indicates acceptance of professional engineering responsibility solely for the design shown. The suitability and use of this drawing for any structure is the responsibility of the Building Designer per ANSI/TPI 1 Sec.2.

For more information see these web sites: Alpine: www.alpineitw.com; TPI: www.tpinet.org; SBCEA: www.sbcindustry.com; ICC: www.iccsafe.org

ALPINE
AN ITW COMPANY
6750 Forum Drive
Suite 305
Orlando FL, 32821

SEQN: 973052 FROM: RJL	GABL Qty: 1	Ply: 1 Qty: 1	Job Number: B51561a -KRAMER RESIDENCE America's Home Place Truss Label: V1-G 26'2"8 Valley	Cust: R 857 JRef: 1WWI8570002 T4 DrwNo: 177.20.1023.43033 SSB / DF 06/25/2020
---------------------------	----------------	------------------	--	---



Loading Criteria (psf)	Wind Criteria	Snow Criteria (Pg, Pf in PSF)	Defl/CSI Criteria	▲ Maximum Reactions (lbs), or *PLF
TCLL: 20.00 TCDL: 7.00 BCLL: 0.00 BCDL: 10.00 Des Ld: 37.00 NCBCLL: 10.00 Soffit: 0.00 Load Duration: 1.25 Spacing: 24.0 "	Wind Std: ASCE 7-10 Speed: 130 mph Enclosure: Closed Risk Category: II EXP: B Kzt: NA Mean Height: 15.00 ft TCDL: 4.2 psf BCDL: 5.2 psf MWFRS Parallel Dist: 0 to h/2 C&C Dist a: 3.00 ft Loc. from endwall: Any GCpt: 0.18 Wind Duration: 1.60	Pg: NA Ct: NA CAT: NA Pf: NA Ce: NA Lu: NA Cs: NA Snow Duration: NA Building Code: FBC 2017 RES TPI Std: 2014 Rep Fac: No FT/RT: 20(0)/10(0) Plate Type(s): WAVE	PP Deflection in loc L/defl L/# VERT(LL): 0.002 X 999 360 VERT(CL): 0.004 X 999 240 HORZ(LL): -0.002 F - - HORZ(TL): 0.003 F - - Creep Factor: 2.0 Max TC CSI: 0.078 Max BC CSI: 0.059 Max Web CSI: 0.133 VIEW Ver: 18.02.01A.0205.19	Gravity Non-Gravity Loc R+ / R- / Rh / Rw / U / RL M* 99 /- /- /40 /4 /8 Wind reactions based on MWFRS M Brg Width = 314 Min Req = - Bearing A is a rigid surface. Members not listed have forces less than 375#

Lumber

Top chord: 2x4 SP #1;
Bot chord: 2x4 SP #1;
Webs: 2x4 SP #1;

Bracing

(a) 1x4 #3SRB SPF-S or better "L" reinforcement.
80% length of web member. Attach with 8d Box or
Gun (0.113"x2.5", min.) nails @ 6" oc.

Plating Notes

All plates are 1.5X3 except as noted.

Loading

Truss designed to support 1-0-0 top chord outlookers
and cladding load not to exceed 5.00 PSF one face
and 24.0" span opposite face. Top chord must not be
cut or notched, unless specified otherwise.


Wind

Wind loads based on MWFRS with additional C&C
member design.

Additional Notes

See DWGS A14015ENC101014 & GBLLETIN0118 for
gable wind bracing and other requirements.

See DWG VAL160101014 for valley details.



06/25/2020

****WARNING**** READ AND FOLLOW ALL NOTES ON THIS DRAWING!

****IMPORTANT**** FURNISH THIS DRAWING TO ALL CONTRACTORS INCLUDING THE INSTALLERS


Trusses require extreme care in fabricating, handling, shipping, installing and bracing. Refer to and follow the latest edition of BCSI (Building Component Safety Information, by TPI and SBCA) for safety practices prior to performing these functions. Installers shall provide temporary bracing per BCSI. Unless noted otherwise, top chord shall have properly attached structural sheathing and bottom chord shall have a properly attached rigid ceiling. Locations shown for permanent lateral restraint of webs shall have bracing installed per BCSI sections B3, B7, or B10, as applicable. Apply plates to each face of truss and position as shown above and on the Joint Details, unless noted otherwise. Refer to drawings 160A-Z for standard plate positions. Refer to job's General Notes page for additional information.

Alpine, a division of ITW Building Components Group Inc. shall not be responsible for any deviation from this drawing, any failure to build the truss in conformance with ANSI/TPI 1, or for handling, shipping, installation and bracing of trusses. A seal on this drawing or cover page listing this drawing, indicates acceptance of professional engineering responsibility solely for the design shown. The suitability and use of this drawing for any structure is the responsibility of the Building Designer per ANSI/TPI 1 Sec.2.

For more information see these web sites: Alpine: www.alpinetw.com; TPI: www.tpinet.org; SBCA: www.sbcindustry.com; ICC: www.iccsafe.org

ALPINE
AN ITW COMPANY
6750 Forum Drive
Suite 305
Orlando FL, 32821

SEQN: 973053 FROM: RJL	GABL Qty: 1	Ply: 1 Qty: 1	Job Number: B51561a -KRAMER RESIDENCE America's Home Place Truss Label: V2-G 18'0"8 Valley	Cust: R 857 JRef: 1WWF8570002 T6 DrwNo: 177.20.1023.57700 SSB / DF 06/25/2020
---------------------------	----------------	------------------	--	---



Loading Criteria (psf)	Wind Criteria	Snow Criteria (Pg, Pf in PSF)	Defl/CSI Criteria	▲ Maximum Reactions (lbs), or *PLF
TCLL: 20.00 TCDL: 7.00 BCLL: 0.00 BCDL: 10.00 Des Ld: 37.00 NCBCLL: 10.00 Soffit: 0.00 Load Duration: 1.25 Spacing: 24.0 "	Wind Std: ASCE 7-10 Speed: 130 mph Enclosure: Closed Risk Category: II EXP: B Kzt: NA Mean Height: 15.00 ft TCDL: 4.2 psf BCDL: 5.2 psf MWFRS Parallel Dist: 0 to h/2 C&C Dist a: 3.00 ft Loc. from endwall: Any GCpi: 0.18 Wind Duration: 1.60	Pg: NA Ct: NA CAT: NA Pf: NA Ce: NA Lu: NA Cs: NA Snow Duration: NA Building Code: FBC 2017 RES TPI Std: 2014 Rep Fac: No FT/RT: 20(0)/10(0) Plate Type(s): WAVE	PP Deflection in loc L/defl L/# VERT(LL): 0.002 J 999 360 VERT(CL): 0.004 J 999 240 HORZ(LL): 0.001 F - - HORZ(TL): 0.002 P - - Creep Factor: 2.0 Max TC CSI: 0.074 Max BC CSI: 0.052 Max Web CSI: 0.075 VIEW Ver: 18.02.01A.0205.19	Gravity Non-Gravity Loc R+ / R- / Rh / Rw / U / RL I* 92 /- /- /40 /3 /8 Wind reactions based on MWFRS l Brg Width = 216 Min Req = - Bearing A is a rigid surface. Members not listed have forces less than 375#

Lumber

Top chord: 2x4 SP #1;
Bot chord: 2x4 SP #1;
Webs: 2x4 SP #1;

Plating Notes

All plates are 1.5X3 except as noted.

Loading

Truss designed to support 1-0-0 top chord outlookers and cladding load not to exceed 5.00 PSF one face and 24.0" span opposite face. Top chord must not be cut or notched, unless specified otherwise.


Wind

Wind loads based on MWFRS with additional C&C member design.

Additional Notes

See DWGS A14015ENC101014 & GBLLETIN0118 for gable wind bracing and other requirements.

See DWG VAL160101014 for valley details.



COA #0 248
06/25/2020

****WARNING**** READ AND FOLLOW ALL NOTES ON THIS DRAWING!
****IMPORTANT**** FURNISH THIS DRAWING TO ALL CONTRACTORS INCLUDING THE INSTALLERS


Trusses require extreme care in fabricating, handling, shipping, installing and bracing. Refer to and follow the latest edition of BCSI (Building Component Safety Information, by TPI and SBCA) for safety practices prior to performing these functions. Installers shall provide temporary bracing per BCSI. Unless noted otherwise, top chord shall have properly attached structural sheathing and bottom chord shall have a properly attached rigid ceiling. Locations shown for permanent lateral restraint of webs shall have bracing installed per BCSI sections B3, B7, or B10, as applicable. Apply plates to each face of truss and position as shown above and on the Joint Details, unless noted otherwise. Refer to drawings 160A-Z for standard plate positions. Refer to job's General Notes page for additional information.

Alpine, a division of ITW Building Components Group Inc. shall not be responsible for any deviation from this drawing, any failure to build the truss in conformance with ANSI/TPI 1, or for handling, shipping, installation and bracing of trusses. A seal on this drawing or cover page listing this drawing, indicates acceptance of professional engineering responsibility solely for the design shown. The suitability and use of this drawing for any structure is the responsibility of the Building Designer per ANSI/TPI 1 Sec.2.

For more information see these web sites: Alpine: www.alpineitw.com; TPI: www.tpinst.org; SBCA: www.sbcindustry.com; ICC: www.iccsafe.org

ALPINE
AN ITW COMPANY
6750 Forum Drive
Suite 305
Orlando FL, 32821

SEQN: 973054 FROM: RJL	GABL Ply: 1 Qty: 2	Job Number: B51561a -KRAMER RESIDENCE America's Home Place Truss Label: PB1-G 18' Gable	Cust: R 857 JRef: 1WWF8570002 T10 DrwNo: 177.20.1023.39290 SSB / DF 06/25/2020
---------------------------	--------------------------	---	--



Loading Criteria (psf)	Wind Criteria	Snow Criteria (Pg, Pf in PSF)	Defl/CSI Criteria	▲ Maximum Reactions (lbs), or *PLF
TCLL: 20.00 TCDL: 7.00 BCLL: 0.00 BCDL: 10.00 Des Ld: 37.00 NCBCLL: 10.00 Soffit: 0.00 Load Duration: 1.25 Spacing: 24.0 "	Wind Std: ASCE 7-10 Speed: 130 mph Enclosure: Closed Risk Category: II EXP: B Kzt: NA Mean Height: 22.89 ft TCDL: 4.2 psf BCDL: 5.2 psf MWFRS Parallel Dist: 0 to h/2 C&C Dist a: 3.00 ft Loc. from endwall: Any GCpi: 0.18 Wind Duration: 1.60	Pg: NA Ct: NA CAT: NA Pf: NA Ce: NA Lu: NA Cs: NA Snow Duration: NA Building Code: FBC 2017 RES TPI Std: 2014 Rep Fac: No FT/RT: 20(0)/10(0) Plate Type(s): WAVE	PP Deflection in loc L/defl L/# VERT(LL): 0.001 E 999 360 VERT(CL): 0.001 E 999 240 HORZ(LL): -0.001 D - - HORZ(TL): 0.001 D - - Creep Factor: 2.0 Max TC CSI: 0.056 Max BC CSI: 0.029 Max Web CSI: 0.030 VIEW Ver: 18.02.01A.0205.19	Gravity Non-Gravity Loc R+ /R- /Rh /Rw /U /RL B* 91 /- /- /40 /15 /7 Wind reactions based on MWFRS B Brg Width = 195 Min Req = - Bearing B is a rigid surface. Members not listed have forces less than 375#

Lumber

Top chord: 2x4 SP #1;
Bot chord: 2x4 SP #1;
Webs: 2x4 SP #1;

Plating Notes

All plates are 1.5X3 except as noted.

Loading

Truss designed to support 1-0-0 top chord outlookers and cladding load not to exceed 5.00 PSF one face and 24.0" span opposite face. Top chord must not be cut or notched, unless specified otherwise.


Wind

Wind loads based on MWFRS with additional C&C member design.

Additional Notes

See DWGS A14030ENC101014 & GBLLETIN0118 for gable wind bracing and other requirements.

Refer to drawing PB160101014 for piggyback detail.



COA #0 218
06/25/2020

WARNING READ AND FOLLOW ALL NOTES ON THIS DRAWING!

IMPORTANT FURNISH THIS DRAWING TO ALL CONTRACTORS INCLUDING THE INSTALLERS


Trusses require extreme care in fabricating, handling, shipping, installing and bracing. Refer to and follow the latest edition of BCSI (Building Component Safety Information, by TPI and SBCA) for safety practices prior to performing these functions. Installers shall provide temporary bracing per BCSI. Unless noted otherwise, top chord shall have properly attached structural sheathing and bottom chord shall have a properly attached rigid ceiling. Locations shown for permanent lateral restraint of webs shall have bracing installed per BCSI sections B3, B7, or B10, as applicable. Apply plates to each face of truss and position as shown above and on the Joint Details, unless noted otherwise. Refer to drawings 160A-Z for standard plate positions. Refer to job's General Notes page for additional information.

Alpine, a division of ITW Building Components Group Inc. shall not be responsible for any deviation from this drawing, any failure to build the truss in conformance with ANSI/TPI 1, or for handling, shipping, installation and bracing of trusses. A seal on this drawing or cover page listing this drawing, indicates acceptance of professional engineering responsibility solely for the design shown. The suitability and use of this drawing for any structure is the responsibility of the Building Designer per ANSI/TPI 1 Sec.2.

For more information see these web sites: Alpine: www.alpineitw.com; TPI: www.tpinst.org; SBCA: www.sbcindustry.com; ICC: www.iccsafe.org

ALPINE
AN ITW COMPANY
6750 Forum Drive
Suite 305
Orlando FL, 32821

SEQN: 973055 FROM: RJL	GABL Ply: 1 Qty: 31	Job Number: B51561a -KRAMER RESIDENCE America's Home Place Truss Label: PB2 18' Common	Cust: R 857 JRef: 1WWf8570002 T11 DrwNo: 177.20.1023.41797 SSB / DF 06/25/2020
---------------------------	---------------------------	--	--



Loading Criteria (psf)	Wind Criteria	Snow Criteria (Pg, Pf in PSF)	Defl/CSI Criteria	▲ Maximum Reactions (lbs), or *PLF
TCLL: 20.00 TCDL: 7.00 BCLL: 0.00 BCDL: 10.00 Des Ld: 37.00 NCBCLL: 10.00 Soffit: 0.00 Load Duration: 1.25 Spacing: 24.0 "	Wind Std: ASCE 7-10 Speed: 130 mph Enclosure: Closed Risk Category: II EXP: B Kzt: NA Mean Height: 22.89 ft TCDL: 4.2 psf BCDL: 5.2 psf MWFRS Parallel Dist: 0 to h/2 C&C Dist a: 3.00 ft Loc. from endwall: Any GCpi: 0.18 Wind Duration: 1.60	Pg: NA Ct: NA CAT: NA Pf: NA Ce: NA Lu: NA Cs: NA Snow Duration: NA Building Code: FBC 2017 RES TPI Std: 2014 Rep Fac: No FT/RT: 20(0)/10(0) Plate Type(s): WAVE	PP Deflection in loc L/defl L/# VERT(LL): 0.001 D 999 360 VERT(CL): 0.002 D 999 240 HORZ(LL): -0.001 J - - HORZ(TL): 0.002 J - - Creep Factor: 2.0 Max TC CSI: 0.423 Max BC CSI: 0.219 Max Web CSI: 0.095 VIEW Ver: 18.02.01A.0205.19	Gravity Non-Gravity Loc R+ /R- /Rh /Rw /U /RL B* 80 /- /- /38 /13 /7 Wind reactions based on MWFRS B Brg Width = 195 Min Req = - Bearing B is a rigid surface. Members not listed have forces less than 375#

Lumber

Top chord: 2x4 SP #1;
Bot chord: 2x4 SP #1;
Webs: 2x4 SP #1;

Plating Notes

All plates are 1.5X3 except as noted.


Wind

Wind loads based on MWFRS with additional C&C member design.

Additional Notes

See DWGS A14030ENC101014 & GBLLETIN0118 for gable wind bracing and other requirements.

Refer to drawing PB160101014 for piggyback detail.



****WARNING**** READ AND FOLLOW ALL NOTES ON THIS DRAWING!

****IMPORTANT**** FURNISH THIS DRAWING TO ALL CONTRACTORS INCLUDING THE INSTALLERS

Trusses require extreme care in fabricating, handling, shipping, installing and bracing. Refer to and follow the latest edition of BCSI (Building Component Safety Information, by TPI and SBCA) for safety practices prior to performing these functions. Installers shall provide temporary bracing per BCSI. Unless noted otherwise, top chord shall have properly attached structural sheathing and bottom chord shall have a properly attached rigid ceiling. Locations shown for permanent lateral restraint of webs shall have bracing installed per BCSI sections B3, B7, or B10, as applicable. Apply plates to each face of truss and position as shown above and on the Joint Details, unless noted otherwise. Refer to drawings 160A-Z for standard plate positions. Refer to job's General Notes page for additional information.

Alpine, a division of ITW Building Components Group Inc. shall not be responsible for any deviation from this drawing, any failure to build the truss in conformance with ANSI/TPI 1, or for handling, shipping, installation and bracing of trusses. A seal on this drawing or cover page listing this drawing, indicates acceptance of professional engineering responsibility solely for the design shown. The suitability and use of this drawing for any structure is the responsibility of the Building Designer per ANSI/TPI 1 Sec.2.

For more information see these web sites: Alpine: www.alpineitw.com; TPI: www.tpinst.org; SBCA: www.sbcindustry.com; ICC: www.iccsafe.org

ALPINE
AN ITW COMPANY
6750 Forum Drive
Suite 305
Orlando FL, 32821

ASCE 7-10: 140 mph Wind Speed, 15' Mean Height, Enclosed, Exposure C, $K_{zt} = 1.00$

Dr	120 mph	Wind Speed, 15'	Mean Height, Exposure C, Kzt = 1.00
Dr	120 mph	Wind Speed, 15'	Mean Height, Exposure D, Kzt = 1.00
Dr	100 mph	Wind Speed, 15'	Mean Height, Exposure D, Kzt = 1.00

Bracing Group Species and Grades			
Group A1		Group B1	
Spruce-Pine-Fir	Hem-Fir	Hem-Fir	Southern Pine
#1 / #2	#2	#1 & Btr	#1
Standard	Standard	#1	#2
#3	Stud		
	Standard		
Douglas Fir-Larch		Southern Pine	
#3	#3	Standard	Standard
Stud	Stud		
Standard	Standard		

Douglas Fir-Larch Southern Pine
 #1 #2

Douglas Fir-Larch Southern Pine
 #1 #2

Douglas Fir-Larch Southern Pine
 #1 #2

Wind Load deflection criterion is L/240,

Provide uplift connections for 55 plf over continuous bearing (5 psf TC Dead Load).

Gable end supports load from 4' 0" outlookers with 2' 0" overhang, or 12" plywood overhang.

Attach "L" braces with 10d (0.128"x3.0" min) nails.

For (1) 'L' brace' space nalls at 2' o.c. in 18' end zones and 4' o.c. between zones

For (2) 'L' braces space rolls at 3' o.c. in 18' end zones and 4' o.c. between zones.

L' bracing must be a minimum of 80% of web member length.

Gable Vertical Plate Sizes	
Vertical Length	No Splice
Less than 4' 0"	1X4 or 2X3
Greater than 4' 0"	2X4


* Refer to common truss design for peak, splice, and heel plates.

Refer to the Building Designer for conditions not addressed by this detail.

REF	ASCE7-10-GABI4015
DATE	10/01/14
DRWG	A14015ENC101014

MAX. TOT. LD. 60 PSF

MAX. SPACING	24.0"
--------------	-------



relative to the vertical length of the

[illegible]


Refer to drawings 160A-Z for standard plate positions.

A seal on this drawing or cover page listing this drawing, indicates acceptance of professional engineering responsibility solely for the design shown. The suitability and use of this drawing

for any structure is the responsibility of the Building Designer per ANSI/TPI 1 Sec.2

ALPINE www.alpine.com TP21 www.tp1st.org SBCH www.sbchindustry.org ICD www.icdinfo.org

Gable Detail For Let-in Verticals




Gable Truss Plate Sizes


Refer to appropriate Alpine gable detail for minimum plate sizes for vertical studs.

Refer to Engineered truss design for peak, splice, web, and heel plates.

If gable vertical plates overlap, use a single plate that covers the total area of the overlapped plates to span the web.



'T' Reinforcement Attachment Detail
'T' Reinforcing Member



To convert from 'L' to 'T' reinforcing members, multiply 'T' increase by length based on appropriate Alpine gable detail.

Maximum allowable 'T' reinforced gable vertical length is 14' from top to bottom chord.
'T' reinforcing member material must match size, specie, and grade of the 'L' reinforcing member.

Web Length Increase w/ 'T' Brace

'T' Reinf. Mar. Size	Increase
2x4	30 %
2x6	20 %

Example:

ASCE 7-10 Wind Speed = 120 mph
Mean Roof Height = 30 ft, Kzt = 1.00
Gable Vertical = 24' o.c. SP #3
'T' Reinforcing Member Size = 2x4
'T' Brace Increase (From Above) = 30% = 1.30
(1) 2x4 'L' Brace Length = 8' 7"
Maximum 'T' Reinforced Gable Vertical Length
1.30 x 8' 7" = 11' 2"

Provide connections for uplift specified on the engineered truss design.

Attach each 'T' reinforcing member with

End Driven Nails:

10d Common (0.148" x 3", min) Nails at 4' o.c. plus

(4) nails in the top and bottom chords.

Toenailed Nails:

10d Common (0.148" x 3", min) Toenails at 4' o.c. plus

(4) toenails in the top and bottom chords.

This detail to be used with the appropriate Alpine gable detail for ASCE wind load.

ASCE 7-05 Gable Detail Drawings

A13015051014, A12015051014, A10015051014, A14015051014,

A13030051014, A12030051014, A11030051014, A10030051014

ASCE 7-10 & ASCE 7-16 Gable Detail Drawings

A11515ENC100118, A12015ENC100118, A14015ENC100118, A16015ENC100118,

A18015ENC100118, A20015ENC100118, A20015END100118, A20015PEDI00118,

A11530ENC100118, A12030ENC100118, A14030ENC100118, A16030ENC100118,

A18030ENC100118, A20030ENC100118, A20030END100118, A20030PEDI00118,


S11515ENC100118, S12015ENC100118, S14015ENC100118, S16015ENC100118,

S18015ENC100118, S20015ENC100118, S20015END100118, S20015PEDI00118,

S11530ENC100118, S12030ENC100118, S14030ENC100118, S16030ENC100118,

S18030ENC100118, S20030ENC100118, S20030END100118, S20030PEDI00118

See appropriate Alpine gable detail for maximum reinforced gable vertical length.



13723 Riverport Drive
Suite 200
Maryland Heights, MO 63043

IMPORTANT: READ AND FOLLOW ALL NOTES ON THIS DRAWING. THE INSTALLER SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND FOR FOLLOWING ALL LOCAL, STATE, AND FEDERAL CODES AND REGULATIONS. THE INSTALLER SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND FOR FOLLOWING ALL LOCAL, STATE, AND FEDERAL CODES AND REGULATIONS. THE INSTALLER SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND FOR FOLLOWING ALL LOCAL, STATE, AND FEDERAL CODES AND REGULATIONS.



REF LET-IN VERT
DATE 01/02/2018
DRWG GBLLETIN0118

MAX. TOT. LD. 60 PSF
DUR. FAC. ANY
MAX. SPACING 24.0"

Piggyback Detail - ASCE 7-16: 160 mph, 30' Mean Height, Enclosed, Exposure C, Kzt=1.00


160 mph Wind, 30.00 ft Mean Hgt, ASCE 7-16, Enclosed Bldg, located anywhere in roof, Exp C, Wind Dir= 5.0 psf (Min), Kzt=1.0, Dr 140 mph wind, 30.00 ft Mean Hgt, ASCE 7-16, Enclosed Bldg, located anywhere in roof, Exp D, Wind Dir= 5.0 psf (Min), Kzt=1.0.

Note: Top chords of trusses supporting piggyback cap trusses must be adequately braced by sheathing or purlins. The building Engineer of Record shall provide diagonal bracing or any other suitable anchorage to permanently restrain purlins, and lateral bracing for out of plane loads over gable ends.

Maximum truss spacing is 24' o.c. detail is not applicable if cap supports additional loads such as cupola, steeple, chimney or drag strut loads.

*** Refer to Engineer's sealed truss design drawing for piggback and base truss specifications.

Detail A : Purlin Spacing = 24" o.c. or less




Piggyback cap truss slant nailed to all top chord
purlin bracing with (2) 16d box nails (135"x3.5")
and secure top chord with 2x4 #3 grade scab
(1 side only at each end) attached with
2 rows of 10d box nails (128"x3") at 4" o.c.

Attach purlin bracing to the flat top chord using (2) 16d box nails (0.135"x3.5").

The top chord #3 grade 2x4 scab may be replaced with either of the following: (1) 3X8 Trulox plate attached with (8) 0.120"x1.375" nails, (4) into cap TC and (4) into base truss TC or (1) 28P8 wave piggyback plate placed to the piggyback truss TC and attached to the base truss TC with (4) 0.120"x1.375" nails. Note: Nailing thru holes of wave plate is acceptable.

Detail B : Purlin Spacing > 24" o.c.



Piggyback cap truss slant nailed to all top chord purlin bracing with (2) 16d box nails (0.135"x3.5") and secure top chord with 2x4 #3 grade scab (1 side only at each end) attached with 2 rows of 10d box nails (0.125"x3.5") at 4" o.c.

Attach purlin bracing to the flat top chord using a minimum of (2) 16d box nails (0.135"x3.5").

≡ In addition, provide connection with one of the following methods:

Trulox

Use 3X8 Trulux plates for 2x4 chord member, and 3X10 Trulux plates for 2x6 and larger chord members. Attach to each face @ 8" o.c. with (4) 0.120"x1.375" nails into cap bottom chord and (4) in base truss top chord. Trulux plates may be staggered 4" o.c. front to back faces.

APA Rated Gusset

8"x8"x7/16" (min) APA rated sheathing gussets (each face). Attach @ 8' o.c. with (8) 6d common (0.113"x2") nails per gusset, (4) in cap bottom chord and (4) in base truss top chord. Gusset may be staggered 4' o.c. front to back faces.

2x4 Vertical Scabs

2x4 SPF #2, full chord depth scabs (each face), Attach @ 8' o.c. with (6) 10d box nails (0.128"x3") per scab, (3) in cap bottom chord and (3) in base truss top chord. Scabs may be staggered 4' o.c. front to back faces.

28PB Wave Piggyback Plate

One 28PB wave piggyback plate to each face
8" o.c. Attach teeth to piggyback at time of
fabrication. Attach to supporting truss with
(4) 0.120"x1.375" bolts per face per ply.
Piggyback plates may be staggered 4" o.c. front
to back faces.

REF PIGGYBACK

DATE 01/02/2018

DRWG PB160160118

SPACING 24.0"

Piggyback Detail - ASCE 7-16: 180 mph, 30' Mean Hgt, Partially Enclosed, Exp. C, Kzt=1.00

180 mph Wind, 30.00 ft Mean Hgt, ASCE 7-16, Part. Enclosed Bldg. located anywhere in roof, Exp C, Wind DL= 5.0 psf (min), Kzt=1.0.
Dr 160 mph wind, 30.00 ft Mean Hgt, ASCE 7-16, Part. Enclosed Bldg. located anywhere in roof, Exp D, Wind DL= 5.0 psf (min), Kzt=1.0.


Note: Top chords of trusses supporting piggyback cap trusses must be adequately braced by sheathing or purlins. The building Engineer of Record shall provide diagonal bracing or any other suitable anchorage to permanently restrain purlins, and lateral bracing for out of plane loads over gable ends.

Maximum truss spacing is 24' o.c. detail is not applicable if cap supports additional loads such as cupola, steeple, chimney or drag strut loads.

Refer to Engineer's sealed truss design drawing for ploggyback and base truss specifications.

Piggyback cap truss slant nailed to all top chord purlin bracing with (2) 16d box nails (0.135"x3.5") and secure top chord with 2x4 #3 grade scab (1 side only at each end) attached with 2 rows of 10d box nails (0.128"x3") at 4" o.c.

++ Flat top chord purlins required at both ends and at a maximum of 24' intervals unless otherwise noted on base truss design drawing. Attach purlin bracing to the flat top chord using a minimum of (2) 16d box nails (0.135"x3.5").



■ In addition, provide connection with one of the following methods:

Trulox Use 3X8 Trulox plates for 2x4 chord member, and 3X10 Trulox plates for 2x6 and larger chord members. Attach to each face @ 8' o.c. with (4) 0.120"x1.375" nails into cap bottom chord and (4) 0.120"x1.375" nails per face per ply. In base truss top chord, Trulox plates may be staggered 4' o.c. front to back faces.	28PB Wave Playback Plate One 28PB wave playback plate to each face @ 8' o.c. Attach teeth to playback at time of fabrication. Attach to supporting truss with (4) 0.120"x1.375" nails per face per ply. Playback plates may be staggered 4' o.c. front to back faces.
APA Rated Gusset 8"x8"x7/16" (min) APA rated sheathing gussets (each face). Attach @ 8' o.c. with (8) 6d common (0.113"x2") nails per gusset. (4) in cap bottom chord and (4) in base truss top chord. Gussets may be staggered 4' o.c. front to back faces.	2x4 Vertical Scabs 2x4 SPF #2, full chord depth scabs (each face). Attach @ 8' o.c. with (6) 10d box nails (0.128"x3") per scab. Cap chord and base chord Scabs may be staggered 4' o.c. front to back faces.

==IMPORTANT== SEND AND FOLLOW UP ALL NOTES ON THIS DRAWING TO THE INSTALLER.
==IMPORTANT== FURNISH THIS DRAWING TO ALL CONTRACTORS INCLUDING THE TRUSSES.

Trusses require extreme care in fabricating, handling, shipping, installing and bracing. Refer to the latest edition of EBCI Guiding Component Safety Information by TPI and SDCO for practices prior to performing these functions. Installers shall provide temporary bracing procedures other than those shown on this drawing. Locations shown for permanent latching and bolting will have a properly attached label calling out locations shown for permanent lateral restraint. Trusses shall have a minimum of two tie-downs per truss as applicable. Apply plates to all trusses at the locations shown above and on the Joint between trusses noted otherwise. Refer to drawings 160A-2 for standard plate positions.

Alpine, a division of ITV Building Components Group Inc. shall not be responsible for any deviations from this drawing, any failure to build the trusses in conformance with ANSII/TPI 1, or for handling, storage, installation or securing of trusses.

This drawing contains no engineering information. The user assumes full responsibility for engineering responsibility solely for the design shown.

For any structure is the responsibility of the Building Designer per ANSII/TPI 1 Sec2.8.

For more information see this job's general notes page and these web sites:
ALPINE: www.alpineinc.com TPI: www.tpi.net SDCO: www.sdcointl.com

REF	PIGGYBACK
DATE	01/02/2018
DRWG	PB180160118

SPACING	24.0"
---------	-------

Cracked or Broken Member Repair Detail

This drawing specifies repairs for a truss with broken chord or web member.

This design is valid only for single ply trusses with 2x4 or 2x6 broken members. No more than one break per chord panel and no more than two breaks per truss are allowed. Contact the truss manufacturer for any repairs that do not comply with this detail.

(CB) = Damaged area, 12' max length of damaged section
(L) = Minimum nailing distance on each side of damaged area (B)
(S) = Two 2x4 or two 2x6 side members, same size, grade, and species as damaged member. Apply one scab per face.
Minimum side member length(s) = $(2 \times L) + (CB)$


Scab member length (S) must be within the broken panel.
Nail into 2x4 members using two (2) rows at 4" o.c., rows staggered.
Nail into 2x6 members using three (3) rows at 4" o.c., rows staggered.
Nail using 10d box or gun nails (0.128"x3", min) into each side member.

The maximum permitted lumber grade for use with this detail is limited to Visual grade #1 and MSR grade 1650f.


This repair detail may be used for broken connector plate at mid-panel splices.

This repair detail may not be used for damaged chord or web sections occurring within the connector plate area.

Broken chord may not support any tie-in loads.



Nail Spacing Detail



		Maximum Member Axial Force				
Member	Size	L	SPF-C	HF	DF-L	SYP
Web Only	2x4	12'	620#	635#	730#	800#
Web Only	2x4	18'	975#	1055#	1295#	1415#
Web or Chord	2x4	24'	975#	1055#	1495#	1745#
Web or Chord	2x6		1465#	1585#	2245#	2620#
Web or Chord	2x4	30'	1910#	1960#	2315#	2555#
Web or Chord	2x6		2230#	2365#	3125#	3575#
Web or Chord	2x4	36'	2470#	2530#	2930#	3210#
Web or Chord	2x6		3535#	3635#	4295#	4745#
Web or Chord	2x4	42'	2975#	3045#	3505#	3835#
Web or Chord	2x6		4395#	4500#	5225#	5725#
Web or Chord	2x4	48'	3460#	3540#	4070#	4445#
Web or Chord	2x6		5165#	5280#	6095#	6660#

ALPINE
AN ITW COMPANY

13723 Riverport Drive
Suite 200
Maryland Heights, MO 63043

IMPORTANT! READ AND FOLLOW ALL NOTES ON THIS DRAWING

Trusses require extreme care in fabricating, handling, shipping, installing and bracing. Refer to the latest edition of ICC Building Component Safety Information, by TPI and SCAQ for details. Trusses shall be installed in accordance with the manufacturer's instructions. Trusses shall have a properly attached rafter ceiling. Locations shown for permanent lateral restraint of web shall have bracing installed per ICC sections 83.37 or 810, as applicable. Apply plates to each end of truss and position as shown above and on the Joint Details, unless noted otherwise. Refer to drawing 100-1 for standard plate positions.

This drawing is the property of Alpine Truss Company. It shall not be reproduced for any device or purpose without the written consent of Alpine Truss Company. A seal on this drawing or cover page listing this drawing indicates acceptance of professional engineering responsibility solely for the design shown. The authority and use of this drawing for any other purpose is strictly prohibited. For more information see this job's title page and the notes.

ALPINE: www.alpine.com TPI: www.tpi.org SCAQ: www.scaq.org

STATE OF FLORIDA
PROFESSIONAL ENGINEER
No. 66848
J. LUCENSE

REF MEMBER REPAIR
DATE 10/01/14
DRWG REPCHRD1014

SPACING 24.0' MAX

6/7/2014

ASCE 7-10: 140 mph Wind Speed, 30' Mean Height, Enclosed, Exposure C, $K_{zt} = 1.00$

Qr 120 mph Wind Speed, 30' Mean Height, Partially Enclosed, Exposure C, Kzt = 1.00
Qr 120 mph Wind Speed, 30' Mean Height, Enclosed, Exposure D, Kzt = 1.00
Qr 100 mph wind speed, 30' Mean Height, Partially Enclosed, Exposure D, Kzt = 1.00

Bracing Group Species and Grades

Group A:

Spruce-Pine-Fir

#1 / #2	Standard
#3	Stud

Hem-Fir

#2	Stud
#3	Standard

Douglas Fir-Larch

#3	Stud
	Standard

Southern Pine

#3	Stud
	Standard

Group B:

Hem-Fir

#1 & #2	#1
---------	----

Douglas Fir-Larch

#1	#2
----	----

Southern Pine

#1	#2
----	----

1x4 Braces shall be S3B (Stress-Rated Board) or S4S (Select Structural) for 1x4 So. Pine use only Industrial S5 or Industrial 45 Stress-Rated Brads. Group B values may be used with these grades.

Gable Truss Detail Notes:

Wind Load deflection criterion is L/240.

Provide uplift connections for 100 plf over continuous bearing (5 psf TC Dead Load).

Gable end supports load from 4' 0" outlookers with 2' 0" overhang, or 12" plywood overhang.

Attach "L" braces with 10d (0.128"x3.0" min) nails.

* For (1) "L" brace; space nalls at 2' o.c.

In 18' end zones and 4' o.c. between zones

For (2) 'L' braces: space nalls at 3' o.c.

In 18' end zones and 6' o.c. between zones

"L" bracing must be a minimum of 80% of web

Vertical Length	No Splice
Less than 4' 0"	2X4
Greater than 4' 0", but less than 11' 6"	3X4
Greater than 11' 6"	4X4


+ Refer to common truss design for peak, splice, and heel plates.

Refer to the Building Designer for conditions not addressed by this detail.

REF	ASCE7-10-GABI4030
DATE	10/01/14
DRWG	A14030ENC101014

MAX. TOT. LD. 60 PSF

MAX. SPACING 24.0"



Refer to chart above for any applicable vertical length.

No 86848

STATE OF

STATE OF

EFF

FLORIDA



1998

1994

COA #0278

100

ALL WALLS SHOWN TO BE BEARING
 AMERICA'S HOME PLACE, INC.
 KRAMER RESIDENCE ~ VICTORIA MOD-FARM



SEMINOLE TRUSSES INC.
 30726 Bluestar Memorial Hwy.
 MIDWAY, FL 32040
 Phone 904.572.5412
 Fax 904.572.5413
 Design By Robert J. Little

Job Name: KRAMER RESIDENCE
 Customer: America's Home Place
 Designer: ROBERT J. LITTLE
 PlanName: VICTORIA MOD-FARM
 Created : 06-25-2020
 SemRef# : B51561a

JOB NO:
 B51561a

PAGE NO:
 1 OF 1