

FLORIDA ENERGY EFFICIENCY CODE FOR BUILDING CONSTRUCTION

Florida Department of Business and Professional Regulation - Residential Performance Method

Project Name: Lennardo Miller Residence		Builder Name: John F. Crawford Homes, LLC		
Street: 348 S.W. Sparrow Terrace	Permit Office: Columbia			
City, State, Zip: Lake City, FL, 32024	Permit Number:			
Owner: Lennardo Miller Residence	Jurisdiction: 221200			
Design Location: FL, Gainesville	County: Columbia(Florida Climate Zone 2)			
1. New construction or existing 2. Single family or multiple family 3. Number of units, if multiple family 4. Number of Bedrooms 5. Is this a worst case? 6. Conditioned floor area above grade (ft ²) Conditioned floor area below grade (ft ²) 7. Windows(366.0 sqft.) Description a. U-Factor: Dbl, U=0.47 SHGC: SHGC=0.31 b. U-Factor: Dbl, U=0.49 SHGC: SHGC=0.32 c. U-Factor: Dbl, U=0.31 SHGC: SHGC=0.24 Area Weighted Average Overhang Depth: Area Weighted Average SHGC: 8. Skylights Description U-Factor:(AVG) N/A SHGC(AVG): N/A 9. Floor Types Insulation Area a. Slab-On-Grade Edge Insulation R= 0.0 1914.80 ft ² b. Floor Over Other Space R= 0.0 20.00 ft ² c. N/A R=		10. Wall Types(2387.8 sqft.) a. Frame - Wood, Exterior b. Frame - Wood, Adjacent c. N/A d. N/A 11. Ceiling Types(1949.0 sqft.) a. Roof Deck (Unvented) b. N/A c. N/A 12. Roof(Comp. Shingles, Unvent)Deck R=30.0 2339 ft ² 13. Ducts, location & insulation level a. Sup: Attic, Ret: Attic, AH: Attic R ft ² b. c. 14. Cooling Systems a. Central Unit kBtu/hr Efficiency 47.0 SEER2:15.00 15. Heating Systems a. Electric Heat Pump kBtu/hr Efficiency 47.0 HSPF2:7.50 16. Hot Water Systems a. Electric Tankless Cap: 1 gallons b. Conservation features EF: 0.990 17. Credits None CF, Pstat		
Glass/Floor Area: 0.150		Total Proposed Modified Loads: 61.64 Total Baseline Loads: 66.95		PASS
NOTE: Proposed residence must have annual total normalized Modified Loads that are less than or equal to 95 percent of the annual total loads of the standard reference design in order to comply.				
I hereby certify that the plans and specifications covered by this calculation are in compliance with the Florida Energy Code.		Review of the plans and specifications covered by this calculation indicates compliance with the Florida Energy Code. Before construction is completed this building will be inspected for compliance with Section 553.908 Florida Statutes.		
PREPARED BY: <u>John Crawford</u>		BUILDING OFFICIAL: _____		
DATE: 12/04/2025		DATE: _____		
I hereby certify that this building, as designed, is in compliance with the Florida Energy Code.		OWNER/AGENT: <u>John Crawford</u>		
DATE: 12/8/2025		DATE: _____		

- Compliance requires certification by the air handler unit manufacturer that the air handler enclosure qualifies as certified factory-sealed in accordance with R403.3.2.1.
- Default duct leakage does not require a Duct Leakage Test Report.
- Compliance requires an Air Barrier and Insulation Inspection Checklist in accordance with R402.4.1.1 and this project requires a PERFORMANCE envelope leakage test report with envelope leakage no greater than 5.12 ACH50 (R402.4.1.2).

INPUT SUMMARY CHECKLIST REPORT**PROJECT**

Title:	Lennardo Miller Residence	Address type:	Street Address
Building Type:	User	Lot #:	---
Owner:	Lennardo Miller Residence	Block/SubDivision:	---
Builder Home ID:		PlatBook:	---
Builder Name:	John F. Crawford Homes, LLC	Street:	348 S.W. Sparrow Terrace
Permit Office:	Columbia	County:	Columbia
Jurisdiction:	221200	City, State, Zip:	Lake City, FL, 32024
Family Type:	Detached		
New/Existing:	New (From Plans)		
Year Construct:	2025		
Comment:			

CLIMATE

✓ Design Location	Tmy Site	Design Temp		Int Design Temp		Heating Degree Days	Design Moisture	Daily temp Range
		97.5%	2.5%	Winter	Summer			
FL, Gainesville	FL_GAINESVILLE_REGIONA	32	92	70	75	1305.5	51	Medium

BLOCKS

✓ Number	Name	Area	Volume
1	Entire House	2435	23099 cu ft

SPACES

✓ Number	Name	Area	Volume	Kitchen	Occupants	Bedrooms	Finished	Cooled	Heated
1	Mstr Bedroom	175	1750	No	2	1	Yes	Yes	Yes
2	Mstr Bathrm	116	1044	No	0		Yes	Yes	Yes
3	Tlt	18	162	No	0		No	Yes	Yes
4	Mstr WIC	110	990	No	0		No	Yes	Yes
5	Bathrm #2	61	549	No	0		Yes	Yes	Yes
6	Bedroom #2	151	1359	No	1	1	Yes	Yes	Yes
7	Study	116	1044	No	0		Yes	Yes	Yes
8	Foyer	123	1107	No	0		Yes	Yes	Yes
9	Laundry	65	585	No	0		No	Yes	Yes
10	Pantry	33	297	No	0		Yes	Yes	Yes
11	Pwdr	33	297	No	0		No	Yes	Yes
12	Mud Room	60	480	No	0		No	Yes	Yes
13	Kitchen/Dine	294	2940	Yes	0		Yes	Yes	Yes
14	Living Room	562	6351	No	0		Yes	Yes	Yes
15	Bedroom #4	138	1104	No	1	1	Yes	Yes	Yes
16	Loft	175	1400	No	0		Yes	Yes	Yes
17	Bathrm #3	63	504	No	0		Yes	Yes	Yes
18	Bedroom #3	142	1136	No	1	1	Yes	Yes	Yes

INPUT SUMMARY CHECKLIST REPORT

FLOORS (Total Exposed Area = 1915 sq.ft.)															
✓ #	Floor Type	Space	Exposed Perim(ft)	Area	R-Value Perim.	U-Factor Joist	Slab Insul. Vert/Horiz	Tile	Wood	Carpet					
— 1	Slab-On-Grade Edge Ins	Mstr Bedroom	26.5	175 sqft	0.0	---	0.473	2 (ft)/0 (ft)	0.00	1.00	0.00				
— 2	Slab-On-Grade Edge Ins	Mstr Bathrm	11	115.5 sqft	0.0	---	0.473	2 (ft)/0 (ft)	0.00	1.00	0.00				
— 3	Slab-On-Grade Edge Ins	Tlt	1	17.5 sqft	0.0	---	0.473	2 (ft)/0 (ft)	0.00	1.00	0.00				
— 4	Slab-On-Grade Edge Ins	Mstr WIC	1	110 sqft	0.0	---	0.473	2 (ft)/0 (ft)	0.00	1.00	0.00				
— 5	Slab-On-Grade Edge Ins	Bathrm #2	14	60.5 sqft	0.0	---	0.473	2 (ft)/0 (ft)	0.00	1.00	0.00				
— 6	Slab-On-Grade Edge Ins	Bedroom #2	25.5	151 sqft	0.0	---	0.473	2 (ft)/0 (ft)	0.00	1.00	0.00				
— 7	Slab-On-Grade Edge Ins	Study	21.5	115.5 sqft	0.0	---	0.473	2 (ft)/0 (ft)	0.00	1.00	0.00				
— 8	Slab-On-Grade Edge Ins	Foyer	4.5	122.5 sqft	0.0	---	0.473	2 (ft)/0 (ft)	0.00	1.00	0.00				
— 9	Slab-On-Grade Edge Ins	Laundry	4.5	65.3 sqft	0.0	---	0.473	2 (ft)/0 (ft)	0.00	1.00	0.00				
— 10	Slab-On-Grade Edge Ins	Pantry	11.5	33 sqft	0.0	---	0.473	2 (ft)/0 (ft)	0.00	1.00	0.00				
— 11	Slab-On-Grade Edge Ins	Pwdr	5.5	33 sqft	0.0	---	0.473	2 (ft)/0 (ft)	0.00	1.00	0.00				
— 12	Slab-On-Grade Edge Ins	Mud Room	7.5	60 sqft	0.0	---	0.473	2 (ft)/0 (ft)	0.00	1.00	0.00				
— 13	Slab-On-Grade Edge Ins	Kitchen/Dine	36.5	294 sqft	0.0	---	0.473	2 (ft)/0 (ft)	0.00	1.00	0.00				
— 14	Slab-On-Grade Edge Ins	Living Room	21.5	562 sqft	0.0	---	0.473	2 (ft)/0 (ft)	0.00	1.00	0.00				
— 15	Floor Over Other Space	Bedroom #4	---	4 sqft	---	0.0	0.220	-----	0.00	1.00	0.00				
— 16	Floor Over Other Space	Bedroom #4	---	16 sqft	---	0.0	0.220	-----	0.00	1.00	0.00				
ROOF															
✓ #	Type	Materials	Roof Area	Gable Area	Framing. Fract.	Roof Color	Rad Barr	Solar Absor.	SA Tested	Emiss	Emiss Tested	Deck Insul.	Pitch (deg)		
— 1	Hip	Composition shingles	2339 ft ²	0 ft ²	0.00	Medium	N	0.9	No	0.9	No	30	33.69		
ATTIC															
✓ #	Type	Ventilation	Vent Ratio (1 in)			Area		RBS		IRCC					
— 1	Full attic	Unvented	0			1946 ft ²		N		N					
CEILING (Total Exposed Area = 1949 sq.ft.)															
✓ #	Ceiling Type	Space	R-Value	Ins. Type	Area	U-Factor	Framing Frac.		Truss Type						
— 1	Flat ceiling under attic(Unvented)	Mstr Bedroom	0.0	Blown	175.0ft ²	0.052	0.00		Wood						
— 2	Flat ceiling under attic(Unvented)	Mstr Bathrm	0.0	Blown	42.0ft ²	0.052	0.00		Wood						
— 3	Flat ceiling under attic(Unvented)	Tlt	0.0	Blown	2.0ft ²	0.052	0.00		Wood						
— 4	Flat ceiling under attic(Unvented)	Mstr WIC	0.0	Blown	60.0ft ²	0.052	0.00		Wood						
— 5	Flat ceiling under attic(Unvented)	Bathrm #2	0.0	Blown	45.0ft ²	0.052	0.00		Wood						
— 6	Flat ceiling under attic(Unvented)	Bedroom #2	0.0	Blown	141.0ft ²	0.052	0.00		Wood						
— 7	Flat ceiling under attic(Unvented)	Study	0.0	Blown	2.0ft ²	0.052	0.00		Wood						
— 8	Flat ceiling under attic(Unvented)	Foyer	0.0	Blown	9.0ft ²	0.052	0.00		Wood						
— 9	Flat ceiling under attic(Unvented)	Pantry	0.0	Blown	33.0ft ²	0.052	0.00		Wood						
— 10	Flat ceiling under attic(Unvented)	Pwdr	0.0	Blown	33.0ft ²	0.052	0.00		Wood						
— 11	Flat ceiling under attic(Unvented)	Mud Room	0.0	Blown	33.0ft ²	0.052	0.00		Wood						
— 12	Flat ceiling under attic(Unvented)	Kitchen/Dine	0.0	Blown	96.0ft ²	0.052	0.00		Wood						
— 13	Flat ceiling under attic(Unvented)	Kitchen/Dine	0.0	Blown	198.0ft ²	0.052	0.00		Wood						
— 14	Flat ceiling under attic(Unvented)	Living Room	0.0	Blown	99.0ft ²	0.052	0.00		Wood						
— 15	Flat ceiling under attic(Unvented)	Living Room	0.0	Blown	463.0ft ²	0.052	0.00		Wood						
— 16	Flat ceiling under attic(Unvented)	Bedroom #4	0.0	Blown	138.0ft ²	0.052	0.00		Wood						
— 17	Flat ceiling under attic(Unvented)	Loft	0.0	Blown	175.0ft ²	0.052	0.00		Wood						
— 18	Flat ceiling under attic(Unvented)	Bathrm #3	0.0	Blown	63.0ft ²	0.052	0.00		Wood						
— 19	Flat ceiling under attic(Unvented)	Bedroom #3	0.0	Blown	142.0ft ²	0.052	0.00		Wood						

INPUT SUMMARY CHECKLIST REPORT**WALLS**

(Total Exposed Area = 2388 sq.ft.)

✓ #	Ornt	Adjacent To	Wall Type	Space	Cavity R-Value	Width Ft	Width In	Height Ft	Height In	Area sq.ft.	U-Factor	Sheath R-Value	Frm. Frac.	Solar Absor.	Below Grade
___ 1	S	Exterior	Frame - Wood	Mstr Bedroom	13.0	12.0	6	10.0	0	125.0	0.095	0	0.25	0.23	0.0 %
___ 2	W	Exterior	Frame - Wood	Mstr Bedroom	13.0	14.0	0	10.0	0	140.0	0.095	0	0.25	0.23	0.0 %
___ 3	S	Exterior	Frame - Wood	Mstr Bathrm	13.0	11.0	0	9.0	0	99.0	0.095	0	0.25	0.23	0.0 %
___ 4	E	Exterior	Frame - Wood	Bathrm #2	13.0	1.0	6	9.0	0	13.5	0.095	0	0.25	0.23	0.0 %
___ 5	S	Exterior	Frame - Wood	Bathrm #2	13.0	11.0	0	9.0	0	99.0	0.095	0	0.25	0.23	0.0 %
___ 6	W	Exterior	Frame - Wood	Bathrm #2	13.0	1.0	6	9.0	0	13.5	0.095	0	0.25	0.23	0.0 %
___ 7	E	Exterior	Frame - Wood	Bedroom #2	13.0	14.0	0	9.0	0	126.0	0.095	0	0.25	0.23	0.0 %
___ 8	S	Exterior	Frame - Wood	Bedroom #2	13.0	11.0	6	9.0	0	103.5	0.095	0	0.25	0.23	0.0 %
___ 9	E	Exterior	Frame - Wood	Study	13.0	10.0	6	9.0	0	94.5	0.095	0	0.25	0.23	0.0 %
___ 10	E	Exterior	Frame - Wood	Foyer	13.0	4.0	6	9.0	0	40.5	0.095	0	0.25	0.23	0.0 %
___ 11	N	Exterior	Frame - Wood	Pantry	13.0	6.0	0	9.0	0	54.0	0.095	0	0.25	0.23	0.0 %
___ 12	N	Exterior	Frame - Wood	Kitchen/Dine	13.0	24.0	6	10.0	0	245.0	0.095	0	0.25	0.23	0.0 %
___ 13	W	Exterior	Frame - Wood	Kitchen/Dine	13.0	12.0	0	10.0	0	120.0	0.095	0	0.25	0.23	0.0 %
___ 14	W	Exterior	Frame - Wood	Living Room	13.0	19.0	0	11.0	4	215.3	0.095	0	0.25	0.23	0.0 %
___ 15	E	Exterior	Frame - Wood	Bedroom #4	13.0	12.0	6	8.0	0	100.0	0.095	0	0.25	0.23	0.0 %
___ 16	S	Exterior	Frame - Wood	Bedroom #4	13.0	11.0	0	8.0	0	88.0	0.095	0	0.25	0.23	0.0 %
___ 17	W	Exterior	Frame - Wood	Bedroom #4	13.0	12.0	6	8.0	0	100.0	0.095	0	0.25	0.23	0.0 %
___ 18	S	Exterior	Frame - Wood	Loft	13.0	7.0	0	8.0	0	56.0	0.095	0	0.25	0.23	0.0 %
___ 19	E	Exterior	Frame - Wood	Bathrm #3	13.0	6.0	0	8.0	0	48.0	0.095	0	0.25	0.23	0.0 %
___ 20	S	Exterior	Frame - Wood	Bathrm #3	13.0	10.0	6	8.0	0	84.0	0.095	0	0.25	0.23	0.0 %
___ 21	E	Exterior	Frame - Wood	Bedroom #3	13.0	12.0	6	8.0	0	100.0	0.095	0	0.25	0.23	0.0 %
___ 22	S	Exterior	Frame - Wood	Bedroom #3	13.0	1.0	0	8.0	0	8.0	0.095	0	0.25	0.23	0.0 %
___ 23	N	Garage	Frame - Wood	Study	13.0	16.0	0	9.0	0	144.0	0.084	0.23	0.23	0.0 %	
___ 24	N	Garage	Frame - Wood	Mud Room	13.0	19.0	0	9.0	0	171.0	0.084	0.23	0.23	0.0 %	

DOORS

(Total Exposed Area = 20 sq.ft.)

✓ #	Ornt	Adjacent To	Door Type	Space	Storms	U-Value	Width Ft	Width In	Height Ft	Height In	Area
___ 1	N	Garage	Wood	Mud Room	Metal	0.46	3.00	0	6.00	8	20.0ft ²

WINDOWS

(Total Exposed Area = 366 sq.ft.)

✓ #	Ornt	Wall ID	Frame	Panes	NFRC	U-Factor	SHGC	Imp	Storm	Total Area (ft ²)	Same Units	Width (ft)	Height (ft)	--Overhang-- Depth (ft)	Sep. (ft)	Interior Shade	Screen
___ 1	S	1	Vinyl	Low-E Double	Y	0.47	0.31	N	N	24.0	2	2.00	6.00	1.5	1.3	Drapes/blinds	Ex. 50%
___ 2	W	2	Vinyl	Low-E Double	Y	0.47	0.31	N	N	36.0	2	3.00	6.00	1.5	1.3	Drapes/blinds	Ex. 50%
___ 3	S	3	Vinyl	Low-E Double	Y	0.45	0.36	N	N	16.0	1	4.00	4.00	1.5	1.3	None	None
___ 4	S	5	Vinyl	Low-E Double	Y	0.47	0.31	N	N	8.0	1	2.00	4.00	1.5	1.3	Drapes/blinds	Ex. 50%
___ 5	E	7	Vinyl	Low-E Double	Y	0.47	0.31	N	N	36.0	2	3.00	6.00	1.5	1.3	Drapes/blinds	Ex. 50%
___ 6	E	9	Vinyl	Low-E Double	Y	0.47	0.31	N	N	30.0	2	2.50	6.00	5.0	1.3	Drapes/blinds	Ex. 50%
___ 7	E	10	Vinyl	Low-E Double	Y	0.49	0.32	N	N	18.0	1	3.00	6.00	5.0	1.3	None	None
___ 8	N	12	Vinyl	Low-E Double	Y	0.45	0.36	N	N	16.0	1	4.00	4.00	1.5	1.3	None	None
___ 9	W	13	Vinyl	Low-E Double	Y	0.47	0.31	N	N	54.0	3	3.00	6.00	1.5	1.3	Drapes/blinds	Ex. 50%
___ 10W		14	Vinyl	Low-E Double	Y	0.49	0.32	N	N	32.0	1	5.33	6.00	8.0	1.3	None	None
___ 11W		14	Vinyl	Low-E Double	Y	0.47	0.31	N	N	54.0	3	3.00	6.00	8.0	1.3	Drapes/blinds	Ex. 50%
___ 12S		16	Vinyl	Low-E Double	Y	0.31	0.24	N	N	15.0	1	3.00	5.00	1.5	1.3	Drapes/blinds	Ex. 50%
___ 13E		19	Vinyl	Low-E Double	Y	0.45	0.36	N	N	3.0	1	3.00	1.00	1.5	1.3	None	None
___ 14E		21	Vinyl	Low-E Double	Y	0.31	0.24	N	N	24.0	2	3.00	4.00	1.5	1.3	Drapes/blinds	Ex. 50%

INFILTRATION

✓ #	Scope	Method	SLA	CFM50	ELA	EqLA	ACH	ACH50	Space(s)	Infiltration Test Volume
___ 1	Wholehouse	Proposed ACH(50)	0.00031	1971	108.14	203.02	0.1417	5.1	All	23099 cu ft

INPUT SUMMARY CHECKLIST REPORT**GARAGE**

✓ #	Floor Area	Length	Width	Roof Area	Exposed Perimeter	Area Under Uncond.	Avg. Wall Height	Exposed Wall Insulation
___ 1	411 ft ²	25.0 ft ²	16.4 ft ²	411 ft ²	49 ft	411 ft	9 ft	13

MASS

✓ #	Mass Type	Area	Thickness	Furniture Fraction	Space
___ 1	Default(8 lbs/sq.ft.)	0 ft ²	0 ft	0.30	Mstr Bedroom
___ 2	Default(8 lbs/sq.ft.)	0 ft ²	0 ft	0.30	Mstr Bathrm
___ 3	Default(8 lbs/sq.ft.)	0 ft ²	0 ft	0.30	Tlt
___ 4	Default(8 lbs/sq.ft.)	0 ft ²	0 ft	0.30	Mstr WIC
___ 5	Default(8 lbs/sq.ft.)	0 ft ²	0 ft	0.30	Bathrm #2
___ 6	Default(8 lbs/sq.ft.)	0 ft ²	0 ft	0.30	Bedroom #2
___ 7	Default(8 lbs/sq.ft.)	0 ft ²	0 ft	0.30	Study
___ 8	Default(8 lbs/sq.ft.)	0 ft ²	0 ft	0.30	Foyer
___ 9	Default(8 lbs/sq.ft.)	0 ft ²	0 ft	0.30	Laundry
___ 10	Default(8 lbs/sq.ft.)	0 ft ²	0 ft	0.30	Pantry
___ 11	Default(8 lbs/sq.ft.)	0 ft ²	0 ft	0.30	Pwdr
___ 12	Default(8 lbs/sq.ft.)	0 ft ²	0 ft	0.30	Mud Room
___ 13	Default(8 lbs/sq.ft.)	0 ft ²	0 ft	0.30	Kitchen/Dine
___ 14	Default(8 lbs/sq.ft.)	0 ft ²	0 ft	0.30	Living Room
___ 15	Default(8 lbs/sq.ft.)	0 ft ²	0 ft	0.30	Bedroom #4
___ 16	Default(8 lbs/sq.ft.)	0 ft ²	0 ft	0.30	Loft
___ 17	Default(8 lbs/sq.ft.)	0 ft ²	0 ft	0.30	Bathrm #3
___ 18	Default(8 lbs/sq.ft.)	0 ft ²	0 ft	0.30	Bedroom #3

HEATING SYSTEM

✓ #	System Type	Subtype/Speed	AHRI #	Efficiency	Capacity kBtu/hr	----Geothermal Entry	HeatPump Power	HeatPump Volt	HeatPump Current	Ducts	Block
___ 1	Electric Heat Pump	Split/Single		HSPF2: 7.50	47.0		0.00	0.00	0.00	sys#1	1

COOLING SYSTEM

✓ #	System Type	Subtype/Speed	AHRI #	Efficiency	Capacity kBtu/hr	Air Flow cfm	SHR	Duct	Block
___ 1	Central Unit	Split/Single		SEER2:15.0	47.0	1600	0.70	sys#1	1

HOT WATER SYSTEM

✓ #	System Type	Subtype	Location	EF(UEF)	Cap	Use	SetPnt	Fixt. Flow	Trap	Pipe Ins.	Pipe length
___ 1	Electric	Tankless	Attic	0.99 (0.99)	1.0 gal	55 gal	120 deg	Low	Yes	None	109
	Recirculation System	Recirc Control Type		Loop length	Branch length	Pump power	DWHR	Facilities Connected	Equal Flow	DWHR Eff	Other Credits
___ 1	No			NA	NA	NA	No	NA	NA	NA	None

DUCTS

✓ Duct #	Supply Location	R-Value	Area	Return Location	R-Value	Area	Leakage Type	AHU Location	CFM 25 TOT OUT	QN OUT	AHU SEALED	RLF	HVAC # Heat Cool
___ 1	Attic	6.0	117 ft ²	Attic	6.0	51 ft ²	Default Leakage	Attic	(Default)	(Default)			1 1

INPUT SUMMARY CHECKLIST REPORT

TEMPERATURES															
Programable Thermostat: Y				Ceiling Fans: N											
Cooling	<input type="checkbox"/> Jan	<input type="checkbox"/> Feb	<input type="checkbox"/> Mar	<input type="checkbox"/> Apr	<input type="checkbox"/> May	<input checked="" type="checkbox"/> Jun	<input type="checkbox"/> Jul	<input type="checkbox"/> Aug	<input type="checkbox"/> Sep	<input type="checkbox"/> Oct	<input type="checkbox"/> Nov	<input type="checkbox"/> Dec			
Heating	<input checked="" type="checkbox"/> Jan	<input checked="" type="checkbox"/> Feb	<input checked="" type="checkbox"/> Mar	<input type="checkbox"/> Apr	<input type="checkbox"/> May	<input type="checkbox"/> Jun	<input type="checkbox"/> Jul	<input type="checkbox"/> Aug	<input type="checkbox"/> Sep	<input type="checkbox"/> Oct	<input checked="" type="checkbox"/> Nov	<input checked="" type="checkbox"/> Dec			
Venting	<input type="checkbox"/> Jan	<input type="checkbox"/> Feb	<input checked="" type="checkbox"/> Mar	<input type="checkbox"/> Apr	<input type="checkbox"/> May	<input type="checkbox"/> Jun	<input type="checkbox"/> Jul	<input type="checkbox"/> Aug	<input type="checkbox"/> Sep	<input checked="" type="checkbox"/> Oct	<input checked="" type="checkbox"/> Nov	<input type="checkbox"/> Dec			
✓ Thermostat Schedule: HERS 2006 Reference				Hours											
Schedule Type				1	2	3	4	5	6	7	8	9	10	11	12
— Cooling (WD)	AM	78	78	78	78	78	78	78	78	78	78	80	80	80	80
— Cooling (WEH)	PM	80	80	78	78	78	78	78	78	78	78	78	78	78	78
— Heating (WD)	AM	78	78	78	78	78	78	78	78	78	78	78	78	78	78
— Heating (WEH)	PM	78	78	78	78	78	78	78	78	78	78	78	78	78	78
— Cooling (WD)	AM	66	66	66	66	66	66	66	66	66	66	68	68	68	68
— Cooling (WEH)	PM	68	68	68	68	68	68	68	68	68	68	68	68	68	68
— Heating (WD)	AM	66	66	66	66	66	66	66	66	66	66	68	68	68	68
— Heating (WEH)	PM	68	68	68	68	68	68	68	68	68	68	68	68	68	68

ENERGY PERFORMANCE LEVEL (EPL) DISPLAY CARD

ESTIMATED ENERGY PERFORMANCE INDEX* = 92

The lower the Energy Performance Index, the more efficient the home.

348 S.W. Sparrow Terrace, Lake City, FL, 32024

1. New construction or existing	New (From Plans)	10. Wall Types(2387.8 sqft.)	Insulation	Area
2. Single family or multiple family	Detached	a. Frame - Wood, Exterior	R=13.0	2072.80 ft ²
3. Number of units, if multiple family	1	b. Frame - Wood, Adjacent	R=13.0	315.00 ft ²
4. Number of Bedrooms	4	c. N/A		
5. Is this a worst case?	No	d. N/A		
6. Conditioned floor area above grade (ft ²)	2435	11. Ceiling Types(1949.0 sqft.)	Insulation	Area
Conditioned floor area below grade (ft ²)	0	a. Roof Deck (Unvented)	R=30.0	1949.00 ft ²
7. Windows**	Description	b. N/A		
a. U-Factor:	Dbl, U=0.47	c. N/A		
SHGC:	SHGC=0.31	12. Roof(Comp. Shingles, Unvent)Deck	R=30.0	2339 ft ²
b. U-Factor:	Dbl, U=0.49	13. Ducts, location & insulation level	R	ft ²
SHGC:	SHGC=0.32	a. Sup: Attic, Ret: Attic, AH: Attic	6	117
c. U-Factor:	Dbl, U=0.31	b.		
SHGC:	SHGC=0.24	c.		
Area Weighted Average Overhang Depth:	3.486 ft	14. Cooling Systems	kBtu/hr	Efficiency
Area Weighted Average SHGC:	0.309	a. Central Unit	47.0	SEER2:15.00
8. Skylights	Description	15. Heating Systems	kBtu/hr	Efficiency
U-Factor:(AVG)	N/A	a. Electric Heat Pump	47.0	HSPF2:7.50
SHGC(AVG):	N/A	16. Hot Water Systems		
9. Floor Types	Insulation	a. Electric Tankless		
a. Slab-On-Grade Edge Insulation	R= 0.0	17. Credits	Cap: 1 gallons	
b. Floor Over Other Space	R= 0.0	b. Conservation features	EF: 0.990	
c. N/A	R=			
				None
				CF, Pstat

I certify that this home has complied with the Florida Energy Efficiency Code for Building Construction through the above energy saving features which will be installed (or exceeded) in this home before final inspection. Otherwise, a new EPL Display Card will be completed based on installed Code compliant features.

Builder Signature: John Crawford Date: 12/8/2025

Address of New Home: 348 S.W. Sparrow Terrace City/FL Zip: Lake City, FL, 32024



*Note: This is not a Building Energy Rating. If your Index is below 70, your home may qualify for energy efficient mortgage (EEM) incentives if you obtain a Florida Energy Rating. For information about the Florida Building Code, Energy Conservation, contact the Florida Building Commission's support staff.

**Label required by Section R303.1.3 of the Florida Building Code, Energy Conservation, if not DEFAULT.

2023 - AIR BARRIER AND INSULATION INSPECTION COMPONENT CRITERIA-TABLE 402.4.1.1^a

Project Name:	Lennardo Miller Residence	Builder Name:	John F. Crawford Homes, LLC
Street:	348 S.W. Sparrow Terrace	Permit Office:	Columbia
City, State, Zip:	Lake City, FL, 32024	Permit Number:	
Owner:	Lennardo Miller Residence	Jurisdiction:	221200
Design Location:	FL, Gainesville	County:	Columbia(Florida Climate Zone 2)
COMPONENT	AIR BARRIER CRITERIA	INSULATION INSTALLATION CRITERIA	IEC
General requirements	A continuous air barrier shall be installed in the building envelope. The exterior thermal envelope contains a continuous air barrier. Breaks or joints in the air barrier shall be sealed.	Air-permeable insulation shall not be used as a sealing material.	IEC
Ceiling/attic	The air barrier in any dropped ceiling/soffit shall be aligned with the insulation and any gaps in the air barrier shall be sealed. Access openings, drop down stairs or knee wall doors to unconditioned attic spaces shall be sealed.	The insulation in any dropped ceiling/soffit shall be aligned with the air barrier.	
Walls	The junction of the foundation and sill plate shall be sealed. The junction of the top plate and the top of exterior walls shall be sealed. Knee walls shall be sealed.	Cavities within corners and headers of frame walls shall be insulated by completely filling the cavity with a material having a thermal resistance of R-3 per inch minimum Exterior thermal envelope insulation for framed walls shall be installed in substantial contact and continuous alignment with the air barrier.	
Windows, skylights and doors	The space between window/door jambs and framing, and skylights and framing shall be sealed.		
Rim joists	Rim joists shall include the air barrier.	Rim joists shall be insulated.	
Floors (including above-garage and cantilevered floors)	The air barrier shall be installed at any exposed edge of insulation.	Floor framing cavity insulation shall be installed to maintain permanent contact with the underside of subfloor decking, or floor framing cavity insulation shall be permitted to be in contact with the top side of sheathing, or continuous insulation installed on the underside of floor framing and extends from the bottom to the top of all perimeter floor framing members.	
Crawl space walls	Exposed earth in unvented crawl spaces shall be covered with a Class I vapor retarder with overlapping joints taped.	Where provided instead of floor insulation, insulation shall be permanently attached to the crawlspace walls.	
Shafts, penetrations	Duct shafts, utility penetrations, and flue shafts opening to exterior or unconditioned space shall be sealed.		
Narrow cavities		Batts in narrow cavities shall be cut to fit, or narrow cavities shall be filled by insulation that on installation readily conforms to the available cavity spaces.	
Garage separation	Air sealing shall be provided between the garage and conditioned spaces.		
Recessed lighting	Recessed light fixtures installed in the building thermal envelope shall be sealed to the finished surface.	Recessed light fixtures installed in the building thermal envelope shall be air tight and IC rated.	
Plumbing and wiring		Batt insulation shall be cut neatly to fit around wiring and plumbing in exterior walls, or insulation that on installation readily conforms to available space shall extend behind piping and wiring.	
Shower/tub on exterior wall	The air barrier installed at exterior walls adjacent to showers and tubs shall separate them from the showers and tubs.	Exterior walls adjacent to showers and tubs shall be insulated.	
Electrical, communication, and other equipment boxes, housings, and enclosures	Boxes, housings, and enclosures that penetrate the air barrier shall be caulked, taped, gasketed, or otherwise sealed to the air barrier element being penetrated. All concealed openings into the box, housing, or enclosure shall be sealed. The continuity of the air barrier shall be maintained around boxes, housings, and enclosures that penetrate the air barrier. Alternatively, air-sealed boxes shall be installed in accordance with R402.4.6	Boxes, housings, and enclosures shall be buried in or surrounded by tightly fitted insulation.	
HVAC register boots	HVAC supply and return register boots that penetrate building thermal envelope shall be sealed to the sub-floor, wall covering or ceiling penetrated by the boot.		
Concealed sprinklers	When required to be sealed, concealed fire sprinklers shall only be sealed in a manner that is recommended by the manufacturer. Caulking or other adhesive sealants shall not be used to fill voids voids between fire sprinkler cover plates and walls or ceilings.		

a. In addition, inspection of log walls shall be in accordance with the provisions of ICC-400.

12/4/2025 10:48:50 AM EnergyGauge® USA 8.0.00 - FlaRes2023 FBC 8th Edition (2023) Compliant Software

Page 1



Certificate of Product Ratings

AHRI Certified Reference Number : 214101900 Date : 12-04-2025 Model Status : Active

AHRI Type : HRCU-A-CB (Split System: Heat Pump with Remote Outdoor Unit-Air-Source)

Series : 15 SEER2 HP

Outdoor Unit Brand Name : CARRIER

Outdoor Unit Model Number (Condenser or Single Package) : GH5SAN548**AA*

Indoor Unit Model Number (Evaporator and/or Air Handler) : FJ5AN*C48L*

The manufacturer of this CARRIER product is responsible for the rating of this system combination.

Rated as follows in accordance with the latest edition of AHRI 210/240 – 2024, Performance Rating of Unitary Air-Conditioning & Air-Source Heat Pump Equipment and subject to rating accuracy by AHRI-sponsored, independent, third party testing:

Cooling Capacity (A_{Full}) – Single or High Stage (95F), btuh : 47000

SEER2 : 15.00

EER2 (A_{Full}) – Single or High Stage (95F) : 12.00

Heating Capacity (H1_{Full}) – Single or High Stage (47F), btuh : 47500

HSPF2 (Region IV) : 7.50



†"Active" Model Status are those that an AHRI Certification Program Participant is currently producing AND selling or offering for sale; OR new models that are being marketed but are not yet being produced."Production Stopped" Model Status are those that an AHRI Certification Program Participant is no longer producing BUT is still selling or offering for sale.

Ratings that are accompanied by WAS indicate an involuntary re-rate. The new published rating is shown along with the previous (i.e. WAS) rating.

The Department of Energy has published updated energy efficiency metrics for central air conditioners and heat pumps. This publication reflects both the 1987 metric (SEER) and the 2023 metric (SEER2). Efficiency requirements are published at 10 C.F.R. 430.32(c). Please refer to www.AHRI.net for more information about updated energy efficiency metrics.

DISCLAIMER

AHRI does not endorse the product(s) listed on this Certificate and makes no representations, warranties or guarantees as to, and assumes no responsibility for, the product(s) listed on this Certificate. AHRI expressly disclaims all liability for damages of any kind arising out of the use or performance of the product(s), or the unauthorized alteration of data listed on this Certificate. Certified ratings are valid only for models and configurations listed in the directory at www.ahridirectory.org.

TERMS AND CONDITIONS

This Certificate and its contents are proprietary products of AHRI. This Certificate shall only be used for individual, personal and confidential reference purposes. The contents of this Certificate may not, in whole or in part, be reproduced; copied; disseminated; entered into a computer database; or otherwise utilized, in any form or manner or by any means, except for the user's individual, personal and confidential reference.

CERTIFICATE VERIFICATION

The information for the model cited on this certificate can be verified at www.ahridirectory.org, click on "Verify Certificate" link and enter the AHRI Certified Reference Number and the date on which the certificate was issued, which is listed above, and the Certificate No., which is listed at bottom right.



we make life better™

14080 S.E. 122nd Lane Road, Ocklawaha, FL 32179 Phone: (352) 288 - 0686 Fax: (352) 288 - 0684 Email: john.newage@gmail.com

Project Information

For: John F Crawford Homes, LLC
 1083 Bessent Road, Starke, FL 32091
 Phone: (904) 338 - 5683
 Email: crawforddevelopmentgroup@gmail.com

Design Information

	Htg	Clg	Infiltration	
Outside db (°F)	33	92	Method	Simplified
Inside db (°F)	68	75	Construction quality	Semi-tight
Design TD (°F)	35	17	Fireplaces	0
Daily range	-	M		
Inside humidity (%)	50	50		
Moisture difference (gr/lb)	29	47		

HEATING EQUIPMENT

Make Carrier
 Trade 15 SEER2 HP
 Model GH5SAN54800AA0
 AHRI ref 214101900

Efficiency 7.5 HSPF2
 Heating input
 Heating output 47500 Btuh @ 47°F
 Temperature rise 27 °F
 Actual air flow 1600 cfm
 Air flow factor 0.047 cfm/Btuh
 Static pressure 0.51 in H2O
 Space thermostat
 Capacity balance point = 28 °F

Backup:

Input = 10 kW, Output = 34121 Btuh, 100 AFUE

COOLING EQUIPMENT

Make Carrier
 Trade 15 SEER2 HP
 Cond GH5SAN54800AA0
 Coil FJ5ANXC48L15
 AHRI ref 214101900



Efficiency 12.0 EER2, 15 SEER2
 Sensible cooling 32900 Btuh
 Latent cooling 14100 Btuh
 Total cooling 47000 Btuh
 Actual air flow 1600 cfm
 Air flow factor 0.049 cfm/Btuh
 Static pressure 0.51 in H2O
 Load sensible heat ratio 0.80

ROOM NAME	Area (ft ²)	Htg load (Btuh)	Clg load (Btuh)	Htg AVF (cfm)	Clg AVF (cfm)
Mstr Bedroom	175	4210	3912	196	193
Mstr Bathrm	116	1468	574	68	28
Tlt	18	50	24	2	1
Mstr WIC	110	108	67	5	3
Bathrm #2	61	1666	494	78	24
Bedroom #2	151	3496	3074	163	151
Study	116	2538	2293	118	113
Foyer	123	794	641	37	32
Laundry	65	389	1012	18	50
Pantry	33	1145	277	53	14
Pwdr	33	521	128	24	6
Mud Room	60	924	889	43	44
Kitchen/Dine	294	5633	5782	263	285
Living Room	562	5405	6742	252	332

Calculations approved by ACCA to meet all requirements of Manual J 8th Ed.

Bedroom #4	138	2297	1944	107	96
Loft	175	1061	1699	50	84
Bathrm #3	63	936	578	44	28
Bedroom #3	142	1664	2367	78	117
Entire House	2432	34305	32498	1600	1600
Other equip loads		3783	3565		
Equip. @ 0.97 RSM			34982		
Latent cooling			9235		
TOTALS	2432	38088	44217	1600	1600

Calculations approved by ACCA to meet all requirements of Manual J 8th Ed.



Job #: Lennardo Miller Residence
Performed by John Pirk for:


John F Crawford Homes, LLC
1083 Bessent Road
Starke, FL 32091
Phone: (904) 338 - 5683
crawforddevelopmentgroup@gmail.com

New Age Dimensions, LLC.


14080 S.E. 122nd Lane Road
Ocklawaha, FL 32179
Phone: (352) 288 - 0686 Fax: (352) 288 - 0684
john.newage@gmail.com

Scale: 1 : 107

Page 1
Right-Suite® Universal 2024
24.0.03 RSU02050
2025-Dec-04 10:25:44
...up\Lennardo Miller Residence.rup



2nd Floor



Manual J was calculated with SPRAY FOAM sprayed 5 1/2" on bottom of roof deck.

Job #: Lennardo Miller Residence
Performed by: John Pirkl for:

John F Crawford Homes, LLC
 1083 Bessent Road
 Starke, FL 32091
 Phone: (904) 338 - 5683
 crawforddevelopmentgroup@gmail.com

New Age Dimensions, LLC.

14080 S.E. 122nd Lane Road
 Ocklawaha, FL 32179
 Phone: (352) 288 - 0686 Fax: (352) 288 - 0684
 john.newage@gmail.com

Scale: 1 : 107

Page 2
 Right-Suite® Universal 2024
 24.0.03 RSU02050
 2025-Dec-04 10:25:44
 ...up\Lennardo Miller Residence.rup

14080 S.E. 122nd Lane Road, Ocklawaha, FL 32179 Phone: (352) 288 - 0686 Fax: (352) 288 - 0684 Email: john.newage@gmail.com

Project Information

For: John F Crawford Homes, LLC
1083 Bessent Road, Starke, FL 32091
Phone: (904) 338 - 5683
Email: crawforddevelopmentgroup@gmail.com

Cooling Equipment

Design Conditions

Outdoor design DB:	92.0°F	Sensible gain:	36063	Btuh	Entering coil DB:	77.2°F
Outdoor design WB:	76.3°F	Latent gain:	9235	Btuh	Entering coil WB:	64.2°F
Indoor design DB:	75.0°F	Total gain:	45299	Btuh		
Indoor RH:	50%	Estimated airflow:	1600	cfm		

Manufacturer's Performance Data at Actual Design Conditions

Equipment type:	Split ASHP		
Manufacturer:	Carrier	Model:	GH5SAN54800AA0+FJ5ANXC48L15
Actual airflow:	1600 cfm		
Sensible capacity:	38165 Btuh	106% of load	
Latent capacity:	9950 Btuh	108% of load	
Total capacity:	48115 Btuh	106% of load	SHR: 79%

Heating Equipment

Design Conditions

Outdoor design DB:	33.4°F	Heat loss:	38088	Btuh	Entering coil DB:	65.6°F
Indoor design DB:	68.0°F					

Manufacturer's Performance Data at Actual Design Conditions

Equipment type:	Split ASHP		
Manufacturer:	Carrier	Model:	GH5SAN54800AA0+FJ5ANXC48L15
Actual airflow:	1600 cfm		
Output capacity:	39674 Btuh	104% of load	
Supplemental heat required:	0 Btuh		Capacity balance: 28 °F
			Economic balance: -99 °F

Backup equipment type:	Elec strip		
Manufacturer:		Model:	
Actual airflow:	1600 cfm		
Output capacity:	10.0 kW	90% of load	Temp. rise: 20 °F

Meets all requirements of ACCA Manual S.

14080 S.E. 122nd Lane Road, Ocklawaha, FL 32179 Phone: (352) 288 - 0686 Fax: (352) 288 - 0684 Email: john.newage@gmail.com

Project Information

For: John F Crawford Homes, LLC
 1083 Bessent Road, Starke, FL 32091
 Phone: (904) 338 - 5683
 Email: crawforddevelopmentgroup@gmail.com

	Heating	Cooling
External static pressure	0.51 in H ₂ O	0.51 in H ₂ O
Pressure losses	0.18 in H ₂ O	0.18 in H ₂ O
Available static pressure	0.33 in H ₂ O	0.33 in H ₂ O
Supply / return available pressure	0.226 / 0.104 in H ₂ O	0.226 / 0.104 in H ₂ O
Lowest friction rate	0.880 in/100ft	0.880 in/100ft
Actual air flow	1600 cfm	1600 cfm
Total effective length (TEL)	301 ft	

Supply Branch Detail Table

Name	Design (Btuh)	Htg (cfm)	Clg (cfm)	Design FR	Diam (in)	H x W (in)	Duct Matl	Actual Ln (ft)	Ftg.Eqv Ln (ft)	Trunk
Bathrm #2	h 1666	78	24	0.880	5.0	0x0	VIFx	36.5	170.0	st2
Bathrm #3	h 936	44	28	0.880	4.0	0x0	VIFx	21.9	165.0	st4
Bedroom #2	h 3496	163	151	0.880	7.0	0x0	VIFx	32.6	165.0	st2
Bedroom #3	c 2367	78	117	0.880	6.0	0x0	VIFx	21.4	165.0	st4
Bedroom #4	h 2297	107	96	0.880	6.0	0x0	VIFx	31.2	165.0	st4
Foyer	h 794	37	32	0.880	4.0	0x0	VIFx	24.0	160.0	st2
Kitchen/Dine	c 2891	131	142	0.880	7.0	0x0	VIFx	26.6	165.0	st3
Kitchen/Dine-A	c 2891	131	142	0.880	7.0	0x0	VIFx	21.7	160.0	st3
Laundry	c 1012	18	50	0.880	4.0	0x0	VIFx	30.5	160.0	st2
Living Room	c 3371	126	166	0.880	7.0	0x0	VIFx	28.2	165.0	st3
Living Room-A	c 3371	126	166	0.880	7.0	0x0	VIFx	17.5	165.0	st3
Loft	c 1699	50	84	0.880	5.0	0x0	VIFx	16.9	160.0	st4
Mstr Bathrm	h 1468	68	28	0.880	5.0	0x0	VIFx	32.0	155.0	st1
Mstr Bedroom	h 2105	98	96	0.880	6.0	0x0	VIFx	37.7	160.0	st1
Mstr Bedroom-A	h 2105	98	96	0.880	6.0	0x0	VIFx	34.0	155.0	st1
Mstr WIC	h 108	5	3	0.880	4.0	0x0	VIFx	38.6	160.0	st1
Mud Room	c 889	43	44	0.880	4.0	0x0	VIFx	20.2	160.0	st3
Pantry	h 1145	53	14	0.880	4.0	0x0	VIFx	28.8	165.0	st3
Pwdr	h 521	24	6	0.880	4.0	0x0	VIFx	24.9	165.0	st3
Study	h 2538	118	113	0.880	6.0	0x0	VIFx	29.3	165.0	st2
Tlt	h 50	2	1	0.880	4.0	0x0	VIFx	39.0	160.0	st1

Supply Trunk Detail Table

Name	Trunk Type	Htg (cfm)	Clg (cfm)	Design FR	Veloc (fpm)	Diam (in)	H x W (in)	Duct Material	Trunk
st1	Peak AVF	272	225	0.880	616	9.0	0 x 0	VinIFlx	
st2	Peak AVF	414	370	0.880	528	12.0	0 x 0	VinIFlx	
st3	Peak AVF	636	680	0.880	636	14.0	0 x 0	VinIFlx	
st4	Peak AVF	278	324	0.880	595	10.0	0 x 0	VinIFlx	

Return Branch Detail Table

Name	Grille Size (in)	Htg (cfm)	Clg (cfm)	TEL (ft)	Design FR	Veloc (fpm)	Diam (in)	H x W (in)	Stud/Joist Opening (in)	Duct Matl	Trunk
rb3	12x 11	272	225	87.3	0.880	616	9.0	0x 0		VIFx	
rb2	20x 24	1050	1050	61.8	0.880	594	18.0	0x 0		VIFx	
rb1	14x 11	278	324	94.9	0.880	595	10.0	0x 0		VIFx	rst4 rst5

Return Trunk Detail Table

Name	Trunk Type	Htg (cfm)	Clg (cfm)	Design FR	Veloc (fpm)	Diam (in)	H x W (in)	Duct Material	Trunk
rst4	Peak AVF	1050	1050	0.880	594	18.0	0 x 0	VinIFlx	
rst5	Peak AVF	278	324	0.880	595	10.0	0 x 0	VinIFlx	