



- NOTES:
1. ALL WORK IS TO COMPLY WITH ALL APPLICABLE CODES & ORDINANCES.
  2. CONSTRUCTED @ 1200 PSI CONCRETE OR EQUAL WITH # 3 REBAR 12" O.C. EACH WAY, TIED AT EVERY OTHER INTERSECTION, MIN COVERAGE FOR REBAR IS 2.5" MIN OVERLAP IS 18".
  3. POOL SHAPE IS FREE FORM, ABOVE SHAPE AND DIMENSIONS ARE APPROX.
  4. ASSUMED SOIL BEARING = 2KSF
  5. CIRCULATION SYSTEMS, COMPONENTS & EQUIPMENT SHALL COMPLY W/ NSF 50
  6. INSTALL CONTROL JOINTS @ 20'-0" O.C. IN POOL DECKING.
  7. FLORIDA BUILDING CODE 2004
  8. CONCRETE STAIRS ARE 12" TREAD WITH AND 10" MAX. RISE
  9. LIFTING IF INSTALLED WILL BE FIBER OPTIC

## PEELER POOLS CONCRETE POOL CONSTRUCT



P.O. Box 187  
130 West Howard Street  
Live Oak FL 32064  
Phone: (386) 362-3678  
Fax: (386) 362-6133  
-Gery G.R., PE  
Auth. # 9487