48

COLUMBIA COUNTY BUILDING DEPARTMENT RESIDENTIAL CHECK LIST REQUIRMENTS

6-25-09

MINIMUM PLAN REQUIREMENTS FOR THE FLORIDA BUILDING CODE RESIDENTIAL 2007 EFFECTIVE 1 MARCH 2009 & 2009 SUPPLEMENTS EFFECTIVE 1 MARCH 2009, ONE (1) AND TWO (2) FAMILY DWELLINGS with Supplements and Revision, OF THE NATIONAL ELECTRICAL 2008

ALL REQUIREMENTS ARE SUBJECT TO CHANGE

ALL BUILDING PLANS MUST INDICATE COMPLIANCE with the Current 2007 FLORIDA BUILDING CODES RESIDENTIAL EFFECTIVE 1 MARCH 2009 & 2009 SUPPLEMENTS EFFECTIVE 1 MARCH 2009. ALL PLANS OR DRAWINGS SHALL PROVIDE CALCULATIONS AND DETAILS THAT HAVE THE SEAL AND SIGNATURE OF A CERTIFIED ARCHITECT OR ENGINEER REGISTERED IN THE STATE OF FLORIDA, OR ALTERNATE METHODOLOGIES, APPROVED BY THE STATE OF FLORIDA BUILDING COMMISSION FOR ONE-AND-TWO FAMILY DWELLINGS.

FOR DESIGN PURPOSES THE FOLLOWING BASIC WIND SPEEDS ARE PER FIGURE R301.2(4) of the FLORIDA BUILDING CODES RESIDENTIAL (Florida Wind speed map) SHALL BE USED.

WIND SPEED LINE SHALL BE DEFINED AS FOLLOWS: THE CENTERLINE OF INTERSTATE 75.

ALL BUILDINGS CONSTRUCTED EAST OF SAID LINE SHALL BE ------ 100 MPH ALL BUILDINGS CONSTRUCTED WEST OF SAID LINE SHALL BE ------110 MPH NO AREA IN COLUMBIA COUNTY IS IN A WIND BORNE DEBRIS REGION

GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL

Items to Include-Each Box shall be Circled as Applicable

			Yes	No	N/A
1	Two (2) complete sets of plans containing the fe	ollowing:	-		
2	All drawings must be clear, concise, drawn to s	cale, details that are not used shall be marked void	-		
3	Condition space (Sq. Ft.)	Total (Sq. Ft.) under roof	шшш	шшш	IIIII

Designers name and signature shall be on all documents and a licensed architect or engineer, signature and official embossed seal shall be affixed to the plans and documents as per the FLORIDA BUILDING CODES RESIDENTIAL R101.2.1

Cita 1	Diam		
one i	cian	information	including:

4	Dimensions of lot or parcel of land		
5	Dimensions of all building set backs	luman	
6	Location of all other structures (include square footage of structures) on parcel, existing or proposed well and septic tank and all utility easements.	~	
7	Provide a full legal description of property.		

Wind-load Engineering Summary, calculations and any details required

	GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL		Items to Include- Each Box shall be Circled as Applicable	
8	Plans or specifications must show compliance with FBCR Chapter 3	ШШ	пш	ппп
		YES	NO	N/A
9	Basic wind speed (3-second gust), miles per hour //o mpH	-		
10	(Wind exposure – if more than one wind exposure is used, the wind exposure and applicable wind direction shall be indicated)	-		
11	Wind importance factor and nature of occupancy	~		
12	The applicable internal pressure coefficient, Components and Cladding	1		1
13	The design wind pressure in terms of psf (kN/m²), to be used for the design of exterior component, cladding materials not specifally designed by the registered design professional.	-		
		*		

Elevations Drawing including:

14	All side views of the structure		
15	Roof pitch	<u></u>	
16	Overhang dimensions and detail with attic ventilation		
17	Location, size and height above roof of chimneys		-
18	Location and size of skylights with Florida Product Approval		-
18	Number of stories		
20A	Building height from the established grade to the roofs highest peak		

Floor Plan including:

20	Dimensioned area plan showing rooms, attached garage, breeze ways, covered porches, deck, balconies	_	
21	Raised floor surfaces located more than 30 inches above the floor or grade	-	
22	All exterior and interior shear walls indicated	-	
23	Shear wall opening shown (Windows, Doors and Garage doors)		
24	Show compliance with Section FBCR 310 Emergency escape and rescue opening shown in each bedroom (net clear opening shown) and Show compliance with Section FBCR 613.2 where the opening of an operable window is located more than 72 inches above the finished grade or surface below, the lowest part of the clear opening of the window shall be a minimum of 24 inches above the finished floor of the room in which the window is located. Glazing between the floor and 24 inches shall be fixed or have openings through which a 4-inch-diameter sphere cannot pass.		
25	Safety glazing of glass where needed		
26	Fireplaces types (gas appliance) (vented or non-vented) or wood burning with Hearth (see chapter 10 of FBCR)		_
27	Show stairs with dimensions (width, tread and riser and total run) details of guardrails, Handrails		-
28	Identify accessibility of bathroom (see FBCR SECTION 322)	-	

All materials placed within opening or onto/into exterior walls, soffits or roofs shall have Florida product approval number and mfg. installation information submitted with the plans (see Florida product approval form)

GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Each I Ci	to Include to Include the Incl	ll be
FBCR 403: Foundation Plans	YES	NO	N/A
29 Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size	125		1071
and type of reinforcing.	1		-
30 All posts and/or column footing including size and reinforcing		-	-
31 Any special support required by soil analysis such as piling.		-	-
32 Assumed load-bearing valve of soil Pound Per Square Foot	-	-	+
Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3	les L		
FBCR 506: CONCRETE SLAB ON GRADE			
34 Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed)	-	-	T
35 Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports	1	1	+
36 Sub mit other approved termite protection methods. Protection shall be provided by registered termiticides	_		
ter mineraes // /			
FBCR 606: Masonry Walls and Stem walls (load bearing & shear Walls)			
FBCR 606: Masonry Walls and Stem walls (load bearing & shear Walls)	1		
	· ~		-
FBCR 606: Masonry Walls and Stem walls (load bearing & shear Walls) 37 Show all materials making up walls, wall height, and Block size, mortar type		of. En	gineer
FBCR 606: Masonry Walls and Stem walls (load bearing & shear Walls) 37 Show all materials making up walls, wall height, and Block size, mortar type 38 Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement wood Frame. Metal frame shear wall and roof systems shall be designed, signed and sealed by Floarchitect		of. En	gineer
FBCR 606: Masonry Walls and Stem walls (load bearing & shear Walls) 37 Show all materials making up walls, wall height, and Block size, mortar type 38 Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement wood France. Metal frame shear wall and roof systems shall be designed, signed and sealed by Floance. Floor Framing System: First and/or second story Floor truss package shall including layout and details, signed and sealed by Florida Registered		of. En	~
FBCR 606: Masonry Walls and Stem walls (load bearing & shear Walls) 37 Show all materials making up walls, wall height, and Block size, mortar type 38 Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement wood France. Metal frame shear wall and roof systems shall be designed, signed and sealed by Floarch Architect Floor Framing System: First and/or second story Floor truss package shall including layout and details, signed and sealed by Florida Registered Professional Engineer Show conventional floor joist type, size, span, spacing and attachment to load bearing walls, stem walls and/or priers		of. En	~
FBCR 606: Masonry Walls and Stem walls (load bearing & shear Walls) 37 Show all materials making up walls, wall height, and Block size, mortar type 38 Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement wood France. Metal frame shear wall and roof systems shall be designed, signed and sealed by Floarce. Floor Framing System: First and/or second story Floor truss package shall including layout and details, signed and sealed by Florida Registered Professional Engineer Show conventional floor joist type, size, span, spacing and attachment to load bearing walls, stem walls and/or priers 40 Girder type, size and spacing to load bearing walls, stem wall and/or priers 41 Girder type, size and spacing to load bearing walls, stem wall and/or priers 42 Attachment of joist to girder		of. En	~
FBCR 606: Masonry Walls and Stem walls (load bearing & shear Walls) 37 Show all materials making up walls, wall height, and Block size, mortar type 38 Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement Metal frame shear wall and roof systems shall be designed, signed and sealed by Floarch Architect Floor Framing System: First and/or second story Floor truss package shall including layout and details, signed and sealed by Florida Registered Professional Engineer Show conventional floor joist type, size, span, spacing and attachment to load bearing walls, stem walls and/or priers 40 Girder type, size and spacing to load bearing walls, stem wall and/or priers		of. En	gineer

	w)	I/A	
45	Show required amount of ventilation opening for under-floor spaces		
46	Show required covering of ventilation opening		-
47	Show the required access opening to access to under-floor spaces		Louise
48	Show the sub-floor structural panel sheathing type, thickness and fastener schedule on the edges & interest of the areas structural panel sheathing		-
49	Show Draftstopping, Fire caulking and Fire blocking		1
50	Show fireproofing requirements for garages attached to living spaces, per FBCR section 309		1
51	Provide live and dead load rating of floor framing systems (psf).		-

FBCR CHAPTER 6 WOOD WALL FRAMING CONSTRUCTION

	GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Each I	to Inclusion to Inclusion to Include as included as opticable	ll be
		YES	NO	N/A
52	Stud type, grade, size, wall height and oc spacing for all load bearing or shear walls	bereit		
53	Fastener schedule for structural members per table FBCR 602.3 are to be shown	1		
54	Show Wood structural panel's sheathing attachment to studs, joist, trusses, rafters and structural members, showing fastener schedule attachment on the edges & intermediate of the areas structural panel sheathing	_		
55	Show all required connectors with a max uplift rating and required number of connectors and oc spacing for continuous connection of structural walls to foundation and roof trusses or rafter systems	~		
56	Show sizes, type, span lengths and required number of support jack studs, king studs for shear wall opening and girder or header per FBCR Table 502.5 (1)	~		
57	Indicate where pressure treated wood will be placed	4		
58	Show all wall structural panel sheathing, grade, thickness and show fastener schedule for structural panel sheathing edges & intermediate areas	4		
59	A detail showing gable truss bracing, wall balloon framing details or/ and wall hinge bracing detail	6		

FBCR :ROOF SYSTEMS:

60	Truss design drawing shall meet section FBCR 802.10 Wood trusses	6	1
61	Include a layout and truss details, signed and sealed by Florida Professional Engineer	down	
62	Show types of connector's assemblies' and resistance uplift rating for all trusses and rafters	low-	
63	Show gable ends with rake beams showing reinforcement or gable truss and wall bracing details		
64	Provide dead load rating of trusses	-	

FBCR 802:Conventional Roof Framing Layout

65	Rafter and ridge beams sizes, span, species and spacing	<u></u>	
66	Connectors to wall assemblies' include assemblies' resistance to uplift rating		
67	Valley framing and support details	-	
68	Provide dead load rating of rafter system	L	

FBCR Table 602,3(2) & FBCR 803 ROOF SHEATHING

	Include all materials which will make up the roof decking, identification of structural panel sheathing, grade, thickness	~	
70	Show fastener Size and schedule for structural panel sheathing on the edges & intermediate areas	L	· ·

FBCR ROOF ASSEMBLIES FRC Chapter 9

71	Include all materials which will make up the roof assembles covering	-	V
72	Submit Florida Product Approval numbers for each component of the roof assembles covering	I	/

FBCR Chapter 11 Energy Efficiency Code for residential building

Residential construction shall comply with this code by using the following compliance methods in the FBCR chapter 11 Residential buildings compliance methods. Two of the required forms are to be submitted, N1100.1.1.1 As an alternative to the computerized Compliance Method A, the Alternate Residential Point System Method hand calculation, Alternate Form 600A, may be used. All requirements specific to this calculation are located in Sub appendix C to Appendix G. Buildings complying by this alternative shall meet all mandatory requirements of this chapter. Computerized versions of the Alternate Residential Point System Method shall not be acceptable for code compliance.

GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL		Items to Include- Each Box shall be Circled as Applicable		
	YES	NO	N/A	
73 Show the insulation R value for the following areas of the structure	- L			
74 Attic space				
	1_			
75 Exterior wall cavity $R = 13$	-			

HVAC information

77	Submit two copies of a Manual J sizing equipment or equivalent computation study	-	$\overline{}$
	Exhaust fans shown in bathrooms Mechanical exhaust capacity of 50 cfm intermittent or 20 cfm continuous required Shown on Clee- Sheef . A-1.0	-	
79	Show clothes dryer route and total run of exhaust duct	-	

Plumbing Fixture layout shown

200				. /
80	All fixtures waste water lines shall be shown on the foundation plan		-	N
81	Show the location of water heater	L-		1

Private Potable Water

			/	1
82	Pump motor horse power		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	1
83	Reservoir pressure tank gallon capacity 86 601"	-		/
84	Rating of cycle stop valve if used	2		

Electrical layout shown including

85	Show Switches, receptacles outlets, lighting fixtures and Ceiling fans		
86	Show all 120-volt, single phase, 15- and 20-ampere branch circuits outlets required to be protected by Ground-Fault Circuit Interrupter (GFCI) Article 210.8 A	-	
87	Show the location of smoke detectors & Carbon monoxide detectors	L	
88	Show service panel, sub-panel, location(s) and total ampere ratings 200 AMP.	L	
89	On the electrical plans identify the electrical service overcurrent protection device for the main electrical service. This device shall be installed on the exterior of structures to serve as a disconnecting means for the utility company electrical service. Conductors used from the exterior disconnecting means to a panel or sub panel shall have four-wire conductors, of which one conductor shall be used as an equipment ground. Indicate if the utility company service entrance cable will be of the overhead or underground type.	~	
	For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an Grounding electrode system. Per the National Electrical Code article 250.52.3		
90	Appliances and HVAC equipment and disconnects		
91	Show all 120-volt, single phase, 15- and 20-ampere branch circuits supplying outlets installed in dwelling unit family rooms, dining rooms, living rooms, parlors, libraries, dens, bedrooms, sunrooms, recreation rooms, closets, hallways, or similar rooms or areas shall be protected by a listed Combination arc-fault circuit interrupter , Protection device.		

<u>Disclosure Statement for Owner Builders</u> If you as the applicant will be acting as an owner/builder under section 489.103(7) of the Florida Statutes, submit the required owner builder disclosure statement form.

Notice Of Commencement

A notice of commencement form **recorded** in the Columbia County Clerk Office is required to be filed with the building department Before Any Inspections can be preformed.

	Items to Include-
GENERAL REQUIREMENTS:	Each Box shall be
APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Circled as
	Applicable

THE FOLLOWING ITEMS MUST BE SUBMITTED WITH BUILDING PLANS

		YES	3	NO	N/A
92	Building Permit Application A current Building Permit Application form is to be completed and submitted for all residential projects		1	-	
93	Parcel Number The parcel number (Tax ID number) from the Property Appraiser (386) 758-1084 is required. A copy of property deed is also requested		-		
94	Environmental Health Permit or Sewer Tap Approval A copy of a approved Columbia County Environmental Health (386) 758-1058		l	-	
95	City of Lake City A permit showing an approved waste water sewer tap				
96	Toilet facilities shall be provided for all construction sites		1		
97	Town of Fort White (386) 497-2321 If the parcel in the application for building permit is within the Corporate city limits of Fort White an approval land use development letter issued by the Town of Fort is required to be submitted with the application for a building permit.				_

98	Flood Information: All projects within the Floodway of the Suwannee or Santa Fe Rivers shall require permitting through the Suwannee River Water Management District, before submitting a application to this office. Any project located within a flood zone where the base flood elevation (100 year flood) has been established shall meet the requirements of Section 8.5.2 of the Columbia County Land Development Regulations. Any project located within a flood zone where the base flood elevation has not been established (Zone A) shall meet the requirements of Section 8.5.3 of the Columbia County Land Development Regulations		_
99	CERTIFIED FINISHED FLOOR ELEVATIONS will be required on any project where the base flood elevation (100 year flood) has been established		-
100	A development permit will also be required. Development permit cost is \$50.00		1
101	Driveway Connection: If the property does not have an existing access to a public road, then an application for a culvert permit (\$25.00) must be made. If the applicant feels that a culvert is not needed, they may apply for a culvert waiver (\$50.00). All culvert waivers are sent to the Columbia County Public Works Department for approval or denial.	-	
102	911 Address: If the project is located in an area where a 911 address has not been issued, then application for a 911 address must be applied for and received through the Columbia County Emergency Management Office of 911 Addressing Department (386) 758-1125	-	

Section R101.2.1 of the Florida Building Code Residential:

The provisions of Chapter 1, Florida Building Code, Building shall govern the administration and enforcement of the Florida Building Code, Residential.

Section 105 of the Florida Building Code defines the:

Time limitation of application.

An application for a permit for any proposed work shall be deemed to have been abandoned 180 days after the date of filing, unless such application has been pursued in good faith or a permit has been issued; except that the building official is authorized to grant one or more extensions of time for additional periods not exceeding 90 days each. The extension shall be requested in writing and justifiable cause demonstrated.

Single-family residential dwelling.

Section 105.3.4 A building permit for a single-family residential dwelling must be issued within 30 working days of application therefor unless unusual circumstances require a longer time for processing the applicatio or unless the permit application fails to satisfy the Florida Building Code or the enforcing agency's laws or ordinances.

Permit intent.

Section 105.4.1: A permit issued shall be constructed to be a license to proceed with the work and not as authority to violate, cancel, alter or set aside any of the provisions of the technical codes, nor shall issuance of a permit prevent the building official from thereafter requiring a correction of errors in plans, construction or violations of this code. Every permit issued shall become invalid unless the work authorized by such permit is commenced within six months after its issuance, or if the work authorized by such permit is suspended or abandoned for a period of six months after the time the work is commenced.

If work has commenced.

Section 105.4.1.1: If work has commenced and the permit is revoked, becomes null and void, or expires because of lack of progress or abandonment, a new permit covering the proposed construction shall be obtained before proceeding with the work.

New Permit.

Section 105.4.1.2: If a new permit is not obtained within 180 days from the date the initial permit became nul and void, the building official is authorized to require that any work which has been commenced or completed be removed from the building site. Alternately, a new permit may be issued on application, providing the work in place and required to complete the structure meets all applicable regulations in effect at the time the initial permit became null and void and any regulations which may have become effective between the date of expiration and the date if issuance of the new permit.

Work Shall Be:

Section 105.4.1.3: Work shall be considered to be in active progress when the permit has received an approved inspection within 180 days. This provision shall not be applicable in case of civil commotion or strike or when the building work is halted due directly to judicial injunction, order or similar process.

The Fee:

Section 105.4.1.4: The fee for renewal reissuance and extension of a permit shall be set forth by the administrative authority.

When the submitted application is approved for permitting the applican will be notified by phone as to the date and time a building permit will be prepared and issued by the Columbia County Building & Zoning Department