

**RESIDENTIAL ENERGY CONSERVATION CODE DOCUMENTATION CHECKLIST****Florida Department of Business and Professional Regulation  
Simulated Performance Alternative (Performance) Method**

**Applications for compliance with the 2020 Florida Building Code, Energy Conservation via the Residential Simulated Performance Alternative shall include:**

- This checklist
- Form R405-2020 report
- Input summary checklist that can be used for field verification (usually four pages/may be greater)
- Energy Performance Level (EPL) Display Card (one page)
- HVAC system sizing and selection based on ACCA Manual S or per exceptions provided in Section R403.7
- Mandatory Requirements (five pages)

**Required prior to CO:**

- Air Barrier and Insulation Inspection Component Criteria checklist (Table R402.4.1.1 - one page)
- A completed 2020 Envelope Leakage Test Report (usually one page); exception in R402.4 allows dwelling units of R-2 Occupancies and multiple attached single family dwellings to comply with Section C402.5
- If Form R405 duct leakage type indicates anything other than "default leakage", then a completed 2020 Duct Leakage Test Report - Performance Method (usually one page)

# FLORIDA ENERGY EFFICIENCY CODE FOR BUILDING CONSTRUCTION

Florida Department of Business and Professional Regulation - Residential Performance Method

Project Name: Lot 17 Huntington at woodcrest Subdivision Street: Anyplace City, State, Zip: Lake City , FL , 32055 Owner: Trent Giebeig Design Location: FL, Gainesville	Builder Name: Trent Giebeig Permit Office: Columbia County Permit Number: Jurisdiction: County: Columbia (Florida Climate Zone 2)
--	---

<table style="width:100%;"> <tr> <td>1. New construction or existing</td> <td>New (From Plans)</td> </tr> <tr> <td>2. Single family or multiple family</td> <td>Detached</td> </tr> <tr> <td>3. Number of units, if multiple family</td> <td>1</td> </tr> <tr> <td>4. Number of Bedrooms</td> <td>3</td> </tr> <tr> <td>5. Is this a worst case?</td> <td>No</td> </tr> <tr> <td>6. Conditioned floor area above grade (ft<sup>2</sup>)</td> <td>1600</td> </tr> <tr> <td>Conditioned floor area below grade (ft<sup>2</sup>)</td> <td>0</td> </tr> <tr> <td>7. Windows(143.0 sqft.)</td> <td>Description Area</td> </tr> <tr> <td>a. U-Factor:</td> <td>DbI, U=0.55 143.00 ft<sup>2</sup></td> </tr> <tr> <td>SHGC:</td> <td>SHGC=0.45</td> </tr> <tr> <td>b. U-Factor:</td> <td>N/A ft<sup>2</sup></td> </tr> <tr> <td>SHGC:</td> <td></td> </tr> <tr> <td>c. U-Factor:</td> <td>N/A ft<sup>2</sup></td> </tr> <tr> <td>SHGC:</td> <td></td> </tr> <tr> <td>Area Weighted Average Overhang Depth:</td> <td>1.500 ft.</td> </tr> <tr> <td>Area Weighted Average SHGC:</td> <td>0.450</td> </tr> <tr> <td>8. Skylights</td> <td>Area</td> </tr> <tr> <td>c. U-Factor:(AVG)</td> <td>N/A ft<sup>2</sup></td> </tr> <tr> <td>SHGC(AVG):</td> <td>N/A</td> </tr> <tr> <td>9. Floor Types (1600.0 sqft.)</td> <td>Insulation Area</td> </tr> <tr> <td>a. Slab-On-Grade Edge Insulation</td> <td>R=0.0 1600.00 ft<sup>2</sup></td> </tr> <tr> <td>b. N/A</td> <td>R= ft<sup>2</sup></td> </tr> <tr> <td>c. N/A</td> <td>R= ft<sup>2</sup></td> </tr> </table>	1. New construction or existing	New (From Plans)	2. Single family or multiple family	Detached	3. Number of units, if multiple family	1	4. Number of Bedrooms	3	5. Is this a worst case?	No	6. Conditioned floor area above grade (ft <sup>2</sup> )	1600	Conditioned floor area below grade (ft <sup>2</sup> )	0	7. Windows(143.0 sqft.)	Description Area	a. U-Factor:	DbI, U=0.55 143.00 ft <sup>2</sup>	SHGC:	SHGC=0.45	b. U-Factor:	N/A ft <sup>2</sup>	SHGC:		c. U-Factor:	N/A ft <sup>2</sup>	SHGC:		Area Weighted Average Overhang Depth:	1.500 ft.	Area Weighted Average SHGC:	0.450	8. Skylights	Area	c. U-Factor:(AVG)	N/A ft <sup>2</sup>	SHGC(AVG):	N/A	9. Floor Types (1600.0 sqft.)	Insulation Area	a. Slab-On-Grade Edge Insulation	R=0.0 1600.00 ft <sup>2</sup>	b. N/A	R= ft <sup>2</sup>	c. N/A	R= ft <sup>2</sup>	<table style="width:100%;"> <tr> <td>10. Wall Types(1639.5 sqft.)</td> <td>Insulation Area</td> </tr> <tr> <td>a. Face Brick - Wood, Exterior</td> <td>R=13.0 1459.50 ft<sup>2</sup></td> </tr> <tr> <td>b. Frame - Wood, Adjacent</td> <td>R=13.0 180.00 ft<sup>2</sup></td> </tr> <tr> <td>c. N/A</td> <td>R= ft<sup>2</sup></td> </tr> <tr> <td>d. N/A</td> <td>R= ft<sup>2</sup></td> </tr> <tr> <td>11. Ceiling Types (1600.0 sqft.)</td> <td>Insulation Area</td> </tr> <tr> <td>a. Under Attic (Vented)</td> <td>R=38.0 1600.00 ft<sup>2</sup></td> </tr> <tr> <td>b. N/A</td> <td>R= ft<sup>2</sup></td> </tr> <tr> <td>c. N/A</td> <td>R= ft<sup>2</sup></td> </tr> <tr> <td>12. Ducts</td> <td>R 6 400</td> </tr> <tr> <td>a. Sup: Attic, Ret: Attic, AH: Main</td> <td></td> </tr> <tr> <td>13. Cooling systems</td> <td>kBtu/hr Efficiency</td> </tr> <tr> <td>a. Central Unit</td> <td>16.0 SEER:15.00</td> </tr> <tr> <td>14. Heating systems</td> <td>kBtu/hr Efficiency</td> </tr> <tr> <td>a. Electric Heat Pump</td> <td>24.6 HSPF:8.40</td> </tr> <tr> <td>15. Hot water systems</td> <td>Cap: 42 gallons EF: 0.920</td> </tr> <tr> <td>a. Electric</td> <td></td> </tr> <tr> <td>b. Conservation features</td> <td>None</td> </tr> <tr> <td>16. Credits</td> <td>CF, Pstat</td> </tr> </table>	10. Wall Types(1639.5 sqft.)	Insulation Area	a. Face Brick - Wood, Exterior	R=13.0 1459.50 ft <sup>2</sup>	b. Frame - Wood, Adjacent	R=13.0 180.00 ft <sup>2</sup>	c. N/A	R= ft <sup>2</sup>	d. N/A	R= ft <sup>2</sup>	11. Ceiling Types (1600.0 sqft.)	Insulation Area	a. Under Attic (Vented)	R=38.0 1600.00 ft <sup>2</sup>	b. N/A	R= ft <sup>2</sup>	c. N/A	R= ft <sup>2</sup>	12. Ducts	R 6 400	a. Sup: Attic, Ret: Attic, AH: Main		13. Cooling systems	kBtu/hr Efficiency	a. Central Unit	16.0 SEER:15.00	14. Heating systems	kBtu/hr Efficiency	a. Electric Heat Pump	24.6 HSPF:8.40	15. Hot water systems	Cap: 42 gallons EF: 0.920	a. Electric		b. Conservation features	None	16. Credits	CF, Pstat
1. New construction or existing	New (From Plans)																																																																																				
2. Single family or multiple family	Detached																																																																																				
3. Number of units, if multiple family	1																																																																																				
4. Number of Bedrooms	3																																																																																				
5. Is this a worst case?	No																																																																																				
6. Conditioned floor area above grade (ft <sup>2</sup> )	1600																																																																																				
Conditioned floor area below grade (ft <sup>2</sup> )	0																																																																																				
7. Windows(143.0 sqft.)	Description Area																																																																																				
a. U-Factor:	DbI, U=0.55 143.00 ft <sup>2</sup>																																																																																				
SHGC:	SHGC=0.45																																																																																				
b. U-Factor:	N/A ft <sup>2</sup>																																																																																				
SHGC:																																																																																					
c. U-Factor:	N/A ft <sup>2</sup>																																																																																				
SHGC:																																																																																					
Area Weighted Average Overhang Depth:	1.500 ft.																																																																																				
Area Weighted Average SHGC:	0.450																																																																																				
8. Skylights	Area																																																																																				
c. U-Factor:(AVG)	N/A ft <sup>2</sup>																																																																																				
SHGC(AVG):	N/A																																																																																				
9. Floor Types (1600.0 sqft.)	Insulation Area																																																																																				
a. Slab-On-Grade Edge Insulation	R=0.0 1600.00 ft <sup>2</sup>																																																																																				
b. N/A	R= ft <sup>2</sup>																																																																																				
c. N/A	R= ft <sup>2</sup>																																																																																				
10. Wall Types(1639.5 sqft.)	Insulation Area																																																																																				
a. Face Brick - Wood, Exterior	R=13.0 1459.50 ft <sup>2</sup>																																																																																				
b. Frame - Wood, Adjacent	R=13.0 180.00 ft <sup>2</sup>																																																																																				
c. N/A	R= ft <sup>2</sup>																																																																																				
d. N/A	R= ft <sup>2</sup>																																																																																				
11. Ceiling Types (1600.0 sqft.)	Insulation Area																																																																																				
a. Under Attic (Vented)	R=38.0 1600.00 ft <sup>2</sup>																																																																																				
b. N/A	R= ft <sup>2</sup>																																																																																				
c. N/A	R= ft <sup>2</sup>																																																																																				
12. Ducts	R 6 400																																																																																				
a. Sup: Attic, Ret: Attic, AH: Main																																																																																					
13. Cooling systems	kBtu/hr Efficiency																																																																																				
a. Central Unit	16.0 SEER:15.00																																																																																				
14. Heating systems	kBtu/hr Efficiency																																																																																				
a. Electric Heat Pump	24.6 HSPF:8.40																																																																																				
15. Hot water systems	Cap: 42 gallons EF: 0.920																																																																																				
a. Electric																																																																																					
b. Conservation features	None																																																																																				
16. Credits	CF, Pstat																																																																																				

Glass/Floor Area: 0.089	Total Proposed Modified Loads: 40.24	PASS
	Total Baseline Loads: 41.77	


I hereby certify that the plans and specifications covered by this calculation are in compliance with the Florida Energy Code.

PREPARED BY: William H. Freeman  
 DATE: 2/28/22

I hereby certify that this building, as designed, is in compliance with the Florida Energy Code.

OWNER/AGENT: \_\_\_\_\_  
 DATE: \_\_\_\_\_

Review of the plans and specifications covered by this calculation indicates compliance with the Florida Energy Code. Before construction is completed this building will be inspected for compliance with Section 553.908 Florida Statutes.



BUILDING OFFICIAL: \_\_\_\_\_  
 DATE: \_\_\_\_\_

- Compliance requires certification by the air handler unit manufacturer that the air handler enclosure qualifies as certified factory-sealed in accordance with R403.3.2.1.
- Compliance requires an Air Barrier and Insulation Inspection Checklist in accordance with R402.4.1.1 and this project requires an envelope leakage test report with envelope leakage no greater than 7.00 ACH50 (R402.4.1.2).
- Compliance requires a roof absorptance test and a roof emittance test in accordance with R405.7.2
- Compliance with a proposed duct leakage Qn requires a Duct Leakage Test Report confirming duct leakage to outdoors, tested in accordance with ANSI/RESNET/ICC 380, is not greater than 0.040 Qn for whole house.



**INPUT SUMMARY CHECKLIST REPORT**

**PROJECT**

Title:	Lot 17 Huntington at woodcre	Bedrooms:	3	Address Type:	Lot Information
Building Type:	User	Conditioned Area:	1600	Lot #	17
Owner Name:	Trent Giebeig	Total Stories:	1	Block/Subdivision:	Huntington
# of Units:	1	Worst Case:	No	PlatBook:	
Builder Name:	Trent Giebeig	Rotate Angle:	0	Street:	Anyplace
Permit Office:	Columbia County	Cross Ventilation:	No	County:	Columbia
Jurisdiction:		Whole House Fan:	No	City, State, Zip:	Lake City , FL , 32055
Family Type:	Detached				
New/Existing:	New (From Plans)				
Comment:					

**CLIMATE**

✓	Design Location	TMY Site	Design Temp		Int Design Temp		Heating Degree Days	Design Moisture	Daily Temp Range
			97.5 %	2.5 %	Winter	Summer			
_____	FL, Gainesville	FL_GAINESVILLE_REGI	32	92	70	75	1305.5	51	Medium

**BLOCKS**

Number	Name	Area	Volume
1	Block1	1600	14400

**SPACES**

Number	Name	Area	Volume	Kitchen	Occupants	Bedrooms	Infil ID	Finished	Cooled	Heated
1	Main	1600	14400	Yes	3	3	1	Yes	Yes	Yes

**FLOORS**

✓	#	Floor Type	Space	Perimeter	R-Value	Area	Tile	Wood	Carpet	
_____	1	Slab-On-Grade Edge Insulatio	Main	176 ft	0	1600 ft²	----	0.25	0.5	0.25

**ROOF**

✓	#	Type	Materials	Roof Area	Gable Area	Roof Color	Rad Barr	Solar Absor.	SA Tested	Emitt	Emitt Tested	Deck Insul.	Pitch (deg)
_____	1	Hip	Composition shingles	1789 ft²	0 ft²	Medium	N	0.75	Yes	0.9	Yes	0	26.57

**ATTIC**

✓	#	Type	Ventilation	Vent Ratio (1 in)	Area	RBS	IRCC
_____	1	Full attic	Vented	300	1600 ft²	N	N

**CEILING**

✓	#	Ceiling Type	Space	R-Value	Ins Type	Area	Framing Frac	Truss Type
_____	1	Under Attic (Vented)	Main	38	Blown	1600 ft²	0.11	Wood

**INPUT SUMMARY CHECKLIST REPORT**

**WALLS**

✓ #	Ornt	Adjacent To	Wall Type	Space	Cavity R-Value	Width Ft	In	Height Ft	In	Area	Sheathing R-Value	Framing Fraction	Solar Absor.	Below Grade%
___ 1	N	Exterior	Face Brick - Wood	Main	13	15	6	9		139.5 ft²		0.23	0.75	0
___ 2	N	Exterior	Face Brick - Wood	Main	13	14	0	9		126.0 ft²		0.23	0.75	0
___ 3	N	Exterior	Face Brick - Wood	Main	13	26	10	9		241.5 ft²		0.23	0.75	0
___ 4	E	Exterior	Face Brick - Wood	Main	13	30	1	9		270.8 ft²		0.23	0.75	0
___ 5	S	Garage	Frame - Wood	Main	13	20	0	9		180.0 ft²		0.23	0.75	0
___ 6	S	Exterior	Face Brick - Wood	Main	13	14	9	9		132.8 ft²		0.23	0.75	0
___ 7	W	Exterior	Face Brick - Wood	Main	13	4	8	9		42.0 ft²		0.23	0.75	0
___ 8	S	Exterior	Face Brick - Wood	Main	13	7	9	9		69.8 ft²		0.23	0.75	0
___ 9	E	Exterior	Face Brick - Wood	Main	13	4	8	9		42.0 ft²		0.23	0.75	0
___ 10	S	Exterior	Face Brick - Wood	Main	13	13	10	9		124.5 ft²		0.23	0.75	0
___ 11	W	Exterior	Face Brick - Wood	Main	13	30	1	9		270.8 ft²		0.23	0.75	0

**DOORS**

✓ #	Ornt	Door Type	Space	Storms	U-Value	Width Ft	In	Height Ft	In	Area
___ 1	N	Insulated	Main	None	.4	6		6	8	40 ft²
___ 2	S	Wood	Main	None	.46	2	8	6	8	17.8 ft²
___ 3	S	Wood	Main	None	.46	3		6	8	20 ft²

**WINDOWS**

Orientation shown is the entered, Proposed orientation.

✓ #	Ornt	Wall ID	Frame	Panes	NFRC	U-Factor	SHGC	Imp	Area	Overhang Depth	Separation	Int Shade	Screening
___ 1	N	1	Vinyl	Double (Tinted)	Yes	0.55	0.45	N	15.0 ft²	1 ft 6 in	1 ft 0 in	Drapes/blinds	None
___ 2	N	3	Vinyl	Double (Tinted)	Yes	0.55	0.45	N	9.0 ft²	1 ft 6 in	1 ft 0 in	Drapes/blinds	None
___ 3	N	3	Vinyl	Double (Tinted)	Yes	0.55	0.45	N	15.0 ft²	1 ft 6 in	1 ft 0 in	Drapes/blinds	None
___ 4	E	4	Vinyl	Double (Tinted)	Yes	0.55	0.45	N	20.0 ft²	1 ft 6 in	1 ft 0 in	Drapes/blinds	None
___ 5	E	4	Vinyl	Double (Tinted)	Yes	0.55	0.45	N	9.0 ft²	1 ft 6 in	1 ft 0 in	Drapes/blinds	None
___ 6	S	6	Vinyl	Double (Tinted)	Yes	0.55	0.45	N	36.0 ft²	1 ft 6 in	1 ft 0 in	Drapes/blinds	None
___ 7	S	10	Vinyl	Double (Tinted)	Yes	0.55	0.45	N	15.0 ft²	1 ft 6 in	1 ft 0 in	Drapes/blinds	None
___ 8	E	4	Vinyl	Double (Tinted)	Yes	0.55	0.45	N	20.0 ft²	1 ft 6 in	1 ft 0 in	Drapes/blinds	None
___ 9	W	11	Vinyl	Double (Tinted)	Yes	0.55	0.45	N	4.0 ft²	1 ft 6 in	1 ft 0 in	Drapes/blinds	None

**GARAGE**

✓ #	Floor Area	Ceiling Area	Exposed Wall Perimeter	Avg. Wall Height	Exposed Wall Insulation
___ 1	440 ft²	440 ft²	60 ft	8 ft	13

**INPUT SUMMARY CHECKLIST REPORT**

**INFILTRATION**

#	Scope	Method	SLA	CFM 50	ELA	EqLA	ACH	ACH 50
1	Wholehouse	Proposed ACH(50)	.0004	1680	92.17	173.04	.1438	7

**HEATING SYSTEM**

<input checked="" type="checkbox"/>	#	System Type	Subtype	Speed	Efficiency	Capacity	Block	Ducts
<input type="checkbox"/>	1	Electric Heat Pump/	Split	Singl	HSPF:8.4	24.59 kBtu/hr	1	sys#1

**COOLING SYSTEM**

<input checked="" type="checkbox"/>	#	System Type	Subtype	Subtype	Efficiency	Capacity	Air Flow	SHR	Block	Ducts
<input type="checkbox"/>	1	Central Unit/	Split	Singl	SEER: 15	15.96 kBtu/hr	480 cfm	0.75	1	sys#1

**HOT WATER SYSTEM**

<input checked="" type="checkbox"/>	#	System Type	SubType	Location	EF	Cap	Use	SetPnt	Conservation
<input type="checkbox"/>	1	Electric	None	Garage	0.92	42 gal	60 gal	120 deg	None

**SOLAR HOT WATER SYSTEM**

<input checked="" type="checkbox"/>	FSEC Cert #	Company Name	System Model #	Collector Model #	Collector Area	Storage Volume	FEF
<input type="checkbox"/>	None	None			ft <sup>2</sup>		

**DUCTS.**

<input checked="" type="checkbox"/>	#	--- Supply ---			--- Return ---		Leakage Type	Air Handler	CFM 25 TOT	CFM25 OUT	QN	RLF	HVAC #	
		Location	R-Value	Area	Location	Area							Heat	Cool
<input type="checkbox"/>	1	Attic	6	400 ft <sup>2</sup>	Attic	100 ft <sup>2</sup>	Proposed Qn	Main	--- cfm	64.0 cfm	0.04	0.50	1	1

**TEMPERATURES**

Programable Thermostat: Y				Ceiling Fans:																					
Cooling	<input checked="" type="checkbox"/> Jan	<input checked="" type="checkbox"/> Feb	<input checked="" type="checkbox"/> Mar	<input checked="" type="checkbox"/> Apr	<input checked="" type="checkbox"/> May	<input checked="" type="checkbox"/> Jun	<input checked="" type="checkbox"/> Jul	<input checked="" type="checkbox"/> Aug	<input checked="" type="checkbox"/> Sep	<input checked="" type="checkbox"/> Oct	<input checked="" type="checkbox"/> Nov	<input checked="" type="checkbox"/> Dec	Heating	<input checked="" type="checkbox"/> Jan	<input checked="" type="checkbox"/> Feb	<input checked="" type="checkbox"/> Mar	<input checked="" type="checkbox"/> Apr	<input checked="" type="checkbox"/> May	<input checked="" type="checkbox"/> Jun	<input checked="" type="checkbox"/> Jul	<input checked="" type="checkbox"/> Aug	<input checked="" type="checkbox"/> Sep	<input checked="" type="checkbox"/> Oct	<input checked="" type="checkbox"/> Nov	<input checked="" type="checkbox"/> Dec
Venting	<input checked="" type="checkbox"/> Jan	<input checked="" type="checkbox"/> Feb	<input checked="" type="checkbox"/> Mar	<input checked="" type="checkbox"/> Apr	<input checked="" type="checkbox"/> May	<input checked="" type="checkbox"/> Jun	<input checked="" type="checkbox"/> Jul	<input checked="" type="checkbox"/> Aug	<input checked="" type="checkbox"/> Sep	<input checked="" type="checkbox"/> Oct	<input checked="" type="checkbox"/> Nov	<input checked="" type="checkbox"/> Dec													

**INPUT SUMMARY CHECKLIST REPORT**

Thermostat Schedule: FloridaCode 2014		Hours											
Schedule Type		1	2	3	4	5	6	7	8	9	10	11	12
Cooling (WD)	AM	75	75	75	75	75	75	75	75	75	75	75	75
	PM	75	75	75	75	75	75	75	75	75	75	75	75
Cooling (WEH)	AM	75	75	75	75	75	75	75	75	75	75	75	75
	PM	75	75	75	75	75	75	75	75	75	75	75	75
Heating (WD)	AM	72	72	72	72	72	72	72	72	72	72	72	72
	PM	72	72	72	72	72	72	72	72	72	72	72	72
Heating (WEH)	AM	72	72	72	72	72	72	72	72	72	72	72	72
	PM	72	72	72	72	72	72	72	72	72	72	72	72
<b>MASS</b>													
Mass Type		Area		Thickness		Furniture Fraction			Space				
Default(8 lbs/sq.ft.)		0 ft <sup>2</sup>		0 ft		0.3			Main				

# ENERGY PERFORMANCE LEVEL (EPL) DISPLAY CARD

ESTIMATED ENERGY PERFORMANCE INDEX\* = 96

The lower the EnergyPerformance Index, the more efficient the home.

Anyplace, Lake City, FL, 32055

1. New construction or existing		New (From Plans)	10. Wall Type and Insulation	Insulation	Area
2. Single family or multiple family		Detached	a. Face Brick - Wood, Exterior	R=13.0	1459.50 ft <sup>2</sup>
3. Number of units, if multiple family		1	b. Frame - Wood, Adjacent	R=13.0	180.00 ft <sup>2</sup>
4. Number of Bedrooms		3	c. N/A	R=	ft <sup>2</sup>
5. Is this a worst case?		No	d. N/A	R=	ft <sup>2</sup>
6. Conditioned floor area (ft <sup>2</sup> )		1600	11. Ceiling Type and insulation level	Insulation	Area
7. Windows**	Description	Area	a. Under Attic (Vented)	R=38.0	1600.00 ft <sup>2</sup>
a. U-Factor:	DbI, U=0.55	143.00 ft <sup>2</sup>	b. N/A	R=	ft <sup>2</sup>
SHGC:	SHGC=0.45		c. N/A	R=	ft <sup>2</sup>
b. U-Factor:	N/A	ft <sup>2</sup>	12. Ducts, location & insulation level		R
SHGC:			a. Sup: Attic, Ret: Attic, AH: Main		6 400
c. U-Factor:	N/A	ft <sup>2</sup>	13. Cooling systems	kBtu/hr	Efficiency
SHGC:			a. Central Unit	16.0	SEER:15.00
d. U-Factor:	N/A	ft <sup>2</sup>	14. Heating systems	kBtu/hr	Efficiency
SHGC:			a. Electric Heat Pump	24.6	HSPF:8.40
Area Weighted Average Overhang Depth:		1.500 ft.	15. Hot water systems		Cap: 42 gallons
Area Weighted Average SHGC:		0.450	a. Electric		EF: 0.92
8. Skylights	Description	Area	b. Conservation features		
a. U-Factor(AVG):	N/A	ft <sup>2</sup>	None		
SHGC(AVG):	N/A		Credits (Performance method)		CF, Pstat
9. Floor Types		Insulation	Area		
a. Slab-On-Grade Edge Insulation		R=0.0	1600.00 ft <sup>2</sup>		
b. N/A		R=	ft <sup>2</sup>		
c. N/A		R=	ft <sup>2</sup>		

I certify that this home has complied with the Florida Energy Efficiency Code for Building Construction through the above energy saving features which will be installed (or exceeded) in this home before final inspection. Otherwise, a new EPL Display Card will be completed based on installed Code compliant features.

Builder Signature: \_\_\_\_\_ Date: \_\_\_\_\_

Address of New Home: \_\_\_\_\_ City/FL Zip: \_\_\_\_\_



\*Note: This is not a Building Energy Rating. If your Index is below 70, your home may qualify for energy efficient mortgage (EEM) incentives if you obtain a Florida Energy Rating. For information about the Florida Building Code, Energy Conservation, contact the Florida Building Commission's support staff.

\*\*Label required by Section R303.1.3 of the Florida Building Code, Energy Conservation, if not DEFAULT.