

COLUMBIA COUNTY BUILDING DEPARTMENT RESIDENTIAL CHECK LIST

MINIMUM PLAN REQUIREMENTS: FLORIDA BUILDING CODE RESIDENTIAL 2020 EFFECTIVE 1 JANUARY 2021 AND THE NATIONAL ELECTRICAL 2017 EFFECTIVE 1 JANUARY 2021

ALL REQUIREMENTS ARE SUBJECT TO CHANGE

ALL BUILDING PLANS MUST INDICATE COMPLIANCE WITH THE CURRENT FLORIDA BUILDING CODES RESIDENTIAL AND THE NATIONAL ELECTRICAL CODE. ALL PLANS OR DRAWINGS SHALL PROVIDE CALCULATIONS AND DETAILS THAT HAVE THE SEAL AND SIGNATURE OF A CERTIFIED ARCHITECT OR ENGINEER REGISTERED IN THE STATE OF FLORIDA, OR ALTERNATE METHODOLOGIES, APPROVED BY THE STATE OF FLORIDA BUILDING COMMISSION FOR ONE-AND-TWO FAMILY DWELLINGS, FBC 1609.1 THRU 1609.6.

FOR DESIGN PURPOSES THE FOLLOWING BASIC WIND SPEEDS ARE PER FLORIDA BUILDING CODE FIGURE 1609.3(1)
THROUGH 1609.3(4) ULTIMATE DESIGN WIND SPEEDS FOR RISK CATEGORY AND BUILDINGS AND OTHER
STRUCTURES Revised 7/1/20

Total (Sq. Ft.) under roof

Designers name and signature shall be on all documents and a licensed architect or engineer, signature and official embossed seal

Submit Online at- http://www.columbiacountyfla.com/BuildingandZoning.asp

GENERAL REQUIREMENTS:

APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL

All drawings must be clear, concise, drawn to scale, details that are not used shall be marked void

shall be affixed to the plans and documents as per the FLORIDA BUILDING CODES BUILDING 107.1.

Two (2) complete sets of plans containing the following:

Condition space (Sq. Ft.) 30 x 90

Items to Include-

Each Box shall be

Circled as

Applicable Select From Drop down

No

NA

Mes)

Si	te Plan information including:			
4	Dimensions of lot or parcel of land	ves		
5	Dimensions of all building set backs	yes		
6	Location of all other structures (include square footage of structures) on parcel, existing or proposed well and septic tank and all utility easements.	yes		
7	Provide a full legal description of property.	yes		
W	ind-load Engineering Summary, calculations and any details are required.	/		
	GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Each I	to Include Box shall ircled as licable	
8	Plans or specifications must show compliance with FBCR Chapter 3	Yes	No	NA
		Select Fro	m Drop	down
9	Basic wind speed (3-second gust), miles per hour	ges		
10	(Wind exposure – if more than one wind exposure			
	is used, the wind exposure and applicable wind direction shall be indicated)	1		
11	Wind importance factor and nature of occupancy 5-e-e	<u> </u>		
12	The applicable internal pressure coefficient, Components and Cladding			
13	The design wind pressure in terms of psf (kN/m²), to be used for the design of exterior component, cladding materials not specifally designed by the registered design professional.	-		
El	evations Drawing including: See Attacked Plans	4.		
14	All side views of the structure	1-		
15	Roofpitch 3in 12 Inch	-yes		
16	Overhang dimensions and detail with attic ventilation See Plans	-7		
17	Overhang dimensions and detail with attic ventilation Location, size and height above roof of chimneys NA	-		NA
18	Location and size of skylights with Florida Product Approval	-		NIA
19	Number of stories	- 1		1
18 12	Building height from the established grade to the roofs highest peak		1	

1	Dimensioned area plan showing rooms, attached garage, breeze ways, covered porches,	., .	
	deck, balconies	425	
2	Raised floor surfaces located more than 30 inches above the floor or grade	1	N/
3	All exterior and interior shear walls indicated	805	///
4	Shear wall opening shown (Windows, Doors and Garage doors)	Ges	
5	Show compliance with Section FBCR 310 Emergency escape and rescue opening shown in each bedroom (net clear opening shown) and Show compliance with Section FBCR 312.2.1 where the opening of an operable window is located more than 72 inches above the finished grade or surface below, the lowest part of the clear opening of the window shall be a minimum of 24 inches above the finished floor of the room in which the window is located. Glazing between the floor and 24 inches shall be fixed or have openings through which a 4-inch-diameter sphere cannot pass.	yes !	
5	Safety glazing of glass where needed	20.00	
_	Fireplaces types (gas appliance) (vented or non-vented) or wood burning with Hearth	tyes	
7	(see chapter 10 and chapter 24 of FBCR)	-	NI
8	Show stairs with dimensions (width, tread and riser and total run) details of guardrails, Handrails	-	N
9	Identify accessibility of bathroom (see FBCR SECTION 320) See plans	-×	/_
		Circle Applic	
В	CR 403: Foundation Plans All Foundation Approved is P		d as able
B	CR 403: Foundation Plans All Foundation Approved in Plans Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.	Applic	d as able
1	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing.	Applic	d as able
0	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size	Applic	d as able
2	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot	Peselbet From	d as able
2	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling.	Peselbet From	d as able
3 3 45	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system.	Pesellect Pron	d as able
	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Va per retarder (6mil. Polyethylene with joints overlaid 6 inches and sealed)	Pesellect Pron	d as able
В	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3	Pescher From Ves	d as able
В	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Va per retarder (6mil. Polyethylene with joints overlaid 6 inches and sealed)	Pescher From Ves	d as able
D	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Va per retarder (6mil. Polyethylene with joints overlaid 6 inches and sealed)	Pescher From Ves	d as able
	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structure with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Va pr retarder (6mil. Polyethylene with joints overlaid 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES	Pescher From Ves	d as able
B	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structs with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Va or retarder (6mil. Polyethylene with joints overlaid 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides	Pescher From Ves Ves Ves Ves Ves Ves	d as able Drop
B 3	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structs with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Va or retarder (6mil. Polyethylene with joints overlaid 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides	Pescher From Ves Ves Ves Ves Ves Ves	d as able Drop
B B B	Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size and type of reinforcing. All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. Assumed load-bearing valve of soil Pound Per Square Foot Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structs with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. Per the National Electrical Code article 250.52.3 CR 506: CONCRETE SLAB ON GRADE Show Va or retarder (6mil. Polyethylene with joints overlaid 6 inches and sealed) Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports CR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered termiticides	Poplice Application (PSelect Promises 1988) - 48 - 48 - 48 - 48 - 48 - 48 - 48 - 4	d as able Drop

Metal frame shear wall and roof systems shall be designed, signed and sealed by Florida Prof. Engineer or Architect

	Steele Sulding Const, Passe	d Pl	20,00
F	oor Framing System: First and/or second story	200	mit.
(HATTAN)	Floor truss package shall including layout and details, signed and sealed by Florida Registered		1 m
40	X		10/11
	Show conventional floor joist type, size, span, spacing and attachment to load bearing walls,	-	. 10
41	stem walls and/or priers		NH
42	Girder type, size and spacing to load bearing walls, stem wall and/or priers See plans	yes	
43	Attachment of joist to girder	yes	
44	Wind load requirements where applicable	ges	
45	Show required under-floor crawl space	1/2	N/A
46	Show required amount of ventilation opening for under-floor spaces	-	W/A
47	Show required covering of ventilation opening	-	NA
48	Show the required access opening to access to under-floor spaces	-	NIA
	Show the sub-floor structural panel sheathing type, thickness and fastener schedule on the edges &		NA
49	intermediate of the areas structural panel sheathing	-	1011
50	Show Draftstopping, Fire caulking and Fire blocking Show fireproofing requirements for garages attached to living spaces, per FBCR section 302.6	-	
51		-	NA
52	Provide live and dead load rating of floor framing systems (psf).		NA
Prenter			, ,
HH	CR CHAPTER 6 WOOD WALL FRAMING CONSTRUCTION		
			o Include-
	GENERAL REQUIREMENTS:		ox shall be
	APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL		cled as
		to do not prove the contract of the contract o	plicable
	Se	lect from	Drop down
53	Stud type, grade, size, wall height and oc spacing for all load bearing or shear walls	yes	
24	Fastener schedule for structural members per table FBC 2304.10.1 are to be shown	yes	
	Show wood structural panel's sheathing attachment to studs, joist, trusses, rafters and structural	7	
55	members, showing fastener schedule attachment on the edges & intermediate of the areas structural	11 5	
	panel sheathing	yes	
	Show all required connectors with a max uplift rating and required number of connectors and		
56	oc spacing for continuous connection of structural walls to foundation and roof trusses or		
	rafter systems	yes	
	Show sizes, type, span lengths and required number of support jack studs, king studs	-	
57	for shear wall opening and girder or header per FBC 2304.3.	yes	
58	Indicate where pressure treated wood will be placed	7128	
-	Show all wall structural panel sheathing, grade, thickness and show fastener schedule for structural	7	
59	panel sheathing edges & intermediate areas	-ye 3	
60		Tap 10	Bloc NIA
		2010	Die July
F	BC :ROOF SYSTEMS:		
61	Truss design drawing shall meet section FBC 2303.1.1.1 Wood trusses	-,,-,-	
62	Include a layout and truss details, signed and sealed by Florida Professional Engineer	ye)	
63	Show types of connector's assemblies' and resistance uplift rating for all trusses and rafters	yes	
64	Show gable ends with rake beams showing reinforcement or gable truss and wall bracing details	- 40)	
65		905	
0.5		yes	
W	BC 2304.4: Conventional Roof Framing Layout		
			A
66	Rafter and ridge beams sizes, span, species and spacing	-	14/2
67	Connectors to wall assemblies' include assemblies' resistance to uplift rating	-	N/A
68	Valley framing and support details	-	N/A
69	Provide dead load rating of rafter system A Steele Bei Airc		8/4
Wak	C agai a DOOD CYYD ATRYYNG		
KI	BC 2304.8 ROOF SHEATHING		
70	Include all materials which will make up the roof decking, identification of structural panel	_	$\sim n$
	sheathing, grade, thickness P// SIPP (Suidally)		NH
71	Show fastener Size and schedule for structural nanel sheathing on the edges & intermediate areas		

R	OOF ASSEMBLIES FRC Chapter 15 Steele Bld,		
72	Include all materials which will make up the roof assembles covering	MPS	
73	Submit Florida Product Approval numbers for each component of the roof assembles covering	17.	

FBC Energy Chapter 4

Residential construction shall comply with this code by using the following compliance methods in the FBC Chapter 4, Residential buildings compliance methods. Two of the required forms are to be submitted, N1100.1.1.1 As an alternative to the computerized Compliance Method A, the Alternate Residential Point System Method hand calculation, Alternate Form 600 A, may be used. All requirements specific to this calculation are located in Sub appendix C to Appendix G. Buildings complying by this alternative shall meet all mandatory requirements of this chapter. Computerized versions of the Alternate Residential Point System Method shall not be acceptable for code compliance.

	GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Each E Ci Ap	to Inclu Box shal rcled as plicable	l be
		elect from	Drop	Down
74	- SE 103	-		
75	Attic space See plans	-yes		
76	Exterior wall cavity	-/	NO	
77	Crawl space	J-	No	L
H	AC information	1		
78	Submit two copies of a Manual J sizing equipment or equivalent computation study	- yes		
79	Exhaust fans shown in bathrooms Mechanical exhaust capacity of 50 cfm intermittent or	190		
	20 cfm continuous required	- Unc		
80	Show clothes dryer route and total run of exhaust duct	- lie		
***	·	9		-
	imbing Fixture layout shown			
	All fixtures waste water lines shall be shown on the foundationplan See plans	-yes		
82	Show the location of water heater	1100		
		ges		
ASSESSMENT OF	ivate Potable Water	ı		
	Pump motor horse power Well 1,5Hp motor	-1005		
84	Reservoir pressure tank gallon capacity	-405		
85	Rating of cycle stop valve if used	-		N/
T74.	etrical lawert above in duding	T		7
86	Show Switches, receptacles outlets, lighting fixtures and Ceiling fans	1		
87		-yes		
0.7	Show all 120-volt, single phase, 15- and 20-ampere branch circuits outlets required to be protected	-, ,		
88	Show the location of smoke detectors & Carbon monoxide detectors	yes		
-		-yes		
89	Show service panel, sub-panel, location(s) and total ampere ratings	-4-65		
90	On the electrical plans identify the electrical service overcurrent protection device for the main electrical service. This device shall be installed on the exterior of structures to serve as a disconnecting means for the utility company electrical service. Conductors used from the exterior disconnecting means to a panel or sub panel shall have four-wire conductors, of which one conductor shall be used as an equipment ground. Indicate if the utility company service entrance cable will be of the overhead or underground type.	yes		
	For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an Grounding electrode system. Per the National Electrical Code article 250.52.3			
91	Appliances and HVAC equipment and disconnects	yes		
92	Show all 120-volt, single phase, 15- and 20-ampere branch circuits supplying outlets installed in dwelling unit family rooms, dining rooms, living rooms, parlors, libraries, dens, bedrooms, sunrooms, recreation rooms, closets, hallways, or similar rooms or areas shall be protected by a listed Combination arc-fault circuit interrupter, Protection device.	yes !		

Notice Of Commencement:

A notice of commencement form RECORDED in the Columbia County Clerk Office is required to be filed with the Building Department BEFORE ANY INSPECTIONS can be performed.

	Items to Include-
GENERAL REQUIREMENTS:	Each Box shall be
APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL	Circled as
	Applicable

[]	FEMS 95, 96, & 98 Are Required After APPROVAL from the ZONING DEPT.	elect from	Drop	down
93	Building Permit Application A current Building Permit Application is to be completed, by following the Checklist all supporting documents must be submitted. There is a \$15.00 application fee. The completed application with attached documents and application fee can be mailed. Lewing in Office in Person	-yes	and the second s	
94	Parcel Number The parcel number (Tax ID number) from the Property Appraisers Office (386) 758-1083 is required. A copy of property deed is also required. www.columbiacountyfla.com	-yes		
95	Environmental Health Permit or Sewer Tap Approval A copy of a approved Septile Columbia County Environmental Health (386) 758-1058 12-50-2367413 Approved	yes.		
96	City of Lake City A City Water and/or Sewer letter. Call 386-752-2031	1		NIH
97	Toilet facilities shall be provided for all construction sites	yes		
98	Town of Fort White (386) 497-2321 If the parcel in the application for building permit is within the Corporate city limits of Fort White, an approval land use development letter issued by the Town of Fort is required to be submitted with the application for a building permit.	-		N/A
99	Flood Information: All projects within the Floodway of the Suwannee or Santa Fe Rivers shall require permitting through the Suwannee River Water Management District, before submitting a application to this office. Any project located within a flood zone where the base flood See elevation (100 year flood) has been established shall meet the requirements of Section 8.5.2 of the Columbia County Land Development Regulations. Any project located within a flood zone Notes where the base flood elevation has not been established (Zone A) shall meet the requirements of Form Section 8.5.3 of the Columbia County Land Development Regulations (Municode.com)	yes	en e	And the second s
100	CERTIFIED FINISHED FLOOR ELEVATIONS will be required on any project where the approved FIRM Flood Maps show the property is in a AE, Floodway, and AH flood zones. Additionally One Foot Rise letters are required for AE and AH zones. In the Floodway Flood zones a Zero Rise letter is required.	yes	NE	0
101	A Flood development permit is also required for AE, Floodway & AH. Development permit cost is \$50.00	-	_	NI
102	If the applicant feels that a culvert is not needed, they may apply for a culvert waiver (\$50.00) Separate Check when issued. If the project is to be located on an F.D.O.T. maintained road, then an F.D.O.T. access permit	i ewa	7	N
103	911 Address: An application for a 911 address must be applied for and received through the Columbia	-		

Ordinance Sec. 90-75. - Construction debris. (e) It shall be unlawful for any person to dispose of or discard solid waste, including construction or demolition debris at any place within the county other than on an authorized disposal site or at the county's solid waste facilities. The temporary storage, not to exceed seven days of solid waste (excluding construction and demolition debris) on the premises where generated or vegetative trash pending disposition as authorized by law or ordinance, shall not be deemed a violation of this section. The temporary storage of construction and demolition debris on the premises where generated or vegetative trash pending disposition as authorized by law or ordinance shall not be deemed in violation of this section; provided, however, such construction and demolition debris must be disposed of in accordance with this article prior to the county's issuance of a certificate of occupancy for the premises. The burning of lumber from a construction or demolition project or vegetative trash when done so with legal and proper permits from the authorized agencies and in accordance with such agencies' rules and regulations, shall not be deemed a violation of this section. No person shall bury, throw, place, or deposit, or cause to be buried, thrown, placed, or deposited, any solid waste, special waste, or debris of any kind into or on any of the public streets, road right-of-way, highways, bridges, alleys, lanes, thoroughfares, waters, canals, or vacant lots or lands within the county. No person shall bury any vegetative trash on any of the public streets, road right-of-way, highways, bridges, lanes, thoroughfares, waters, canals, or lots less than ten acres in size within the county.