



General Roofing NOTES:

SELECTION OF FINISH ROOFING TO BE MADE DURING CONSTRUCTION BY THE OWNER

DECK REQUIREMENTS:

ASPHALT SHINGLES SHALL BE FASTENED TO SOLIDLY SHEATHED DECKS.

ASPHALT SHINGLES SHALL BE USED ONLY ON ROOF SLOPES OF 3:12

OR GREATER. FOR ROOF SLOPES FROM 3:12 TO 4:12, DECK UNDERLAYMENT

IS REQUIRED.

UNDERLAYMENT

ASPHALT SHINGLES SHALL HAVE SELF-ADHERING POLYMER MODIFIED BITUMEN SHALL COMPLY W/ ASTM D 216,

TYPE I OR ASTM D 4663 TYPE I.

SELF-ADHERING POLYMER MODIFIED BITUMEN SHALL COMPLY W/ ASTM D 1910

AND COMPLY WITH ASTM D 225 OR ASTM D 5462.

FASTENERS:

FASTENERS FOR ASPHALT SHINGLES SHALL BE GALVANIZED STAINLESS

STEEL, ALUMINUM OR COPPER ROOFING NAILS MINIMUM 12 GAUGE SHANK WITH

A MINIMUM 3/8 INCH DIAMETER HEAD OF A LENGTH TO PENETRATE THROUGH

UNDERLAYMENT AND SHINGLES A MINIMUM 3 INCH INTO THE ROOF SHEATHING

WHERE THE SHEATHING IS LESS THAN 3/4" THICK. THE NAILS SHALL PENETRATE

THROUGH THE SHEATHING.

ATTACHMENT:

ASPHALT SHINGLES SHALL BE SECURED TO THE ROOF WITH NOT LESS THAN

FOUR FASTENERS PER STRIP SHINGLE OR TWO FASTENERS PER INDIVIDUAL

SHINGLE. THESE ROOFERS LOCATED IN EAVES AND STEEPS OF 10:12 OR

GREATER SHALL BE FASTENED WITH 12 GAUGE SHANK WITH A MINIMUM 3/8 INCH

DIAMETER HEAD OF A LENGTH TO PENETRATE THROUGH UNDERLAYMENT

AND SHINGLES A MINIMUM 3 INCH INTO THE ROOF SHEATHING WHERE THE

SHEATHING IS LESS THAN 3/4" THICK. THE NAILS SHALL PENETRATE THROUGH

THROUGH THE SHEATHING.

UNDERLAYMENT APPLICATION:

1. STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

1" STARTING AT THE EAVE, A 1/2 UNDERLAYMENT SHALL BE A MINIMUM

Digitally signed by: N. P. GEISLER
DN: CN = N. P. GEISLER C = US O
= AR0007005 OU = ARCHITECT
Date: 2023.09.20 11:55:05 -05'00'

AR0007005

A.2
2 OF 7

SHEET:

2K2301

DATE:

10 MAR 2023

CONTRACT:

2K2301

1758 NW BROWN RD
356 353-4355

DATE:

10 MAR 2023

CONTRACT:

2K2301

DATE:

10 MAR 2023

CONTRACT:

2K2301

DATE:

10 MAR 2023

CONTRACT:

2K2301

DATE:

10 MAR 2023

CONTRACT:

2K2301

DATE:

10 MAR 2023

CONTRACT:

2K2301

DATE:

10 MAR 2023

CONTRACT:

2K2301

DATE:

10 MAR 2023

CONTRACT:

2K2301

DATE:

10 MAR 2023

CONTRACT:

2K2301

1758 NW BROWN RD
356 353-4355

DATE:

10 MAR 2023

CONTRACT:

2K2301

DATE:

10 MAR 2023

CONTRACT:

2K2301

DATE:

10 MAR 2023

CONTRACT:

2K2301

DATE:

10 MAR 2023

CONTRACT:

2K2301

DATE:

10 MAR 2023

CONTRACT:

2K2301

DATE:

10 MAR 2023

CONTRACT:

2K2301

DATE:

10 MAR 2023

CONTRACT:

2K2301

DATE:

10 MAR 2023

CONTRACT:

2K2301

DATE:

10 MAR 2023

CONTRACT:

2K2301

DATE:

10 MAR 2023

CONTRACT:

2K2301

DATE:

10 MAR 2023

CONTRACT:

2K2301

DATE:

10 MAR 2023

CONTRACT:

2K2301

DATE:

10 MAR 2023

CONTRACT:

2K2301

DATE:

10 MAR 2023

CONTRACT:

2K2301

DATE:

10 MAR 2023

CONTRACT:

2K2301

DATE:

10 MAR 2023

CONTRACT:

2K2301

DATE:

10 MAR 2023

CONTRACT:

2K2301

DATE:

10 MAR 2023

CONTRACT:

2K2301

NEW CUSTOM RESIDENTIAL DESIGN for:
JOHN and DEBBIE STALLINGS
860 EVERGREEN DRIVE - LAKE CITY, FLORIDA
ELEVATIONS

DATE:

10 MAR 2023

CONTRACT:

2K2301

DATE:

10 MAR 2023

CONTRACT:

2K2301

DATE:

10 MAR 2023

CONTRACT:

2K2301

DATE:

10 MAR 2023

CONTRACT:

2K2301

DATE:

10 MAR 2023

CONTRACT:

2K2301