

DATE 03/13/2009

Columbia County Building Permit

This Permit Must Be Prominently Posted on Premises During Construction

PERMIT
000027691

APPLICANT JOEL PHINNEY PHONE 754-6667
ADDRESS 120 SW SMITH LANE LAKE CITY FL 32024
OWNER PAUL & EMILY PHINNEY PHONE 984-0905
ADDRESS 331 SW EMORYWOOD GLEN LAKE CITY FL 32024
CONTRACTOR JOEL PHINNEY PHONE 365-2100

LOCATION OF PROPERTY 47S, TL WALTER AVE, TL EMORYWOOD GLEN, 8TH LOT ON LEFT

TYPE DEVELOPMENT STORAGE SHED ESTIMATED COST OF CONSTRUCTION 10000.00

HEATED FLOOR AREA TOTAL AREA 1200.00 HEIGHT STORIES

FOUNDATION WALLS ROOF PITCH FLOOR

LAND USE & ZONING A-3 MAX. HEIGHT

Minimum Set Back Requirments: STREET-FRONT 30.00 REAR 25.00 SIDE 25.00

NO. EX.D.U. 1 FLOOD ZONE AH DEVELOPMENT PERMIT NO.

PARCEL ID 01-5S-16-03397-304 SUBDIVISION COVE AT ROSE CREEK

LOT 4 BLOCK PHASE UNIT TOTAL ACRES 1.66

Culvert Permit No. Culvert Waiver Contractor's License Number
EXISTING X09-072 BK WR N
Driveway Connection Septic Tank Number LU & Zoning checked by Approved for Issuance New Resident

COMMENTS: MFE@ 83.9 PER PLAT,ELEVATION CONFIRMATION LETTER REQUIRED AT SLAB,
MEET SRWMD EXEMPT REQUIREMENTS, NOC ON FILE, SFD/PERMIT #27681

Check # or Cash 1001

FOR BUILDING & ZONING DEPARTMENT ONLY

(footer/Slab)

Temporary Power Foundation Monolithic
date/app. by date/app. by date/app. by
Under slab rough-in plumbing Slab Sheathing/Nailing
date/app. by date/app. by date/app. by
Framing Insulation
date/app. by date/app. by
Rough-in plumbing above slab and below wood floor Electrical rough-in
date/app. by date/app. by
Heat & Air Duct Peri. beam (Lintel) Pool
date/app. by date/app. by date/app. by
Permanent power C.O. Final Culvert
date/app. by date/app. by date/app. by
Pump pole Utility Pole M/H tie downs, blocking, electricity and plumbing
date/app. by date/app. by date/app. by
Reconnection RV Re-roof
date/app. by date/app. by date/app. by

BUILDING PERMIT FEE \$ 50.00 CERTIFICATION FEE \$ 6.00 SURCHARGE FEE \$ 6.00

MISC. FEES \$ 0.00 ZONING CERT. FEE \$ FIRE FEE \$ 0.00 WASTE FEE \$

FLOOD DEVELOPMENT FEE \$ FLOOD ZONE FEE \$ CULVERT FEE \$ TOTAL FEE 62.00

INSPECTORS OFFICE CLERKS OFFICE

NOTICE: IN ADDITION TO THE REQUIREMENTS OF THIS PERMIT, THERE MAY BE ADDITIONAL RESTRICTIONS APPLICABLE TO THIS PROPERTY THAT MAY BE FOUND IN THE PUBLIC RECORDS OF THIS COUNTY. AND THERE MAY BE ADDITIONAL PERMITS REQUIRED FROM OTHER GOVERNMENTAL ENTITIES SUCH AS WATER MANAGEMENT DISTRICTS, STATE AGENCIES, OR FEDERAL AGENCIES.

"WARNING TO OWNER: YOUR FAILURE TO RECORD A NOTICE OF COMMENCEMENT MAY RESULT IN YOUR PAYING TWICE FOR IMPROVEMENTS TO YOUR PROPERTY. IF YOU INTEND TO OBTAIN FINANCING, CONSULT WITH YOUR LENDER OR AN ATTORNEY BEFORE RECORDING YOUR NOTICE OF COMMENCEMENT."

EVERY PERMIT ISSUED SHALL BECOME INVALID UNLESS THE WORK AUTHORIZED BY SUCH PERMIT IS COMMENCED WITHIN 180 DAYS AFTER ITS ISSUANCE, OR IF THE WORK AUTHORIZED BY SUCH PERMIT IS SUSPENDED OR ABANDONED FOR A PERIOD OF 180 DAYS AFTER THE TIME THE WORK IS COMMENCED. A VALID PERMIT RECIEVES AN APPROVED INSPECTION EVERY 180 DAYS. WORK SHALL BE CONSIDERED NOT SUSPENDED, ABANDONED OR INVALID WHEN THE PERMIT HAS RECIEVED AN APPROVED INSPECTION WITHIN 180 DAYS OT THE PREVIOUS INSPECTION.

The Issuance of this Permit Does Not Waive Compliance by Permittee with Deed Restrictions.

Columbia County Building Permit Application

For Office Use Only Application # 0903-21 Date Received 3-12-09 By LH Permit # 27691
 Zoning Official BLK Date 16.03.09 Flood Zone X Land Use A-3 Zoning A-3
 FEMA Map # N/A Elevation N/A MFE 83.98 River N/A Plans Examiner WR Date 3/13/9
 Comments SFD Permit is 27681 meet SFD requirements Elevation confirmed 3/13/9 also required
☒ NOC ☒ EH ☐ Deed or PA ☐ Site Plan ☐ State Road Info ☐ Parent Parcel #
☐ Dev Permit # ☐ In Floodway Letter of Auth. from Contractor ☐ F W Comp. letter
 IMPACT FEES: EMS ☐ Fire ☐ Corr ☐ Road/Code ☐
 School ☐ = TOTAL EXEMPT - Accessory Structure

Septic Permit No. X09-072 Fax 866-381-9482

Name Authorized Person Signing Permit Joe I Phinney Phone 386-754-6667

Address -

Owners Name Paul Phinney & Emily Phinney Phone 386-984-0905

911 Address 331 SW Emorywood Gl Lake City FL 32024

Contractors Name Joel Phinney Phone 365-2100

Address 120 SW Smith Lane, Lake City, FL 32024

Fee Simple Owner Name & Address NA

Bonding Co. Name & Address NA

Architect/Engineer Name & Address William Myers / Nicholas Geisler

Mortgage Lenders Name & Address non

Circle the correct power company - FL Power & Light Clay Elec - Suwannee Valley Elec. - Progress Ener

Property ID Number 01-55-16-03397-304 Estimated Cost of Construction 10K

Subdivision Name Cove at Rose Creek Lot 4 Block - Unit - Phase -

Driving Directions State Rd 475, L on Walter Ave, L on Emorywood GLN, Lot on left (4th lot down on L) 8th lot on left
 Number of Existing Dwellings on Property 0

Construction of Storage Shed (detached) Total Acreage 1.66^{ac} Lot Size 1.66

Do you need a - Culvert Permit or Culvert Waiver or Have an Existing Drive Total Building Height 17'6"

Actual Distance of Structure from Property Lines - Front 300 Side 135 Side 50 Rear 25
315 100 Access 1' Old at 4x12

Number of Stories 1 Heated Floor Area 0 Total Floor Area 1200 Roof Pitch 4x12

Application is hereby made to obtain a permit to do work and installations as indicated. I certify that no work or

Columbia County Building Permit Application

TIME LIMITATIONS OF APPLICATION : An application for a permit for any proposed work shall be deemed to have been abandoned 180 days after the date of filing, unless such application has been pursued in good faith or a permit has been issued; except that the building official is authorized to grant one or more extensions of time for additional periods not exceeding 90 days each. The extension shall be requested in writing and justifiable cause demonstrated.

FLORIDA'S CONSTRUCTION LIEN LAW: Protect Yourself and Your Investment

According to Florida Law, those who work on your property or provide materials, and are not paid-in-full, have a right to enforce their claim for payment against your property. This claim is known as a construction lien. If your contractor fails to pay subcontractors or material suppliers or neglects to make other legally required payments, the people who are owed money may look to your property for payment. even if you have paid your contractor in full. This means if a lien is filed against your property, it could be sold against your will to pay for labor, materials or other services which your contractor may have failed to pay.

NOTICE OF RESPONSIBILITY TO BUILDING PERMITEE:

YOU ARE HEREBY NOTIFIED as the recipient of a building permit from Columbia County, Florida, you will be held responsible to the County for any damage to sidewalks and/or road curbs and gutters, concrete features and structures, together with damage to drainage facilities, removal of sod, major changes to lot grades that result in ponding of water, or other damage to roadway and other public infrastructure facilities caused by you or your contractor, subcontractors, agents or representatives in the construction and/or improvement of the building and lot for which this permit is issued. No certificate of occupancy will be issued until all corrective work to these public infrastructures and facilities has been corrected.

WARNING TO OWNER: YOUR FAILURE TO RECORD A NOTICE OF COMMENCEMENT MAY RESULT IN YOU PAYING TWICE FOR IMPROVEMENTS TO YOUR PROPERTY. A NOTICE OF COMMENCEMENT MUST BE RECORDED AND POSTED ON THE JOB SITE BEFORE THE FIRST INSPECTION. IF YOU INTEND TO OBTAIN FINANCING, CONSULT WITH YOUR LENDER OR ATTORNEY BEFORE RECORDING YOUR NOTICE OF COMMENCEMENT.

OWNERS CERTIFICATION: I hereby certify that all the foregoing information is accurate and all work will be done in compliance with all applicable laws and regulating construction and zoning. I further understand the above written responsibilities in Columbia County for obtaining this Building Permit.


Owners Signature

CONTRACTORS AFFIDAVIT: By my signature I understand and agree that I have informed and provided this written statement to the owner of all the above written responsibilities in Columbia County for obtaining this Building Permit.


Contractor's Signature (Permitee)

Contractor's License Number CBC 1256243
Columbia County
Competency Card Number

Affirmed under penalty of perjury to by the Contractor and subscribed before me this 12 day of March 2009
Personally known or Produced Identification FD DL


State of Florida Notary Signature (For the Contractor)

SEAL:



Permit Number:

Tax Folio Number: 01-55-16-03397-304

State of: Florida
County of: Columbia

File Number: 08-0476


NOTICE OF COMMENCEMENT

Inst: 200912004132 Date: 3/13/2009 Time: 3:52 PM
DC, P. DeWitt Cason, Columbia County Page 1 of 1 B: 1169 P: 469

The undersigned hereby gives notice that improvement will be made to certain real property, and, in accordance with Chapter 713, Florida Statutes, the following information is provided in this Notice of Commencement.


1. Description of Property:
PART OF LOT 4, COVE AT ROSE CREEK, A SUBDIVISION ACCORDING TO PLAT THEREOF RECORDED IN PLAT BOOK 8, PAGES 107 THROUGH 109 OF THE PUBLIC RECORDS OF COLUMBIA COUNTY, FLORIDA, BEING MORE PARTICULARLY DESCRIBED AS FOLLOWS:

BEGIN AT THE NORTHWEST CORNER OF SAID LOT 4 AND RUN THENCE S 00°14'08" E, ALONG THE EAST RIGHT OF WAY OF SOUTHWEST EMORYWOOD GLEN, 178.79 FEET THENCE N 90°00'00" E 365.17 FEET TO THE EAST LINE OF SAID LOT 4; THENCE N 00°14'08" W, ALONG SAID EAST LINE, 215.59 FEET; THENCE N 00°02'17" W ALONG SAID EAST LINE, 2.77 FEET TO THE NORTH LINE OF SAID LOT 4; THENCE S 83°48'42" W, ALONG SAID NORTH LINE, 367.16 FEET TO THE POINT OF BEGINNING.
2. General Description of Improvements: Storage Shed
3. Owner Information:
 - a. Name and Address: Paul R. Phinney and Emily S. Phinney
385 SW Peace Road
Lake City, FL 32024
 - b. Interest in property: Fee Simple
 - c. Names and address of fee simple title holder (if other than owner):
4. Contractor: Skyline Homes, Inc., 120 SW Smith Lane, Lake City, FL 32024
5. Surety:
6. Persons within the State of Florida designated by Owner upon whom notices or other documents may be served as provided by Section 713.13(1) (a) 7., Florida Statutes.
7. In addition to himself, Owner designates the following persons to receive a copy of the Lienor's Notice as provided in Section 713.13(1)(b), Florida Statutes.
8. Expiration date of Notice of Commencement (the expiration date is 1 year from date of recording unless a different date is specified):


Paul R. Phinney


Emily S. Phinney

Sworn to and subscribed before me March 13, 2008 by Paul R. Phinney and Emily S. Phinney, his wife who is personally known to me or who did provide _____ as identification.


Notary Public
My Commission Expires: July 28, 2012



DONNA FARRIS
MY COMMISSION # DD 788183
EXPIRES: July 28, 2012
Bonded Thru Budget Notary Services

WARRANTY DEED

Made this FEBRUARY _____, 2009 A.D. By **Paul Phinney, a married man**, 385 SW Peace Drive, Lake City, Florida 32024, hereinafter called the grantor, to **Paul Phinney, and his wife, Emily S. Phinney**, whose post office address is: 385 SW Peace Drive, Lake City, Florida 32024, hereinafter called the grantee:

(Whenever used herein the term "grantor" and "grantee" include all the parties to this instrument and the heirs, legal representatives and assigns of individuals, and the successors and assigns of corporations)

Witnesseth, that the grantor, for and in consideration of the sum of Ten Dollars, (\$10.00) and other valuable considerations, receipt whereof is hereby acknowledged, hereby grants, bargains, sells, aliens, remises, releases, conveys and confirms unto the grantee, all that certain land situate in Columbia County, Florida, viz:

SEE EXHIBIT "A" ATTACHED HERETO AND BY THIS REFERENCE MADE A PART HEREOF.

EMILY S. PHINNEY IS THE SISTER OF THE GRANTOR JOSH NICKELSON AS DESCRIBED IN WARRANTY DEED - RECORDED IN O.R. BOOK 1161 PAGE 2254

Said property is not the homestead of the Grantor(s) under the laws and constitution of the State of Florida in that neither Grantor(s) or any members of the household of Grantor(s) reside thereon.

Parcel ID Number: **01-5S-16-03397-304**

Inst:200912002312 Date:2/13/2009 Time:1:20 PM
Doc Stamp-Deed:0.70
DC,P,DeWitt Cason,Columbia County Page 1 of 2 B:1167 P:708

Together with all the tenements, hereditaments and appurtenances thereto belonging or in anywise appertaining.

To Have and to Hold, the same in fee simple forever.

And the grantor hereby covenants with said grantee that the grantor is lawfully seized of said land in fee simple; that the grantor has good right and lawful authority to sell and convey said land; that the grantor hereby fully warrants the title to said land and will defend the same against the lawful claims of all persons whomsoever; and that said land is free of all encumbrances except taxes accruing subsequent to December 31, 2008.

In Witness Whereof, the said grantor has signed and sealed these presents the day and year first above written.

Signed, sealed and delivered in our presence:

Laura M. Cady

Witness Printed Name Laura Cady

Paul Phinney

Paul Phinney


(Se:)

Charles Nickelson

Witness Printed Name Charles Nickelson

State of Florida
County of Columbia

The foregoing instrument was acknowledged before me this 9 day of FEBRUARY, 2009, by PAUL PHINNEY, a married man, who is/are personally known to me or who has produced a Drivers License as identification.



Jacob C. Kirsch
Notary Public
Print Name: Jacob C. Kirsch

My Commission Expires: 9-25-2009

PREPARED BY
JOSHUA A. NICKELSON
484 NW Turner AVENUE
Lake City, FL 32055

DESCRIPTION:

PART OF LOT 4, COVE AT ROSE CREEK, A SUBDIVISION ACCORDING TO PLAT THEREOF RECORDED IN PLAT BOOK 8, PAGES 107 THROUGH 109 OF THE PUBLIC RECORDS OF COLUMBIA COUNTY, FLORIDA, BEING MORE PARTICULARLY DESCRIBED AS FOLLOWS:

BEGIN AT THE NORTHWEST CORNER OF SAID LOT 4 AND RUN THENCE S 00°14'06" E, ALONG THE EAST RIGHT OF WAY OF SW EMORYWOOD GLEN, 178.79 FEET; THENCE N 90°00'00" E, 365.17 FEET TO THE EAST LINE OF SAID LOT 4; THENCE N 00°14'06" W, ALONG SAID EAST LINE, 215.59 FEET; THENCE N 00°02'17" W, ALONG SAID EAST LINE, 2.77 FEET TO THE NORTH LINE OF SAID LOT 4; THENCE S 83°48'42" W, ALONG SAID NORTH LINE, 387.16 FEET TO THE POINT OF BEGINNING. CONTAINING 1.86 ACRES, MORE OR LESS.

PHONE: (386) 758-1125 * FAX: (386) 758-1365 * Email: ron_croft@columbiacountyfla.com

PHONE: (386) 758-1125 * FAX: (386) 758-1365 * Email: ron_croft@columbiacountyfla.com


To maintain the Countywide Addressing Policy you must make application for a 9-1-1 Address at the time you apply for a building permit. The established standards for assigning and posting numbers to all principal buildings, dwellings, businesses and industries are contained in Columbia County Ordinance 2001-9. The addressing system is to enable Emergency Service Agencies to locate you in an emergency, and to assist the United States Postal Service and the public in the timely and efficient provision of services to residents and businesses of Columbia County.


PART OF LOT 4 COVE AT ROSE CREEK

Columbia County 9-1-1 Addressing / GIS Department

FEB-05-2009 13:51 FROM:

Paul Phinney
 01-55-16-03397-304
 Part of Lot 14
 Cove at Rose Creek





From: The Columbia County Building & Zoning Department
Plan Review
135 NE Hernando Av.
P.O. Box 1529
Lake City Florida 32056-1529

Reference to a building permit application Number: **0903-21**
Applicant: Joel Phinney, Property Identification number: 01-5S-16-03397-304

On the date of March 13, 2009 application 0903-21 and plans were reviewed for compliance of the 2007 Florida building code. The documents and plans submitted are for construction of a Group U Utility structure.

Reviewed the following listed information: On Page A.1 of the submitted plans a Typical Wall Section is drawn do not use for construction refer to page S.3 Florida Building Code Compliance Summary by Nicholas Paul Geisler Architect of record.

This is a plan review for compliance with the Florida Building Code 2007 only and doesn't make any consideration toward the land use and zoning requirements.

Thank You:

Columbia County Building
Department



Office

PRODUCT APPROVAL SPECIFICATION SHEET

Submittal

Location:

Project Name:

As required by Florida Statute 553.842 and Florida Administrative Code 9B-72, please provide the information and the product approval number(s) on the building components listed below if they will be utilized on the construction project for which you are applying for a building permit on or after April 1, 2004. We recommend you contact your local product supplier should you not know the product approval number for any of the applicable listed products. More information about statewide product approval can be obtained at www.floridabuilding.org


Category/Subcategory	Manufacturer	Product Description	Approval Number
A. EXTERIOR DOORS			
1. Swinging			
2. Sliding	Mayfair	entry door	FL 1311
3. Sectional			
4. Roll up	General American	garage door	FL 2868
5. Automatic			
6. Other			
B. WINDOWS			
1. Single hung	Danvid	Single Hung windows	FL 1369
2. Horizontal Slider			
3. Casement			
4. Double Hung			
5. Fixed			
6. Awning			
7. Pass-through			
8. Projected			
9. Mullion			
10. Wind Breaker			
11. Dual Action			
12. Other			
C. PANEL WALL			
1. Siding	James Hardie	hardiboard Siding	FL 889-R1
2. Soffits	Alcoa	Aluminum	FL 406
3. EIFS			
4. Storefronts			
5. Curtain walls			
6. Wall louver			
7. Glass block			
8. Membrane			
9. Greenhouse			
10. Other			
D. ROOFING PRODUCTS			
1. Asphalt Shingles	Tamko	30-year Shingles asphalt	FL 673
2. Underlayments			
3. Roofing Fasteners			
4. Non-structural Metal Rf			
5. Built-Up Roofing			
6. Modified Bitumen			
7. Single Ply Roofing Sys			
8. Roofing Tiles			
9. Roofing Insulation			
10. Waterproofing			
11. Wood shingles /shakes			
12. Roofing Slate			



Category/Subcategory (cont.)	Manufacturer	Product Description	Approval Number(s)
13. Liquid Applied Roof Sys			
14. Cements-Adhesives - Coatings			
15. Roof Tile Adhesive			
16. Spray-Applied Polyurethane Roof			
17. Other			
E. SHUTTERS			
1. Accordion			
2. Bahama			
3. Storm Panels			
4. Colonial			
5. Roll-up			
6. Equipment			
7. Others			
F. SKYLIGHTS			
1. Skylight			
2. Other			
G. STRUCTURAL COMPONENTS			
1. Wood connector/anchor			
2. Truss plates			
3. Engineered lumber			
4. Railing			
5. Coolers-freezers			
6. Concrete Admixtures			
7. Material			
8. Insulation Forms			
9. Plastics			
10. Deck-Roof			
11. Wall			
12. Sheds			
13. Other			
H. NEW EXTERIOR ENVELOPE PRODUCTS			
1.			
2.			

The products listed below did not demonstrate product approval at plan review. I understand that at the time of inspection of these products, the following information must be available to the inspector on the jobsite; 1) copy of the product approval, 2) the performance characteristics which the product was tested and certified to comply with, 3) copy of the applicable manufacturers installation requirements.

I understand these products may have to be removed if approval cannot be demonstrated during inspection


Contractor or Contractor's Authorized Agent Signature

Print Name

Soel Phinney 3/11/09
Date

Location

Permit # (FOR STAFF USE ONLY)


REVISIONS	DATE	DESCRIPTION
1	MARCH 10, 2009	ISSUED FOR PERMIT

SOFTPLAN
ARCHITECTURAL SOFTWARE

FLOOR PLAN
SCALE: 1/8" = 1'-0"
EXTERIOR ELEVATIONS
SCALE: 1/8" = 1'-0"

PALL PLINNEY
PROJECT ADDRESS: PALL 01-05-10-0000-00L, COLUMBIA COUNTY, FLORIDA 32025


OVERLAPMENTS
PALL PLINNEY
1000 N. W. 10TH AVE.
SUITE 100
FORT LAUDERDALE, FL 33304
(954) 755-8406




JOB NUMBER
090202

SHEET NUMBER
A.1
OF 1 SHEET


Handwritten signature




FLOOR PLAN
SCALE: 1/8" = 1'-0"
AREA: 1,350 square feet




REAR ELEVATION
SCALE: 1/8" = 1'-0"



FRONT ELEVATION
SCALE: 1/8" = 1'-0"



TYPICAL WALL SECTION
SCALE: N.T.S.



RIGHT ELEVATION
SCALE: 1/8" = 1'-0"

NOTE: ALL DRAWINGS NOT TO BE SCALED. WRITTEN DIMENSIONS TAKE PRECEDENCE OVER SCALED DIMENSIONS



CAL-TECH TESTING, INC.

ENGINEERING & TESTING LABORATORY

P.O. Box 1625, Lake City, FL 32056-1625
4784 Rosselle St. • Jacksonville, FL 32254
2230 Greensboro Hwy., Quincy, FL 32351

Lake City • (386) 755-3633

Fax • (386) 752-5456

Jacksonville • (904) 381-8901

Fax • (904) 381-8902

Quincy • (850) 442-3495

Fax • (850) 442-4008

JOB NO.: 09-117

DATE TESTED:

~~3-26-09~~
3-30-09

REPORT OF IN-PLACE DENSITY TEST

ASTM METHOD: ✓ (D-2922) Nuclear (D-2937) Drive Cylinder Other

PROJECT: Paul Pichimey Residence + School # 27691

CLIENT: Subylene Homes

GENERAL CONTRACTOR: SAC EARTHWORK CONTRACTOR: SAC

SOIL USE (SEE NOTE): 1 - Footing SPECIFICATION REQUIREMENTS: 98%

TECHNICIAN: C. Day

MODIFIED (ASTM D-1557): ✓ STANDARD (ASTM D-698):

TEST NO.	TEST LOCATION	TEST:	PROCTOR NO.	WET DENS. LBS./CU.FT.	DRY DENS. LBS./CU.FT.	MOIST PERCENT	% MAX. DENS.
		DEPTH ELEV. LIFT					
	* Sched Footing *						
6A	S.E. Corner 10' North West	12"	TP	113.1	102.7	10.1	98
7A	N.W. Corner 10' East	12"	TP	113.1	102.6	10.2	98
8A	S.W. Corner 10' North	12"	TP	112.8	102.6	9.9	98
9A	N.E. Corner 10' South	12"	TP	113.5	102.9	10.3	98

REMARKS: Speedy Moisture Test performed on each test due to conditions of footing.

PROCTOR NO.	SOIL DESCRIPTION	PROCTOR VALUE	OPT. MOIST.
TP	Dark Tan Sand (Timmerman Pit)	104.7 / 105.2	12.41

NOTE: 1. Building Fill 2. Trench Backfill 3. Base Course 4. Subbase/Stabilized Subgrade 5. Embankment 6. Subgrade/Natural Soil 7. Other
The test results presented in this report are specific only to the samples tested at the time of testing. The tests were performed in accordance with generally accepted methods and standards. Since material conditions can vary between test location and change with time, sound judgement should be exercised with regard to the use and interpretation of the data.

21691

D
G **Daniel & Gore, LLC**
Professional Surveying and Mapping

P.O. Box 1501
Lake City, Florida 32056

April 21, 2009

Paul Phinney
385 SW Peace Dr.
Lake City, FL 42024

Subject: Lot 4A Elevation Letter

Dear Mr. Phinney:

We have performed a vertical survey on Parcel 4A of Lot 4, Cove at Rose Creek (being parcel #03397-304), Columbia County, Florida from a benchmark being a 4"x4" concrete monument, LS 1079 at the NE corner of NW 1/4 of SW 1/4, Section 1, T5-S, R16-E (elevation - 84.30', NGVD 1929) and have determined the following:

- The Subdivision plat requires the minimum finish floor elevation to be 83.9'.
- We have set a TBM (Temporary Benchmark) on a 60d nail in a 8" pine, being 34.0' North of the SW corner and 43.5' East of the edge of pavement, with an elevation of 83.9', NGVD 1929.
- The elevation of the poured concrete foundation (residence) is at 84.9', being 1 foot above the minimum finish floor requirement.
- The elevation of the form boards (out building) is at 84.0', being 0.1 foot above the minimum finish floor requirement.

If you have any questions, please call me.

Sincerely,


Scott Daniel, PSM

Original in SFD
File 27681

New Construction Subterranean Termite Soil Treatment Record

OMB Approval No. 2502-0525

This form is completed by the licensed Pest Control Company.

Public reporting burden for this collection of information is estimated to average 15 minutes per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. This information is mandatory and is required to obtain benefits. HUD may not collect this information, and you are not required to complete this form, unless it displays a currently valid OMB control number.

Section 24 CFR 200.926d(b)(3) requires that the sites for HUD insured structures must be free of termite hazards. This information collection requires the builder to certify that an authorized Pest Control company performed all required treatment for termites, and that the builder guarantees the treated area against infestation for one year. Builders, pest control companies, mortgage lenders, homebuyers, and HUD as a record of treatment for specific homes will use the information collected. The information is not considered confidential.

This report is submitted for informational purposes to the builder on proposed (new) construction cases when soil treatment for prevention of subterranean termite infestation is specified by the builder, architect, or required by the lender, architect, FHA, or VA.

All contracts for services are between the Pest Control Operator and builder, unless stated otherwise.

Section 1: General Information (Treating Company Information)

Company Name: Aspen Pest Control, Inc.Company Address: P.O. Box 1795 City Lake City State FL Zip 32056Company Business License No. JB109476 Company Phone No. 386-755-3611 • 352-494-5751

FHA/VA Case No. (if any) _____

Section 2: Builder Information

Company Name: Skyline Homes Company Phone No. 365-2100

Section 3: Property Information

Location of Structure(s) Treated (Street Address or Legal Description, City, State and Zip) Phinney Residence331 SW Emorywood Glen
Lake City, FL 32224Type of Construction (More than one box may be checked) ☒ Slab ☐ Basement ☐ Crawl ☒ Other Monolithic

Approximate Depth of Footing: Outside _____ Inside _____ Type of Fill _____

Section 4: Treatment Information

Date(s) of Treatment(s) 4/21/09Brand Name of Product(s) Used Bifen XTSEPA Registration No. 53883-189Approximate Final Mix Solution % .6%Approximate Size of Treatment Area: Sq. ft. 1200 Linear ft. _____ Linear ft. of Masonry Voids _____Approximate Total Gallons of Solution Applied 120 gals.Was treatment completed on exterior? ☐ Yes ☒ NoService Agreement Available? ☒ Yes ☐ No

Note: Some state laws require service agreements to be issued. This form does not preempt state law.

Attachments (List) _____

Comments Workshop @ back of propertyName of Applicator(s) S. Gregory Certification No. (if required by State law) JF104376

The applicator has used a product in accordance with the product label and state requirements. All treatment materials and methods used comply with state and federal regulations.

Authorized Signature [Signature] Date 4/21/09

Warning: HUD will prosecute false claims and statements. Conviction may result in criminal and/or civil penalties. (18 U.S.C. 1001, 1010, 1012; 31 U.S.C. 3729, 3802)

Form NPCA-99-B may still be used

form HUD-NPCA-99-B (04/2003)



Lake City (386) 755-3611
Gainesville (352) 494-5751
Fax (386) 755-3885
Toll Free 1-800-616-4707

Certificate of Compliance for Termite Protection
(as required by Florida Building Code (FBC) 1816.1.7)

Aspen Pest Control, Inc.
(386) 755-3611
State License # - JB109476
State Certification # - JF104376

Phinney Residence (workshop) - Lake City, FL 32024
Address of Treatment or Lot/Block of Treatment

Soil Barrier

(Method of Termite Prevention Treatment – Soil Barrier, Wood Treatment, Bait System, Other)

Horizontal, Vertical, Void and Exterior Treatment

Description of Treatment

The above named structure has received a complete treatment for the prevention of subterranean termites. Treatment was done in accordance with the rules and laws established by the Florida Department of Agriculture and Consumer Services.


Authorized Signature

10/28/09
Date

22691

COLUMBIA COUNTY, FLORIDA

OCCUPANCY

COLUMBIA COUNTY, FLORIDA

Department of Building and Zoning Inspection

This Certificate of Occupancy is issued to the below named permit holder for the building and premises at the below named location, and certifies that the work has been completed in accordance with the Columbia County Building Code.

Parcel Number 01-5S-16-03397-304

Building permit No. 000027691

Use Classification STORAGE SHED

Fire: 0.00

Permit Holder JOEL PHINNEY

Waste: 0.00

Owner of Building PAUL & EMILY PHINNEY

Total: 0.00

Location: 331 SW EMORYWOOD GLEN, LAKE CITY, FL


Date: 11/04/2009

Harry Dick

Building Inspector

POST IN A CONSPICUOUS PLACE
(Business Places Only)





Builders FirstSource
2525 E. Duval St.
Lake City, FL 32055

Wind
Wind Standard: ASCE 7-05
Wind Speed: 110 mph
Mean Roof Ht: 15 ft

Note: Refer to individual truss design drawings for special loading conditions, design criteria, truss geometry, lumber, and plate information.

Design Professional Of Record: Joel Phinney
Delegated Truss Engineer: Julius Lee

License # : CBC1256243
License # : 34869

This truss specification package consists of this index sheet and 2 truss design drawings. This signed and sealed index sheet indicates acceptance of my professional engineering responsibility solely for listed truss design drawings. The suitability and use of each truss component for any particular building is the responsibility of the building designer per TPI.

[illegible]

LOAD CASE(S) Standard
1) Regular: Lumber Increase=1.25, Plate Increase=1.25
Uniform Loads (plf)
Vert: 1-4=54, 4-7=54, 2-10=10, 8-10=70(F=60), 6-8=10


#2 HIP OR COMMON TRUSS

2' TYP.
MAX

REVIEWED
By Julius Lee at 10:52 am, Jun 27, 2008

ASCE 7-02: 130 MPH WIND SPEED, 30' MEAN HEIGHT, ENCLOSED, I = 1.00, EXPOSURE C

MAX GABLE VERTICAL LENGTH																																		
CABLE VERTICAL SPACING	2x4 SPECIES	GRADE	BRACE	NO. BRACES	(1) 1x4 "L" BRACE *														(1) 2x4 "L" BRACE *				(2) 2x4 "L" BRACE **				(1) 2x6 "L" BRACE *				(2) 2x6 "L" BRACE **			
					GROUP A		GROUP B		GROUP A		GROUP B		GROUP A		GROUP B		GROUP A		GROUP B		GROUP A		GROUP B		GROUP A		GROUP B							
					#1 / #2	#3	#1 / #2	#3	#1 / #2	#3	#1 / #2	#3	#1 / #2	#3	#1 / #2	#3	#1 / #2	#3	#1 / #2	#3	#1 / #2	#3	#1 / #2	#3	#1 / #2	#3	#1 / #2	#3	#1 / #2	#3	#1 / #2			
12" O.C.	SPF	STANDARD	DFL	3' 2"	5' 6"	6' 8"	6' 8"	6' 9"	7' 10"	8' 0"	10' 3"	10' 7"	12' 3"	12' 7"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"					
					4' 5"	4' 5"	5' 10"	6' 10"	7' 10"	7' 10"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"			
					4' 6"	4' 5"	5' 10"	6' 10"	7' 10"	7' 10"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"	9' 1"			
					2' 11"	3' 9"	3' 9"	6' 0"	6' 0"	6' 9"	7' 10"	7' 10"	8' 5"	10' 3"	10' 3"	12' 3"	13' 2"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"		
					#1	3' 6"	5' 6"	5' 11"	6' 6"	7' 0"	7' 10"	8' 5"	10' 3"	11' 1"	12' 3"	13' 2"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"		
	SP	STANDARD	DFL	3' 3"	4' 6"	4' 6"	5' 11"	6' 6"	7' 0"	8' 5"	10' 3"	11' 1"	12' 3"	13' 2"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"					
					#2	3' 3"	4' 6"	4' 6"	5' 11"	6' 6"	7' 0"	8' 5"	10' 3"	11' 1"	12' 3"	13' 2"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"				
					#3	3' 3"	4' 6"	4' 6"	5' 11"	6' 6"	7' 0"	8' 5"	10' 3"	11' 1"	12' 3"	13' 2"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"			
					STUD	3' 3"	4' 6"	4' 6"	5' 11"	6' 6"	7' 0"	8' 5"	10' 3"	11' 1"	12' 3"	13' 2"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"			
					#1	3' 3"	4' 6"	4' 6"	5' 11"	6' 6"	7' 0"	8' 5"	10' 3"	11' 1"	12' 3"	13' 2"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"	12' 3"		
SPF	STANDARD	DFL	3' 0"	3' 10"	3' 10"	6' 1"	5' 1"	7' 6"	8' 11"	9' 2"	11' 9"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"					
				#2	3' 8"	3' 8"	6' 4"	6' 6"	7' 6"	7' 6"	8' 11"	9' 2"	11' 9"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"				
				#3	3' 7"	3' 7"	5' 5"	5' 5"	7' 2"	7' 2"	8' 11"	9' 2"	11' 9"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"				
				STUD	3' 7"	3' 7"	5' 5"	5' 5"	7' 2"	7' 2"	8' 11"	9' 2"	11' 9"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"				
				#1	3' 7"	3' 7"	5' 5"	5' 5"	7' 2"	7' 2"	8' 11"	9' 2"	11' 9"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"			
16" O.C.	SPF	STANDARD	DFL	4' 0"	8' 4"	8' 4"	8' 10"	7' 6"	8' 1"	8' 11"	9' 7"	11' 9"	12' 8"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"						
					#2	3' 11"	3' 11"	8' 4"	6' 10"	7' 6"	8' 1"	8' 11"	9' 7"	11' 9"	12' 8"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"				
					#3	3' 9"	3' 9"	5' 7"	6' 7"	7' 3"	7' 3"	8' 11"	9' 5"	11' 4"	11' 4"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"			
					STUD	3' 9"	3' 9"	5' 6"	5' 6"	7' 3"	7' 3"	8' 11"	9' 5"	11' 4"	11' 4"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"			
					#1	3' 9"	3' 9"	5' 6"	5' 6"	7' 3"	7' 3"	8' 11"	9' 5"	11' 4"	11' 4"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"			
	SP	STANDARD	DFL	4' 0"	8' 4"	8' 4"	8' 10"	7' 6"	8' 1"	8' 11"	9' 7"	11' 9"	12' 8"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"					
					#2	3' 11"	3' 11"	8' 4"	6' 10"	7' 6"	8' 1"	8' 11"	9' 7"	11' 9"	12' 8"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"				
					#3	3' 9"	3' 9"	5' 7"	6' 7"	7' 3"	7' 3"	8' 11"	9' 5"	11' 4"	11' 4"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"				
					STUD	3' 9"	3' 9"	5' 6"	5' 6"	7' 3"	7' 3"	8' 11"	9' 5"	11' 4"	11' 4"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"				
					#1	3' 9"	3' 9"	5' 6"	5' 6"	7' 3"	7' 3"	8' 11"	9' 5"	11' 4"	11' 4"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"				
SPF	STANDARD	DFL	4' 0"	8' 4"	8' 4"	8' 10"	7' 6"	8' 1"	8' 11"	9' 7"	11' 9"	12' 8"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"						
				#2	3' 11"	3' 11"	8' 4"	6' 10"	7' 6"	8' 1"	8' 11"	9' 7"	11' 9"	12' 8"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"					
				#3	3' 9"	3' 9"	5' 7"	6' 7"	7' 3"	7' 3"	8' 11"	9' 5"	11' 4"	11' 4"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"					
				STUD	3' 9"	3' 9"	5' 6"	5' 6"	7' 3"	7' 3"	8' 11"	9' 5"	11' 4"	11' 4"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"					
				#1	3' 9"	3' 9"	5' 6"	5' 6"	7' 3"	7' 3"	8' 11"	9' 5"	11' 4"	11' 4"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"					
SP	STANDARD	DFL	4' 0"	8' 4"	8' 4"	8' 10"	7' 6"	8' 1"	8' 11"	9' 7"	11' 9"	12' 8"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"						
				#2	3' 11"	3' 11"	8' 4"	6' 10"	7' 6"	8' 1"	8' 11"	9' 7"	11' 9"	12' 8"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"					
				#3	3' 9"	3' 9"	5' 7"	6' 7"	7' 3"	7' 3"	8' 11"	9' 5"	11' 4"	11' 4"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"					
				STUD	3' 9"	3' 9"	5' 6"	5' 6"	7' 3"	7' 3"	8' 11"	9' 5"	11' 4"	11' 4"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"					
				#1	3' 9"	3' 9"	5' 6"	5' 6"	7' 3"	7' 3"	8' 11"	9' 5"	11' 4"	11' 4"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"					
SPF	STANDARD	DFL	4' 0"	8' 4"	8' 4"	8' 10"	7' 6"	8' 1"	8' 11"	9' 7"	11' 9"	12' 8"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"						
				#2	3' 11"	3' 11"	8' 4"	6' 10"	7' 6"	8' 1"	8' 11"	9' 7"	11' 9"	12' 8"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"					
				#3	3' 9"	3' 9"	5' 7"	6' 7"	7' 3"	7' 3"	8' 11"	9' 5"	11' 4"	11' 4"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"					
				STUD	3' 9"	3' 9"	5' 6"	5' 6"	7' 3"	7' 3"	8' 11"	9' 5"	11' 4"	11' 4"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"					
				#1	3' 9"	3' 9"	5' 6"	5' 6"	7' 3"	7' 3"	8' 11"	9' 5"	11' 4"	11' 4"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"					
SP	STANDARD	DFL	4' 0"	8' 4"	8' 4"	8' 10"	7' 6"	8' 1"	8' 11"	9' 7"	11' 9"	12' 8"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"						
				#2	3' 11"	3' 11"	8' 4"	6' 10"	7' 6"	8' 1"	8' 11"	9' 7"	11' 9"	12' 8"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"					
				#3	3' 9"	3' 9"	5' 7"	6' 7"	7' 3"	7' 3"	8' 11"	9' 5"	11' 4"	11' 4"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"					
				STUD	3' 9"	3' 9"	5' 6"	5' 6"	7' 3"	7' 3"	8' 11"	9' 5"	11' 4"	11' 4"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"						
				#1	3' 9"	3' 9"	5' 6"	5' 6"	7' 3"	7' 3"	8' 11"	9' 5"	11' 4"	11' 4"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"	14' 0"</											




BRACING GROUP SPECIES AND GRADES:			
GROUP A:		GROUP B:	
SPRUE-PINE-YR	NOEL-YR	SPRUE-PINE-YR	NOEL-YR
#1 / #2	#1 / #2	#1 / #2	#1 / #2
STANDARD	STANDARD	STANDARD	STANDARD
STUD	STUD	STUD	STUD
STANDARD	STANDARD	STANDARD	STANDARD

CABLE TRUSS DETAIL NOTES:
 LIVE LOAD DEFLECTION CRITERIA IS L/240.
 PROVIDE UPLIFT CONNECTIONS FOR 100 PSF OVER CONTINUOUS BEARING (6 PSF TO DEAD LOAD).
 CABLE END SUPPORTS LOAD FROM 4' 0" OUTLOOKERS WITH 8' 0" OVERHANG, OR 12" PLYWOOD OVERHANG.
 ATTACH EACH "L" BRACE WITH 104 NAILS.
 * FOR (1) "L" BRACE, SPACE NAILS AT 8" O.C. ON 16" END ZONES AND 4" O.C. BETWEEN ZONES.
 ** FOR (2) "L" BRACES, SPACE NAILS AT 8" O.C. ON 16" END ZONES AND 4" O.C. BETWEEN ZONES.
 "L" BRACING MUST BE A MINIMUM OF 80% OF WEB MEMBER LENGTH.

CABLE VERTICAL PLATE SIZES			
VERTICAL LENGTH	NO SERVICE	LESS THAN 4' 0"	1x4 OR 2x3
GREATER THAN 4' 0" BUT LESS THAN 11' 6"	2x4		
GREATER THAN 11' 6"	2x6		

+ REFER TO COMMON TRUSS DESIGN FOR PLATE, SPRUCE, AND BEEL PLATES.



ADVANCE TRUSSES REQUIRE EXTREME CARE IN FABRICATING, HANDLING, STORING, INSTALLING AND ERECTING. REFER TO BCST-1-03 GUIDING COMPONENT SAFETY INFORMATION, PUBLISHED BY THE TRUSS ASSOCIATION, 6800 ENTERPRISE LN., SUITE 200, MARIETTA, GA 30067 AND VICA (WOOD TRUSS COUNCIL) WEBSITE. UNLESS OTHERWISE INDICATED, TOP CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PLATES AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED ROOF CEILING.

REVIEWED
 By Julius Lee at 12:00 pm, Jun 11, 2008

JULIUS LEE'S
 CONSULTING ENGINEERS P.A.
 1456 SW 4th Avenue
 DELRAY BEACH, FL 33444-2611

No. 34869
 STATE OF FLORIDA

MAX. TOT. LD. 60 PSF
 MAX. SPACING 24.0"

REF ASCE 7-02-GAB10030
 DATE 11/26/03
 DWG. NUMBER STD. GABLE 06 2 11
 -ENG

TOP CHORD 2X4 #2 OR BETTER
BOT CHORD 2X4 #2 OR BETTER
WEBS 2X4 #3 OR BETTER

PIGGYBACK DETAIL

REFER TO SEALED DESIGN FOR DASHED PLATES.

SPACE PIGGYBACK VERTICALS AT 4' OC MAX.

TOP AND BOTTOM CHORD SPICES MUST BE STAGGERED SO THAT ONE SPICE IS NOT DIRECTLY OVER ANOTHER.

PIGGYBACK BOTTOM CHORD MAY BE OMITTED. ATTACH VERTICAL WEBS TO TRUSS TOP CHORD WITH 1.5X3 PLATE.

ATTACH PURLINS TO TOP OF FLAT TOP CHORD. IF PIGGYBACK IS SOLID LUMBER OR THE BOTTOM CHORD IS OMITTED, PURLINS MAY BE APPLIED BENEATH THE TOP CHORD OF SUPPORTING TRUSS.

REFER TO ENGINEER'S SEALED DESIGN FOR REQUIRED PURLIN SPACING.

THIS DETAIL IS APPLICABLE FOR THE FOLLOWING WIND CONDITIONS:


110 MPH WIND, 30' MEAN HGT, ASCE 7-02, CLOSED BLDG, LOCATED ANYWHERE IN ROOF, 1 MI FROM COAST

CAT I, EXP C, WIND TC DL=5 PSF, WIND BC DL=5 PSF

110 MPH WIND, 30' MEAN HGT, ETC ENCLOSED BLDG, LOCATED ANYWHERE IN ROOF WIND TC DL=5 PSF, WIND BC DL=5 PSF


FRONT FACE (E*) PLATES MAY BE OFFSET FROM BACK FACE PLATES AS LONG AS BOTH FACES ARE SPACED 4' OC MAX.

130 MPH WIND, 30' MEAN HGT, ASCE 7-02, CLOSED BLDG, LOCATED ANYWHERE IN ROOF, CAT II, EXP. C, WIND TC DL=6 PSF, WIND BC DL=6 PSF



BETTER PLATE LOCATION IS ACCEPTABLE

OPTIONAL SPLICE




ATTACH TRUSS PLATES WITH (6) 0.120" X 1.375" NAILS OR EQUAL, PER FACE PER PLY. (4) NAILS IN EACH MEMBER TO BE CONNECTED. REFER TO DRAWING 160 TL FOR TRUSS INFORMATION.

JOINT TYPE	SPANS UP TO		
	30'	36'	62'
A	2X4	2.5X4	3X6
B	4X6	6X6	6X6
C	1.5X3	1.5X4	1.5X4
D	5X4	6X5	6X5
E	4X6 OR 3X6 TRUSS AT 4' OC, ROTATED VERTICALLY		

WEB LENGTH	WEB BRACING CHART
0' TO 7'9"	NO BRACING
7'9" TO 10'	1X4 "T" BRACE, SAME GRADE, SPECIES AS WEB MEMBER, OR BETTER, AND 80% LENGTH OF WEB MEMBER. ATTACH WITH 6d NAILS AT 4' OC.
10' TO 14'	2X4 "T" BRACE, SAME GRADE, SPECIES AS WEB MEMBER, OR BETTER, AND 80% LENGTH OF WEB MEMBER. ATTACH WITH 16d NAILS AT 4' OC.

* PIGGYBACK SPECIAL PLATE

ATTACH TEETH TO THE PIGGYBACK AT THE TRUE OR FABRICATION. ATTACH TO SUPPORTING TRUSS WITH (4) 0.120" X 1.375" NAILS PER FACE PER PLY. APPLY PIGGYBACK SPECIAL PLATE TO EACH TRUSS FACE AND SPACE 4' OC OR LESS.



THIS DRAWING REPLACES DRAWINGS 634.016 634.017 & 647.045

JULIUS LEE'S
CONS. ENGINEERS P.A.

1499 SW 4TH AVENUE
DIABLO BEACH, FL 33411-2161

MAX LOADING

55 PSF AT

1.33 DUR. FAC.

50 PSF AT

1.25 DUR. FAC.

47 PSF AT

1.15 DUR. FAC.

SPACING


24.0"

REF PIGGYBACK

DATE 09/12/07

DRWG/ITEK STD PIGGY

-ENG JL



REVIEWED

By Julius Lee at 11:59 am, Jun 11, 2008

No. 34869
STATE OF FLORIDA

TOE-NAIL DETAIL

TOE-NAILS TO BE DRIVEN AT AN ANGLE OF APPROXIMATELY THIRTY DEGREES WITH THE PIECE AND STARTED APPROXIMATELY ONE-THIRD THE LENGTH OF THE NAIL FROM THE END OF THE MEMBER.

PER ANSI/AF&PA NDS-2001 SECTION 12.4.1 - EDGE DISTANCE, END DISTANCE, SPACING, "EDGE DISTANCES, END DISTANCES AND SPACINGS FOR NAILS AND SPIKES SHALL BE SUFFICIENT TO PREVENT SPLITTING OF THE WOOD."



THE NUMBER OF TOE-NAILS TO BE USED IN A SPECIFIC APPLICATION IS DEPENDENT UPON PROPERTIES FOR THE CHORD SIZE, LUMBER SPECIES AND NAIL TYPE. PROPER CONSTRUCTION PRACTICES AS WELL AS GOOD JUDGEMENT SHOULD DETERMINE THE NUMBER OF NAILS TO BE USED.

THIS DETAIL DISPLAYS A TOE-NAILED CONNECTION FOR JACK FRAMING INTO A SINGLE OR DOUBLE PLY SUPPORTING GIRDER.

MAXIMUM VERTICAL RESISTANCE OF 16d (0.162"x3.5") COMMON TOE-NAILS


NUMBER OF TOE-NAILS	SOUTHERN PINE		DOUGLAS FIR-LARCH		HEM-FIR		SPRUCE PINE FIR	
	1 PLY	2 PILES	1 PLY	2 PILES	1 PLY	2 PILES	1 PLY	2 PILES
2	187#	256#	181#	234#	156#	203#	154#	199#
3	296#	383#	271#	351#	234#	304#	230#	298#
4	394#	511#	361#	468#	312#	406#	307#	397#
5	493#	639#	452#	585#	390#	507#	384#	496#

ALL VALUES MAY BE MULTIPLIED BY APPROPRIATE DURATION OF LOAD FACTOR.



THIS DRAWING REPLACES DRAWING 784040

VARIOUS TRUSSES REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND ERECTION. REFER TO BEST PRACTICES FOR TRUSS CONSTRUCTION, PUBLISHED BY THE TRUSS COUNCIL OF AMERICA, 6800 ENTERPRISE LN, NORTON, VT 50719 FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, THIS CHORD SHALL HAVE PROPERLY ATTACHED STRUCTURAL PANELS AND BATTEN CHORD SHALL HAVE A PROPERLY ATTACHED ROOF CEILING.



REVIEWED
By Julius Lee at 11:59 am, Jun 11, 2008

JULIUS LEE'S
CONS. ENGINEERS P.A.
1490 ST 4TH AVENUE
DELRAY BEACH, FL 33444-2161

No. 34869
STATE OF FLORIDA

TC LL	PSF	REF	TOE-NAIL
TC DL	PSF	DATE	09/12/07
BC DL	PSF	DRWG	CNTONALL1103
BC LL	PSF	-ENG	JL
TOT. LD.	PSF		
DUR. FAC.	1.00		
SPACING			




TRULOX CONNECTION DETAIL

11 GAUGE (0.120" X 1.375") NAILS REQUIRED FOR TRULOX PLATE ATTACHMENT. FILL ROWS COMPLETELY WHERE SHOWN (Φ).

* NAILS MAY BE OMITTED FROM THESE ROWS.

THIS DETAIL MAY BE USED WITH SO. PINE, DOUGLAS-FIR OR HEM-FIR CHORDS WITH A MINIMUM 1.00 DURATION OF LOAD OR SPRUCE-PINE-FIR CHORDS WITH A MINIMUM 1.15 DURATION OF LOAD. CHORD SIZE OF BOTH TRUSSES MUST EXCEED THE TRULOX PLATE WIDTH.

TRULOX PLATE IS CENTERED ON THE CHORDS AND BENT BETWEEN NAIL ROWS.
REFER TO ENGINEER'S SEALED DESIGN REFERENCING THIS DETAIL FOR LUMBER, PLATES, AND OTHER INFORMATION NOT SHOWN.




MINIMUM 3X6 TRULOX PLATE

TRULOX PLATE SIZE	REQUIRED NAILS PER TRUSS	MAXIMUM LOAD UP OR DOWN
3X6	9	350#
6X6	15	990#

MINIMUM 5X6 TRULOX PLATE

THIS DRAWING REPLACES DRAWINGS 1,158,986 1,158,986/R 1,154,844 1,152,217 1,152,017 1,159,154 & 1,151,524



WARNING: TRUSSES REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND BRACING. REFER TO 2031-1-03 (BUILDING DEPARTMENT SAFETY INFORMATION, PUBLISHED BY THE TRUSS BRACING INSTITUTE, 5851 JENNIFER DR., SUITE 200, WATSON, VA 22093) AND VITA (WOOD TRUSS COUNCIL, 1000 N. 10TH ST., SUITE 100, WATSON, VA 22093) FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, TOP CHORD SHALL HAVE PROPERLY ATTACHED ROOFING PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED ROOF CEILING.

JULIUS LEE'S
CONS. ENGINEERS P.A.

1255 SW 4TH AVENUE
DELRAY BEACH, FL 33444-2101

No. 34869
STATE OF FLORIDA

REF TRULOX







DATE 11/26/03

DRWG CNTRULOX1103

-ENG JL

MULTIPLE-MEMBER CONNECTIONS FOR SIDE-LOADED BEAMS

Maximum Uniform Load Applied to Either Outside Member (PLF)


Connector Type	Number of Rows	Connector On-Center Spacing	Connector Pattern					
			Assembly A	Assembly B	Assembly C	Assembly D	Assembly E	Assembly F
								
			3 1/2" 2-ply	5 1/4" 3-ply	5 1/4" 2-ply	7" 3-ply	7" 2-ply	7" 4-ply
10d (0.128" x 3") Nail ⁽¹⁾	2	12"	370	280	280	245		
	3	12"	555	415	415	370		
1/2" A307 Through Bolts ⁽²⁾⁽⁴⁾	2	24"	505	380	520	465	860	340
		19.2"	635	475	655	580	1,075	425
		16"	760	570	785	695	1,290	505
SDS 1/4" x 3 1/2" ⁽⁴⁾	2	24"	680	510	510	455		
		19.2"	850	640	640	565		
		16"	1,020	765	765	680		
SDS 1/4" x 6" ⁽³⁾⁽⁴⁾	2	24"				455	465	455
		19.2"				565	580	565
		16"				680	695	680
USP WS35 ⁽⁴⁾	2	24"	480	360	360	320		
		19.2"	600	450	450	400		
		16"	715	540	540	480		
USP WS6 ⁽³⁾⁽⁴⁾	2	24"				350	525	350
		19.2"				440	660	440
		16"				525	790	525
3 3/4" TrussLok ⁽⁴⁾	2	24"	635	475	475	425		
		19.2"	795	595	595	530		
		16"	955	715	715	635		
5" TrussLok ⁽⁴⁾	2	24"		500	500	445	480	445
		19.2"		625	625	555	600	555
		16"		750	750	665	725	665
6 3/4" TrussLok ⁽⁴⁾	2	24"				445	620	445
		19.2"				555	770	555
		16"				665	925	665

- (1) Nailed connection values may be doubled for 6" on-center or tripled for 4" on-center nail spacing.
- (2) Washers required. Bolt holes to be 1/16" maximum.
- (3) 6" SDS or WS screws can be used with Parallam® PSL and Microllam® LVL, but are not recommended for TimberStrand® LSL.
- (4) 24" on-center bolted and screwed connection values may be doubled for 12" on-center spacing.

General Notes

- Connections are based on NDS® 2005 or manufacturer's code report.
- Use specific gravity of 0.5 when designing lateral connections.
- Values listed are for 100% stress level. Increase 15% for snow-loaded roof conditions or 25% for non-snow roof conditions, where code allows.
- Bold Italic** cells indicate **Connector Pattern** must be installed on both sides. Stagger fasteners on opposite side of beam by 1/2 the required **Connector Spacing**.
- Verify adequacy of beam in allowable load tables on pages 16–33.
- 7" wide beams should be side-loaded only when loads are applied to both sides of the members (to minimize rotation).
- Minimum end distance for bolts and screws is 6".
- Beams wider than 7" require special consideration by the design professional.

Uniform Load Design Example



First, check the allowable load tables on pages 16–33 to verify that three pieces can carry the total load of 715 plf with proper live load deflection criteria. Maximum load applied to either outside member is 415 plf. For a 3-ply 1 3/4" assembly, two rows of 10d (0.128" x 3") nails at 12" on-center is good for only 280 plf. Therefore, use three rows of 10d (0.128" x 3") nails at 12" on-center (good for 415 plf).

Alternates:

Two rows of 1/2" bolts or SDS 1/4" x 3 1/2" screws at 19.2" on-center.

MULTIPLE-MEMBER CONNECTIONS FOR SIDE-LOADED BEAMS

Point Load—Maximum Point Load Applied to Either Outside Member (lbs)

Connector Type	Number of Connectors	Connector Pattern					
		Assembly A	Assembly B	Assembly C	Assembly D	Assembly E	Assembly F
		3 1/2" 2-ply	5 1/4" 3-ply	5 1/4" 2-ply	7" 3-ply	7" 2-ply	7" 4-ply
10d (0.128" x 3") Nail	6	1,110	835	835	740		
	12	2,225	1,670	1,670	1,485		
	18	3,335	2,505	2,505	2,225		
	24	4,450	3,335	3,335	2,965		
SDS Screws 1/4" x 3 1/2" or WS35 1/4" x 6" or WS6(1)	4	1,915	1,435(4)	1,435	1,275	1,860(2)	1,405(2)
	6	2,870	2,150 (4)	2,150	1,915	2,785(2)	2,110(2)
	8	3,825	2,870 (4)	2,870	2,550	3,715(2)	2,810(2)
3 3/8" or 5" TrussLok™	4	2,545	1,910 (4)	1,910	1,695	1,925(3)	1,775(3)
	6	3,815	2,860 (4)	2,860	2,545	2,890(3)	2,665(3)
	8	5,090	3,815 (4)	3,815	3,390	3,855(3)	3,550(3)

(1) 6" SDS or WS screws can be used with Parallam® PSL and Microllam® LVL, but are not recommended for TimberStrand® LSL.

See General Notes on page 38


(2) 6" long screws required.

(3) 5" long screws required.


(4) 3 1/2" and 3 3/8" long screws must be installed on both sides.

Connections


4 or 6 or Screw Connection



8 Screw Connection




Nail Connection



There must be an equal number of nails on each side of the connection

Point Load Design Example



First, verify that a 3-ply 1 3/4" x 14" beam is capable of supporting the 3,000 lb point load as well as all other loads applied. The 3,000 lb point load is being transferred to the beam with a face mount hanger. For a 3-ply 1 3/4" assembly, eight 3 3/8" TrussLok™ screws are good for 3,815 lbs with a face mount hanger.

MULTIPLE-MEMBER CONNECTIONS FOR TOP-LOADED BEAMS

1 3/4" Wide Pieces

- Minimum of three rows of 10d (0.128" x 3") nails at 12" on-center.
- Minimum of four rows of 10d (0.128" x 3") nails at 12" on-center for 14" or deeper.
- If using 12d–16d (0.148"–0.162" diameter) nails, the number of nailing rows may be reduced by one.
- Minimum of two rows of SDS, WS, or TrussLok™ screws at 16" on-center. Use 3 3/8" minimum length with two or three plies; 5" minimum for 4-ply members. 6" SDS and WS screws are not recommended for use with TimberStrand® LSL. For 3- or 4-ply members, connectors must be installed

on both sides. Stagger fasteners on opposite side of beam by 1/2 of the required connector spacing.


- Load must be applied evenly across entire beam width. Otherwise, use connections for side-loaded beams.

3 1/2" Wide Pieces

- Minimum of two rows of SDS, WS, or TrussLok™ screws, 5" minimum length, at 16" on-center. 6" SDS and WS screws are not recommended for use with TimberStrand® LSL. Connectors must be installed on both sides. Stagger fasteners on opposite side of beam by 1/2 of the required connector spacing.

- Load must be applied evenly across entire beam width. Otherwise, use connections for side-loaded beams.


- Minimum of two rows of 1/2" bolts at 24" on-center staggered.




Multiple pieces can be nailed or bolted together to form a header or beam of the required size, up to a maximum width of 7"

L6

STRONG BACK DETAIL SYSTEM-42 OR FLAT TRUSS




ALTERNATE DETAIL FOR STRONG BACK WITH VERTICAL NOT LINING UP



REVIEWED

By Julius Lee at 11:58 am, Jun 11, 2008



JULIUS LEE'S
CONS. ENGINEERS P.A.


1425 SW 4th AVENUE
ORLANDO BEACH, FL 32844-2611

No. 34869
STATE OF FLORIDA

1/2" DIAMETER BOLT SPACING FOR LOAD APPLIED PARALLEL TO GRAIN.

* GRADE AND SPECIES AS SPECIFIED ON THE ALPINE DESIGN.
BOLT HOLES SHALL BE A MINIMUM OF 1/32" TO A MAXIMUM OF 1/16" LARGER THAN BOLT DIAMETER.


TYPICAL LOCATION OF 1/2" DIAMETER THRU BOLTS. BOLT QUANTITIES AS NOTED ON SEALED DESIGN MUST BE APPLIED IN ONE OF THE PATTERNS SHOWN BELOW.
WASHERS REQUIRED UNDER BOLT HEAD AND NUT



2X6 DETAIL

2X8 DETAIL

THIS DRAWING REPLACES DRAWING A628.016



WARNING: TRUSSES REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND ERECTION. REFER TO BOSS L-03 BUILDING COMPONENT SAFETY INFORMATION, PUBLISHED BY THE TRUSS ASSOCIATION, 3665 DOWNEY DR., SUITE 200, MADISON, VA 22719, AND VICTA CYCLED TRUSS COUNCIL, 1000 W. 10TH AVE., SUITE 100, DENVER, CO 80202. ALL TRUSSES SHALL HAVE A PROPERLY ATTACHED STRUCTURAL PANELS AND BOLTING CHORDS SHALL HAVE A PROPERLY ATTACHED RIBBON DETAIL.

REVIEWED
By Julius Lee at 11:59 am, Jun 11, 2008

JULIUS LEE'S
CONS. ENGINEERS P.A.
1450 87 4TH AVENUE
DELRAY BEACH, FL 33444-2161

No. 34869
STATE OF FLORIDA

TC IL	PSF	REF	BOLT SPACING
TC DL	PSF	DATE	11/26/03
BC DL	PSF	DRWG	CNBOLTSPI103
BC IL	PSF	-ENG	JL
TOT. LD.	PSF		
DUR. FAC.			
SPACING			

VALLEY TRUSS DETAIL


TOP CHORD 2X4 SP #2 OR SPF #1/#2 OR BETTER.
BOT CHORD 2X3(*) OR 2X4 SP #2N OR SPF #1/#2 OR BETTER.
WEBS 2X4 SP #3 OR BETTER.

* 2X3 MAY BE RIPPED FROM A 2X6 (PITCHED OR SQUARE).


** ATTACH EACH VALLEY TO EVERY SUPPORTING TRUSS WITH:

(2) 16d BOX (0.135" X 3.5") NAILS TOE-NAILED FOR
FBC 2004 110 MPH, ASCE 7-02 110 MPH WIND OR (3) 16d FOR
ASCE 7-02 130 MPH WIND. 15' MEAN HEIGHT, ENCLOSED
BUILDING, EXP. C. RESIDENTIAL, WIND TC DL=6 PSF.

CUT FROM 2X6 OR
LARGER AS REQ'D



PITCHED CUT
BOTTOM CHORD
VALLEY



SQUARE CUT
BOTTOM CHORD
VALLEY

*** NOTE THAT THE PURLIN SPACING FOR BRACING THE TOP CHORD OF THE TRUSS
BENEATH THE VALLEY IS MEASURED ALONG THE SLOPE OF THE TOP CHORD.
++ LARGER SPANS MAY BE BUILT AS LONG AS THE VERTICAL HEIGHT DOES
NOT EXCEED 12'0".
BOTTOM CHORD MAY BE SQUARE OR PITCHED CUT AS SHOWN.


BY VALLEY TRUSSES USED IN LIEU OF PURLIN SPACING AS SPECIFIED ON
ENGINEERS' SEALED DESIGN.

UNLESS SPECIFIED ON ENGINEER'S SEALED DESIGN, APPLY 1X4 "L"-BRACE, 80%
LENGTH OF WEB, VALLEY WEB, SAME SPECIES AND GRADE OR BETTER, ATTACHED
WITH 8d BOX (0.135" X 2.5") NAILS AT 6" OC, OR CONTINUOUS LATERAL BRACING,
EQUALLY SPACED, FOR VERTICAL VALLEY WEBS GREATER THAN 7'9".
MAXIMUM VALLEY VERTICAL HEIGHT MAY NOT EXCEED 12'0".

TOP CHORD OF TRUSS BENEATH VALLEY SET MUST BE BRACED WITH:


PROPERLY ATTACHED, RATED SHEATHING APPLIED PRIOR TO VALLEY TRUSS
INSTALLATION

PURLINS AT 24" OC OR AS OTHERWISE SPECIFIED ON ENGINEERS' SEALED DESIGN
OR
BY VALLEY TRUSSES USED IN LIEU OF PURLIN SPACING AS SPECIFIED ON
ENGINEERS' SEALED DESIGN.




OPTIONAL STUB
END DETAIL

OPTIONAL HIP
JOINT DETAIL



20-0-0 MAX (++)



COMMON TRUSSES
AT 24" OC

PARTIAL FRAMING
PLAN

THIS DRAWING REPLACES DRAWING A105


JULIUS LEE'S
CONS. ENGINEERS P.A.

1455 SW 4th AVENUE
DELRAY BEACH, FL 33444-5001


TC IL	20	20	PSF	REF	VALLEY DETAIL
TC DL	7	15	PSF	DATE	11/26/03
BC DL	5	5	PSF	DRWG	VALTRUSS1103
BC IL	0	0	PSF	-ENG	IL
TOT. LD.	32	40	PSF		

REVIEWED


By Julius Lee at 11:59 am, Jun 11, 2008




TYPICAL ATTIC TRUSS BRACING



TYPICAL ALTERNATE BRACING DETAIL FOR EXTERIOR FLAT GIRDER TRUSS




GABLE END TRUSS DETAIL



MONITOR DO BRACING ON GABLE TRUSS OTHER PERMANENT BRACING DESIGNED BY ARCHITECT OR EOR


TYPICAL WALL GIRDER VERTICAL WEB BRACING DETAIL



SEE ROOF TRUSSES FOR UPLIFT

ROOF 24" O/C


SEE GABLE END DETAIL FOR T-BRACE BEHIND EACH VERTICAL



A-A


No. 34680
STATE OF FLORIDA

JULIUS LEE'S
CONS. ENGINEERS P.A.
1455 SW 4th AVENUE
DIKRAY BLDG. FL 33444-2611



REVIEWED
By Julius Lee at 11:59 am, Jun 14, 2008

MAX GABLE VERTICAL LENGTH													
CABLE VERTICAL SPACING	BRACE SPECIES	BRACE GRADE	NO BRACES	(1) 1X4 "L" BRACE *		(1) 2X4 "L" BRACE *		(1) 2X6 "L" BRACE *		(2) 2X8 "L" BRACE *			
				GROUP A	GROUP B	GROUP A	GROUP B	GROUP A	GROUP B	GROUP A	GROUP B		
24" O.C.	SPF	#1 / #2	3' 4"	6' 10"	8' 0"	8' 11"	8' 3"	8' 6"	10' 10"	11' 2"	12' 11"	13' 3"	
		#8	3' 3"	4' 11"	4' 11"	6' 6"	6' 6"	8' 3"	8' 3"	10' 1"	10' 1"	12' 11"	12' 11"
		STUD	3' 3"	4' 11"	4' 11"	6' 5"	6' 5"	8' 3"	8' 3"	10' 0"	10' 0"	12' 11"	12' 11"
		STANDARD	3' 3"	4' 2"	4' 2"	5' 6"	5' 6"	7' 5"	7' 5"	8' 8"	8' 8"	11' 8"	11' 8"
		#1	3' 8"	5' 10"	6' 3"	6' 11"	7' 5"	8' 3"	8' 11"	10' 10"	11' 6"	12' 11"	13' 11"
		#2	3' 7"	6' 10"	6' 3"	6' 11"	7' 5"	8' 3"	8' 11"	10' 10"	11' 6"	12' 11"	13' 11"
	SP	#3	3' 6"	5' 0"	5' 0"	6' 3"	6' 6"	8' 3"	8' 3"	10' 4"	10' 4"	12' 11"	13' 7"
		STUD	3' 6"	5' 0"	5' 0"	6' 7"	6' 7"	8' 3"	8' 8"	10' 3"	10' 3"	12' 11"	13' 7"
		STANDARD	3' 4"	4' 3"	4' 3"	5' 8"	5' 8"	7' 8"	7' 8"	8' 10"	8' 10"	12' 0"	12' 0"
		#1 / #2	3' 10"	6' 8"	6' 10"	7' 11"	8' 1"	9' 6"	9' 8"	12' 6"	12' 9"	14' 0"	14' 0"
		#8	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"
		STUD	3' 9"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"
SPF	#1 / #2	3' 10"	6' 8"	6' 10"	7' 11"	8' 1"	9' 6"	9' 8"	12' 6"	12' 9"	14' 0"	14' 0"	
	#8	3' 8"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
	STUD	3' 9"	6' 0"	6' 0"	7' 11"	7' 11"	9' 5"	9' 5"	12' 4"	12' 4"	14' 0"	14' 0"	
	STANDARD	3' 9"	5' 8"	6' 2"	6' 10"	6' 10"	8' 2"	8' 2"	10' 7"	10' 7"	14' 0"	14' 0"	
	#1	4' 2"	6' 8"	7' 2"	7' 11"	8' 6"	9' 5"	10' 2"	12' 5"	13' 5"	14' 0"	14' 0"	
	#2	4' 2"	6' 8"	7' 2"	7' 11"	8' 6"	9' 5"	10' 2"	12' 5"	13' 5"	14' 0"	14' 0"	
SP	#3	4' 0"	6' 8"	6' 2"	7' 11"	8' 2"	9' 6"	9' 11"	12' 6"	13' 8"	14' 0"	14' 0"	
	STUD	4' 0"	6' 8"	6' 2"	7' 11"	8' 2"	9' 6"	9' 11"	12' 6"	13' 8"	14' 0"	14' 0"	
	STANDARD	4' 10"	5' 1"	6' 1"	7' 11"	8' 1"	9' 5"	9' 11"	12' 5"	12' 6"	14' 0"	14' 0"	
	#1 / #2	4' 3"	7' 4"	7' 4"	8' 11"	8' 11"	10' 8"	10' 8"	13' 8"	14' 0"	14' 0"	14' 0"	
	#8	4' 2"	6' 11"	6' 11"	8' 9"	8' 9"	10' 5"	10' 5"	13' 8"	13' 8"	14' 0"	14' 0"	
	STUD	4' 2"	6' 11"	6' 11"	8' 9"	8' 9"	10' 5"	10' 5"	13' 8"	13' 8"	14' 0"	14' 0"	
SPF	#1 / #2	4' 3"	7' 4"	7' 4"	8' 11"	8' 11"	10' 8"	10' 8"	13' 8"	14' 0"	14' 0"	14' 0"	
	#8	4' 2"	6' 11"	6' 11"	8' 9"	8' 9"	10' 5"	10' 5"	13' 8"	13' 8"	14' 0"	14' 0"	
	STUD	4' 2"	6' 11"	6' 11"	8' 9"	8' 9"	10' 5"	10' 5"	13' 8"	13' 8"	14' 0"	14' 0"	
	STANDARD	4' 2"	6' 11"	6' 11"	7' 10"	7' 10"	10' 6"	10' 6"	13' 9"	13' 9"	14' 0"	14' 0"	
	#1	4' 8"	7' 4"	7' 11"	8' 9"	8' 5"	10' 5"	11' 2"	13' 8"				



REFER TO CHART ABOVE FOR MAX CABLE VERTICAL LENGTH

BRACING GROUP SPECIES AND GRADES:			
GROUP A:			
SPRUCE-PINE-YR		KID-FIR	
#1 / #2	STANDARD	#2	STUD
#3	STUD	#3	STANDARD
DOUGLAS FIR-LARCH		SOUTHERN PINE	
#2		#3	
STUD		STUD	
STANDARD		STANDARD	
GROUP B:			
RED-FIR		KID-FIR	
#1 & BITE		#2	BITE
#1			
SOUTHERN PINE		DOUGLAS FIR-LARCH	
#2		#1	
		#2	


CABLE TRUSS DETAIL NOTES:

LIVE LOAD DEFLECTION CRITERIA IS $L/240$.
 PROVIDE UPLIFT CONNECTIONS FOR 136 PLF OVER
 CONTINUOUS BEARING (6 PSF VC DEAD LOAD).
 GABRIEL END SUPPORTS LOAD FROM 4'-0"

ATTACH T¹ BRACE WITH 104 NAILS.
FOR (1) T¹ BRACE, SPACE NAILS AT 8" O.C.
IN 18" END ZONES AND 4" O.C. BETWEEN ZONES
FOR (2) T¹ BRACES, SPACE NAILS AT 3" O.C.
IN 18" END ZONES AND 6" O.C. BETWEEN ZONES
T¹ BRACING MUST BE A MINIMUM OF 80% OF WEB
MEMBER LENGTH.

CHALE VERTICAL PLATE SIZES	
VERTICAL LENGTH	NO. SPLICES
LESS THAN 4' 0"	1X4 OR 2X3
GREATER THAN 4' 0", BUT LESS THAN 11' 6"	2X4
GREATER THAN 11' 6"	2, 3X4

+ REFER TO COLUMN TIEUS DESIGN FOR
PEAK, SPLICE, AND BEEL PLATES.



—WARNING— THESE REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHOPPING, INSTALLING AND BRACING. REFER TO 2001 I-90 (BUILDING COMPONENT SAFETY INFORMATION) PUBLISHED BY THE FEDERAL BUREAU OF INVESTIGATION, 384 POLICE PL. BLDG., SUITE 200, WASHINGTON, DC 20535 AND VITA (VIOLENCE INFORMATION) PUBLISHED BY THE FEDERAL BUREAU OF INVESTIGATION, 384 POLICE PL. BLDG., SUITE 200, WASHINGTON, DC 20535 FOR SAFETY PRACTICES PRIOR TO PERFORMING THESE FUNCTIONS. UNLESS OTHERWISE INDICATED, THE CARD SHALL HAVE PROPERLY ATTACHED PRACTICAL PANELS AND BOTTOM CARD SHALL HAVE A PROPERLY ATTACHED ROOF CEILING.


JULIUS LEE'S
CONS. ENGINEERS P.A.

REF	ASCE7-02-CMB13015
DATE	11/26/03
DRWG	MTRK STD CASE 15 E HT
-ENG	

REVIEWED
By Julius Lee at 12:00 pm, Jun 11, 2008

No: 34869
STATE OF FLORIDA



MAX. TOT. L.D. 60 PSF
MAX. SPACING 24.0"



BEARING HEIGHT SCHEDULE

12'-0"

4/12 PITCH
2'-0" O/H



NOTES:

- 1) REFER TO HB 91 (RECOMMENDATIONS FOR HANDING INSTALLATION AND TEMPORARY BRACING) REFER TO ENGINEERED DRAWINGS FOR PERMANENT BRACING REQUIRED.
- 2) ALL TRUSSES INCLUDING TRUSSES UNDER VALLEY FRAMING MUST BE COMPLETELY DECKED OR REFER TO DETAIL V05 FOR ALTERNATE BRACING REQUIREMENTS.
- 3) ALL VALLEYS ARE TO BE CONVENTIONALLY FRAMED BY BUILDER.
- 4) ALL TRUSSES ARE DESIGNED FOR 2 o.c. MAXIMUM SPACING, UNLESS OTHERWISE NOTED.
- 5) ALL WALLS SHOWN ON PLACEMENT PLAN ARE CONSIDERED TO BE LOAD BEARING, UNLESS OTHERWISE NOTED.
- 6) 5x42 TRUSSES MUST BE INSTALLED WITH THE TOP BEING UP.
- 7) ALL E200F TRUSS HANGERS TO BE SIMPSON H1026 UNLESS OTHERWISE NOTED. ALL FLOOR TRUSS HANGERS TO BE SIMPSON TH4422 UNLESS OTHERWISE NOTED.
- 8) BEAMW/AD/EQU/INTEL (H20) TO BE FURNISHED BY BUILDER.

SHOP DRAWING APPROVAL

THIS LAYOUT IS THE SOLE SOURCE FOR FABRICATION OF TRUSSES AND V05S. ALL PERIODS ARCHITECTURAL OR OTHER TRUSS LAYOUTS, REVIEW AND APPROVAL OF THIS LAYOUT MUST BE RECEIVED BEFORE ANY TRUSSES WILL BE BUILT. VERIFY ALL CONDITIONS TO INSURE AGAINST CHANGES THAT WILL RESULT IN EXTRA CHARGES TO YOU.

Request Delivery Date: _____

Approved By: _____ Date: _____



Bunnell

PHONE: 904-437-3349 FAX: 904-437-3994

Jacksonville

PHONE: 904-772-6100 FAX: 904-772-1973

Lake City

PHONE: 386-795-6894 FAX: 386-795-7973

Sanford

PHONE: 407-322-0094 FAX: 407-322-9593

SKYLINE HOMES

PHINNEY SHED

CUSTOM

3-5-09 K.L.H. 300049