

WEST LAKE CITY FA# 10096114 CROWN CASTLE BU# 824653


299 NORTHWEST BROWN ROAD LAKE CITY. FL 32055

TENANT IMPROVEMENT - 5G NR RADIO/5G NR/4TX4RX/BBU

PACE JOB #:MRTFL026618/MRTFL026819/MRTFL026590/MRTFL026357/MRTFL026375/

MRTFL025745/MRTFL026347/MRTFL026376

5. NO SOLID WASTE WILL BE GENERATED AT THIS LOCATION.



DESCRIPTION A 10/28/22 PRELIMINARY CDs REV " 0 11/30/22 FINAL CDs ISSUED 6 9 GEN3 PROJECT NO.: 102210047 DRAWN BY: CHECKED BY:



MF

12150 RESEARCH PARKWAY ORLANDO, FL 32826

ММ



1997 ANNAPOLIS EXCHANGE PKWY SUITE 200 ANNAPOLIS, MD 21401



27139 SEA BREEZE WAY WESLEY CHAPEL, FLORIDA 33544 (813)917-2671

THIS ITEM HAS BEEN ELECTRONICALLY SIGNED & SEALED BY MARC P. MAIER, P.E., FL. LICENSE #72513 USING A DIGITAL SIGNATURE. PRINTED COPIES OF THIS DOCUMENT ARE NOT CONSIDERED SIGNED & SEALED & THE SIGNATURE MUST BE VERIFIED ON ANY ELECTRONIC COPIES.

STATE OF . SSONAL ENGLIS CORIDA 177, STONAL ENGLIST **NOVEMBER 30, 2022** MARC P. MAIER. PE

FL PROFESSIONAL ENGINEER LIC # 72513

WEST LAKE CITY FA #10096114

299 NW BROWN RD LAKE CITY, FL 32055

SHEET DESCRIPTION

TITLE SHEET

SHEET NUMBER

T-1

GENERAL NOTES:

- 1. ALL REFERENCES TO OWNER HEREIN SHALL BE CONSTRUED TO MEAN AT&T OR IT'S DESIGNATED REPRESENTATIVE.
- 2. ALL WORK PRESENTED ON THESE DRAWINGS MUST BE COMPLETED BY THE CONTRACTOR UNLESS NOTED OTHERWISE. THE CONTRACTOR MUST HAVE CONSIDERABLE EXPERIENCE IN PERFORMANCE OF WORK SIMILAR TO THAT ATTESTING THAT HE DOES HAVE SUFFICIENT EXPERIENCE AND ABILITY, THAT HE IS KNOWLEDGEABLE OF THE WORK TO BE PERFORMED AND THAT HE IS PROPERLY LICENSED AND PROPERLY REGISTERED TO DO THIS WORK IN THE STATE AND/OR COUNTY IN WHICH IT IS TO BE PERFORMED.
- UNLESS SHOWN OR NOTED OTHERWISE ON THE CONTRACT DRAWINGS, OR IN THE SPECIFICATIONS, THE FOLLOWING NOTES SHALL APPLY TO THE MATERIALS LISTED HEREIN, AND TO THE PROCEDURES TO BE USED ON THIS PROJECT.
- 4. IT IS THE CONTRACTOR'S SOLE RESPONSIBILITY TO DETERMINE ERECTION PROCEDURE AND SEQUENCE TO INSURE THE SAFETY OF THE STRUCTURE AND ITS COMPONENT PARTS DURING ERECTION AND/OR FIELD MODIFICATIONS. THIS INCLUDES, BUT IS NOT LIMITED TO, THE ADDITION OF WHATEVER TEMPORARY BRACING, GUYS OR TIE DOWNS THAT MAY BE NECESSARY. SUCH MATERIAL SHALL BE REMOVED AND SHALL REMAIN THE PROPERTY OF THE CONTRACTOR AFTER THE COMPLETION OF THE PROJECT.
- 5. ALL DIMENSIONS, ELEVATIONS, AND EXISTING CONDITIONS SHOWN ON THE DRAWINGS SHALL BE FIELD VERIFIED BY THE CONTRACTOR AND THE TESTING AGENCY PRIOR TO BEGINNING ANY MATERIALS ORDERING, FABRICATION OR CONSTRUCTION WORK ON THIS PROJECT. ANY DISCREPANCIES SHALL BE IMMEDIATELY BROUGHT TO THE ATTENTION OF THE OWNER AND THE OWNER'S ENGINEER. THE DISCREPANCIES MUST BE RESOLVED BEFORE THE CONTRACTOR IS TO PROCEED WITH THE WORK. THE CONTRACT DOCUMENTS DO NOT INDICATE THE METHOD OF CONSTRUCTION. THE CONTRACTOR SHALL SUPERVISE AND DIRECT THE WORK AND SHALL BE SOLELY RESPONSIBLE FOR ALL CONSTRUCTION MEANS, METHODS, TECHNIQUES, SEQUENCES, AND PROCEDURES. OBSERVATION VISITS TO THE SITE BY THE OWNER AND/OR THE ENGINEER SHALL NOT INCLUDE INSPECTION OF THE PROTECTIVE MEASURES OR THE CONSTRUCTION PROCEDURES.
- ALL MATERIALS AND EQUIPMENT FURNISHED SHALL BE NEW AND OF GOOD QUALITY, FREE FROM FAULTS AND DEFECTS AND IN CONFORMANCE WITH THE CONTRACT DOCUMENTS. ANY AND ALL SUBSTITUTIONS MUST BE PROPERLY APPROVED AND AUTHORIZED IN WRITING BY THE OWNER AND ENGINEER PRIOR TO INSTALLATION. THE CONTRACTOR SHALL FURNISH SATISFACTORY EVIDENCE AS TO THE KIND AND QUALITY OF THE MATERIALS AND EQUIPMENT BEING SUBSTITUTED.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR INITIATING, MAINTAINING, AND SUPERVISING ALL SAFETY PRECAUTIONS AND PROGRAMS IN CONNECTION WITH THE WORK. THE CONTRACTOR IS RESPONSIBLE FOR INSURING THAT THIS PROJECT AND RELATED WORK COMPLIES WITH ALL APPLICABLE LOCAL, STATE, AND FEDERAL SAFETY CODES AND REGULATIONS GOVERNING THIS WORK.
- 8. ALL WORK SHALL BE COMPLETED IN ACCORDANCE WITH THE LATEST EDITION OF THE LOCAL BUILDING CODE.
- ALL PROPOSED CELLULAR EQUIPMENT AND FIXTURES SHALL BE FURNISHED BY OWNER FOR INSTALLATION BY THE CONTRACTOR, UNLESS SPECIFICALLY NOTED OTHERWISE HEREIN
- 10. ACCESS TO THE PROPOSED WORK SITE MAY BE RESTRICTED. THE CONTRACTOR SHALL COORDINATE INTENDED CONSTRUCTION ACTIVITY, INCLUDING WORK SCHEDULE AND MATERIALS ACCESS, WITH THE RESIDENT LEASING AGENT FOR

STRUCTURAL STEEL NOTES:

- STRUCTURAL STEEL SHALL CONFORM TO THE LATEST EDITION OF THE A.I.S.C. SPECIFICATIONS FOR STRUCTURAL STEEL BUILDINGS- ALLOWABLE STRESS DESIGN AND PLASTIC DESIGN INCLUDING THE COMMENTARY AND THE A.I.S.C. CODE OF STANDARD PRACTICE.
- 2. STRUCTURAL STEEL PLATES AND SHAPES SHALL CONFORM TO ASTM A36. ALL STRUCTURAL STEEL PIPES SHALL CONFORM TO ASTM A53 GRADE B. ALL STRUCTURAL STEEL TUBING SHALL CONFORM TO ASTM A500 GRADE B. ALL STRUCTURAL STEEL COMPONENTS AND FABRICATED ASSEMBLIES SHALL BE HOT DIP GALVANIZED AFTER FABRICATION.
- WELDING SHALL BE IN ACCORDANCE WITH THE AMERICAN WELDING SOCIETY (AWS) D.1.1/D1.1M:2010. STRUCTURAL WELDING CODE-STEEL WELD ELECTRODES SHALL BF F70XX

- 4. ALL COAXIAL CABLE CONNECTORS AND TRANSMITTER EQUIPMENT SHALL BE AS SPECIFIED BY THE OWNER AND IS NOT INCLUDED IN THESE CONSTRUCTION DOCUMENTS. THE CONTRACTOR SHALL FURNISH ALL CONNECTION HARDWARE REQUIRED TO SECURE THE CABLES. CONNECTION HARDWARE SHALL BE GRADE 304 STAINLESS STEEL.
- DESCRIBED HEREIN. BY ACCEPTANCE OF THIS ASSIGNMENT, THE CONTRACTOR IS 5. ALL REINFORCING STEEL SHALL CONFORM TO ASTM 615 GRADE 60, DEFORMED BILLET STEEL BARS. WELDED WIRE FABRIC REINFORCING SHALL CONFORM TO
 - 6. THE FABRICATION AND ERECTION OF STRUCTURAL STEEL SHALL CONFORM TO THE LATEST A.L.S.C. SPECIFICATIONS.
 - 7. ALL CONNECTIONS NOT FULLY DETAILED ON THESE PLANS SHALL BE DETAILED BY THE STEEL FABRICATOR IN ACCORDANCE WITH A.I.S.C. SPECIFICATIONS.
 - 8. HOT-DIP GALVANIZE ITEMS SPECIFIED TO BE ZINC-COATED, AFTER FABRICATION WHERE PRACTICAL. GALVANIZING: ASTM A 123, ASTM, A 153/A 153M OR ASTM A 653/A 653M, G90, AS APPLICABLE.
 - 9. REPAIR DAMAGED SURFACES WITH GALVANIZING REPAIR METHOD AND PAINT CONFORMING TO ASTM A 780 OR BY APPLICATION OF STICK OR THICK PASTE MATERIAL SPECIFICALLY DESIGNED FOR REPAIR OF GALVANIZING. CLEAN AREAS TO BE REPAIRED, AND REMOVE SLAG FROM WELDS. HEAT SURFACES TO WHICH STICK OR PASTE MATERIAL IS APPLIED WITH A TORCH TO A TEMPERATURE SUFFICIENT TO MELT THE METALLICS. IN STICK OR PASTE, SPREAD MOLTEN MATERIAL UNIFORMLY OVER SURFACES TO BE COATED AND WIPE OFF EXCESS
 - 10. CONTRACTOR SHALL FOLLOW THE MANUFACTURER'S INSTRUCTIONS/SPECIFICATIONS IF NO INFORMATION IS CONTAINED IN THESE PLANS OR IF THE MANUFACTURER'S SPECIFICATIONS ARE STRICTER.

PERMITS:

- 1. CONTRACTOR SHALL SECURE ALL NECESSARY PERMITS FOR THIS PROJECT FROM ALL APPLICABLE GOVERNMENTAL AGENCIES.
- 2. ANY PERMITS WHICH MUST BE OBTAINED SHALL BE THE CONTRACTOR'S RESPONSIBILITY. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ABIDING BY ALL CONDITIONS AND REQUIREMENTS OF THE PERMITS.
- 3. ALL WORK SHALL BE IN ACCORDANCE WITH LOCAL CODES AND THE ACI 318-14, "BUILDING REQUIREMENTS FOR STRUCTURAL CONCRETE".
- 4. THE CONTRACTOR SHALL NOTIFY THE APPLICABLE JURISDICTIONAL (STATE, COUNTY OR CITY) ENGINEER 24 HOURS PRIOR TO THE BEGINNING OF CONSTRUCTION.
- 5. ALL DIMENSIONS SHALL BE VERIFIED WITH THE PLANS (LATEST REVISION) PRIOR TO COMMENCING CONSTRUCTION. NOTIFY THE OWNER IMMEDIATELY IF DISCREPANCIES ARE DISCOVERED. THE CONTRACTOR SHALL HAVE A SET OF APPROVED PLANS AVAILABLE AT THE SITE AT ALL TIMES WHEN WORK IS BEING PERFORMED. A DESIGNATED RESPONSIBLE EMPLOYEE SHALL BE AVAILABLE FOR CONTACT BY GOVERNING AGENCY INSPECTORS.

MISCELLANEOUS:

- 1. ALL THREADED STRUCTURAL FASTENERS FOR ANTENNA SUPPORT ASSEMBLES SHALL CONFORM TO ASTM A307 OR ASTM 36. ALL STRUCTURAL FASTENERS FOR STRUCTURAL STEEL FRAMING SHALL CONFORM TO ASTM A325. FASTENERS SHALL 5/8" MIN. DIA. BEARING TYPE CONNECTIONS WITH THREADS EXCLUDED FROM THE PLANE. ALL EXPOSED FASTENERS, NUTS, AND WASHERS SHALL BE GALVANIZED UNLESS OTHERWISE NOTED. ALL ANCHORS INTO CONCRETE SHALL BE STAINLESS STEEL.
- 2. THE CONTRACTOR SHALL FURNISH ALL CONNECTION HARDWARE REQUIRED TO SECURE THE CABLES. CONNECTION HARDWARE SHALL BE STAINLESS STEEL.
- 3. NORTH ARROW SHOWN ON PLANS REFERS TO TRUE NORTH. CONTRACTOR SHALL VERIFY NORTH AND NOTIFY CONSULTANT OF ANY DISCREPANCY BEFORE STARTING CONSTRUCTION.
- 4. PROVIDE LOCK WASHERS FOR ALL MECHANICAL CONNECTIONS FOR GROUND CONDUCTORS. USE GRADE 304 STAINLESS STEEL HARDWARE THROUGHOUT.
- 5. THOROUGHLY REMOVE ALL PAINT AND CLEAN ALL DIRT FROM SURFACES REQUIRING GROUND CONNECTIONS.

- 6. MAKE ALL GROUND CONNECTIONS AS SHORT AND DIRECT AS POSSIBLE. AVOID SHARP BENDS, ALL BENDS TO BE A MIN. OF 8" RADIUS.
- 7. FOR GROUNDING TO BUILDING FRAME AND HATCH PLATE GROUND BARS, USE A TWO-BOLT HOLE NEPA DRILLED CONNECTOR SUCH AS T&B 32007 OR APPROVED
- 8. FOR ALL EXTERNAL GROUND CONNECTIONS, CLAMPS AND CADWELDS, APPLY A LIBERAL PROTECTIVE COATING OR AN ANTI-OXIDE COMPOUND SUCH AS 'NO-OXIDE A' BY DEARBORN CHEMICAL COMPANY.
- 9. REPAIR ALL METAL SURFACES THAT HAVE BEEN CUT OR DAMAGED BY REMOVING ANY EXISTING RUST AND APPLYING COLD GALVANIZATION.
- 10. ANTENNA CABLE LENGTHS HAVE BEEN DETERMINED BASED ON THESE PLANS. CABLE LENGTHS LISTED ARE APPROXIMATED AND ARE NOT INTENDED TO BE USED FOR FABRICATION. DUE TO FIELD CONDITIONS, ACTUAL CABLE LENGTHS VARY. CONTRACTOR MUST FIELD VERIFY ANTENNA CABLE LENGTHS PRIOR TO

ì	REV	DATE	DESCRIPTION
	Α	10/28/22	PRELIMINARY CDs REV "A"
	0	11/30/22	FINAL CDs ISSUED
	1		
	2		
	3		
	4		
	5		
	6		
	7		
	8		
	9		
	CENT	DDO IECT	NO - 100010047

EN3 PROJECT NO.: 102210047

DRAWN BY: CHECKED BY: ME MM




12150 RESEARCH PARKWAY ORLANDO, FL 32826



1997 ANNAPOLIS EXCHANGE PKWY SUITE 200 ANNAPOLIS, MD 21401



27139 SEA BREEZE WAY WESLEY CHAPEL, FLORIDA 33544 (813)917-2671



WEST LAKE CITY FA #10096114

299 NW BROWN RD LAKE CITY, FL 32055

SHEET DESCRIPTION

GENERAL NOTES, **ABBREVIATIONS**


SHEET NUMBER

GN-1

- 2. THE CONTRACTOR TO ENSURE THAT NO DAMAGE OR DEBRIS OCCURS ON THE ADJACENT PROPERTIES.
- 3. THE CONTRACTOR SHALL SEED ALL DISTURBED AREAS WITH LOW MAINTENANCE NATIVE GRASS AND COVER WITH APPROVED STRAW.
- CONTRACTOR SHALL PROVIDE ALL REQUIRED EROSION CONTROL TECHNIQUES AND BEST MANAGEMENT PRACTICES PER LOCAL AND AND STATE REQUIREMENTS AS APPLICABLE.
- NORTH ARROW SHOWN ON PLANS REFERS TO TRUE NORTH. CONTRACTOR SHALL VERIFY NORTH AND INFORM ARCHITECT/ENGINEER OF ANY DISCREPANCY BEFORE STARTING CONSTRUCTION.

CONTRACTOR IS RESPONSIBLE FOR MODIFYING THE RAYCAP INSTALL ON THE TOWER TO ACCOMMODATE THE QUANTITY OF RRU'S.

THE CONTRACTOR MUST FIELD VERIFY ALL MEASUREMENTS AND FIELD CONDITIONS PRIOR TO THE COMMENCEMENT OF CONSTRUCTION.




REV DATE DESCRIPTION


A 10/28/22 PRELIMINARY CDs REV "A"

0 11/30/22 FINAL CDs ISSUED

1 2 3 4 5 5 6 6 7 8 9 9 GEN3 PROJECT NO.: 102210047










1997 ANNAPOLIS EXCHANGE PKWY SUITE 200 ANNAPOLIS, MD 21401

PREPARED BY:



27139 SEA BREEZE WAY WESLEY CHAPEL, FLORIDA 33544 (813)917-2671 COA # 35409

THIS ITEM HAS BEEN ELECTRONICALLY SIGNED & SEALED BY MARC P. MAIER, P.E., FL
LICENSE #72513 USING A DIGITAL SIGNATURE.
PRINTED COPIES OF THIS DOCUMENT ARE
NOT CONSIDERED SIGNED & SEALED & THE
SIGNATURE MUST BE VERIFIED ON ANY
ELECTRONIC COPIES.



WEST LAKE CITY FA #10096114

299 NW BROWN RD LAKE CITY, FL 32055

SHEET DESCRIPTION

SITE PLAN

SHEET NUMBER

C-1

State State One Call

CALL FLORIDA 811

ONE CALL - DIAL 811


CALL 3 WORKING DAYS

BEFORE YOU DIG

1-800-638-4097

SITE PLAN

SCALE: 1" = 10'
SCALE BASED ON 11"x17" ONLY



REV DATE DESCRIPTION

A 10/28/22 PRELIMINARY CDs REV "A

O 11/30/22 FINAL CDs ISSUED

1
2
3
4
5
6
7
8
9

GEN3 PROJECT NO.: 102210047

DRAWN BY:



CHECKED BY:

12150 RESEARCH PARKWAY ORLANDO, FL 32826




1997 ANNAPOLIS EXCHANGE PKWY SUITE 200 ANNAPOLIS, MD 21401

PREPARED BY:



27139 SEA BREEZE WAY
WESLEY CHAPEL, FLORIDA 33544
(813)917-2671
COA # 35409

THIS ITEM HAS BEEN ELECTRONICALLY SIGNED & SEALED BY MARC P. MAIER, P.E., FL.
LICENSE #72513 USING A DIGITAL SIGNATURE.
PRINTED COPIES OF THIS DOCUMENT ARE
NOT CONSIDERED SIGNED & SEALED & THE
SIGNATURE MUST BE VERIFIED ON ANY
ELECTRONIC COPIES.



WEST LAKE CITY FA #10096114

299 NW BROWN RD LAKE CITY, FL 32055

SHEET DESCRIPTION

TOWER ELEVATION
AND ANTENNA
ORIENTATION

SHEET NUMBER

S-1

AIR 6419 B77G (320W) Candidate Not to exceed figures


 Antenna Elements 192 TRX Branches 64T64R Antenna configuration (3x1)x(4x8)

3450~3550 MHz Operation band: · IBW 100 MHz TCBW 100MHz

320W Output Power · Peak EIRP 79dBm

· PSD 4W/MHz (Target 8W/MHz for rural) 720x410x200mm (28.3x16.1x7.9 in) Size(HxWxD) 30kg (66.1 lbs) Weight

 Type of cooling **Passive** · eCPRI link 2*25G · Power Supply -48V VDC 3-wires • Multi-layer MU MIMO: 16/8 DL/UL layer




ERICSSON AIR 6419 B77G
S-2 SCALE: N.T.S.


ERICSSON AIR 6449 B77

Doorglos over BY7 band (3.3-4.2 GHz)

Operation erver (877 hand (3.3 4.24/s))
Breater rate = SAL PC, DC Power Consumption = 1259W
(for dimensioning)
Dimensions
— Height 30.07 (776 mm)
— Virialls 1587 (400 mm)
— Depth: 10.6° (256 mm)
— Depth: 10.6° (256 mm)
Weight, deel, mounting hardware = 82.5 tos (37.5 kg)
Weight with Subaring Hardware = 82.5 tos (37.5 kg)
Weight with Subaring Hardware = 82.5 tos (37.5 kg)
Max Frontal Wind Leed (8.47m) = 47th
Hartcrantal Separation (Reg. Lind Oberbare ARI 6446 = 100mm
Maintam Vertical Separa Req. Lind Delete ARI 6446 = 300mm
Maintam Height, Above Usine = 500mm

Minimum Height Above Users = 5m Outdoor Installation locations to svoid






ERICSSON AIR 6449 B77D


CONTRACTOR TO MAKE SURE THAT VERTICAL SEPARATION FROM TIP OF LOWER C-BAND ANTENNA TO BOTTOM OF THE HIGHER C-BAND ANTENNA IS AT LEAST 1 FT. DO NOT OBSTRUCT NEARBY ANTENNAS FROM OTHER

NEARBY ANIENNAS FROM OTHER CARRIERS.


IF ONLY (1) ANTENNA IS PROPOSED, INSTALL AT THE TOP OF THE MOUNT PIPE TO ALLOW A FUTURE ANTENNA TO BE INSTALLED BELOW.




AIR ANTENNA MOUNTING DETAIL



△ NNHH-65B-R4 S-2 SCALE: N.T.S.




ANTENNA MOUNTING DETAIL 5 ANTEN S-2 SCALE: N.T.S.



- 1. UNIT SHALL BE MOUNTED AS PER MANUFACTURER'S RECOMMENDATIONS.
- 2. CONTRACTOR SHALL TIGHTEN ALL BOLTS TO A "SNUG
- TIGHT" CONDITION AS DEFINED BY AISC.

 3. CONTRACTOR SHALL INSTALL RAYCAP DISTRIBUTION UNIT WITHIN 15 FEET FROM ALL RRH'S.

DC9-48-60-24-8C-EV MOUNT DETAIL S-2 SCALE: N.T.S.



ANTENNA GROUNDING SCHEMATIC S-2 SCALE: N.T.S.

ADD GROUND BARS IF THERE ARE INSUFFICIENT LUG POSITIONS. REFERENCE AT&T BONDING & GROUNDING PRACTICE TP76416.

DESCRIPTION A 10/28/22 PRELIMINARY CDs REV "A 0 11/30/22 FINAL CDs ISSUED 6 9 GEN3 PROJECT NO.: 102210047



DRAWN BY:

12150 RESEARCH PARKWAY ORLANDO, FL 32826

CHECKED BY:

MM



1997 ANNAPOLIS EXCHANGE PKWY SUITE 200 ANNAPOLIS, MD 21401

PREPARED BY:



27139 SEA BREEZE WAY WESLEY CHAPEL, FLORIDA 33544 (813)917-2671

THIS ITEM HAS BEEN ELECTRONICALLY SIGNED & SEALED BY MARC P. MAIER, P.E., FL LICENSE #72513 USING A DIGITAL SIGNATURE. PRINTED COPIES OF THIS DOCUMENT ARE NOT CONSIDERED SIGNED & SEALED & THE SIGNATURE MUST BE VERIFIED ON ANY ELECTRONIC COPIES. PRO P. MAIN No 72513 STATE OF STA

WEST LAKE CITY FA #10096114

MARC P. MAIER, PE

FL PROFESSIONAL ENGINEER LIC. # 72513


299 NW BROWN RD LAKE CITY, FL 32055

SHEET DESCRIPTION

MISCELLANEOUS DETAILS


SHEET NUMBER

S-2




RRUS 4449 B5/B12 DETAIL
S3 SCALE: N.T.S.

ERICSSON RRUS-4415 B25 -WEIGHT: 44 LBS -TX = 1930 - 1995 MHz -RX = 1850 - 1915 MHz -CPRI 2 PORTS x 2.5/4.9/9.8/10.1 Gbps




RRUS CAN <u>ONLY</u> BE PAINTED ON SOLAR SHIELD.


RRUS-4415 B25 DETAIL
S-3 SCALE: N.T.S.



DETAIL IS DIAGRAMMATIC. CONTRACTOR TO INSTALL RRU'S ON RRU MOUNT BEST SUITED FOR ANTENNA CONFIGURATION.

BACK VIEW





DRAWN BY: CHECKED BY: ME MM




12150 RESEARCH PARKWAY ORLANDO, FL 32826



1997 ANNAPOLIS EXCHANGE PKWY SUITE 200 ANNAPOLIS, MD 21401

PREPARED BY:

27139 SEA BREEZE WAY WESLEY CHAPEL, FLORIDA 33544 (813)917-2671 COA # 35409



WEST LAKE CITY FA #10096114

299 NW BROWN RD LAKE CITY, FL 32055

SHEET DESCRIPTION

MISCELLANEOUS DETAILS

SHEET NUMBER

S-3

				- COMMING	50.00-01:				ANTENNA AND COAX SCHEDULE												
		ANTENNAS					CABLES					RRU			COMPONENT			TMA			
SECTOR	AZ	RAD CENTER	MAKE	ANTENNA MODEL	(QTY)	APPROXIMATE ANTENNA SPECS		N TILT MECH	MODEL	SIZE	(QTY)	LENGTH/	COLOR	MODEL	TWR (QTY)	GRND (QTY)	MODEL		GRND (QTY)	MODEL	(QT
			-				ELEC	MECH	WIODEL	3126	(QH)	LINE	CODE	MODEL	(QII)	(QIT)		(QII)	(UII)	MODEL	IQI
ALPHA (A1)	0°	186'-0"	ERICSSON	AIR6449 B77D	1	H=31.6" x W=15.9" x D=10.6"		*	POSENDERGER FIRER HIMARER (DCG TO BRILL)	3/8"	4	15'-0"	1 RED		2		•	-	à	575	
			ERICSSON	AIR6419 B77G	1	H=26.2" x W=16.1" x D=7.8"			ROSENBERGER FIBER JUMPER (DC9 TO RRU) ROSENBERGER SINGLE PAIR DC CABLE (DC9 TO RRU)	7/16"	2	15'-0"	1 RED	-		-					
ALPHA (A2)	0"	186'-0"	ANDREW	NNHH-65B-R4	1	H=72" x W=19.6" x D=7.8"	(*)	-	-	-	-	-	-		-	-		*	*	5. 4 0	- 3
									ROSENBERGER FIBER JUMPER (DC9 TO RRU)	3/8"	2	15'-0"	2 RED	4449 B5/B12	1	-					
									ROSENBERGER SINGLE PAIR DC CABLE (DC9 TO RRU)	7/16"	3	15'-0"	2 RED	4415 B25	1						
									1/2" COAX JUMPER (RRU TO ANTENNA)	1/2"	8	10'-0"	2 RED	*	#	+					_
ALPHA (A3)	0°	186'-0"	ANDREW	SBNHH-1D65B	1	H=72.7" x W=11.9" x D=7.1"	1/2	1/20	-	- tou	120			-	2	2	127		2		-
								l	ROSENBERGER FIBER JUMPER (DC9 TO RRU)	3/8"	1	15'-0" 15'-0"	3 RED 3 RED	RRUS-32 B30	1						
								l	ROSENBERGER SINGLE PAIR DC CABLE (DC9 TO RRU) 1/2" COAX JUMPER (RRU TO ANTENNA)	7/16" 1/2"	4	10'-0"	3 RED			1 1					
ALPHA (A4)	O°	186'-0"	ANDREW	NNHH-65B-R4	1	H=72" x W=19.6" x D=7.8"	3°/2°		- TO ANTENNA	1/2	-	10.0	JILLO	1/2/	2 S		-	-	-	-	-
									ROSENBERGER FIBER JUMPER (DC9 TO RRU)	3/8"	3	15'-0"	4 RED	4478 B14	1	2				1.00	
								l	ROSENBERGER SINGLE PAIR DC CABLE (DC9 TO RRU)	7/16"	2	15'-0"	4 RED	4426 B66	1	-					
						2			1/2" COAX JUMPER (RRU TO ANTENNA)	1/2"	8	10'-0"	4 RED	320		- 2					
BETA (B1)	120°	186'-0"	ERICSSON	AIR6449 B77D	1	H=31.6" x W=15.9" x D=10.6"				-	-		-		2	-	-	-	÷	-	
			ERICSSON	AIR6419 B77G	1	H=26.2" x W=16.1" x D=7.8"			ROSENBERGER FIBER JUMPER (DC9 TO RRU)	3/8"	4	15'-0"	1 BLUE	1981			-				
				VOCATION DE MINOR					ROSENBERGER SINGLE PAIR DC CABLE (DC9 TO RRU)	7/16"	2	15'-0"	1 BLUE	82	- 4	-				2	_
BETA (B2)	120°	186'-0"	ANDREW	NNHH-65B-R4	1	H=72" x W=19.6" x D=7.8"			-	***					-	-	(*)				
								l	ROSENBERGER FIBER JUMPER (DC9 TO RRU)	3/8"	2	15'-0"	2 BLUE	4449 B5/B12	1	-					
								l	ROSENBERGER SINGLE PAIR DC CABLE (DC9 TO RRU)	7/16"	3	15'-0"	2 BLUE	4415 B25	1	- 1					
DETA (D2)	120°	186'-0"	ANDREW	COMMU 1 DCED	1	H=72.7" x W=11.9" x D=7.1"		-	1/2" COAX JUMPER (RRU TO ANTENNA)	1/2"	8	10'-0"	2 BLUE		-	-		-		p.=x.	_
BETA (B3)	120	100 -0	ANDREW	SBNHH-1D65B	1	H=/2./ X W=11.9 X D=/.1	153	1553	ROSENBERGER FIBER JUMPER (DC9 TO RRU)	3/8"	1	15'-0"	3 BLUE	RRUS-32 B30	1	8	(50)	8	8	326	631
								l	ROSENBERGER SINGLE PAIR DC CABLE (DC9 TO RRU)	7/16"	1	15'-0"	3 BLUE	-	1	2					
									1/2" COAX JUMPER (RRU TO ANTENNA)	1/2"	4	10'-0"	3 BLUE	100	8	- 2					
BETA (84)	120°	186'-0"	ANDREW	NNHH-65B-R4	1	H=72" x W=19.6" x D=7.8"	3°/2°	170	-	-	11-01	-	-	1.5	-	-	14 5 01	- 5	- 5	Ų ≅ n	-
	11-000-01		VIDA CONTRACTOR OF THE PROPERTY OF THE PROPERT			(Fig. 1) (Fi			ROSENBERGER FIBER JUMPER (DC9 TO RRU)	3/8"	3	15'-0"	4 BLUE	4478 B14	1	-	5*55*				
								l	ROSENBERGER SINGLE PAIR DC CABLE (DC9 TO RRU)	7/16"	2	15'-0"	4 BLUE	4426 B66	1	_					
								<u> </u>	1/2" COAX JUMPER (RRU TO ANTENNA)	1/2"	8	10'-0"	4 BLUE	16.	-	-					
GAMMA (G1)	240°	186'-0"	ERICSSON	AIR6449 B77D	1	H=31.6" x W=15.9" x D=10.6"			-		-	-				-			*		-
			ERICSSON	AIR6419 B77G	1	H=26.2" x W=16.1" x D=7.8"			ROSENBERGER FIBER JUMPER (DC9 TO RRU)	3/8"	4	15'-0"	1 GREEN	-	8	8					
									ROSENBERGER SINGLE PAIR DC CABLE (DC9 TO RRU)	7/16"	2	15'-0"	1 GREEN	(20)	•	-					-
GAMMA (G2)	240°	186'-0"	ANDREW	NNHH-65B-R4	1	H=72" x W=19.6" x D=7.8"			POSENDERGER FIRED HAMBER (DGG TO BRILL)	3/8"	2	15'-0"	3 CDEEN	4440 DE /D13		-		-	~	-	
								l	ROSENBERGER FIBER JUMPER (DC9 TO RRU) ROSENBERGER SINGLE PAIR DC CABLE (DC9 TO RRU)	7/16"	3	15'-0"	2 GREEN 2 GREEN	4449 B5/B12 4415 B25	1	8					
									1/2" COAX JUMPER (RRU TO ANTENNA)	1/2"	8	10'-0"	2 GREEN	4413 623		2					
GAMMA (G3)	240°	186'-0"	ANDREW	SBNHH-1D65B	1	H=72.7" x W=11.9" x D=7.1"		-	-	-/-		-	-	199	-	-	(-	-	-	10 - 11	-
				- VIII-VIII VIII-VIII VIII-VIII-VIII-VI					ROSENBERGER FIBER JUMPER (DC9 TO RRU)	3/8"	1	15'-0"	3 GREEN	RRUS-32 B30	1	25					
								l	ROSENBERGER SINGLE PAIR DC CABLE (DC9 TO RRU)	7/16"	1	15'-0"	3 GREEN	(17)	8						
								_	1/2" COAX JUMPER (RRU TO ANTENNA)	1/2"	4	10'-0"	3 GREEN	(4)		-					
GAMMA (G4)	240°	186'-0"	ANDREW	NNHH-65B-R4	1	H=72" x W=19.6" x D=7.8"	3°/2°			20.00	5	2002	E CONSTRUCTO	2	23	9	-	=	-	V-	-
									ROSENBERGER FIBER JUMPER (DC9 TO RRU)	3/8"	3	15'-0"	4 BLUE	4478 B14	1						
									ROSENBERGER SINGLE PAIR DC CABLE (DC9 TO RRU) 1/2" COAX JUMPER (RRU TO ANTENNA)	7/16"	2	15'-0" 10'-0"	4 BLUE 4 BLUE	4426 B66	1	2					
						1			THE CHARLOWIER IRRUITO ANTENNAL	1 1/2		1111-11	4 DLUE		170		i				- 1

- ANTENNA AND COAX INFORMATION PROVIDED FROM THE 5G NR RADIO RFDS V2.00 DATED 09/28/22.

- CONTRACTOR TO VERIFY RFINFO WITH CLIENT PRIOR TO CONSTRUCTION.

- COAX LENGTHS ARE APPROXIMATE AND MUST BE VERIFIED PRIOR TO CONSTRUCTION.

-ALL COAX SHALL BE COLOR CODED AT TOP AN BOTTOM JUMPER AND AT TOP OF TOWER

BOTTOM OF TOWER, AND INSIDE SHELTER ON MAIN COAX.

-EACH MAIN COAX SHALL HAVE CORROSION PROOF "ID TAGS" INSTALLED INSIDE THE SHELTER

AT THE PORT AND AT THE ANTENNA.

-QUANTITIES GIVEN ARE TOTAL EXISTING AND PROPOSED.

TOTAL 1-5/8"COAX (INACTIVE TO REMAIN)	10	2600'-0"
TOTAL FIBER JUMPER	30	450'-0"
TOTAL DC JUMPER	2.4	360'-0"
TOTAL 1/2" COAX JUMPERS	60	600'-0"
TOTAL 5/16" RET CABLES	3	780'-0"
TOTAL 2-1/4" INNER DUCTS	2	****

NOTE: AT&T MUST REMOVE (2) INACTIVE 1-5/8" COAX CABLES AS PART OF THIS PROJECT



_											
7	REV	DATE	DESCRIPTION								
	Α	10/28/22	PRELIMINARY CDs REV "A"								
	0	11/30/22	FINAL CDs ISSUED								
	1										
	2										
	3										
	4										
	5										
	6										
	7										
	8										
	9										
	GEN3	PROJECT	NO.: 102210047								

DRAWN BY: CHECKED BY: ME MM



12150 RESEARCH PARKWAY ORLANDO, FL 32826



1997 ANNAPOLIS EXCHANGE PKWY. SUITE 200 ANNAPOLIS, MD 21401



27139 SEA BREEZE WAY WESLEY CHAPEL, FLORIDA 33544 (813)917-2671 COA # 35409

THIS ITEM HAS BEEN ELECTRONICALLY SIGNED & SEALED BY MARC P. MAER, P.E., FL LICENSE #72513 USING A DIGITAL SIGNATURE. PRINTED COPIES OF THIS DOCUMENT ARE NOT CONSIDERED SIGNED & SEALED & THE SIGNATURE MUST BE VERIFIED ON ANY ELECTRONIC COPIES.



WEST LAKE CITY FA #10096114

299 NW BROWN RD LAKE CITY, FL 32055

SHEET DESCRIPTION

ANTENNA SCHEDULE

SHEET NUMBER

AN-1