

0-8

4/12 PITCH  
2' OVERHANGS

1) REFER TO HD 91 (RECOMMENDATIONS FOR HANDLING INSTALLATION AND TEMPORARY BRACING) REFER TO ENGINEERED DRAWINGS FOR PERMANENT BRACING REQUIRED

- 2) ALL T05555, INCLUDING T05555 UNDER VALLEY FRAMING, MUST BE COMPLETELY DECKED OR REFEE TO DETAIL AND FOR ALTERNATE BRACING REQUIREMENTS.
- 3) ALL VALLEYS ARE TO BE CONVENTIONALLY FRAMED BY BUILDER
- 4) ALL T05555, ARE DESIGNED FOR 7' x 6' MAXIMUM SPACING, UNLESS OTHERWISE NOTED
- 5) ALL WALLS SHOWN ON PLACEMENT PLAN ARE CONSIDERED TO BE LOAD BEARING, UNLESS OTHERWISE NOTED
- 6) 5'x4' T05555, MUST BE INSTALLED WITH THE TOP BEING UP
- 7) ALL R207, T055, ANCHAGES TO BE SHOWN HUBS UNLESS OTHERWISE NOTED. ALL FLOOR T055, ANCHAGES TO BE SHOWN THRU-2 UNLESS OTHERWISE NOTED
- 8) BECAUSE OVERLAP, (AND) TO BE FINISHED BY BUILDER

THIS LAYOUT IS THE SOLE SOURCE FOR FABRICATION OF TROUSERS AND VESTS. ALL PREVIOUS ARCHITECTURAL OR OTHER TROUSERS LAYOUTS, REVIEW AND APPROVAL OF THIS LAYOUT MUST BE RECEIVED BEFORE ANY TROUSERS WILL BE BUILT. WE EMPLOY ALL CONDITIONS TO INSURE AGAINST CHANGES THAT WILL RESULT IN EXTRA CHARGES TO YOU.

Approved by \_\_\_\_\_ Date \_\_\_\_\_



**Bunnell**  
PHONE: 904-437-3349 FAX: 904-437-3994

**Jacksonville**  
PHONE: 904-772-6100 FAX: 904-772-1977

**Lake City**  
PHONE: 386-755-6894 FAX: 386-755-7973

**Sanford**  
PHONE: 407-322-0059 FAX: 407-322-5555

## MAIN RESULTS

MODEL	CUSTOM		REVISION	SERIAL	NTS
DATE	04-17-06	STAMP BY	RAL	ISS /	L159972