

FLORIDA DEPARTMENT OF
Business & Professional Regulation



[DBPR HOME](#) [ABOUT DBPR](#) [DBPR DIVISIONS](#) [CONTACT DBPR](#)

[BCIS Home](#) [Log In](#) [User Registration](#) [Hot Topics](#) [Submit Surcharge](#) [Stats & Facts](#) [Publications](#) [Contact Us](#) [BCIS Site Map](#) [Links](#) [Search](#)



Product Approval
USER: Public User

[Product Approval Menu](#) > [Product or Application Search](#) > [Application List](#) > **Application Detail**

► OFFICE OF THE
SECRETARY

FL #	FL19563-R6										
Application Type	Affirmation										
Code Version	2023										
Application Status	Approved										
Comments											
Archived	<input type="checkbox"/>										
Product Manufacturer	Andersen Corporation										
Address/Phone/Email	100 Fourth Avenue North Bayport, MN 55003 (651) 264-5308 alan.barstad@AndersenCorp.com										
Authorized Signature	Alan Barstad alan.barstad@AndersenCorp.com										
Technical Representative											
Address/Phone/Email											
Quality Assurance Representative											
Address/Phone/Email											
Category	Windows										
Subcategory	Horizontal Slider										
Compliance Method	Evaluation Report from a Florida Registered Architect or a Licensed Florida Professional Engineer <input type="checkbox"/> Evaluation Report - Hardcopy Received										
Florida Engineer or Architect Name who developed the Evaluation Report	Hermes F. Norero, P.E.										
Florida License	PE-73778										
Quality Assurance Entity	Window and Door Manufacturers Association-QA										
Quality Assurance Contract Expiration Date	12/16/2030										
Validated By	Zachary R. Priest, P.E. <input type="checkbox"/> Validation Checklist - Hardcopy Received										
Certificate of Independence	FL19563_R6_COI_COI Andersen SS 2021-10-18.pdf										
Referenced Standard and Year (of Standard)	<table> <thead> <tr> <th>Standard</th><th>Year</th></tr> </thead> <tbody> <tr> <td>AAMA/WDMA/CSA 101/I.S.2/A440</td><td>2008</td></tr> <tr> <td>AAMA/WDMA/CSA 101/I.S.2/A440</td><td>2011</td></tr> <tr> <td>AAMA/WDMA/CSA 101/I.S.2/A440</td><td>2017</td></tr> <tr> <td>ASTM E1886</td><td>2013</td></tr> </tbody> </table>	Standard	Year	AAMA/WDMA/CSA 101/I.S.2/A440	2008	AAMA/WDMA/CSA 101/I.S.2/A440	2011	AAMA/WDMA/CSA 101/I.S.2/A440	2017	ASTM E1886	2013
Standard	Year										
AAMA/WDMA/CSA 101/I.S.2/A440	2008										
AAMA/WDMA/CSA 101/I.S.2/A440	2011										
AAMA/WDMA/CSA 101/I.S.2/A440	2017										
ASTM E1886	2013										

ASTM E1996	2017
TAS 201	1994
TAS 202	1994
TAS 203	1994

Sections from the Code

☒ I affirm that there are no changes in the new Florida Building Code which affect my product(s) and my product(s) are in compliance with the new Florida Building Code.

Documentation from approved Evaluation or Validation Entity ☒ Yes ☐ No ☐ N/A

[FL19563_R6_COC_SA19563 SS 2023-06-19.pdf](#)

Product Approval Method

Method 1 Option D

Date Submitted	08/08/2023
Date Validated	08/08/2023
Date Pending FBC Approval	
Date Approved	08/10/2023
Date Revised	08/27/2024

Summary of Products

FL #	Model, Number or Name	Description
19563.1	Renewal by Andersen Glider Window (Non-HVHZ) (Non-Impact)	Renewal by Andersen Glider Window (Non-HVHZ) (Non-Impact)
Limits of Use Approved for use in HVHZ: No Approved for use outside HVHZ: Yes Impact Resistant: No Design Pressure: N/A Other: See Installation Details and Evaluation Report for allowable design pressures, sizes, configurations, installation requirements and limits of use.		Installation Instructions FL19563_R6_II_AWD243 SS 2018-12-17.pdf Verified By: Hermes F. Norero, P.E. FL PE No. 73778 Created by Independent Third Party: Yes Evaluation Reports FL19563_R6_AE_PER5898 SS 2018-12-16.pdf Created by Independent Third Party: Yes
19563.2	Renewal by Andersen Glider Windows (HVHZ) (Impact)	Renewal by Andersen Glider Windows (HVHZ) (Impact)
Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: Yes Design Pressure: +60/-70 Other: See Installation Details and Evaluation Report for allowable sizes, configurations, installation requirements and limits of use.		Installation Instructions FL19563_R6_II_AWD322 SS 2022-10-13.pdf Verified By: Hermes F. Norero, P.E. Florida P.E. 73778 Created by Independent Third Party: Yes Evaluation Reports FL19563_R6_AE_PER8163 SS 2022-10-13.pdf Created by Independent Third Party: Yes

Back Next

Contact Us :: 2601 Blair Stone Road, Tallahassee FL 32399 Phone: 850-487-1824

The State of Florida is an AA/EEO employer. [Copyright 2007-2013 State of Florida.](#) :: [Privacy Statement](#) :: [Accessibility Statement](#) :: [Refund Statement](#)

Under Florida law, email addresses are public records. If you do not want your e-mail address released in response to a public-records request, do not send electronic mail to this entity. Instead, contact the office by phone or by traditional mail. If you have any questions, please contact 850.487.1395. *Pursuant to Section 455.275(1), Florida Statutes, effective October 1, 2012, licensees licensed under Chapter 455, F.S. must provide the Department with an email address if they have one. The emails provided may be used for official communication with the licensee. However email addresses are public record. If you do not wish to supply a personal address, please provide the Department with an email address which can be made available to the public. To determine if you are a licensee under Chapter



BUILDING DROPS

A Perfect Solution in Every Drop!

Certificate of Authorization: 29578

398 E. Dania Beach Blvd.
Suite 338
Dania Beach, FL 33004
954.399.8478 PH
954.744.4738 FX
contact@buildingdrops.com

Product Evaluation Report

of

**Andersen Corporation
Renewal by Andersen Glider Windows**

for

Florida Product Approval

FL# FL19563

Report No. 5898

Current Florida Building Code

Method:	1 – D (Engineering Evaluation)
Category:	Windows
Sub – Category:	Glider Window

Product:	<i>Renewal by Andersen Glider Windows</i>
Material:	<i>Fibrex® & PVC</i>
Product Dimensions:	<i>See installation instructions, AWD243</i>

Prepared For:

**Andersen Corporation
100 4th Ave. N
Bayport, Minnesota 55003**

Prepared by:

Hermes F. Norero, P.E.

Florida Professional Engineer # 73778

Date: 12/15/18

Contents:

Evaluation Report Pages 1 – 4

Digitally signed by Hermes F. Norero, P.E.
Reason: I am approving this document
Date: 2018.12.16 18:10:20 -05'00'



Hermes F. Norero, P.E.
Florida No. 73778



BUILDING DROPS

A Perfect Solution in Every Drop!

Certificate of Authorization: 29578

FL#: FL19563

Date: 12/15/18

Report No: 5898

Manufacturer: Andersen Corporation

Product Category: Windows

Product Sub-Category: Glider Window

Compliance Method: State Product Approval Method (1)(d)

Product Name: Renewal Glider Windows

Scope: This is a Product Evaluation Report issued by Hermes F. Norero, P.E. (FL # 73778) for **Andersen Corporation** based on Method 1d of the State of Florida Product Approval, Florida Department of Business and Professional Regulation - Florida Building Commission.

Hermes F. Norero, P.E. does not have nor will acquire financial interest in the company manufacturing or distributing the product or in any other entity involved in the approval process of the product named herein.

This product has been evaluated for use in locations adhering to the Current Florida Building Code.

See Installation Instructions **AWD243**, signed and sealed by Hermes F. Norero, P.E. (FL # 73778) for specific use parameters.

Limits of Use:

1. This product has been evaluated and is in compliance with the Current Florida Building Code, excluding the "High Velocity Hurricane Zone" (HVHZ).
2. Product anchors shall be as listed and spaced as shown on details. Anchor embedment into substrate material shall be beyond wall dressing or stucco.
3. When used in areas requiring wind borne debris protection this product complies with Chapter 16 of the Current Florida Building Code and does require an impact resistant covering.
4. Site conditions that deviate from the details of drawing **AWD243** require further engineering analysis by a licensed engineer or registered architect.
5. See Installation Instructions **AWD243** for size and design pressure limitations.



BUILDING DROPS

A Perfect Solution in Every Drop!

Certificate of Authorization: 29578

FL#: FL19563

Date: 12/15/18

Report No: 5898

Quality Assurance:

The manufacturer has demonstrated compliance of products in accordance with the Florida Building Code for manufacturing under a quality assurance program audited by an approved quality assurance entity through **Window and Door Manufacturers Association** (FBC Organization #: QUA2515).

Performance Standards:

The product described herein has been tested per:

- AAMA/WDMA/CSA 101/I.S.2/A440-08/11

Referenced Data:

1. Product Testing performed by **Architectural Testing**
(FBC Organization # TST1795)

D2720.01-201-47-R0	01/06/14
D2720.02-201-47-R0	01/06/14
D2721.01-201-47-R0	01/06/14
D2721.02-201-47-R0	01/06/14
D2722.01-201-47-R0	01/06/14
D2722.02-201-47-R0	01/06/14
D3502.02-201-47-R0	01/06/14
D3502.01-201-47-R0	01/06/14
D3503.01-201-47-R0	01/06/14
D3503.02-201-47-R0	01/06/14
D3499.01-201-47-R0	01/06/14
D3499.02-201-47-R0	01/06/14
D3500.01-201-47-R0	01/06/14
D3500.02-201-47-R0	01/06/14
D3501.01-201-47-R0	01/06/14
D3501.02-201-47-R0	01/06/14
D2724.01-201-47-R0	01/06/14
D2724.02-201-47-R0	01/06/14
D2730.01-201-47-R0	01/06/14
D2730.02-201-47-R0	01/06/14
D3498.01-201-47-R0	01/06/14
D3498.02-201-47-R0	01/06/14
D2733.01-201-47-R0	01/06/14
D2733.02-201-47-R0	01/06/14
D2726.01-201-47-R0	01/06/14
D2726.02-201-47-R0	01/06/14

Hermes F. Norero, P.E.

Florida No. 73778

Page 3 of 4



BUILDING DROPS

A Perfect Solution in Every Drop!

Certificate of Authorization: 29578

FL#: FL19563

Date: 12/15/18

Report No: 5898

D2728.01-201-47-R0	01/06/14
D2728.02-201-47-R0	01/06/14
D2734.01-201-47-R0	01/06/14
D2734.02-201-47-R0	01/06/14
D2736.01-201-47-R0	01/06/14
D2736.02-201-47-R0	01/06/14
D2727.01-201-47-R0	01/06/14
D2727.02-201-47-R0	01/06/14
D2729.01-201-47-R0	01/06/14
D2729.02-201-47-R0	01/06/14
D2735.01-201-47-R0	01/06/14
D2735.02-201-47-R0	01/06/14
D2737.01-201-47-R0	01/06/14
D2737.02-201-47-R0	01/06/14

2. Product Testing performed by **Intertek**
(FBC Organization # TST1795)

I9389.01-201-47	12/10/18
I9393.01-201-47	12/11/18
I9398.01-201-47	12/10/18
I9388.01-201-47	12/10/18
I9392.01-201-47	12/10/18
I9397.01-201-47	12/10/18
I9390.01-201-47	12/10/18
I9396.01-201-47	12/11/18
I9301.01-201-47	12/10/18
I9394.01-201-47	12/11/18
I9300.01-201-47	12/10/18

3. Quality Assurance
Window and Door Manufacturers Association
(FBC Organization #: QUA2515)

Installation:

Refer to Installation Instructions (**AWD243**) for anchor type, embedment, edge distance and anchor spacing details.

Design Pressure:

Refer to Installation Instructions (**AWD243**) for design pressures based on unit construction, size, and configuration.

ANDERSEN CORPORATION

RENEWAL BY ANDERSEN SERIES GLIDER WINDOW (NON-IMPACT) (NON-HVHZ)

GENERAL NOTES:

- THE PRODUCT SHOWN HEREIN IS DESIGNED AND MANUFACTURED TO COMPLY WITH THE CURRENT EDITION FLORIDA BUILDING CODE (FBC), EXCLUDING HVHZ AND HAS BEEN EVALUATED ACCORDING TO THE FOLLOWING:
 - AAMA/WDMA/CSA 101/1.5.2/A440-08/11
- ADEQUACY OF THE EXISTING STRUCTURAL CONCRETE/MASONRY, 2X FRAMING, AND METAL FRAMING AS A MAIN WIND FORCE RESISTING SYSTEM CAPABLE OF WITHSTANDING AND TRANSFERRING APPLIED PRODUCT LOADS TO THE FOUNDATION IS THE RESPONSIBILITY OF THE ENGINEER OR ARCHITECT OF RECORD FOR THE PROJECT OF INSTALLATION.
- 1X AND 2X BUCKS (WHEN USED) SHALL BE DESIGNED AND ANCHORED TO PROPERLY TRANSFER ALL LOADS TO THE STRUCTURE. BUCK DESIGN AND INSTALLATION IS THE RESPONSIBILITY OF THE ENGINEER OR ARCHITECT OF RECORD FOR THE PROJECT OF INSTALLATION.
- INSTALL INDIVIDUAL INSTALLATION ANCHORS WITHIN A TOLERANCE OF $\pm 1/4$ INCH OF THE DEPICTED LOCATION IN THE ANCHOR LAYOUT DETAIL (I.E. WITHOUT CONSIDERATION OF TOLERANCES). TOLERANCES ARE NOT CUMULATIVE FROM ONE INSTALLATION ANCHOR TO THE NEXT.
- THE INSTALLATION DETAILS DESCRIBED HEREIN ARE GENERIC AND MAY NOT REFLECT ACTUAL CONDITIONS FOR A SPECIFIC SITE. IF SITE CONDITIONS CAUSE INSTALLATION TO DEVIATE FROM THE REQUIREMENTS DETAILED HEREIN, A LICENSED ENGINEER OR ARCHITECT SHALL PREPARE SITE SPECIFIC DOCUMENTS FOR USE WITH THIS DOCUMENT IN NON-HVHZ AREAS.
- APPROVED IMPACT PROTECTIVE SYSTEM **IS REQUIRED** ON THIS PRODUCT IN AREAS REQUIRING IMPACT RESISTANCE.
- WINDOW FRAME MATERIAL: FIBREX & PVC
- IN ACCORDANCE WITH THE CURRENT EDITION FBC, WOOD COMPONENTS SHALL HAVE BEEN PRESERVATIVE TREATED OR SHALL BE OF A DURABLE SPECIES AS DEFINED IN CHAPTER 23.
- GLASS SHALL MEET THE REQUIREMENTS OF ASTM E 1300 GLASS CHARTS. SEE SHEET 1 FOR GLAZING DETAILS.

DESIGN PRESSURE RATING			
SIZE	CONFIGURATION	DESIGN PRESSURE	SASH WIDTH RATIO
72" X 80"	XO	+40.0 / -40.0 PSF	1:1
96" X 54"	XO	+40.0 / -40.0 PSF	1:1
96" X 72"	XO	+40.0 / -40.0 PSF	1:1
108" X 54"	XO	+25.0 / -25.0 PSF	1:2
108" X 72"	XO	+20.0 / -20.0 PSF	1:2
56" X 80"	XO	+40.0 / -40.0 PSF	1:2
74" X 54"	XO	+40.0 / -40.0 PSF	1:2
74" X 72"	XO	+35.0 / -35.0 PSF	1:2
48" X 48"	XX	+40.0 / -40.0 PSF	1:1
72" X 80"	XX	+30.0 / -30.0 PSF	1:1
96" X 54"	XX	+35.0 / -35.0 PSF	1:1
96" X 60"	XX	+35.0 / -35.0 PSF	1:1
96" X 72"	XX	+20.0 / -20.0 PSF	1:1
144" X 54"	XOX	+30.0 / -30.0 PSF	1:1:1
144" X 72"	XOX	+25.0 / -25.0 PSF	1:1:1
84" X 60"	XOX	+40.0 / -40.0 PSF	1:1:1
84" X 80"	XOX	+35.0 / -35.0 PSF	1:1:1
144" X 54"	XOX	+30.0 / -30.0 PSF	1:2:1
144" X 72"	XOX	+25.0 / -25.0 PSF	1:2:1
84" X 60"	XOX	+40.0 / -40.0 PSF	1:2:1
84" X 80"	XOX	+35.0 / -35.0 PSF	1:2:1


DESIGN PRESSURE UPGRADE RATING			
SIZE	CONFIGURATION	DESIGN PRESSURE	SASH WIDTH RATIO
56" X 48"	XO	+61.0 / -79.0 PSF	1:1
40" X 40"	XO	+81.0 / -100.0 PSF	1:1
88" X 64"	XO	+42.0 / -43.0 PSF	1:1
74" X 72"	XO	+50.0 / -50.0 PSF	1:1
74" X 64"	XO	+50.0 / -65.0 PSF	1:1
108" X 72"	XOX	+26.0 / -26.0 PSF	1:1:1 & 1:2:1
120" X 64"	XOX	+28.0 / -28.0 PSF	1:1:1 & 1:2:1
56" X 48"	XOX	+61.0 / -79.0 PSF	1:1:1 & 1:2:1
74" X 64"	XOX	+50.0 / -65.0 PSF	1:1:1 & 1:2:1
108" X 64"	XOX	+40.0 / -40.0 PSF	1:1:1 & 1:2:1

*SEE FRAME DESCRIPTIONS ON SHEET 6 & 8

NOTES:

- DP UPGRADE PRODUCT POSITIVE RATING IS DRIVEN BY STRUCTURAL ONLY. WATER IS NOT INCLUDED.
- DP UPGRADE PRODUCT MUST BE INSTALLED THROUGH FRAME ONLY. EXCEPT ON SILL WHERE JAMB CLIPS MUST BE USED.

TABLE OF CONTENTS	
SHEET	REVISION
1	-
2	-
3	-
4	-
5	-
6	-
7	-
8	-
9	-



GLAZING DETAIL

GLAZING NOTES:

- GLASS TYPE & THICKNESS SHALL COMPLY WITH ASTM E1300 REQUIREMENTS AS WELL AS APPLICABLE SAFETY GLAZING REQUIREMENTS PER THE FBC. TEMPER AND SAFETY GLAZING REQUIREMENTS SHALL BE REVIEWED ON A SITE SPECIFIC BASIS. SETTING BLOCK DUREMETER HARDNESS OF 70-90 (SHORE A) AS REFERENCED IN FBC CHAPTER 24.
- SETTING BLOCKS TO BE LOCATED AT 1/4 SPAN LENGTH FOR GLASS WIDER THAN 36" AS PER FBC CHAPTER 24. D.L.O. AND DESIGN PRESSURES MAY NOT EXCEED MAX VALUES IN DESIGN PRESSURE TABLES ON SHEET 1.



100 FOURTH AVE NORTH
DAYTONA, FL 32109-3500
PH: (651) 284-5150 FX: (651) 284-5485

RENEWAL SERIES GLIDING
WINDOW (NON-IMPACT)
(NON-HVHZ)
GENERAL NOTES &
GLAZING DETAIL

BUILDING DROPS, INC.
398 E. DANIA BEACH BLVD., STE. 338
DANIA BEACH, FL 33004
PH: (954) 944-4738
FAX: (954) 944-4738
WEB: www.buildingdrops.com



PREPARED BY:

TITLE:


REMARKS

BY

DATE

THE INSTALLATION DETAILS DESCRIBED HEREIN ARE GENERIC AND MAY NOT REFLECT ACTUAL CONDITIONS FOR A SPECIFIC SITE. IF SITE CONDITIONS CAUSE INSTALLATION TO DEVIATE FROM THE REQUIREMENTS DETAILED HEREIN, A LICENSED ENGINEER OR ARCHITECT SHALL PREPARE SITE SPECIFIC DOCUMENTS FOR USE WITH THIS DOCUMENT.

Digitally signed by **Jeffery F. Norero, P.E.**
Reason: Not approving this document
Date: 2018.12.17 15:52:19 -0500



FL #:

FL195563

DATE: 11.07.18

DWG BY: RV

CHK BY: HFN

SCALE: NTS


DWG #: AWD243

SHEET:

1


OF 9

OF 9



ELEVATION
84" X 80" XOX UNIT
1:1:1 SASH RATIO

NOTE:
ALTERNATE MEETING STILE
LOCATIONS MAY BE USED SUCH
THAT MAX. DLO DIMENSIONS
SHOWN HEREIN ARE NOT
EXCEEDED.




ELEVATION
84" X 80" XOX UNIT
1:2:1 SASH RATIO

ELEVATION
144" X 72" XOX UNIT
1:2:1 SASH RATIO

REMARKS	BY	DATE
---------	----	------

THE INSTALLATION DETAILS DESCRIBED HEREIN ARE GENERIC AND MAY NOT REFLECT ACTUAL CONDITIONS FOR A SPECIFIC SITE. IF SITE CONDITIONS CAUSE INSTALLATION TO DEVIATE FROM THE REQUIREMENTS DETAILED HEREIN, A LICENSED ENGINEER OR ARCHITECT SHALL PREPARE SITE SPECIFIC DOCUMENTS FOR USE WITH THIS DOCUMENT.



HERMES/FJ NORRIS, P.E.
FLORIDA P.E. No 73778
BUILDING DROPS, INC
398 E. DANIA BEACH BLVD. # 338
DANIA BEACH, FL 33004
FBPE CERT. OF AUTHORIZATION No. 29578

FL #: FL19563

DATE: 11.07.18

DWG. BY: RV	CHK. BY: HEN
-----------------------	------------------------

SCALE: NTS

DWG. #: AWD243

SHEET:



6 OF 9

NEWAL SERIES GLIDING
WINDOW (NON-IMPACT)
(NON-HVHZ)
ELEVATIONS



Y:


BUILDING DROPS, INC.

398 E. DANIA BEACH BLVD., STE. 338
DANIA BEACH, FL 33004
PH: (954) 399-8478
FAX: (954) 744-4738
WEB: www.buildingdrops.com




TI

		1200 FOURTH AVE NORTH RAYMOND, MN 55405-1095 PH: (612) 284-5700 FAX: (612) 284-5455	
RENEWAL SERIES GLIDING WINDOW (NON-HVHZ) ANCHOR LAYOUTS		PREPARED BY: BUILDING DROPS, INC.  285 E. CHAMBERLAIN BLVD. STE. 320 MINNEAPOLIS, MN 55414 WWW.BUILDINGDROPS.COM	
TITLE:		REMARKS	BY DATE
		THIS DOCUMENT IS FOR EXCLUSIVE USE OF THE CLIENT. IT IS NOT TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, WITHOUT THE WRITTEN PERMISSION OF BUILDING DROPS, INC. THIS DOCUMENT IS NOT A CONTRACT. IT IS A GUIDE ONLY. THE CLIENT IS RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND FOR VERIFYING THE ACCURACY OF ALL INFORMATION PROVIDED. BUILDING DROPS, INC. IS NOT RESPONSIBLE FOR ANY DAMAGE TO PROPERTY OR PERSONS ARISING FROM THE USE OF THIS DOCUMENT.	



TYPICAL ANCHOR LAYOUT



REQUIRE

ALL METHODS OF INSTALLATION REQUIRE
A CONTINUOUS $\frac{3}{4}$ " BEAD OF SILICONE
BELOW THE SILL

RENEWAL SERIES GLIDER ANCHOR SPACING					
CONFIG.	INSTALLATION METHOD	FROM CORNERS (IN)	MAX O.C. HEAD (IN)	MAX O.C. SILL (IN)	MAX O.C. JAMBS (IN)
"XO" OR "XX" GLIDER 1:1 SASH RATIO	NAIL FIN	3.5	3.5	3.5	3.5
	INSTALLATION CLIP	5.5	15.25	15.25	16
	THROUGH FRAME	5.5	10.125	SEE NOTES	15.25
"XO" OR "XX" GLIDER 1:2 SASH RATIO	NAIL FIN	3.5	3.5	3.5	3.5
	INSTALLATION CLIP	5.5	15	15	16
	THROUGH FRAME	5.5	11.25	SEE NOTES	17.25

INSTALLATION NOTES:

- FOR THROUGH FRAME INSTALLATIONS, INSTALLATION CLIPS MUST BE USED AT THE SILL IN LIEU OF FASTENERS THROUGH FRAME, SPACED IN ACCORDANCE WITH THE INSTALLATION CLIP SPACING REQUIREMENTS LISTED IN THE ABOVE TABLE.
- FOR CUSTOM SASH RATIOS, USE WORST CASE ANCHOR SPACING BETWEEN EQUAL SASH AND 1:2 OR 1:2.1 SASH RATIOS FROM TABLE ABOVE. REFER TO SHEET 1, SEE TABLE ON SHEET 9 FOR ANCHOR TYPE DEPENDENT ON INSTALLATION METHOD AND SUBSTRATE.

RENEWAL SERIES DP UPGRADE GLIDER ANCHOR SPACING					
CONFIG. & SIZE	INSTALLATION METHOD	FROM CORNERS (IN)	MAX O.C. HEAD (IN)	MAX O.C. SILL (IN)	MAX O.C. JAMBS (IN)
XO & OX 40" X 40" GLIDER	THROUGH FRAME & JAMB CLIP INSTALL (SILL ONLY)	5.5	9	9	9
XO & OX 48" X 48" GLIDER	THROUGH FRAME & JAMB CLIP INSTALL (SILL ONLY)	5.5	9	9	9
XO & OX 56" X 64" GLIDER	THROUGH FRAME & JAMB CLIP INSTALL (SILL ONLY)	5.5	9	9	9
XO & OX 74" X 64" GLIDER	THROUGH FRAME & JAMB CLIP INSTALL (SILL ONLY)	5.5	9	9	9
XO & OX 74" X 72" GLIDER	THROUGH FRAME & JAMB CLIP INSTALL (SILL ONLY)	5.5	12.5	12.5	12.5
XO & OX 88" X 64" GLIDER	THROUGH FRAME & JAMB CLIP INSTALL (SILL ONLY)	5.5	15.25	15.25	15.25
XO & OX 98" X 64" GLIDER	THROUGH FRAME & JAMB CLIP INSTALL (SILL ONLY)	5.5	15.25	15.25	15.25

INSTALLATION NOTES:

- DP UPGRADE PRODUCTS WHEN ANCHORING WITH $\frac{1}{2}$ " ITW TAPCON FASTENERS THE JAMB SHIM MUST BE USED BETWEEN THE FRAME AND THE 1/4" SHIM STACK. JAMB SHIM NOT REQUIRED WHEN USING JAMB CLIP FOR SILL FASTENING.



200 FOURTH AVE. NORTH
NATOPOL, MN 55055-1099
PH: (651) 244-5300 FAX: (651) 244-5455

PREPARED BY:
BUILDING DROPS, INC.
388 E. DUNN BEACH BLVD. SUITE 300
DUNN BEACH, FL 33004
PH: (904) 244-4738
WWW.BUILDINGDROPS.COM



REMARKS

BY DATE

TITLE

ANCHOR LAYOUTS

RENEWAL SERIES GLIDING WINDOW (NON-IMPACT) (NON-HVHZ)

FL #:

FL19563

DATE: 11.07.18

DWG. BY: RV

CHK. BY: HFN

SCALE: NTS


DWG. #: AWD243

SHEET:

5

OF 9

TWO INSTALLATION ANCHORS (SEE INSTALL NOTES 7-9, SHEET 1) AT MEETING STILE END LOCATIONS THROUGH HEAD, SPACED 2.5" ON EACH SIDE OF MEETING STILE. EXCLUDES UNITS $\leq 36" \times 48"$




TYPICAL ANCHOR LAYOUT

XOX GLIDER

1:1:1 SASH RATIO

TWO INSTALLATION ANCHORS (SEE INSTALL NOTES 7-9, SHEET 1) AT MEETING STILE END LOCATIONS THROUGH HEAD, SPACED 2.5" ON EACH SIDE OF MEETING STILE. EXCLUDES UNITS $\leq 36" \times 48"$



TYPICAL ANCHOR LAYOUT

XOX GLIDER

1:2:1 SASH RATIO

ALL METHODS OF INSTALLATION REQUIRE A CONTINUOUS 3/8" BEAD OF SILICONE BELOW THE SILL

RENEWAL SERIES GLIDER ANCHOR SPACING						
CONFIG.	INSTALLATION METHOD	FROM CORNERS (IN)	MAX O.C. HEAD (IN)	MAX O.C. SILL (IN)	MAX O.C. JAMBS (IN)	
"XOX" GLIDER 1:1:1 SASH RATIO	NAIL FIN	3.5	3.5	3.5	3.5	
	INSTALLATION CLIP	5.5	14.5	14.5	16	
	THROUGH FRAME	5.5	10.375	SEE NOTES	21.5	
"XOX" GLIDER 1:2:1 SASH RATIO	NAIL FIN	3.5	3.5	3.5	3.5	
	INSTALLATION CLIP	5.5	12.125	12.125	16	
	THROUGH FRAME	5.5	10.5	SEE NOTES	22	


INSTALLATION NOTES:

- FOR THROUGH FRAME INSTALLATIONS, INSTALLATION CLIPS MUST BE USED AT THE SILL IN LIEU OF FASTENERS THROUGH FRAME, SPACED IN ACCORDANCE WITH THE INSTALLATION CLIP SPACING REQUIREMENTS LISTED IN THE ABOVE TABLE.
- FOR CUSTOM SASH RATIOS, USE WORST CASE ANCHOR SPACING BETWEEN EQUAL SASH AND 1:2 OR 1:2:1 SASH RATIOS FROM TABLE ABOVE.
- REFER TO SHEET 1, INSTALLATION NOTES 4-11 FOR ANCHOR TYPE DEPENDENT ON INSTALLATION METHOD AND SUBSTRATE.


INSTALLATION NOTES:

- DP UPGRADE PRODUCTS WHEN ANCHORING WITH 1/4" ITW TAPCON FASTENERS THE JAMB SHIM MUST BE USED BETWEEN THE FRAME AND THE 1/4" INCH SHIM STACK. JAMB SHIM NOT REQUIRED WHEN USING JAMB CLIP FOR SILL FASTENING.


RENEWAL SERIES DP UPGRADE GLIDER ANCHOR SPACING						
CONFIG. & SIZE	INSTALLATION METHOD	FROM CORNERS (IN)	MAX O.C. HEAD (IN)	MAX O.C. SILL (IN)	MAX O.C. JAMBS (IN)	
XOX GLIDER 1:1:1 & 1:2:1	THROUGH FRAME & JAMB CLIP INSTALL (SILL ONLY)	5.5	9	9	9	
	THROUGH FRAME & JAMB CLIP INSTALL (SILL ONLY)	5.5	9	9	9	
	THROUGH FRAME & JAMB CLIP INSTALL (SILL ONLY)	5.5	10.5	12.125	13.75	
XOX GLIDER 1:1:1 & 1:2:1	THROUGH FRAME & JAMB CLIP INSTALL (SILL ONLY)	5.5	10.5	12.125	19.25	
	THROUGH FRAME & JAMB CLIP INSTALL (SILL ONLY)	5.5	10.5	12.125	17.5	
	THROUGH FRAME & JAMB CLIP INSTALL (SILL ONLY)	5.5	10.5	12.125	17.5	



A VERTICAL SECTION
THROUGH FRAME AND THROUGH CLIP INSTALLATION



ALTERNATE EJ FRAME
MAY BE USED AS EQUAL ALTERNATE FRAME TYPE



B VERTICAL SECTION
NAIL FIN INSTALLATION

NAIL FIN/FLANGE IS REVERSIBLE, SEE ORIENTATION DIFFERENCE BETWEEN HEAD AND SILL.



100 FOURTH AVE NORTH
DAYTON, OH 45424-1199
PH: (651) 284-5150 FX: (651) 284-5485

RENEWAL SERIES GLIDING
WINDOW (NON-IMPACT)
(NON-HVHZ)
VERTICAL SECTIONS

PREPARED BY:
BUILDING DROPS, INC.
398 E. DANIA BEACH BLVD., STE. 338
DANIA BEACH, FL 33004
PH: (954) 399-4878
FAX: (954) 744-4738
WEB: www.buildingdrops.com



TITLE: REMARKS BY DATE

THE INSTALLATION DETAILS DESCRIBED HEREIN ARE GENERAL IN NATURE AND ARE NOT TO BE USED AS A BASIS FOR A SPECIFIC SITE. IF SITE CONDITIONS CAUSE INSTALLATION TO DEVIATE FROM THE REQUIREMENTS DETAILED HEREIN, A LICENSED PROFESSIONAL ENGINEER MUST BE CONSULTED FOR THE APPROPRIATE DOCUMENTS FOR USE WITH THIS DOCUMENT.



FL19563
DATE: 11.07.18
DWG. BY: RV
CHK. BY: HFN
SCALE: NTS
DWG. #: AWD243
SHEET: 6



INSTALLATION NOTES:

- ONE (1) INSTALLATION ANCHOR IS REQUIRED AT EACH ANCHOR LOCATION, UNLESS OTHERWISE SHOWN.
- THE NUMBER OF INSTALLATION ANCHORS DEPICTED IS THE MINIMUM NUMBER OF ANCHORS TO BE USED FOR PRODUCT INSTALLATION OF THE MAXIMUM SIZE LISTED.
- INSTALL INDIVIDUAL INSTALLATION ANCHORS WITHIN A TOLERANCE OF +/- 1/4 INCH THE DEPICTED LOCATION & SPACING IN THE ANCHOR LAYOUT DETAILS (I.E., WITHOUT CONSIDERATION OF TOLERANCES). TOLERANCES ARE NOT CUMULATIVE FROM ONE INSTALLATION ANCHOR TO THE NEXT.
- SHIM AS REQUIRED AT EACH INSTALLATION ANCHOR WITH LOAD BEARING SHIM(S). MAXIMUM ALLOWABLE SHIM STACK TO BE 1/4 INCH. SHIM WHERE SPACE OF 1/16 INCH OR GREATER OCCURS. SHIM(S) SHALL BE CONSTRUCTED OF HIGH DENSITY PLASTIC OR BETTER.
- FOR MASONRY OR CONCRETE OPENINGS, A 1X WOOD BUCK MAY BE USED (OPTIONAL) AS LONG AS THE MINIMUM EMBEDMENT AND EDGE DISTANCE REQUIREMENTS ARE STILL MET WITHIN THE CORRESPONDING HOST SUBSTRATE. SEE GENERAL NOTE #3 ON SHEET 1 FOR MORE INFORMATION.
- MINIMUM EMBEDMENT AND EDGE DISTANCE EXCLUDE WALL FINISHES, INCLUDING BUT NOT LIMITED TO STUCCO, FOAM, BRICK VENEER, AND SIDING.
- INSTALLATION ANCHORS AND ASSOCIATED HARDWARE MUST BE MADE OF CORROSION RESISTANT MATERIAL OR HAVE A CORROSION RESISTANT COATING.
- FOR HOLLOW BLOCK AND GROUT FILLED BLOCK, DO NOT INSTALL INSTALLATION ANCHORS INTO MORTAR JOINTS. EDGE DISTANCE IS MEASURED FROM FREE EDGE OF BLOCK OR EDGE OF MORTAR JOINT INTO FACE SHELL OF BLOCK.
- INSTALLATION ANCHORS SHALL BE INSTALLED IN ACCORDANCE WITH ANCHOR MANUFACTURER'S INSTALLATION INSTRUCTIONS, AND ANCHORS SHALL NOT BE USED IN SUBSTRATES WITH STRENGTHS LESS THAN THE MINIMUM STRENGTH SPECIFIED BY THE ANCHOR MANUFACTURER.

ANCHOR SCHEDULE				
METHOD	SUBSTRATE	ANCHOR SCHEDULE	MIN EMBEDMENT	MIN. EDGE DISTANCE
THROUGH FRAME	WOOD: MIN. SG = 0.55	#10 WOOD SCREW FLAT HEAD	1.5"	0.75"
	METAL: 18 GAUGE Steel, MIN. Fy = 33KSI	#10 TEK SCREW FLAT HEAD	3 THREADS MIN PENETRATION BEYOND METAL	0.5"
THROUGH FRAME & THROUGH CLIP	CONCRETE: MIN. f'c=3000PSI	3/16" ITW TAPCON FLAT HEAD	1.25"	2.5
	MASONRY: CMU per ASTM C90 MIN. 2000 PSI	3/16" ITW TAPCON FLAT HEAD	1"	2.25
NAIL FIN & THROUGH CLIP	WOOD: MIN. SG = 0.55	#8 WOOD SCREW FLAT HEAD	1.5"	0.75"
	METAL: 18 GAUGE Steel, MIN. Fy = 33KSI	#8 TEK SCREW FLAT HEAD	3 THREADS MIN PENETRATION BEYOND METAL	0.5"



100 FOURTH AVE NORTH
DAYTON, OH 45424-1099
PH: (651) 284-5150 FX: (651) 284-5485


RENEWAL SERIES GLIDING
WINDOW (NON-IMPACT)
(NON-HVHZ)
ANCHOR SCHEDULE &
INSTALLATION NOTES

PREPARED BY:
BUILDING DROPS, INC.
398 E. DANIA BEACH BLVD., STE. 338
DANIA BEACH, FL 33004
PH: (954) 399-8478
FAX: (954) 744-4738
WEB: www.buildingdrops.com



TITLE:	REMARKS	BY	DATE

THE INSTALLATION DETAIL(S) DESCRIBED HEREIN ARE GENERAL INSTRUCTIONS. THE USER SHALL BE RESPONSIBLE FOR VERIFYING THE SITE, IF SITE CONDITIONS CAUSE INSTALLATION TO DEVIATE FROM THE REQUIREMENTS SET FORTH HEREIN, A LICENSED PROFESSIONAL ENGINEER SHALL BE REQUIRED TO SIGN OFF ON ANY DEVIATIONS. DOCUMENTS FOR USE WITH THIS DOCUMENT.



HERIBERTO ROMERO, P.E.
FLORIDA P.E. NO. 73778
BUILDING DROPS, INC.
398 E. DANIA BEACH BLVD., # 338
DANIA BEACH, FL 33004
FPECE CERT. OF AUTHORIZATION No. 290578

FL #:

FL19563

DATE: 11.07.18

DWG. BY: RV

CHK. BY: HFN

SCALE: NTS

DWG. #: AWD243

SHEET: