



TEMPERED GLASS NOTES:

THE FOLLOWING SHALL BE CONSIDERED SPECIFIC HAZARDOUS LOCATIONS FOR THE PURPOSES OF GLAZING.

- GLAZING IN SITTING ROOMS AND FIXED AND SLIDING PANELS OF SLIDING (PATIO) DOOR ASSEMBLIES.
- GLAZING IN DOORS AND WALLS OF ENCLOSURES FOR HOT TUBS, JACUZZIS, SAUNAS, STEAM ROOMS, BATHUBS, SHOWERS AND OTHER SUCH FACILITIES. GLAZING IN DOORS AND WALLS OF ENCLOSURES FOR HOT TUBS, JACUZZIS, SAUNAS, STEAM ROOMS, BATHUBS, SHOWERS AND OTHER SUCH FACILITIES. GLAZING IN DOORS AND WALLS OF ENCLOSURES FOR HOT TUBS, JACUZZIS, SAUNAS, STEAM ROOMS, BATHUBS, SHOWERS AND OTHER SUCH FACILITIES.
- GLAZING IN AN INDIVIDUAL FIXED OR OPERABLE PANEL ADJACENT TO A DOOR WHERE THE NEAREST VERTICAL EDGE IS WITHIN 4.24 INCH (107 MM) RADIIUS OF THE DOOR IN A CLOSED POSITION AND UPON BOTTOM EDGE IS LESS THAN 60 INCHES (1524 MM) ABOVE THE FLOOR OR WALKING SURFACE. EXCEPTION: GLAZING IN WALLS PERPENDICULAR TO THE PLANE OF THE DOOR IN A CLOSED POSITION IN GROUP R2 OR WITHIN DWELLING UNITS IN GROUP R3 SHALL BE SUBJECT TO 2004 IBC 1409.21.4.
- GLAZING IN AN INDIVIDUAL FIXED OR OPERABLE PANEL, OTHER THAN THOSE LOCATIONS DESCRIBED IN ITEMS 2 AND 3 ABOVE, THAT MEETS ALL OF THE FOLLOWING CONDITIONS:
  - EXPOSED AREA OF AN INDIVIDUAL PANE GREATER THAN 9 SQ FT (834 ITZ).
  - BOTTOM EDGE LESS THAN 36 INCHES (914 MM) ABOVE THE FLOOR.
  - TOP EDGE GREATER THAN 36 INCHES (914 MM) ABOVE THE FLOOR.
  - ONE OR MORE WALKING SURFACES WITHIN 36 INCHES (914 MM) HORIZONTALLY OF THE PLANE OF THE GLAZING.