

MULTIPLE-MEMBER CONNECTIONS FOR SIDE-LOADED BEAMS

Point Load—Maximum Point Load Applied to Either Outside Member (lbs)

Connector Type	Number of Connectors	Connector Pattern					
		Assembly A	Assembly B	Assembly C	Assembly D	Assembly E	Assembly F
		2"	2"	1 1/4"	1 1/4"	2"	2"
		3 1/2" 2-ply	5 1/4" 3-ply	5 1/4" 2-ply	7" 3-ply	7" 2-ply	7" 4-ply
10d (0.128" x 3") Nail	6	1,110	835	835	740		
	12	2,225	1,670	1,670	1,485		
	18	3,335	2,505	2,505	2,225		
	24	4,450	3,335	3,335	2,965		
SDS Screws 1/4" x 3 1/2" or WS35 1/4" x 6" or WS6 ⁽¹⁾	4	1,915	1,435 ⁽⁴⁾	1,435	1,275	1,860 ⁽²⁾	1,405 ⁽²⁾
	6	2,870	2,150 ⁽⁴⁾	2,150	1,915	2,785 ⁽²⁾	2,110 ⁽²⁾
	8	3,825	2,870 ⁽⁴⁾	2,870	2,550	3,715 ⁽²⁾	2,810 ⁽²⁾
3 1/8" or 5" TrussLok™	4	2,545	1,910 ⁽⁴⁾	1,910	1,695	1,925 ⁽³⁾	1,775 ⁽³⁾
	6	3,815	2,860 ⁽⁴⁾	2,860	2,545	2,890 ⁽³⁾	2,665 ⁽³⁾
	8	5,090	3,815 ⁽⁴⁾	3,815	3,390	3,855 ⁽³⁾	3,550 ⁽³⁾

(1) 6" SDS or WS screws can be used with Parallam® PSL and Microlam® LVL, but are not recommended for TimberStrand® LSL.




See General Notes on page 38

(2) 6" long screws required.


(3) 5" long screws required.

(4) 3 1/2" and 3 1/8" long screws must be installed on both sides.

Connections



Point Load Design Example



First, verify that a 3-ply 1 1/4" x 14" beam is capable of supporting the 3,000 lb point load as well as all other loads applied. The 3,000 lb point load is being transferred to the beam with a face mount hanger. For a 3-ply 1 1/4" assembly, eight 3 1/8" TrussLok™ screws are good for 3,815 lbs with a face mount hanger.

MULTIPLE-MEMBER CONNECTIONS FOR TOP-LOADED BEAMS

1 3/4" Wide Pieces

- Minimum of three rows of 10d (0.128" x 3") nails at 12" on-center.
- Minimum of four rows of 10d (0.128" x 3") nails at 12" on-center for 14" or deeper.
- If using 12d-16d (0.148"-0.162" diameter) nails, the number of nailing rows may be reduced by one.
- Minimum of two rows of SDS, WS, or TrussLok™ screws at 16" on-center. Use 3 1/8" minimum length with two or three plies; 5" minimum for 4-ply members. 6" SDS and WS screws are not recommended for use with TimberStrand® LSL. Connectors must be installed on both sides. Stagger fasteners on opposite side of beam by 1/2 of the required connector spacing.


on both sides. Stagger fasteners on opposite side of beam by 1/2 of the required connector spacing.

- Load must be applied evenly across entire beam width. Otherwise, use connections for side-loaded beams.

3 1/2" Wide Pieces

- Minimum of two rows of SDS, WS, or TrussLok™ screws, 5" minimum length, at 16" on-center. 6" SDS and WS screws are not recommended for use with TimberStrand® LSL. Connectors must be installed on both sides. Stagger fasteners on opposite side of beam by 1/2 of the required connector spacing.


- Load must be applied evenly across entire beam width. Otherwise, use connections for side-loaded beams.
- Minimum of two rows of 1/2" bolts at 24" on-center staggered.




Multiple pieces can be nailed or bolted together to form a header or beam of the required size, up to a maximum width of 7".

L6


STRONG BACK DETAIL
SYSTEM-42 OR FLAT TRUSS



ALTERNATE DETAIL FOR
STRONG BACK WITH VERTICAL
NOT LINING UP



REVIEWED
By julius lee at 11:58 am, Jun 11, 2008



JULIUS LEE
CONS. ENGINEERS P.A.
1455 SW 4th AVENUE
MIAMI BEACH, FL 33144-2811


No. 34869
STATE OF FLORIDA

1/2" DIAMETER BOLT SPACING FOR LOAD APPLIED PARALLEL TO GRAIN.


* GRADE AND SPECIES AS SPECIFIED ON THE ALPINE DESIGN.
BOLT HOLES SHALL BE A MINIMUM OF 1/32" TO A MAXIMUM
OF 1/16" LARGER THAN BOLT DIAMETER.

TYPICAL LOCATION OF 1/2" DIAMETER THRU BOLTS. BOLT QUANTITIES AS NOTED ON SEALED DESIGN MUST BE APPLIED IN ONE OF THE PATTERNS SHOWN BELOW.


WASHERS REQUIRED UNDER BOLT HEAD AND NUT




2X6 MEMBER
DIRECTION
OF GRAIN
AND LOAD



2X8 MEMBER
DIRECTION
OF GRAIN
AND LOAD



2X6 DETAIL




2X8 DETAIL

THIS DRAWING REPLACES DRAWING A028.016

JULIUS LEE'S CONS. ENGINEERS P.A.		TC LL	REF	BOLT SPACING
1400 NW 4th AVENUE		TC DL	PSF	DATE 11/26/03
DEBARY BEACH, FL 32444-2261		BC DL	PSF	DRWG CNBOLTSP1103
		BC LL	PSF	-ENG JL
		TOT. LD.	PSF	
DUR. FAC.		SPACING		

REVIEWED
By:Julius Lee at 11:59 am, Jun 11, 2008





VALLEY TRUSS DETAIL

TOP CHORD 2X4 SP #2 OR SPF #1/#2 OR BETTER.
 BOT CHORD 2X3(*) OR 2X4 SP #2N OR SPF #1/#2 OR BETTER.
 WEBS 2X4 SP #3 OR BETTER.

* 2X3 MAY BE RIPPED FROM A 2X6 (PITCHED OR SQUARE).
 ** ATTACH EACH VALLEY TO EVERY SUPPORTING TRUSS WITH:

(2) 16d BOX (0.135" X 3.5") NAILS TOE-NAILED FOR
 FHC 2004 110 MPH, ASCE 7-02 110 MPH WIND OR (3) 16d FOR
 ASCE 7-02 130 MPH WIND. 15' MEAN HEIGHT, ENCLOSED
 BUILDING, EXP. C, RESIDENTIAL, WIND TC DL-5 PSF.

CUT FROM 2X6 OR
 LARGER AS REQ'D



BOTTOM CHORD MAY BE SQUARE OR PITCHED CUT AS SHOWN.

*** NOTE THAT THE PURLIN SPACING FOR BRACING THE TOP CHORD OF THE TRUSS
 BENEATH THE VALLEY IS MEASURED ALONG THE SLOPE OF THE TOP CHORD.
 ++ LARGER SPANS MAY BE BUILT AS LONG AS THE VERTICAL HEIGHT DOES
 NOT EXCEED 12'0".


BY VALLEY TRUSSES USED IN LIEU OF PURLIN SPACING AS SPECIFIED ON
 ENGINEERS' SEALED DESIGN.

UNLESS SPECIFIED ON ENGINEER'S SEALED DESIGN, APPLY 1X4 "T"-BRACE, 80%
 LENGTH OF WEB, VALLEY WEB SAME SPECIES AND GRADE OR BETTER, ATTACHED
 WITH 8d BOX (0.113" X 2.5") NAILS AT 6" OC, OR CONTINUOUS LATERAL BRACING,
 EQUALLY SPACED, FOR VERTICAL VALLEY WEBS GREATER THAN 7'9".

MAXIMUM VALLEY VERTICAL HEIGHT MAY NOT EXCEED 12'0".
 TOP CHORD OF TRUSS BENEATH VALLEY SET MUST BE BRACED WITH:
 PROPERLY ATTACHED, RATED SHEATHING APPLIED PRIOR TO VALLEY TRUSS
 INSTALLATION

OR
 PURLINS AT 24" OC OR AS OTHERWISE SPECIFIED ON ENGINEERS' SEALED DESIGN

OR
 BY VALLEY TRUSSES USED IN LIEU OF PURLIN SPACING AS SPECIFIED ON
 ENGINEERS' SEALED DESIGN.



THIS DRAWING REPLACES DRAWING A105

WARNING: TRUSSES REQUIRE EXTREME CARE IN FABRICATING, HANDLING, SHIPPING, INSTALLING AND
 BRACING. REFER TO NEXT (ED) BUILDING COMPONENT SAFETY INFORMATION, PUBLISHED BY THE TRUSS
 INSTITUTE, SEE PUBLISHED IN THE 2004 NATIONAL BUILDING CODE FOR VALLEY TRUSS DESIGN.
 THE ENGINEER OF RECORD, THE CONTRACTOR, THE TRUSS MANUFACTURER, THE
 STRUCTURAL PANELS AND BOTTOM CHORD SHALL HAVE A PROPERLY ATTACHED RIGID CEILING.

NO. 34869
 JULIUS LEE'S
 ENGINEERS
 CONS. P.A.
 1455 SW 4th AVENUE
 MIAMI, FL 33144-2611


STATE OF
 FLORIDA
 PROFESSIONAL ENGINEER

REVIEWED


By Julius Lee at 11:59 am, Jun 11, 2008

No. 34869
 STATE OF FLORIDA


TYPICAL ATTIC TRUSS BRACING




TYPICAL ALTERNATE BRACING DETAIL FOR EXTERIOR FLAT GIRDER TRUSS



REVIEWED
By Julius Lee at 11:59 am, Jun 11, 2008




GABLE END TRUSS DETAIL



MINIMUM BC BRACING ON GABLE TRUSS. OTHER PERMANENT BRACING DESIGNS BY ARCHITECT OR BOR


TYPICAL WALL GIRDER VERTICAL WEB BRACING DETAIL



SEE ROOF TRUSSES FOR UPLIFT
ROOF 24" o/c

SEE GABLE END DETAIL
FOR T-BRACE BEHIND
EACH VERTICAL

JULIUS LEE
CONS. ENGINEERS
P.A.
1405 SW 4th AVENUE
MIAMI BEACH, FL 33144-2181



No. 34869
STATE OF FLORIDA

