

FLORIDA BUILDING CODE	
Compliance Summary	
TYPE OF CONSTRUCTION	
Roof:	Hip Construction, Wood Trusses @ 24" O.C.
Walls:	2x4 Wood Studs @ 16" O.C.
Floor:	4" Thk. Concrete Slab w/ Fibermesh Concrete Additive
Foundation:	Continuous Footer/Stem Wall
ROOF DECKING	
Material:	1/2" CDX Plywood or 1/6" O.S.B.
Sheet Size:	48"x96" Sheets Perpendicular to Roof Framing
Fasteners:	8d Ring Shank per schedule on sheet 6.4
SHEAR WALLS	
Material:	1/6" O.S.B. WINDSTORM BOARD
Sheet Size:	48"x96" Sheets Placed Vertical
Fasteners:	8d Common Nails @ 4" O.C. Edges & 8" O.C. Interior
Dragstrut:	Double Top Plats (S.T.F.) w/16d Nails @ 12" O.C.
Wall Studs:	2x4 Studs @ 16" O.C.
HURRICANE UPLIFT CONNECTORS	
Truss Anchors:	SIMPSON H2.5a @ Ea. Truss End (Typ. U.O.N.)
Wall Tension:	Wall Sheathing Nailing is Adequate - 8d @ 4" O.C. Top & Bot.
Anchor Bolts:	1/2" A307 Bolts @ 48" O.C. - 1st Bolt 12"-16" from corner
Corner Hold-down Device:	(1) HTB @ each corner
Porch Column Base Connector:	Simpson ABU66 @ each column
Porch Column to Beam Connector:	Simpson EPC66/PC66 @ each column
FOOTINGS AND FOUNDATIONS	
Footings:	20" x 12" x CONT., CONCRETE FOOTING W/ 2 #5 REBAR.
Int. Footings:	12"x 12" x Cont. W/ 2 - #5 Bars Cont. on wire/plastic chairs @ 48" o.c.

STRUCTURAL DESIGN CRITERIA:

1. THE DESIGN COMPLIES WITH THE REQUIREMENTS OF THE 2023 FLORIDA, 8th EDITION BUILDING CODE - SECTION 1609 AND OTHER REFERENCED CODES AND SPECIFICATIONS. ALL CODES AND SPECIFICATIONS SHALL BE LATEST EDITION AT TIME OF PERMIT.

2. WIND LOAD CRITERIA: RISK CATAGORY: 2, EXPOSURE: "B"

BASED ON ANSI/ASCE 7-22, 2023 FBC 1609-A WIND VELOCITY: V_{ULT} = 130 MPH
V_{ASD} = 101 MPH

3. ROOF DESIGN LOADS:
SUPERIMPOSED DEAD LOADS: 20 PSF
SUPERIMPOSED LIVE LOADS: 20 PSF

4. FLOOR DESIGN LOADS:
SUPERIMPOSED DEAD LOADS: 25 PSF
SUPERIMPOSED LIVE LOADS:
RESIDENTIAL 40 PSF
BALCONIES 60 PSF

5. WIND NET UPLIFT: ARE AS INDICATED ON PLANS

TERMITE PROTECTION NOTES:

SOIL CHEMICAL BARRIER METHOD:

- A PERMANENT SIGN WHICH IDENTIFIES THE TERMITE TREATMENT PROVIDER AND NEED FOR REINSPECTION AND TREATMENT CONTRACT RENEWAL SHALL BE PROVIDED. THE SIGN SHALL BE POSTED NEAR THE WATER HEATER OR ELECTRIC PANEL. FBC 1403.2.6
- CONDENSATE AND ROOF DOWNSPOUTS SHALL DISCHARGE AT LEAST 1'-0" AWAY FROM BUILDING SIDE WALLS. FBC 1503.4.4
- IRRIGATION/SPRINKLER SYSTEMS INCLUDING ALL RISERS AND SPRAY HEADS SHALL NOT BE INSTALLED WITHIN 1'-0" FROM BUILDING SIDE WALLS. FBC 1503.4.4
- TO PROVIDE FOR INSPECTION FOR TERMITE INFESTATION, BETWEEN WALL COVERINGS AND FINAL EARTH GRADE SHALL NOT BE LESS THAN 6". EXCEPTION: PAINT AND DECORATIVE CEMENTIOUS FINISH LESS THAN 5/8" THICK ADHERED DIRECTLY TO THE FOUNDATION WALL. FBC 1403.1.6
- INITIAL TREATMENT SHALL BE DONE AFTER ALL EXCAVATION AND BACKFILL IS COMPLETE. FBC 1816.1.1
- SOIL DISTURBED AFTER THE INITIAL TREATMENT SHALL BE RETREATED INCLUDING SPACES BOXED OR FORMED. FBC 1816.1.2
- BOXED AREAS IN CONCRETE FLOOR FOR SUBSEQUENT INSTALLATION OF TRAPS, ETC., SHALL BE MADE WITH PERMANENT METAL OR PLASTIC FORMS. PERMANENT FORMS MUST BE OF A SIZE AND DEPTH THAT WILL ELIMINATE THE DISTURBANCE OF SOIL AFTER THE INITIAL TREATMENT. FBC 1816.1.3
- MINIMUM 6 MIL VAPOR RETARDER MUST BE INSTALLED TO PROTECT AGAINST RAINFALL DILUTION. IF RAINFALL OCCURS BEFORE VAPOR RETARDER PLACEMENT, RETREATMENT IS REQUIRED. FBC 1816.1.4
- CONCRETE OVERPOUR AND MORTAR ALONG THE FOUNDATION PERIMETER MUST BE REMOVED BEFORE EXTERIOR SOIL TREATMENT. FBC 1816.1.5
- SOIL TREATMENT MUST BE APPLIED UNDER ALL EXTERIOR CONCRETE OR GRADE WITHIN 1'-0" OF THE STRUCTURE SIDEWALLS. FBC 1816.1.6
- AN EXTERIOR VERTICAL CHEMICAL BARRIER MUST BE INSTALLED AFTER CONSTRUCTION IS COMPLETE INCLUDING LANDSCAPING AND IRRIGATION. ANY SOIL DISTURBED AFTER THE VERTICAL BARRIER IS APPLIED, SHALL BE RETREATED. FBC 1816.1.6
- ALL BUILDINGS ARE REQUIRED TO HAVE PER-CONSTRUCTION TREATMENT. FBC 1816.1.7
- A CERTIFICATE OF COMPLIANCE MUST BE ISSUED TO THE BUILDING DEPARTMENT BY: * LICENSED PEST CONTROL COMPANY BEFORE A CERTIFICATE OF OCCUPANCY WILL BE ISSUED. THE CERTIFICATE OF COMPLIANCE SHALL STATE: "THE BUILDING HAS RECEIVED A COMPLETE TREATMENT FOR THE PREVENTION OF SUBTERRANEAN TERMITES. THE TREATMENT IS IN ACCORDANCE WITH THE RULES AND LAWS OF THE FLORIDA DEPARTMENT OF AGRICULTURE AND CONSUMER SERVICES". FBC 1816.1.7
- AFTER ALL WORK IS COMPLETED, LOOSE WOOD AND FILL MUST BE REMOVED FROM BELOW AND WITHIN 1'-0" OF THE BUILDING. THIS INCLUDES ALL GRADE STAKES, TUB TRAP BOXES, FORMS, SHORING OR OTHER CELLULOSE CONTAINING MATERIAL. FBC 2303.1.3
- NO WOOD, VEGETATION, STUMPS, CARDBOARD, TRASH, ETC., SHALL BE BURIED WITHIN 15'-0" OF ANY BUILDING OR PROPOSED BUILDING. FBC 2303.1.4

FRAMING ANCHOR SCHEDULE

APPLICATION	MANUF/R/MODEL	CAP.
TRUSS TO WALL:	SIMPSON H2.5a or SDWC15600	600*
GIRDER TRUSS TO POST/HEADER:	SIMPSON LGT, W/ 28 - 16d NAILS	1785*
HEADER TO KING STUD(S):	SIMPSON ST22	1370*
PLATE TO STUD:	NO CONNECTION REQ. WHEN USING WINDSTORM BOARD	
STUD TO GILL:	NO CONNECTION REQ. WHEN USING WINDSTORM BOARD	
PORCH BEAM TO POST:	SIMPSON PC66/EPC66	1700*
PORCH POST TO FND.:	SIMPSON ABU66	2200*
MISC. JOINTS	SIMPSON A34	315*/240*

NOTE:
ALL ANCHORS SHALL BE SECURED W/ NAILS AS PRESCRIBED BY THE MANUFACTURER FOR MAXIMUM JOINT STRENGTH, UNLESS NOTED OTHERWISE.
NOTE:
REFER TO THE INCLUDED STRUCTURAL DETAILS FOR ADDITIONAL ANCHORS/ JOINT REINFORCEMENT AND FASTENERS.
NOTE:
ALL UNLISTED JOINTS IN THE LOAD PATH SHALL BE REINFORCED WITH SIMPSON A34 FRAMING ANCHORS, TYPICAL T.O.

NOTE:
ALL UNLISTED JOINTS IN THE LOAD PATH SHALL BE REINFORCED WITH SIMPSON A34 FRAMING ANCHORS, TYPICAL T.O.

NOTE:
"SEMCO" PRODUCT APPROVAL:
MIAMI/DADE COUNTY REPORT #35-0818.15

NOTE:
"SIMPSON" PRODUCT APPROVALS:
MIAMI/DADE COUNTY REPORT #37-0107.05, #36-1126.11, #39-0623.04
SBCCI NER-443, NER-393

		45°		30°		15°	
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N
		4	4	4	4	4	4
		W	H	W	H	W	H
		O	N	O	N	O	N