

AZING - HAZARDOUS LOCATIONS: (PER F.B.C. RESIDENTIAL 2007)

1) EACH PANE OF GLAZING INSTALLED IN HAZARDOUS LOCATIONS PER R308.4 SHALL BE PROVIDED WITH A MANUFACTURER'S OR INSTALLER'S LABEL, DESIGNATING THE TYPE AND THICKNESS OF GLASS AND THE SAFETY GLAZING STANDARD WITH WHICH IT COMPLIES, WHICH IS VISIBLE IN THE FINAL INSTALLATION. THE LABEL SHALL BE ACID ETCHED, SANDBLASTED, CERAMIC-FIRED, EMBOSSED MARK, OR SHALL BE OF A TYPE WHICH ONCE APPLIED CANNOT BE REMOVED WITHOUT BEING DESTROYED. SEE R308 FOR EXCEPTIONS. IDENTIFICATION OF MULTIPANE ASSEMBLIES PER R308.1.1.


2) HAZARDOUS LOCATIONS. R308.4


- 1) GLAZING IN SWINGING DOORS EXCEPT JALOUSIES.
- 2) GLAZING IN FIXED AND SLIDING PANELS OF SLIDING DOOR ASSEMBLIES AND PANELS IN SLIDING
- AND BIFOLD CLOSET DOOR ASSEMBLIES.
- 3) GLAZING IN STORM DOORS. 4) GLAZING IN ALL UNFRAMED SWINGING DOORS.
- 5) GLAZING IN DOORS AND ENCLOSURES FOR HOT TUBS, WHIRLPOOLS, SAUNAS, STEAM ROOMS, BATHTUBS, AND SHOWERS. GLAZING IN ANY PART OF A BUILDING WALL ENCLOSING THESE COMPARTMENTS WHERE THE BOTTOM EXPOSED EDGE OF THE GLAZING IS LESS THAN 60" MEASURED VERTICALLY ABOVE ANY STANDING OR WALKING SURFACE.
- 6) GLAZING, IN AN INDIVIDUAL FIXED OR OPERABLE PANEL ADJACENT TO A DOOR WHERE THE NEAREST VERTICAL EDGE IS WITHIN A 24" ARC OF THE DOOR IN A CLOSED POSITION AND WHOSE BOTTOM EDGE IS LESS THAN 60" ABOVE THE FLOOR OR WALKING SURFACE.
- 7) GLAZING IN AN INDIVIDUAL FIXED OR OPERABLE PANEL, OTHER THAN THOSE LOCATIONS DESCRIBED IN ITEMS 5 AND 6 ABOVE, THAT MEETS ALL OF THE FOLLOWING CONDITIONS:
- 7.1 EXPOSED AREA OF AN INDIVIDUAL PANE GREATER THAN 9 SQ.FT. 7.2 BOTTOM EDGE LESS THAN 18" ABOVE THE FLOOR.
- 7.3 TOP EDGE GREATER THAN 36" ABOVE THE FLOOR. 7.4 ONE OR MORE WALKING SURFACES WITHIN 36" HORIZONTALLY OF THE GLAZING.


EXCEPTIONS: (SEE CODE FOR ADDITIONAL EXCEPTIONS)

- 2) DECORATIVE GLASS IN ITEMS 1, 6, AND 7.
- CONTINUOUS BACKING SUPPORT.
- 8) MIRRORS AND OTHER GLASS PANELS MOUNTED OR HUNG ON A SURFACE THAT PROVIDES A

- CONTRACTOR TO COORDINATE DOOR AND WINDOW STYLE AND PANEL TYPE WITH OWNER.
- 2. ALL SIZING INFORMATION IS FOR GENERAL DESIGN ONLY. CONTRACTOR TO SELECT EXACT WINDOW SIZES FROM CONTRACTOR'S STANDARD DOOR AND WINDOW MANUFACTURER'S OPTIONS.
- 3. FRAME SIZE AND ROUGH OPENING SIZE PER MANUFACTURER'S PRODUCT DATA.
- 4. PROVIDE SAFETY GLAZING WHERE REQUIRED. SEE 2007 FLORIDA BUILDING CODE R308.4.
- 5. CONTRACTOR TO SUPPLY SPECIFIC DOOR AND WINDOW INFORMATION AS REQUIRED BY LOCAL AUTHORITIES FOR PERMITTING PROCESS.
- 5. DOORS AND WINDOWS SHALL MEET ALL APPLICABLE CODES INCLUDING THOSE REGARDING HIGH IMPACT RATINGS.
- . PROVIDE PANEL ANCHORS, REINFORCING, AND EXPANSION STRIPS FOR GLASS BLOCK AS REQUIRED BY PRODUCT MANUFACTURER AND BY CODE.
- 8. ALL WOOD TRIM WORK PER CONTRACTOR'S STANDARD CONSTRUCTION AND PER ALLOWANCE.
- 9. SEE FLOOR PLAN FOR DOOR SWING.







W003

LOCATIONS: LIVING ROOM, BEDROOM

TYPE: DOUBLE HUNG

GLAZING: DOUBLE PANE

COATINGS: LOW-E

GRILLS: BETWEEN GLASS

QTY: 2

W001

LOCATIONS: GARAGE TYPE: DOUBLE HUNG GLAZING: DOUBLE PANE COATINGS: LOW-E GRILLS: BETWEEN GLASS

-2'-8"→

LOCATIONS: TYPICAL INTERIOR DOOR

TYPE: HOLLOW CORE INTERIOR SWING DOOR

QTY: 2


LOCATIONS: LIVING ROOM, KITCHEN TYPE: DOUBLE HUNG GLAZING: DOUBLE PANE COATINGS: LOW-E GRILLS: BETWEEN GLASS

W002


QTY: 2

-2'-8"-

PD01 LOCATIONS: BATHROOM



TYPE: HOLLOW CORE POCKET DOOR




LOCATIONS: BEDROOM TYPE: HOLLOW CORE DOUBLE BIFOLD


-3'-0"- ED01

LOCATIONS: TYPICAL EXTERIOR TYPE: INSULATED EXTERIOR SWING DOOR

QTY: 2




LOCATIONS: GARAGE INTERIOR TYPE: PER 2007 FRC R309.1



SGD1 LOCATIONS: BEDROOM SLIDING GLASS DOOR GLAZING: DOUBLE PANE COATINGS: LOW-E GRILLS: BETWEEN GLASS

QTY: 1



GD01

LOCATIONS: GARAGE TYPE: OVERHEAD

SCALE: 1/4"=1'-0"

-ARCHITECT -

WARREN E. BARRY

FLORIDA ARCHITECT, LICENSE #AR93495

www.WEBarryDesigns.com

SIGNITURE:

THE DRAWINGS CONTAINED WITHIN THIS

SET OF DOCUMENTS ARE INTENDED FOR

THE ONE TIME USE IN REFERENCE TO THE PROJECT LISTED ABOVE ONLY, ANY

UTILIZATION OF THE DOCUMENTS OR ANY

THE DRAWINGS CONTAINED WITHIN THIS

SET OF DOCUMENTS ARE INTENDED FOR

CONTRACTOR'S STANDARD CONSTRUCTION.

W.E.B. DESIGNS IS RESPONSIBLE ONLY

COORDINATION, AND DEPICTION OF THE GENERAL DESIGN. THE CONTRACTOR IS

FOR THE ACCURATE REPRESENTATION,

RESPONSIBLE AND LIABLE FOR THE

SELECTION OF BOTH MATERIALS AND

MOISTURE PROTECTION, PROPER

PRODUCTS ACCORDING TO

AND THE UTILIZATION AND IMPLEMENTATION OF INDUSTRY

CONSTRUCTION PRIOR TO THE

NEW WORK. ACCEPTANCE BY

CONDITIONS.

PROJECT NO .:

REVISION DATES:

OPENING TYPES

APPLICATION AND INSTALLATION OF

MANUFACTURER'S RECOMMENDATIONS,

STANDARDS. THE CONTRACTOR IS ALSO RESPONSIBLE FOR FIELD VERIFICATION OF ALL DIMENSIONS OF PREEXISTING

FABRICATION OR COMMENCEMENT OF ANY

AND AGREEMENT WITH THESE TERMS AND

CONSTRUCTION

DOCUMENTS FOR

CONTRACTOR'S

STANDARD

CONSTRUCTION

DATE CHECKED: DECEMBER 03, 2009

EXTERIOR WALL SECTION,

CONTRACTOR OF THESE DRAWINGS FOR CONSTRUCTION IS ACKNOWLEDGMENT TO

METHODS OF CONSTRUCTION IN REGARDS

TO BUT NOT LIMITED TO THERMAL AND

UNAUTHORIZED COPYING OF OR

INFRINGEMENT OF INTELLECTUAL

LIABILITY DISCLAIMER:

PART WITHIN IS COPYRIGHT

PROPERTY.

DATE: 12/03/09

(352) 472-2600 (352) 472-2611

D.B.A.: W.E.B. DESIGNS

4409 NW 186TH STREET

NEWBERRY, FLORIDA 32669

COPYRIGHT ©

09024

DECEMBER 03, 2009

SCALE: NOT TO SCALE \ A5.10