



ENGINEERING & TESTING LABORATORY

P.O. Box 1625, Lake City, FL 32056-1625
7540 103rd St. Suite 215 • Jacksonville, FL 32210

Lake City • (386) 755-3633
Fax • (386) 752-5456

Jacksonville • (904) 381-8901
Fax • (904) 381-8902

JOB NO.:
DATE TESTED: 6-27-22

REPORT OF IN-PLACE DENSITY TEST

ASTM METHOD: X (D-2922) Nuclear _____ (D-2937) Drive Cylinder _____ Other _____

PROJECT: 2488 Tommy Liles

CLIENT: _____

GENERAL CONTRACTOR: SAC EARTHWORK CONTRACTOR:

SOIL USE (SEE NOTE): _____ SPECIFICATION REQUIREMENTS: _____

TECHNICIAN: Kyo

MODIFIED (ASTM D-1557): X STANDARD (ASTM D-698):

[illegible]

REMARKS: _____

PROCTOR NO.	SOIL DESCRIPTION	PROCTOR VALUE	OPT. MOIST.
1		103.9	14.2

NOTE: 1. Building Fill 2. Trench Backfill 3. Base Course 4. Subbase/Stabilized Subgrade 5. Embankment 6. Subgrade/Natural Soil 7. Other
The test results presented in this report are specific only to the samples tested at the time of testing. The tests were performed in accordance with generally accepted methods and standards. Since material conditions can vary between test location and change with time, sound judgement should be exercised with regard to the use and interpretation of the data.