

ENERGY PERFORMANCE LEVEL (EPL) DISPLAY CARD

ESTIMATED ENERGY PERFORMANCE INDEX* = 80

The lower the EnergyPerformance Index, the more efficient the home.

, Lake Ccity, FL,

1. New construction or existing	New (From Plans)		9. Wall Types	Insulation	Area
2. Single family or multiple family	Single-family		a. Frame - Wood, Exterior	R=13.0	1446.00 ft ²
3. Number of units, if multiple family	1		b. Frame - Wood, Adjacent	R=13.0	204.00 ft ²
4. Number of Bedrooms	3		c. N/A	R=	ft ²
5. Is this a worst case?	No		d. N/A	R=	ft ²
6. Conditioned floor area (ft ²)	1621		10. Ceiling Types	Insulation	Area
7. Windows**	Description	Area	a. Under Attic (Vented)	R=30.0	1621.00 ft ²
a. U-Factor:	Dbl, U=0.36	234.33 ft ²	b. Knee Wall (Vented)	R=30.0	100.00 ft ²
SHGC:	SHGC=0.28		c. N/A	R=	ft ²
b. U-Factor:	N/A	ft ²	11. Ducts	R	ft ²
SHGC:			a. Sup: Attic, Ret: Attic, AH: Main	6	324.2
c. U-Factor:	N/A	ft ²	12. Cooling systems	kBtu/hr	Efficiency
SHGC:			a. Central Unit	34.4	SEER:14.50
d. U-Factor:	N/A	ft ²	13. Heating systems	kBtu/hr	Efficiency
SHGC:			a. Electric Heat Pump	34.6	HSPF:8.50
Area Weighted Average Overhang Depth:	2.000 ft.		14. Hot water systems		
Area Weighted Average SHGC:	0.280		a. Electric	Cap: 50 gallons	EF: 0.92
8. Floor Types	Insulation	Area	b. Conservation features		
a. Slab-On-Grade Edge Insulation	R=0.0	1621.00 ft ²	None		
b. N/A	R=	ft ²	15. Credits		CF, Pstat
c. N/A	R=	ft ²			

I certify that this home has complied with the Florida Energy Efficiency Code for Building Construction through the above energy saving features which will be installed (or exceeded) in this home before final inspection. Otherwise, a new EPL Display Card will be completed based on installed Code compliant features.

Builder Signature: Shirley Crayford

Date: 4/15/2013

Address of New Home: 171 Asheville Way

City/FL Zip: Lake City, FL



*Note: This is not a Building Energy Rating. If your Index is below 70, your home may qualify for energy efficient mortgage (EEM) incentives if you obtain a Florida EnergyGauge Rating. Contact the EnergyGauge Hotline at (321) 638-1492 or see the EnergyGauge web site at energygauge.com for information and a list of certified Raters. For information about the Florida Building Code, Energy Conservation, contact the Florida Building Commission's support staff.

**Label required by Section 303.1.3 of the Florida Building Code, Energy Conservation, if not DEFAULT

EnergyGauge® USA - FlaRes2010 Section 405.4.1 Compliant Software




FLORIDA ENERGY EFFICIENCY CODE FOR BUILDING CONSTRUCTION

Florida Department of Business and Professional Regulation - Residential Performance Method

Project Name: SCCI Lot 4 Hickory Cove Street: City, State, Zip: Lake City, FL, Owner: SCCI Design Location: FL, Gainesville	Builder Name: Stanley Crawford Construction Permit Office: Permit Number: Jurisdiction:
--	--

<table style="width: 100%;"> <tr> <td style="width: 60%;">1. New construction or existing</td> <td style="width: 40%;">New (From Plans)</td> </tr> <tr> <td>2. Single family or multiple family</td> <td>Single-family</td> </tr> <tr> <td>3. Number of units, if multiple family</td> <td>1</td> </tr> <tr> <td>4. Number of Bedrooms</td> <td>3</td> </tr> <tr> <td>5. Is this a worst case?</td> <td>No</td> </tr> <tr> <td>6. Conditioned floor area above grade (ft²)</td> <td>1621</td> </tr> <tr> <td> Conditioned floor area below grade (ft²)</td> <td>0</td> </tr> <tr> <td>7. Windows (234.3 sqft.)</td> <td> <table style="width: 100%;"> <tr> <th style="width: 40%;">Description</th> <th style="width: 60%;">Area</th> </tr> <tr> <td>a. U-Factor: Dbl, U=0.36</td> <td>234.33 ft²</td> </tr> <tr> <td> SHGC: SHGC=0.28</td> <td></td> </tr> <tr> <td>b. U-Factor: N/A</td> <td>ft²</td> </tr> <tr> <td> SHGC:</td> <td></td> </tr> <tr> <td>c. U-Factor: N/A</td> <td>ft²</td> </tr> <tr> <td> SHGC:</td> <td></td> </tr> <tr> <td>d. U-Factor: N/A</td> <td>ft²</td> </tr> <tr> <td> SHGC:</td> <td></td> </tr> <tr> <td>Area Weighted Average Overhang Depth:</td> <td>2.000 ft.</td> </tr> <tr> <td>Area Weighted Average SHGC:</td> <td>0.280</td> </tr> </table> </td> </tr> <tr> <td>8. Floor Types (1621.0 sqft.)</td> <td> <table style="width: 100%;"> <tr> <th style="width: 40%;">Insulation</th> <th style="width: 60%;">Area</th> </tr> <tr> <td>a. Slab-On-Grade Edge Insulation</td> <td>R=0.0 1621.00 ft²</td> </tr> <tr> <td>b. N/A</td> <td>R= ft²</td> </tr> <tr> <td>c. N/A</td> <td>R= ft²</td> </tr> </table> </td> </tr> </table>	1. New construction or existing	New (From Plans)	2. Single family or multiple family	Single-family	3. Number of units, if multiple family	1	4. Number of Bedrooms	3	5. Is this a worst case?	No	6. Conditioned floor area above grade (ft²)	1621	Conditioned floor area below grade (ft²)	0	7. Windows (234.3 sqft.)	<table style="width: 100%;"> <tr> <th style="width: 40%;">Description</th> <th style="width: 60%;">Area</th> </tr> <tr> <td>a. U-Factor: Dbl, U=0.36</td> <td>234.33 ft²</td> </tr> <tr> <td> SHGC: SHGC=0.28</td> <td></td> </tr> <tr> <td>b. U-Factor: N/A</td> <td>ft²</td> </tr> <tr> <td> SHGC:</td> <td></td> </tr> <tr> <td>c. U-Factor: N/A</td> <td>ft²</td> </tr> <tr> <td> SHGC:</td> <td></td> </tr> <tr> <td>d. U-Factor: N/A</td> <td>ft²</td> </tr> <tr> <td> SHGC:</td> <td></td> </tr> <tr> <td>Area Weighted Average Overhang Depth:</td> <td>2.000 ft.</td> </tr> <tr> <td>Area Weighted Average SHGC:</td> <td>0.280</td> </tr> </table>	Description	Area	a. U-Factor: Dbl, U=0.36	234.33 ft²	SHGC: SHGC=0.28		b. U-Factor: N/A	ft²	SHGC:		c. U-Factor: N/A	ft²	SHGC:		d. U-Factor: N/A	ft²	SHGC:		Area Weighted Average Overhang Depth:	2.000 ft.	Area Weighted Average SHGC:	0.280	8. Floor Types (1621.0 sqft.)	<table style="width: 100%;"> <tr> <th style="width: 40%;">Insulation</th> <th style="width: 60%;">Area</th> </tr> <tr> <td>a. Slab-On-Grade Edge Insulation</td> <td>R=0.0 1621.00 ft²</td> </tr> <tr> <td>b. N/A</td> <td>R= ft²</td> </tr> <tr> <td>c. N/A</td> <td>R= ft²</td> </tr> </table>	Insulation	Area	a. Slab-On-Grade Edge Insulation	R=0.0 1621.00 ft²	b. N/A	R= ft²	c. N/A	R= ft²	<table style="width: 100%;"> <tr> <td style="width: 60%;">9. Wall Types (1650.0 sqft.)</td> <td style="width: 40%;">Insulation Area</td> </tr> <tr> <td>a. Frame - Wood, Exterior</td> <td>R=13.0 1446.00 ft²</td> </tr> <tr> <td>b. Frame - Wood, Adjacent</td> <td>R=13.0 204.00 ft²</td> </tr> <tr> <td>c. N/A</td> <td>R= ft²</td> </tr> <tr> <td>d. N/A</td> <td>R= ft²</td> </tr> <tr> <td>10. Ceiling Types (1721.0 sqft.)</td> <td>Insulation Area</td> </tr> <tr> <td>a. Under Attic (Vented)</td> <td>R=30.0 1621.00 ft²</td> </tr> <tr> <td>b. Knee Wall (Vented)</td> <td>R=30.0 100.00 ft²</td> </tr> <tr> <td>c. N/A</td> <td>R= ft²</td> </tr> <tr> <td>11. Ducts</td> <td>R ft²</td> </tr> <tr> <td>a. Sup: Attic, Ret: Attic, AH: Main</td> <td>6 324.2</td> </tr> <tr> <td>12. Cooling systems</td> <td>kBtu/hr Efficiency</td> </tr> <tr> <td>a. Central Unit</td> <td>34.4 SEER:14.50</td> </tr> <tr> <td>13. Heating systems</td> <td>kBtu/hr Efficiency</td> </tr> <tr> <td>a. Electric Heat Pump</td> <td>34.6 HSPF:8.50</td> </tr> <tr> <td>14. Hot water systems</td> <td></td> </tr> <tr> <td>a. Electric</td> <td>Cap: 50 gallons</td> </tr> <tr> <td>b. Conservation features</td> <td>EF: 0.920</td> </tr> <tr> <td>15. Credits</td> <td>CF, Pstat</td> </tr> </table>	9. Wall Types (1650.0 sqft.)	Insulation Area	a. Frame - Wood, Exterior	R=13.0 1446.00 ft²	b. Frame - Wood, Adjacent	R=13.0 204.00 ft²	c. N/A	R= ft²	d. N/A	R= ft²	10. Ceiling Types (1721.0 sqft.)	Insulation Area	a. Under Attic (Vented)	R=30.0 1621.00 ft²	b. Knee Wall (Vented)	R=30.0 100.00 ft²	c. N/A	R= ft²	11. Ducts	R ft²	a. Sup: Attic, Ret: Attic, AH: Main	6 324.2	12. Cooling systems	kBtu/hr Efficiency	a. Central Unit	34.4 SEER:14.50	13. Heating systems	kBtu/hr Efficiency	a. Electric Heat Pump	34.6 HSPF:8.50	14. Hot water systems		a. Electric	Cap: 50 gallons	b. Conservation features	EF: 0.920	15. Credits	CF, Pstat
1. New construction or existing	New (From Plans)																																																																																						
2. Single family or multiple family	Single-family																																																																																						
3. Number of units, if multiple family	1																																																																																						
4. Number of Bedrooms	3																																																																																						
5. Is this a worst case?	No																																																																																						
6. Conditioned floor area above grade (ft²)	1621																																																																																						
Conditioned floor area below grade (ft²)	0																																																																																						
7. Windows (234.3 sqft.)	<table style="width: 100%;"> <tr> <th style="width: 40%;">Description</th> <th style="width: 60%;">Area</th> </tr> <tr> <td>a. U-Factor: Dbl, U=0.36</td> <td>234.33 ft²</td> </tr> <tr> <td> SHGC: SHGC=0.28</td> <td></td> </tr> <tr> <td>b. U-Factor: N/A</td> <td>ft²</td> </tr> <tr> <td> SHGC:</td> <td></td> </tr> <tr> <td>c. U-Factor: N/A</td> <td>ft²</td> </tr> <tr> <td> SHGC:</td> <td></td> </tr> <tr> <td>d. U-Factor: N/A</td> <td>ft²</td> </tr> <tr> <td> SHGC:</td> <td></td> </tr> <tr> <td>Area Weighted Average Overhang Depth:</td> <td>2.000 ft.</td> </tr> <tr> <td>Area Weighted Average SHGC:</td> <td>0.280</td> </tr> </table>	Description	Area	a. U-Factor: Dbl, U=0.36	234.33 ft²	SHGC: SHGC=0.28		b. U-Factor: N/A	ft²	SHGC:		c. U-Factor: N/A	ft²	SHGC:		d. U-Factor: N/A	ft²	SHGC:		Area Weighted Average Overhang Depth:	2.000 ft.	Area Weighted Average SHGC:	0.280																																																																
Description	Area																																																																																						
a. U-Factor: Dbl, U=0.36	234.33 ft²																																																																																						
SHGC: SHGC=0.28																																																																																							
b. U-Factor: N/A	ft²																																																																																						
SHGC:																																																																																							
c. U-Factor: N/A	ft²																																																																																						
SHGC:																																																																																							
d. U-Factor: N/A	ft²																																																																																						
SHGC:																																																																																							
Area Weighted Average Overhang Depth:	2.000 ft.																																																																																						
Area Weighted Average SHGC:	0.280																																																																																						
8. Floor Types (1621.0 sqft.)	<table style="width: 100%;"> <tr> <th style="width: 40%;">Insulation</th> <th style="width: 60%;">Area</th> </tr> <tr> <td>a. Slab-On-Grade Edge Insulation</td> <td>R=0.0 1621.00 ft²</td> </tr> <tr> <td>b. N/A</td> <td>R= ft²</td> </tr> <tr> <td>c. N/A</td> <td>R= ft²</td> </tr> </table>	Insulation	Area	a. Slab-On-Grade Edge Insulation	R=0.0 1621.00 ft²	b. N/A	R= ft²	c. N/A	R= ft²																																																																														
Insulation	Area																																																																																						
a. Slab-On-Grade Edge Insulation	R=0.0 1621.00 ft²																																																																																						
b. N/A	R= ft²																																																																																						
c. N/A	R= ft²																																																																																						
9. Wall Types (1650.0 sqft.)	Insulation Area																																																																																						
a. Frame - Wood, Exterior	R=13.0 1446.00 ft²																																																																																						
b. Frame - Wood, Adjacent	R=13.0 204.00 ft²																																																																																						
c. N/A	R= ft²																																																																																						
d. N/A	R= ft²																																																																																						
10. Ceiling Types (1721.0 sqft.)	Insulation Area																																																																																						
a. Under Attic (Vented)	R=30.0 1621.00 ft²																																																																																						
b. Knee Wall (Vented)	R=30.0 100.00 ft²																																																																																						
c. N/A	R= ft²																																																																																						
11. Ducts	R ft²																																																																																						
a. Sup: Attic, Ret: Attic, AH: Main	6 324.2																																																																																						
12. Cooling systems	kBtu/hr Efficiency																																																																																						
a. Central Unit	34.4 SEER:14.50																																																																																						
13. Heating systems	kBtu/hr Efficiency																																																																																						
a. Electric Heat Pump	34.6 HSPF:8.50																																																																																						
14. Hot water systems																																																																																							
a. Electric	Cap: 50 gallons																																																																																						
b. Conservation features	EF: 0.920																																																																																						
15. Credits	CF, Pstat																																																																																						

Glass/Floor Area: 0.145	Total Proposed Modified Loads: 30.08	PASS
	Total Standard Reference Loads: 37.56	

<p>I hereby certify that the plans and specifications covered by this calculation are in compliance with the Florida Energy Code.</p> <p>PREPARED BY: <u>Stanley Crawford</u></p> <p>DATE: <u>4/15/2013</u></p> <p>I hereby certify that this building, as designed, is in compliance with the Florida Energy Code.</p> <p>OWNER/AGENT: <u>Stanley Crawford</u></p> <p>DATE: <u>4/15/2013</u></p>	<p>Review of the plans and specifications covered by this calculation indicates compliance with the Florida Energy Code. Before construction is completed this building will be inspected for compliance with Section 553.908 Florida Statutes.</p> <div style="text-align: center;">  </div> <p>BUILDING OFFICIAL: _____</p> <p>DATE: _____</p>
---	---

- Compliance requires completion of a Florida Air Barrier and Insulation Inspection Checklist

PROJECT

Title: SCCI Lot 4 Hickory Cove	Bedrooms: 3	Address Type: Lot Information
Building Type: User	Conditioned Area: 1621	Lot #: 4
Owner: SCCI	Total Stories: 1	Block/SubDivision: Hickory Cove
# of Units: 1	Worst Case: No	PlatBook:
Builder Name: Stanley Crawford Constructio	Rotate Angle: 0	Street:
Permit Office:	Cross Ventilation:	County: Columbia
Jurisdiction:	Whole House Fan:	City, State, Zip: Lake Ccity , FL ,
Family Type: Single-family		
New/Existing: New (From Plans)		
Comment:		

CLIMATE

✓	Design Location	TMY Site	IECC Zone	Design Temp 97.5 %	Design Temp 2.5 %	Int Design Temp Winter	Int Design Temp Summer	Heating Degree Days	Design Moisture	Daily Temp Range
_____	FL, Gainesville	FL_GAINESVILLE_REGI	2	32	92	70	75	1305.5	51	Medium

BLOCKS

Number	Name	Area	Volume
1	Block1	1621	12968

SPACES

Number	Name	Area	Volume	Kitchen	Occupants	Bedrooms	Infil ID	Finished	Cooled	Heated
1	Main	1621	12968	Yes	1	3	1	Yes	Yes	Yes

FLOORS

✓	#	Floor Type	Space	Perimeter	R-Value	Area	Tile	Wood	Carpet
_____	1	Slab-On-Grade Edge Insulatio	Main	195 ft	0	1621 ft²	----	0	0 1

ROOF

✓	#	Type	Materials	Roof Area	Gable Area	Roof Color	Solar Absor.	SA Tested	Emitt	Emitt Tested	Deck Insul.	Pitch (deg)
_____	1	Hip	Composition shingles	1813 ft²	0 ft²	Medium	0.96	No	0.9	No	0	26.6

ATTIC

✓	#	Type	Ventilation	Vent Ratio (1 in)	Area	RBS	IRCC
_____	1	Full attic	Vented	300	1621 ft²	N	N

CEILING

✓	#	Ceiling Type	Space	R-Value	Area	Framing Frac	Truss Type
_____	1	Knee Wall (Vented)	Main	30	100 ft²	0.11	Wood
_____	2	Under Attic (Vented)	Main	30	1621 ft²	0.11	Wood

WALLS

✓ #	Ornt	Adjacent To	Wall Type	Space	Cavity R-Value	Width Ft	In	Height Ft	In	Area	Sheathing R-Value	Framing Fraction	Solar Absor.	Below Grade%
1	W	Garage	Frame - Wood	Main	13	25	6	8		204.0 ft²		0.23	0.75	0
2	W	Exterior	Frame - Wood	Main	13	44	4	10		443.3 ft²		0.23	0.75	0
3	N	Exterior	Frame - Wood	Main	13	31	4	8		250.7 ft²		0.23	0.75	0
4	E	Exterior	Frame - Wood	Main	13	72	4	8		578.7 ft²		0.23	0.75	0
5	S	Exterior	Frame - Wood	Main	13	21	8	8		173.3 ft²		0.23	0.75	0

DOORS

✓ #	Ornt	Door Type	Space	Storms	U-Value	Width Ft	In	Height Ft	In	Area
1	W	Insulated	Main	None	0.460000	3		6	8	20 ft²
2	W	Insulated	Main	None	0.460000	3		6	8	20 ft²
3	E	Insulated	Main	None	0.460000	3		8		24 ft²

WINDOWS

Orientation shown is the entered, Proposed orientation.

✓ #	Ornt	Wall ID	Frame	Panes	NFRC	U-Factor	SHGC	Area	Overhang Depth	Separation	Int Shade	Screening
1	W	2	Vinyl	Low-E Double	Yes	0.36	0.28	54.0 ft²	2 ft 0 in	5 ft 0 in	Drapes/blinds	None
2	W	2	Vinyl	Low-E Double	Yes	0.36	0.28	30.0 ft²	2 ft 0 in	5 ft 0 in	Drapes/blinds	None
3	W	2	Vinyl	Low-E Double	Yes	0.36	0.28	13.3 ft²	2 ft 0 in	8 ft 0 in	Drapes/blinds	None
4	N	3	Vinyl	Low-E Double	Yes	0.36	0.28	4.0 ft²	2 ft 0 in	5 ft 0 in	Drapes/blinds	None
5	E	4	Vinyl	Low-E Double	Yes	0.36	0.28	60.0 ft²	2 ft 0 in	5 ft 0 in	Drapes/blinds	None
6	E	4	Vinyl	Low-E Double	Yes	0.36	0.28	36.0 ft²	2 ft 0 in	5 ft 0 in	Drapes/blinds	None
7	E	4	Vinyl	Low-E Double	Yes	0.36	0.28	15.0 ft²	2 ft 0 in	5 ft 0 in	Drapes/blinds	None
8	S	5	Vinyl	Low-E Double	Yes	0.36	0.28	6.0 ft²	2 ft 0 in	5 ft 0 in	Drapes/blinds	None
9	S	5	Vinyl	Low-E Double	Yes	0.36	0.28	16.0 ft²	2 ft 0 in	5 ft 0 in	Drapes/blinds	None

GARAGE

✓ #	Floor Area	Ceiling Area	Exposed Wall Perimeter	Avg. Wall Height	Exposed Wall Insulation
1	484 ft²	484 ft²	61 ft	8 ft	1

INFILTRATION

#	Scope	Method	SLA	CFM 50	ELA	EqLA	ACH	ACH 50
1	Wholehouse	Best Guess	0.000500	2125.9	116.71	219.49	0.3850	9.8363

HEATING SYSTEM

✓ #	System Type	Subtype	Efficiency	Capacity	Block	Ducts
(Invalid)	Electric Heat Pump	None	HSPF: 8.5	34.6 kBtu/hr	1	sys#1

COOLING SYSTEM

✓	#	System Type	Subtype	Efficiency	Capacity	Air Flow	SHR	Block	Ducts
_____	(Invalid)	Central Unit	None	SEER: 14.5	34.4 kBtu/hr	1032 cfm	0.75	1	sys#1

HOT WATER SYSTEM

✓	#	System Type	SubType	Location	EF	Cap	Use	SetPnt	Conservation
_____	1	Electric	None	Garage	0.92	50 gal	60 gal	120 deg	None

SOLAR HOT WATER SYSTEM

✓	FSEC	Company Name	System Model #	Collector Model #	Collector Area	Storage Volume	FEF
_____	None	None			ft²		

DUCTS

✓	#	Location	Supply R-Value	Area	Location	Return Area	Leakage Type	Air Handler	CFM25	CFM25 OUT	QN	RLF	HVAC #
_____	(Invalid)	Attic	6	324.2 ft	Attic	81.05 ft	Default Leakage	Main	(invalid) c	(Default)			1 1

TEMPERATURES

Programable Thermostat: Y				Ceiling Fans:																				
Cooling	<input checked="" type="checkbox"/>	Jan	<input checked="" type="checkbox"/>	Feb	<input checked="" type="checkbox"/>	Mar	<input type="checkbox"/>	Apr	<input type="checkbox"/>	May	<input checked="" type="checkbox"/>	Jun	<input checked="" type="checkbox"/>	Jul	<input checked="" type="checkbox"/>	Aug	<input checked="" type="checkbox"/>	Sep	<input type="checkbox"/>	Oct	<input checked="" type="checkbox"/>	Nov	<input checked="" type="checkbox"/>	Dec
Heating	<input checked="" type="checkbox"/>	Jan	<input checked="" type="checkbox"/>	Feb	<input checked="" type="checkbox"/>	Mar	<input type="checkbox"/>	Apr	<input type="checkbox"/>	May	<input checked="" type="checkbox"/>	Jun	<input checked="" type="checkbox"/>	Jul	<input checked="" type="checkbox"/>	Aug	<input checked="" type="checkbox"/>	Sep	<input type="checkbox"/>	Oct	<input checked="" type="checkbox"/>	Nov	<input checked="" type="checkbox"/>	Dec
Venting	<input checked="" type="checkbox"/>	Jan	<input checked="" type="checkbox"/>	Feb	<input checked="" type="checkbox"/>	Mar	<input type="checkbox"/>	Apr	<input type="checkbox"/>	May	<input checked="" type="checkbox"/>	Jun	<input checked="" type="checkbox"/>	Jul	<input checked="" type="checkbox"/>	Aug	<input checked="" type="checkbox"/>	Sep	<input type="checkbox"/>	Oct	<input checked="" type="checkbox"/>	Nov	<input checked="" type="checkbox"/>	Dec
Thermostat Schedule: HERS 2006 Reference				Hours																				
Schedule Type		1	2	3	4	5	6	7	8	9	10	11	12											
Cooling (WD)	AM	78	78	78	78	78	78	78	78	78	78	78	78											
	PM	80	80	78	78	78	78	78	78	80	80	80	80											
Cooling (WEH)	AM	78	78	78	78	78	78	78	78	78	78	78	78											
	PM	78	78	78	78	78	78	78	78	78	78	78	78											
Heating (WD)	AM	66	66	66	66	66	68	68	68	68	68	68	68											
	PM	68	68	68	68	68	68	68	68	68	68	66	66											
Heating (WEH)	AM	66	66	66	66	66	68	68	68	68	68	68	68											
	PM	68	68	68	68	68	68	68	68	68	68	66	66											

Florida Code Compliance Checklist

Florida Department of Business and Professional Regulations
Residential Whole Building Performance Method

ADDRESS:

Lake Ccity, FL,

PERMIT #:

MANDATORY REQUIREMENTS SUMMARY - See individual code sections for full details.

COMPONENT	SECTION	SUMMARY OF REQUIREMENT(S)	CHECK
Air leakage	402.4	To be caulked, gasketed, weatherstripped or otherwise sealed. Recessed lighting IC-rated as meeting ASTM E 283. Windows and doors = 0.30 cfm/sq.ft. Testing or visual inspection required. Fireplaces: gasketed doors & outdoor combustion air. Must complete envelope leakage report or visually verify Table 402.4.2.	
Thermostat & controls	403.1	At least one thermostat shall be provided for each separate heating and cooling system. Where forced-air furnace is primary system, programmable thermostat is required. Heat pumps with supplemental electric heat must prevent supplemental heat when compressor can meet the load.	
Ducts	403.2.2	All ducts, air handlers, filter boxes and building cavities which form the primary air containment passageways for air distribution systems shall be considered ducts or plenum chambers, shall be constructed and sealed in accordance with Section 503.2.7.2 of this code.	
	403.3.3	Building framing cavities shall not be used as supply ducts.	
Water heaters	403.4	Heat trap required for vertical pipe risers. Comply with efficiencies in Table 403.4.3.2. Provide switch or clearly marked circuit breaker (electric) or shutoff (gas). Circulating system pipes insulated to = R-2 + accessible manual OFF switch.	
Mechanical ventilation	403.5	Homes designed to operate at positive pressure or with mechanical ventilation systems shall not exceed the minimum ASHRAE 62 level. No make-up air from attics, crawlspaces, garages or outdoors adjacent to pools or spas.	
Swimming Pools & Spas	403.9	Pool pumps and pool pump motors with a total horsepower (HP) of = 1 HP shall have the capability of operating at two or more speeds. Spas and heated pools must have vapor-retardant covers or a liquid cover or other means proven to reduce heat loss except if 70% of heat from site-recovered energy. Off/timer switch required. Gas heaters minimum thermal efficiency=78% (82% after 4/16/13). Heat pump pool heaters minimum COP= 4.0.	
Cooling/heating equipment	403.6	Sizing calculation performed & attached. Minimum efficiencies per Tables 503.2.3. Equipment efficiency verification required. Special occasion cooling or heating capacity requires separate system or variable capacity system. Electric heat >10kW must be divided into two or more stages.	
Ceilings/knee walls	405.2.1	R-19 space permitting.	