

8 FT

DUAL PITCH 18" O.H.

REFER TO HIB 41 (RECOMMENDATIONS FOR HANDLING INSTALLATION AND TEMPORARY BRACING.) REFER TO ENGINEERED DRAWINGS FOR PERMANENT BRACING REQUIRED

- () ALL TRUSSES (INCLUDING TRUSSES UNDER VALLEY FRAMING) MUST BE COMPLETELY DECKED OR REFER TO DETAIL V05 FOR ALTERNATE BRACING REQUIREMENTS.
- () ALL VALETS ARE TO BE CONVENTIONALLY FRAMED BY BUILDER
- () ALL TRUSSES ARE DESIGNED FOR 2.0 c MAXIMUM SPACING, UNLESS OTHERWISE NOTED
- () ALL WALLS SHOWN ON PLACEMENT PLAN ARE CONSIDERED TO BE LOAD BEARING, UNLESS OTHERWISE NOTED
- () S742 TRUSSES MUST BE INSTALLED WITH THE TOP BEING UP
- () ALL ROOF TRUSSES HANGERS TO BE SHAPSON H836 UNLESS OTHERWISE NOTED
- () FLOOR TRUSSES HANGERS TO BE SHAPSON THA422 UNLESS OTHERWISE NOTED
- () BEAMA/ADVERT LUTER (HD9) TO BE FURNISHED BY BUILDER

THIS LAYOUT IS THE SOLE SOURCE FOR FURNICATION OF TDS555 AND VOIDS ALL PREVIOUS ARCHITECTURAL OR OTHER DOWNS LAYOUTS. REVIEW AND APPROVAL OF THIS LAYOUT MUST BE RECEIVED BEFORE ANY TDS555 WILL BE BUILT. VERIFY ALL CONDITIONS TO INSURE AGAINST CHANGES THAT WILL RESULT IN EXTRA CHARGES TO YOU.

Prepared by: _____ Date: _____



Jacksonville
PHONE 904-772 6100 FAX 904-772-1973

PHONE 904-772 6100 FAX 904-772-1973

Lake City

PHONE 904-755-6894 FAX 904-755-7973

Sanford

PHONE 407-322 0059 FAX 407-322-5553

CHILD

DON REED CONSTRUCTION

6AL ADDRESS

RIGGS RESIDENCE

DEL REVISION

CD5	CD4	CD3	CD2	CD1	CD0
5	4	3	2	1	0

TE
SEARCHED
SERIAL