## **REQUIRED FOR WALK-IN OR PAPER SUBMITTALS**

Job Address: 386 S.W. TIMBERLAND CT. LAKE CITY, FLA. 32024
I ( <u>Print Name</u> ) <u>DARRIN SUMMER LIN</u> , as a Florida license Roofing Contractor or an Owner Builder, I understand to comply with the 2020 Florida Building Code 7 <sup>th</sup> Edition underlayment requirements, I must select an option for sealing the roof deck.
The options are summarized below
a self-adhering polymer-modified bitumen underlayment complying with ASTM D1970 applied over the entire roof.
a minimum 4-inch wide strip of selfadhering polymer-modified bitumen complying with ASTM D1970 or a minimum 3 ¾ - inch wide strip of selfadhering flexible flashing tape complying with AAMA 711, applied over all joints in the roof decking. A felt underlayment complying with ASTM D226 Type II, ASTM D4869 Type III or IV, or ASTM D6757, or a synthetic underlayment meeting the performance requirements specified, is required to be applied over the strips/tape over the entire roof.
two layers of felt underlayment comply ASTM 0226 Type II or ASTM D4869 Type III or IV, or two layers of a synthetic underlayment meeting the performance requirements specified, lapped and fastened as specified.
Other (explain)
Contractor/Owners Signature

## **FINAL INSPECTION & CERTIFICATE OF COMPLETION:**

This completed form and photographs must be uploaded to your permit via online at the Application