


FAIRBANKS

- BE A MIX DESIGN UTILIZING TYPE II PORTLAND CEMENT AND NORMAL WEIGHT AGGREGATES WITH 5-7% AIR ENTRAINMENT. NO FLY ASH WILL BE ALLOWED. MAXIMUM ALLOWABLE SLUMP SHALL BE 4 1/2". CONCRETE TO BE MECHANICALLY VIBRATED TO INSURE PROPER CONSOLIDATION.
- USE A MIX DESIGN WHICH WILL DEVELOP 4000 PSI STRENGTH IN 7 DAYS ON THE APPROACHES.
- 3. ALL REINFORCING TO BE ASTM A-615 GR 60 DEFORMED BARS. ALL BAR TO BE LOCATED AS SHOWN ON PLANS WITH ALL INTERSECTING BAR SECURELY TIED AND CHAIRED INTO POSITION. BEND BARS COLD. REMOVE SCALE, LOOSE FLAKEY RUST, DIRT AND OTHER COATING THAT WOULD IMPAIR BONDING.
- 4. ALL CONCRETE SURFACES SHALL BE FORMED WITH WOOD OR METAL FORMS USING APPROVED METHODS. NO CONCRETE VERTICAL SURFACE SHALL BE POURED AGAINST DIRT.

- 8. BOTTOM OF PIT SHOULD BE SUPPORTED ON NON-EXPANSIVE WELL DRAINED MATERIAL CAPABLE OF SAFELY SUPPORTING 1500 PSF WITH LESS THAN 3/4 INCH TOTAL SETTLEMENT.
- 9. ALL BACKFILL SHOULD BE PLACED IN 8 INCH LIFTS AND COMPACTED TO 95% OF MAXIMUM DENSITY PER ASTM 1557 OR APPROVED ALTERNATE.
- 10. SUITABLE CONDUIT FOR LOW VOLTAGE CONDUCTOR SHIELDED CABLE MUST PASS THRU THE PIT WALL AS INDICATED ON THIS DRAWING. CONDUIT MUST EXTEND BEYOND PIT WALL 2" MIN.
- 11. WORK FROM CENTER LINES WHEN ERECTING FORMS AND PLACING FOUNDATION EMBEDMENTS. PLACE EMBEDMENTS TO WITHIN +/-1/8" OF POSITIONS INDICATED ON DRAWINGS. (EMBEDMENT MUST BE PLACED WITHIN +/-1/8" OF TOTAL DIMENSIONS OF SCALE.)

5 C.A.T. SCALE CO. P.O. Box 639 4 Walcott, Iowa 52773 3 Shuttle Truck Stop 75 2 Lake City, FL 32024 PLAN - 5'-0" DEEP SCALE PIT DR. APPVD. SCALE REV. DATE REVISION DESCRIPTION TB REVISIONS NONE 1/2016 MTN



SECTION A-A

8/19/20 Michael Nugent 91CF4EC659214FA.. STATE OF

STATE OF

ORIDAR

ONAL ENGINEERING

This item has been digitally signed and sealed by Michael T Nugent on the date adjacent to the seal. Printed copies of this document are not considered signed and sealed and the signature must be verified on any electronic copies.


5					
4					
3					TITLE
2					l <u>-</u>
1					
REV.	DATE	REVISION DESCRIPTION	DR.	APPVD.	SCALE
REVISIONS					NONE


C.A.T. SCALE CO. P.O. Box 639 Walcott, Iowa 52773


Shuttle Truck Stop 75 Lake City, FL 32024

ELEVATION - 5'-0" DEEP SCALE PIT


FAIRBANKS CHK'D MTN







DETAIL - END WALL CHECKING



_DETAIL — SAFETY PIER

This item has been digitally signed and sealed by Michael T Nugent on the date adjacent to the seal. Printed copies of this document are not considered signed and sealed and the signature must be verified on any electronic copies.

-DocuSigned by: Michael Nugent -91CF4EC659214FA...

8/19/20

5					
4					
3					TITLE
2]
1] Г.
REV.	DATE	REVISION DESCRIPTION	DR.	APPVD.	SCALE
REVISIONS					


C.A.T. SCALE CO. P.O. Box 639 Walcott, Iowa 52773

Shuttle Truck Stop 75 Lake City, FL 32024


DETAILS - WALL CHECKING & SAFETY PIERS

FAIRBANKS

TB CHK'D MTN 1/2016




TYPICAL 20'-0" COPING 8 - REQ'D.



<u>TYPICAL END WALL COPING</u>
<u>2 — REQ'D.</u>

This item has been digitally signed and sealed by Michael T Nugent on the date adjacent to the seal. Printed copies of this document are not considered signed and sealed and the signature must be verified on any electronic copies.




-91CF4EC659214FA...

REINFORCING STEEL SCHEDULE - 5'-0" PIT

<u>MARK</u>	<u>QTY</u>	<u>DESCRIPTION</u>	<u>LENGTH</u>	_A_	<u>_B_</u>
B1 B2 B3	60 86 28	# 4 STRAIGHT # 4 STRAIGHT # 5 STRAIGHT	22'-6" 13'-10" 13'-10"		
B4a	12	# 6 BENT — DET A	15'-9"	2'-0"	11'-9"
B4b	12	# 6 BENT — DET A	16'-8"	2'-0"	12'-8"
B5	188	# 4 STRAIGHT	6'-6"		
B6	30	# 4 STRAIGHT	12'-2"		
В7	40	# 4 STRAIGHT	9'–10"		
B8	18	# 4 STIRRUPS — DET B	12'-8" <u>.</u>	0'-11"	5' –1"
В9	96	# 5 STRAIGHT	22'-6"		
B10	110	# 4 STIRRUPS — DET B	12'-0"	0'-7"	5'-1"
B11	32	# 4 BENT — DET E	8'-6"	0'–10"	3 ' -0"
B12	50	# 4 STRAIGHT	22'-6"		
*B13	40	# 4 STRAIGHT	4'-0"		
B14	8	# 5 TIES — DET B	14'-8"	4'-6"	2'-6"
B15	4	# 5 TIES — DET B	8'-8"	1'-6"	2'-6"
B16	8	# 5 TIES — DET B	9'-8"	2'-0"	2'-6"
B17	40	# 4 BENT — DET C	2'-10"	1'-0"	1'-10"
B18	72	# 6 BENT — DET C	3'-3"	1'-0"	2'-3"
B19	8	# 6 BENT — DET C	6'-2 "	1'-0"	5'-2"
B20	16	# 5 TIES — DET B	10'-4"	2'-8"	2'-2"
B21	6	# 5 HOOP — DET D	8'-3 "	(DIA.)	2'-6"
B22	8	# 6 STRAIGHT	10 ' –2"		
B23	128	# 4 BENT — DET C	5 ' -0"	2'-0"	3'-0"

*MK B13 IS SUPPLEMENTARY AND IS NOT PART OF THE SCALE PIT REBAR



NOTE:

ALL REINFORCING STEEL TO BE ASTM A615 GRADE 60 DEFORMED. ALL BENDING MUST BE COLD FORMED.

5						
4						
3					TITLE	
2						
1						(
REV.	DATE	REVISION DESCRIPTION	DR.	APPVD.	SCALE	_
					007.22	



C.A.T. SCALE CO. P.O. Box 639 Walcott, Iowa 52773

Walcott, Iowa 5277

Shuttle Truck Stop 75
Lake City, FL 32024

COPING DETAIL & REINFORCING STEEL DETAIL

FAIRBANKS

BANKS | REVISIONS

;

NONE CHK,D WLN

1/2016

6