

# Roof Replacement or Repair Application #72287

Thursday, July 24, 2025 3:44 PM



## Checklist:

___ Address	___ Application Submitted	
___ Drive/ROW	___ Zoning Review	___ Legal Lot of Record
___ Septic	___ Plans Reviewed	___ Flood Zone
___ Site Use Approved	___ Required Inspections Assigned	___ FDEP Needed
___ Docs Reviewed/Accepted	___ Invoiced	

**APPLICANT:** Daniel Dufresne

**PHONE:** (904) 423-0819

**ADDRESS:** 4590 CR 218 Middleburg, FL 32068

**OWNER:** ALLISON JAMES MICHAEL, ALLISON CHRISTY L

**PHONE:** (904) 423-0819

**ADDRESS:** 351 SW LIGHTWOOD PL FORT WHITE, FL 32038

**PARCEL ID:** 24-7S-16-04313-007

**SUBDIVISION:** RUM ISLAND WOODS

**LOT:** 5 **BLOCK:** **PHASE:** **UNIT:** **ACRES:** 4.00

CONTRACTOR	TYPE	LIC#	BUSINESS NAME
Daniel Dufresne	General	CCC1332763	Covenant Roofing & Construction INC.

### ROOFING JOB DETAILS

Type Roofing Job	Replacement - Tear off Existing and Replace
Further Job Details (Explain if decking is being replaced and or Repairs are being done.)	
Type of structure	House
Further Structure Details (if needed)	
Total Estimated Cost	22333
Commercial or Residential	Residential
Roof Area (for this job) Sq Ft	4400
No. of Stories	1
Ventilation:	Ridge Vent
Flashing:	Replace All
Drip Edge:	Replace All
Valley Treatment:	New Mineral Surface
Roof Pitch	4:12 or Greater
Second Roof Pitch (if applicable)	Less than 2:12
Any cable and/or race-way wiring located on or within the roof assembly?	No
Is the existing roof being removed?	Yes
Explain if not removing the existing roofing material?	
Type of New Roofing Product	Asphalt Shingles
Florida Product Approval Number	FL5444-R25
Product Manufacturer	Certainteed
Product Description	Laminated Asphalt shingles
Other Roofing Product Type Not Listed	12sq Modified Bitumen   Certaineed   FL2533-R33

Sealed roof decking options: (Must select an option.)

a minimum 4-inch wide strip of selfadhering polymer-modified bitumen complying with ASTM D1970 or a minimum 3 ¼ - inch wide strip of selfadhering flexible flashing tape complying with AAMA 711, applied over all joints in the roof decking. A felt underlayment complying with ASTM D226 Type II, ASTM D4869 Type III or IV, or ASTM D6757, or a synthetic underlayment meeting the performance requirements specified, is required to be applied over the strips/tape over the entire roof.

Sealed roof decking explanation for other option.

**Review Notes:**