



















02 AUG SHIFT 3

SMALLER
1/8 INCH AT SIDES
1/16 INCH AT CORNERS
SPACE BETWEEN
SHEETS
DO NOT
WALK ON
THIS
SHEATHING

MANUFACTURING
TEMPERATURE
EXCEEDED
EQUIVALENT
TERMINATE
AND REJECT

DO NOT
WALK ON
THIS
SHEATHING

APA
32/16
EXPOSURE 1
3/4 INCH
SHEATHING

20 5000

APA
32/16
EXPOSURE 1
3/4 INCH
SHEATHING

APA
32/16
EXPOSURE 1
3/4 INCH
SHEATHING



02 AUG SHIFT 3

SMALLER
1/8 INCH AT SIDES
1/16 INCH AT CORNERS
SPACE BETWEEN
SHEETS
DO NOT
WALK ON
THIS
SHEATHING

MANUFACTURING
TEMPERATURE
EXCEEDED
EQUIPMENT
TEMPERATURE
AND WELDED
JOINTS
DO NOT
USE FOR
LOADS

DO NOT
USE FOR
LOADS

APA
32/16
EXPOSURE 1
3/4 INCH
SHEATHING

20 5000

APA
32/16
EXPOSURE 1
3/4 INCH
SHEATHING



OK BOON GARD





Megan Glen



TOPSMOOL Synthetic
Waterproofing Membrane

ASTM F108 CLASS A
TPI Listed
FBC Approved
ICC-ES E1007

10 Mason Glen

TOPSMOOL Synthetic
Waterproofing Membrane

ASTM F108 CLASS A
TPI Listed
FBC Approved
ICC-ES E1007

TOPSMOOL Synthetic
Waterproofing Membrane

ASTM F108 CLASS A
TPI Listed
FBC Approved
ICC-ES E1007

TOPSMOOL Synthetic
Waterproofing Membrane

ASTM F108 CLASS A
TPI Listed
FBC Approved
ICC-ES E1007

TOPSMOOL Synthetic
Waterproofing Membrane

ASTM F108 CLASS A
TPI Listed
FBC Approved
ICC-ES E1007



ASTM E108
CLASS A



FBC
Approved

Meets ASTM D226, ASTM D4869 & ASTM D8257

PLASTIC CAP NAILS / ROOFING NAILS

FBC
Approved

ASTM D226, ASTM D4869 & ASTM D8257

ment
03-30

TopSynthetic

Q16964

81-3A SA-331
REQUIREMENTS OF
THE SHEETS



Top
Synthetic

Q150619

81-3A SA-331
REQUIREMENTS OF
THE SHEETS

