

51850





MEETS / SATISFACIT / ASTM D328 TYPE IV, ASTM D328 TYPE IV, ASTM D328 TYPE IV, ASTM D328 TYPE IV
CAN/CSA A123.3 & A123.1
FLORIDA PRODUCT APPROVAL
eavetoppeak.com/RhinoRoof | 800-567-9727

PROFESIONAL CERTIFIED
APPROVED

Si se instalan en una zona con viento fuerte, se debe asegurar el material con alfileres.
La instalación en zonas con viento fuerte debe ser realizada por personal capacitado.
Le aconsejamos que consulte al fabricante para obtener más información sobre el uso correcto del producto.

eavetoppeak.com/RhinoRoof | 800-567-9727

51850

MEETS / SATISFACIT / ASTM D328 TYPE IV, ASTM D328 TYPE IV, ASTM D328 TYPE IV, ASTM D328 TYPE IV
CAN/CSA A123.3 & A123.1
FLORIDA PRODUCT APPROVAL
eavetoppeak.com/RhinoRoof | 800-567-9727

and roof with
razado o clima y la pendiente del techo
assure utiliser et le toit pente

MEETS / SATISFACIT / ASTM D328 TYPE IV, ASTM D328 TYPE IV, ASTM D328 TYPE IV, ASTM D328 TYPE IV
CAN/CSA A123.3 & A123.1
FLORIDA PRODUCT APPROVAL
eavetoppeak.com/RhinoRoof | 800-567-9727



51850

RhinoRoof®

U20

envelopepeak.com/RhinoRoof | 800-567-9721

envelopepeak.com/RhinoRoof | 800-567-9721
MEETS / SATISFIED / AFFORDABLE
FLORIDA PROUDLY APPROVED
CALIFORNIA ALECA ALECA

