



ROOFING UNDERLAYMENT AFFIDAVIT

www.columbiacountyfla.com

Columbia County, Florida
Building Department
135 NE Hernando Avenue
Lake City, Florida 32055
Phone: 386-758-1008

REQUIRED FOR WALK-IN OR PAPER SUBMITTALS

Job Address: 216 SW Riverside Avenue Ft. White, FL 32038

I (Print Name) Roger Whidson, as a Florida license Roofing Contractor or an Owner
Builder, I understand to comply with the 2020 Florida Building Code 7th Edition underlayment requirements, I
must select an option for sealing the roof deck.

The options are summarized below...

☐ a self-adhering polymer-modified bitumen underlayment complying with ASTM D1970
applied over the entire roof.

☐ a minimum 4-inch wide strip of selfadhering polymer-modified bitumen complying with
ASTM D1970 or a minimum 3 1/4 - inch wide strip of selfadhering flexible flashing tape complying with
AAMA 711, applied over all joints in the roof decking. A felt underlayment complying with ASTM
D226 Type II, ASTM D4869 Type III or IV, or ASTM D6757, or a synthetic underlayment meeting the
performance requirements specified, is required to be applied over the strips/tape over the entire
roof.

☐ two layers of felt underlayment comply ASTM 0226 Type II or ASTM D4869 Type III or IV, or
two layers of a synthetic underlayment meeting the performance requirements specified, lapped
and fastened as specified.

☒ Other (explain) 1x4 puling on 2x" center nailed/screwed
with 29 gauge metal roofing

Contractor/Owners Signature R. Whidson

FINAL INSPECTION & CERTIFICATE OF COMPLETION:

This completed form and photographs must be uploaded to your permit via online at the Application
Submission login (link) [Welcome to Columbia County Online \(columbiacountyfla.com\)](http://Welcome to Columbia County Online (columbiacountyfla.com)).

Clearly visible in the Photographs must be the permit number or address and must include a ruler or
measuring device to confirm nail spacing and overlaps including drip edge and valley flashing.