

ELECTRICAL PLAN NOTES

- E -1 WIRE ALL APPLIANCES, HVAC UNITS AND OTHER EQUIPMENT PER MANUF. SPECIFICATIONS.
 - E -2 CONSULT THE OWNER FOR THE NUMBER OF SEPERATE TELEPHONE LINES TO BE INSTALLED.
 - E -3 ALL INSTALLATIONS SHALL BE PER NAT'L. ELECTRIC CODE.
- ALL SMOKE DETECTORS SHALL BE 120V W/ BATTERY BACKUP OF THE PHOTOELECTRIC TYPE, AND SHALL BE INTERLOCKED TOGETHER. INSTALL INSIDE AND NEAR ALL BEDROOMS.
- E -5
 TELEPHONE, TELEVISION AND OTHER LOW VOLTAGE
 DEVICES OR OUTLETS SHALL BE AS PER THE OWNER'S
 DIRECTIONS, & IN ACCORDANCE W/ APPLICABLE
 SECTIONS OF NEC-LATEST EDITION.
- E -6 ELECTRICAL CONT'R SHALL BE RESPONSIBLE FOR THE DESIGN & SIZING OF ELECTRICAL SERVICE AND CIRCUITS.
- E -7 ENTRY OF SERVICE (UNDERGROUND OR OVERHEAD)
 TO BE DETERMINED BY POWER COMPANY.
- E -8 ALL BEDROOM RECEPTACLES SHALL BE AFCI (ARC FAULT CIRCUIT INTERRUPT)
- E -9 ALL OUTLETS TO BE LOCATED ABOVE BASE FLOOD ELEVATION

	ELECTRICAL LEG
	CEILING FAN (PRE-WIRE FOR LIGHT KIT)
QP	DOUBLE SECURITY LIGHT
	2X4 FLUORESCENT LIGHT FIXTURE
0	RECESSED CAN LIGHT
- ♦	BATH EXAUST FAN WITH LIGHT
#	BATH EXAUST FAN
- \(-	LIGHT FIXTURE
Ф	DUPLEX OUTLET
₩	220v OUTLET
Фан	GFI DUPLEX OUTLET
•	SMOKE DETECTOR
\$	WALL SWITCH
\$3	3 WAY WALL SWITCH
\$	4 WAY WALL SWITCH
₩ _{P/GFI}	WATER PROOF GFI OUTLET
∇	PHONE JACK
0	TELEVISION JACK
1	GARAGE DOOR OPENER
	WALL HEATER