Parcel:

25-2S-15-00093-007

Owner & Property Info

BAYHAM STEVEN

Owner 1508 LAWRENCE AVENUE

TOMS RIVER, NJ 08757

Site

Description* THE E1/2 OF NE1/4 OF NE1/4 OF NE1/4. 626-377, 680-355, PROB #00-10-CP 895-1664,1671, 938-

753, WD 1050-2484, WD 1394 -1576,

Area 5 AC S/T/R 25-2S-15 Result: 1 of 1

Use Code** VACANT (000000) Tax District 3

MOBILE HOME INSTALLATION SUBCONTRACTOR VERIFICATION FORM

APPLICATION NUMBER	CONTRACTOR	Ernest Scott Johnson	PHONE 352-494-8099

THIS FORM MUST BE SUBMITTED PRIOR TO THE ISSUANCE OF A PERMIT

Steven Bayham

In Columbia County one permit will cover all trades doing work at the permitted site. It is <u>REQUIRED</u> that we have records of the subcontractors who actually did the trade specific work under the permit. Per Florida Statute 440 and Ordinance 89-6, a contractor shall require all subcontractors to provide evidence of workers' compensation or exemption, general liability insurance and a valid Certificate of Competency license in Columbia County.

Any changes, the permitted contractor is responsible for the corrected form being submitted to this office prior to the start of that subcontractor beginning any work. Violations will result in stop work orders and/or fines.

ELECTRICAL	Print Name Steven Ba	yham Signature	Stud Bah
	License #: Owner	Phone #	732-598-8851
		Qualifier Form Attached	
MECHANICAL/	Print NameTimothy S	hatto Signature	
A/C	License #: CAC 057875	Phone #:	386-496-8224
		Qualifier Form Attached	

Qualifier Forms cannot be submitted for any Specialty License.

Specialty License	License Number	Sub-Contractors Printed Name	Sub-Contractors Signature
MASON			
CONCRETE FINISHER			

F. S. 440.103 Building permits; identification of minimum premium policy.--Every employer shall, as a condition to applying for and receiving a building permit, show proof and certify to the permit issuer that it has secured compensation for its employees under this chapter as provided in ss. 440.10 and 440.38, and shall be presented each time the employer applies for a building permit.

Revised 10/30/2015



COLUMBIA COUNTY BUILDING DEPARTMENT 135 NE Hernando Ave, Suite B-21, Lake City, FL 32055

Phone: 386-758-1008 Fax: 386-758-2160

LICENSED QUALIFIER AUTHORIZATION

i, Timothy Shatto	(license holder name), licensed qualifier
for Shatto Heat & Air	
person(s) is/are under my direct supervision an sign permits; call for inspections and sign subco	ough an employee leasing arrangement; or, is an in Florida Statutes Chapter 468, and the said
Printed Name of Person Authorized	Signature of Authorized Person
1. Bo Royals	1. BoTh
2. Dale Burd	2.
3.	3.
4.	4.
5.	5.
under my license and fully responsible for comp Local Ordinances. I understand that the State at authority to discipline a license holder for violatic officers, or employees and that I have full responsand ordinances inherent in the privilege granted lif at any time the person(s) you have authorized officer(s), you must notify this department in writ authorization form, which will supersede all prey unauthorized persons to use your name and/or life.	ind County Licensing Boards have the power and cons committed by him/her, his/her agents, nsibility for compliance with all statutes, codes by issuance of such permits. is/are no longer agents, employee(s), or ing of the changes and submit a new letter of inus lists. Failure to do so mits all employee in the changes and submit a new letter of inus lists.
Licensed Qualifiers Signature (Notarized)	CAC 057875 2/32/1V
NOTARY INFORMATION: STATE OF:COUNTY OF:	11
The above license holder, whose name is personally appeared before me and is known by (type of I.D.) On 1 NOTARY'S SIGNATURE	me or has produced identification this 20 day of february, 20 18.
THE STORY OF THE S	VICTORIA K. PALMER Notary Public - State of Florida Commission # FF 207489 My Comm. Expires Mar 9, 2019

Bonded through National Not my Asso.

	marriage wall piers within 2' of end of home per Rule 15C			2' Show locations of Longitudinal and Lateral Systems (use dark lines to show these locations)	If home is a triple or quad wide sketch in remainder of home I understand Lateral Arm Systems cannot be used on any home (new or used) where the sidewall ties exceed 5 ft 4 in. Installer's initials	Address of home MANNAR VAIN, Road being installed Manufacturer Scotbilt Length x width 80 x 28 NOTE: If home is a single wide fill out one half of the blocking plan	Scott
Opening Ope	Draw the approximate locations of marriage wall openings 4 foot or greater. Use this symbol to show the piers. List all marriage wall openings greater than 4 foot and their pier pad sizes below.	I-beam pier pad size 23/31 70C Olivat 1055-1104 218 Penmeter pier pad size Other pier pad sizes (required by the mfg.)	7'6'' 8' 8' 8' 8' 8' 8' 8' 8' 8' 8' 8' 8' 8	(sq in) (256) 1/2 0 psf 3' 0 psf 4'6"	PIER SPACING TABLE F	Home is installed in accordance with Rule 15-C Single wide	
within 2' spaced a Sidewall Longitud Marriage Sheanwa		Pul AR PAD Siz Pad Size 16 16 x 16 16 x 18 8.5 x 18.5 16 x 22.5	ගු ගු ගු	111 %	ED HOMES	Manual	bage i oi z

Site Preparation

manufacturer's installation instructions and the	Connect all sewer drains to an existing sewer tap or septic tank. Pg.
installer verifies all information given with this permit workshee	Dimping
	source. This includes the bonding wire between mult-wide units. Pg.
	Connect electrical conductors between multi-wide units, but not to the main power
Other	Electrical
protected. Yes	1011100 CC F
Drain lines supported at 4 foot intervals. Yes	
NA	Date Tested ASSumed Oliver 1101 VISES
Skirting to be installed, Wes No	Installer Name Conest S Johnson
Miscellaneous	ALL TESTS MUST BE PERFORMED BY A LICENSED INSTALLER
r l'epiace chimney installed so as not to allow intrusion of rain water. Yés	mistanci simuais
1 1	requires anchors with 4000 holding capacity.
The bottomboard will be repaired and/or taped. 'Yes Pg.	reading is 275 or less and where the mobile home manufacturer may
Billionid Jamesas	anchors are required at all centerline tie points where the torque test
Weatherproofing	Note: A state approved lateral arm system is being used and 4 ft. anchors are allowed at the sidewall locations. I understand 5 ft
Bottom of ridgebeam Yes/	g - c man positivo di roco mii loduno di roco minilo di roco minil
	showing 275 inch pounds or less will require 5 foot anchors
Pg Between Floors Yes	inch poun
Type pasket	
Installer's initials	TOROUG BROBE TEST
of tape will not serve as a gasket.	1 1
a result of a poorly installed or no gasket being installed. I understand a strip	
homes and that condensation, mold, meldew and buckled marriage walls are	
I understand a properly installed gasket is a requirement of all new and used	reading and round down to that increment.
Gds Ret (weather propring requirement)	Using 500 lb. increments, take the lowest
	2. Take the reading at the depth of the footer.
will be centered over the peak of the roof and fastened with galveron foofing nails at 2" on center on both sides of the centerine	
	Total Control of the
Walls: Type Fastener, 1445 Length: Spacing: 12	POCKET PENETROMETER TESTING METHOD
Fastening multi wide units	Y /200
Water drainage: Natural Swale Pad Other	The pocket penetrometer tests are rounded down to psf or check here to declare 1000 lb. soil without testing.
	TOCKET TENETROMETER TEST
Site Preparation	

		ı	
5			
S			
2			
P			
<			
erifies			
20		١	
ע			
3			
3			
3	1		
1			
3	1		
n given with th			
5			
3	1		
-			
7	1		
h. 0	ı		
,	1		
2	1		
	1		
Commit workshop	1		
-	1		
	1		
-	1		
	1		

Installer Signature Date 10/15/20

independent water supply systems. Pg.

Connect all potable water supply piping to an existing water meter, water tap, or other

manufacturer's installation in	is accurate and true based on the	Installer verifies all information given with this permit worksheet
anufacturer's installation instructions and or Rule 15C-1 & 2	based on the	en with this permit worksheet

156 - SIDE B 156 - SIDE A 30% 2.0. FOUNDATION NOTES:
- THIS DRAWING IS DESIGNED FOR THE STANDARD WIND ZONE AND IS TO BE USED IN CONJUNCTION WITH THE INSTALLATION MANUAL AND IT'S SUPPLEMENTS.
- FOOTINGS ARE SHOWN FOR EXAMPLE ONLY QUANTITY AND SPACING MAY VARY BASED ON PAD TYPE, SOIL CONDITION, ETC. MARRIAGE LINE OPENING SUPPORT PIERTYPE SUPPORT PIER - TYP 4'-0" 4'-0" 8.0 8'-0" -42:11: -39:01: DOOR 8'-0" 8.0 4095# - 36'-5', OPT, SGD 9.0 8.0. 8-0 -18'-11'-9.0 -14-11 -12-01-8.0 DOOR -11-10% 1170# -10-11-WINDOWS 9.0 B.-0. 5:5 1170# , 2:0", , 2:-0"

- 35-41/

- 29'41

26'-0"

2856256GSM

GRANDSLAM 28 × 60 - 3BR 2Bath

5-28-2019 D RE 1,456 SQ. FT. 1,456 SQ. FT. 0 SQ. FT.

26'-0" 156 - SIDE A 156 - SIDE B 95 30% 2.0. 2.0 MARRIAGE LINE OPENING SUPPORT PIER/TYP.6" 4.0. 4'-0" 83423 8'-0" 8.0 1365# - 42:11: - 39:01: DOOR 4095# 8.0. - 36:-51 140 PER OPT. SGD 8'-0" - 29'-4% 56-0 8.0. 8.0. 4095# - 18'-111'." 8.0 -14-11" -12-04" 9-0 DOOR 1170# -11-10--10'-11" SMODNIM 8'-0" B.0. -5-5 1170# 51/2 2:-0*

SUPPORT PIER - TYP

FOUNDATION NOTES:

THIS DRAWING IS DESIGNED FOR THE STANDARD WIND ZONE AND IS TO BE USED IN CONJUNCTION WITH THE INSTALLATION MANUAL AND IT'S SUPPLEMENTS. FOOTINGS ARE SHOWN FOR EXAMPLE ONLY QUANTITY AND SPACING MAY VARY BASED ON PAD TYPE, SOIL CONDITION, ETC.

2856256GSM

GRANDSLAM 28 × 60 - 3BR 2Bath

5-28-2019 D

RE 1,456 SQ. FT. 1,456 SQ. FT. 0 SQ. FT.

0 SQ. FT.



