

BEARING HEIGHT SCHEDULE

9' 1-1/8"

4/12 PITCH PORCHES - 24" O/H  
7/12 PITCH MAIN HOUSE

NOTES:

- 1) REFER TO HD-91 (RECOMMENDATIONS FOR BEARING INSTALLATION AND TEMPORARY BRACING). REFER TO ENGINEERED DRAWINGS FOR PERMANENT BRACING REQUIRED.
- 2) ALL TRUSSES (INCLUDING TRUSSES UNDER VALLEY FRAMING) MUST BE COMPLETELY DECKED OR REFER TO DETAIL W05 FOR ALTERNATE BRACING REQUIREMENTS.
- 3) ALL VALLEYS ARE TO BE CONVENTIONALLY FRAMED BY BUILDER.
- 4) ALL TRUSSES ARE DESIGNED FOR 2" OC WOODEN BRACING, UNLESS OTHERWISE NOTED.
- 5) ALL WALLS SHOWN ON PLACEMENT PLAN ARE CONSIDERED TO BE LOAD BEARING, UNLESS OTHERWISE NOTED.
- 6) 5/4x2 TRUSSES MUST BE INSTALLED WITH THE TOP BEING UP.
- 7) BEARING ADDED INTEL. (APR) TO BE FORWARDED BY BUILDER.



Jacksonville  
Tampa  
PHONE: 904-772-5100 FAX: 904-772-1973  
PHONE: 813-621-9831 FAX: 813-628-8756  
Lake City  
PHONE: 386-755-6844 FAX: 386-755-7473

BUILDER:  
EDGLEY CONST.

TEL. AREA(S):

URL:

Company:

DATE:

Drawn by:

Original Estimate #:

9-17-19

KLH

2089496

Material ref.:

Material ref.:

Total job #:

2089496

FL Approval Codes - Mitek Plates #'s 2197.2 - 2197.4, Versa-Lam #1644-R4 & BCI Joists #1392-R4