DATE 06/15/2006 Columbia County	_	PERMIT
This Permit Expires One Y APPLICANT JACK ESPENSHIP	Year From the Date of Issue PHONE 758.0055	000024630
ADDRESS 2915 OLD BAYA AVE	LAKE CITY	– FL 32024
OWNER LAKE CITY CHRISTIAN ACADEMY	PHONE SAME	-
ADDRESS 3035 SW PINEMOUNT ROAD	LAKE CITY	– FL 32024
CONTRACTOR JACK ESPENSHIP	PHONE 758-3018	<u> </u>
LOCATION OF PROPERTY C-252 JUST BEFORE JOY EXP	LOSION CHURCH	
TYPE DEVELOPMENT MODULAR ES	STIMATED COST OF CONSTRUCTION	0.00
HEATED FLOOR AREA TOTAL AR	EA HEIGHT	STORIES 1
FOUNDATION WALLS	ROOF PITCH F	LOOR
LAND USE & ZONING A-3	MAX. HEIGHT	13
Minimum Set Back Requirments: STREET-FRONT 30.00	REAR 25.00	SIDE <u>25.00</u>
NO. EX.D.U. 11 FLOOD ZONE X	DEVELOPMENT PERMIT NO.	
PARCEL ID 07-4S-16-02792-003 SUBDIVISION	ON	
LOT BLOCK PHASE00 UNIT	0 TOTAL ACRES	
GGG00615	11/19	1
Culvert Permit No. Culvert Waiver Contractor's License Nu	mber Applicant/Owne	Contractor
EXISTING 06-536-E BK	JH	N
	ing checked by Approved for Issuar	nce New Resident
COMMENTS: ONE FOOT ABOVE THE ROAD		
	Check # or C	Cash 12199
FOR BUILDING & ZONI	NG DEPARTMENT ONLY	(footer/Slab)
Temporary Power Foundation	Monolithic	W
date/app. by	date/app. by	date/app. by
Under slab rough-in plumbing Slab date/app. by	date/app. by	z/Nailingdate/app. by
Toronto.	above slab and below wood floor	date/app. by
date/app. by		
Electrical rough-in		date/app. by
Heat & All Duct	Peri. beam (Line	•••
date/app. by	Peri. beam (Line date/app. by	•••
date/app. by Permanent power C.O. Final	date/app. by Culvert	date/app. by
Permanent power date/app. by C.O. Final date/app. by M/H tie downs, blocking, electricity and plumbing	date/app. by Culvert date/app. by Pool	tel)
Permanent power date/app. by C.O. Final date/app. by M/H tie downs, blocking, electricity and plumbing date/app	date/app. by Culvert date/app. by Pool p. by	date/app. by
date/app. by Permanent power C.O. Final date/app. by M/H tie downs, blocking, electricity and plumbing Reconnection Pump pole date/app. by	date/app. by Culvert date/app. by Pool p. by Utility Pole e/app. by date/app. b	date/app. by date/app. by date/app. by
All Duct date/app. by Permanent power date/app. by M/H tie downs, blocking, electricity and plumbing Reconnection date/app. by M/H Pole Travel Trailer	date/app. by Culvert date/app. by Pool p. by Utility Pole	date/app. by date/app. by date/app. by
All Duct date/app. by Permanent power date/app. by M/H tie downs, blocking, electricity and plumbing date/app Reconnection Pump pole date/app. by M/H Pole date/app. by Travel Trailer	date/app. by Culvert date/app. by Pool p. by Utility Pole e/app. by Re-roof date/app. by	date/app. by date/app. by date/app. by date/app. by
All Duct date/app. by Permanent power C.O. Final date/app. by M/H tie downs, blocking, electricity and plumbing Reconnection Pump pole date/app. by Travel Trailer date/app. by BUILDING PERMIT FEE \$ 0.00 CERTIFICATION FE	date/app. by Culvert date/app. by Pool p. by Utility Pole e/app. by date/app. b Re-roof date/app. by SE \$ 0.00 SURCHARG	date/app. by date/app. by date/app. by date/app. by date/app. by
All Duct date/app. by C.O. Final	date/app. by Culvert date/app. by Pool p. by Utility Pole e/app. by date/app. b Re-roof date/app. by SURCHARG D FIRE FEE \$ 0.00 WAS	date/app. by date/app. by date/app. by date/app. by date/app. by TE FEE \$ 0.00
All Duct date/app. by C.O. Final	date/app. by Culvert date/app. by Pool p. by Utility Pole e/app. by date/app. b Re-roof date/app. by SURCHARG D FIRE FEE \$ 0.00 WAS	date/app. by date/app. by date/app. by date/app. by date/app. by

NOTICE: IN ADDITION TO THE REQUIREMENTS OF THIS PERMIT, THERE MAY BE ADDITIONAL RESTRICTIONS APPLICABLE TO THIS PROPERTY THAT MAY BE FOUND IN THE PUBLIC RECORDS OF THIS COUNTY. AND THERE MAY BE ADDITIONAL PERMITS REQUIRED FROM OTHER GOVERNMENTAL ENTITIES SUCH AS WATER MANAGEMENT DISTRICTS, STATE AGENCIES, OR FEDERAL AGENCIES.

"WARNING TO OWNER: YOUR FAILURE TO RECORD A NOTICE OF COMMENCEMENT MAY RESULT IN YOUR PAYING TWICE FOR IMPROVEMENTS TO YOUR PROPERTY. IF YOU INTEND TO OBTAIN FINANCING, CONSULT WITH YOUR LENDER OR AN ATTORNEY BEFORE RECORDING YOUR NOTICE OF COMMENCEMENT."

This Permit Must Be Prominently Posted on Premises During Construction

PLEASE NOTIFY THE COLUMBIA COUNTY BUILDING DEPARTMENT AT LEAST 24 HOURS IN ADVANCE OF EACH INSPECTION, IN ORDER THAT IT MAY BE MADE WITHOUT DELAY OR INCONVIENCE, PHONE 758-1008. THIS PERMIT IS NOT VALID UNLESS THE WORK AUTHORIZED BY IT IS COMMENCED WITHIN 6 MONTHS AFTER ISSUANCE.

The Issuance of this Permit Does Not Waive Compliance by Permittee with Deed Restrictions.

For Office Use Only Application # (606-40) Date	Received 6/14 By 21/1 Permit # 24630
Application Approved by - Zoning Official BLK Di	ate 14.06.06 Plans Examiner ASTH Date 6-14-00
Flood Zone Development Permit Zon	ning A-3 Land Use Plan Map Category A-3
Comments Specil Efection 0 215	See CAL-Tech Testing & latter of the post
<u> </u>	
Applicants Name JOHN JACK ESENSKA	Phone 386-758-3018
Address 2715 ON BAYA AVE, L	1-1 take City, Ft 32055
Owners Name L-C. Chaster	Acrocus Phone SAME
911 Address 3035 Su Piru	out ld 60,71 3204
Contractors Name Sack Espenship	Phone 386 - 752-1824
Address 2915-DId Baya HUE	lake City, FL 32085
Fee Simple Owner Name & Address	J 2
Bonding Co. Name & Address DIA	
Architect/Engineer Name & Address Sohn A Contigue Lenders Name & Address W M	Sidziack 3637 4th St North
Mortgage Lenders Name & Address W/A	Lisens + A 10 -0005 065
Circle the correct power company - FL Power & Light -	Clay Elec Suwannee Valley Elec Progressive Energ
Property ID Number 07-45-16-02792-10	03 Estimated Cost of Construction 11,350.00
Subdivision Name D/A	Lot Block Unit Phase
Driving Directions Go down Pinemour	of Road 4 miles on the
left	
Type of Construction Lodular Buldiw	- Transfer of Examing Off Property
Total Acreage 20Lot Size Do you need a -	Culvert Permit or Culvert Walver or Have an Existing Dit
Actual Distance of Structure from Property Lines - Front	23 Side <u>50</u> Side <u>520</u> Rear <u>420</u>
Total Building Height 13 6" Number of Stories	
	275
Application is hereby made to obtain a permit to do work a installation has commenced prior to the issuance of a permali laws regulating construction in this jurisdiction.	and installations as indicated. I certify that no work or mit and that all work be performed to meet the standards o
OWNERS AFFIDAVIT: I hereby certify that all the foregoing	Information is accurate and all work with the day of
compliance with all applicable laws and regulating constru	iction and zoning.
WARNING TO OWNER: YOUR FAILURE TO RECORD A NO	TICE OF COMMENCMENT MAY RESULT IN YOU PAYING
TWICE FOR IMPROVEMENTS TO YOUR PROPERTY, IF YO LENDER OR ATTORNEY BEFORE RECORDING YOUR NO	U INTEND TO OBTAIN FINANCING, CONSULT WITH YOUR
1- 6- 10	
Mara (spersy)	Jack Soul !!
Owner Builder or Agent (Including Contractor)	Contractor Signature Contractors License Number (60 006017
STATE OF FLORIDA COUNTY OF COLUMBIA	Competency Card Number_NOTARY \$TAMP/SEAL
Sworn to (or affirmed) and subscribed before me	MOTART BIAMPISEAL
this 13th day of June 2006.	The forther
Personally known or Produced Identification	Notana Cimpatana



Environmental

P.O. Box 1625 • Lake City, FL 32056-1625 6919 Distribution Avenue S., Unit #5 • Jacksonville, FL 32257

Tel. (386) 755-3633 • Fax (386) 752-5456 Tel. (904) 262-4046 • Fax (904) 262-4047

April 14, 2003

Lake City Christian Academy Rt. 11, Box 10521 Lake City, Florida 32024

Attention:

Tana Espenship

Reference:

Proposed Prefabricated Buildings

Lake City Christian Academy

Lake City, Florida

Cal-Tech Project No. 03-170

Dear Ms. Espenship,

Cal-Tech Testing, Inc. has completed an investigation and evaluation of subgrade soils at the referenced site. Specifically, bearing level soils in a foundation area for one of three prefabricated buildings were investigated. Our work was performed in conjunction with and authorized by you. The purpose of our investigation was to evaluate the existing subgrade soils for an allowable bearing pressure of 2,000 pounds per square foot.

Site Investigation

The site was investigated by performing one (1) dynamic-cone penetration test and hand-auger boring advanced to a depth of 6 feet. The boring was performed near the center of the proposed construction area. This location was selected on site by you. A site plan was not available.

The dynamic cone penetration test is performed by driving a standard 60 degree cone into the soil by blows from a 15-pound slide-hammer falling 20 inches. The number of blows required to advance the cone 1.75 inches is designated the dynamic cone penetration resistance. This value can be correlated to N-values of the Standard Penetration Test and is an index of soil density or consistency.

Hand-auger borings are performed by manually advancing a 3-inch diameter, metal sleeve into the soil to recover samples from limited depths. Samples are examined for soil type and color.

Findings

The soil boring generally encountered two soil strata. The first layer consists of about 4 feet of very loose to loose, tannish gray or grayish tan sand (SP) or sand with silt (SP/SM). Equivalent N-values of this layer range from 3 to 10 blows per foot.

The second layer consists of an undetermined thickness of loose to medium dense, tannish gray, orange and red, clayey sand or slightly clayey sand (SC). Equivalent N-values for this layer range from 5 to 16 blows per foot. Groundwater was not encountered at the time of our investigation.

For a more detailed description of the subsurface conditions encountered, please refer to the attached Boring Log. On this log values of cone penetration resistance have been converted to equivalent N-values of the Standard Penetration Test.

Discussion

Based upon the results of the soil boring, we have performed a bearing capacity analysis for the subgrade soils at the specific location of the boring. We have assumed a foundation width of 16 inches with the foundation bottom embedded 14 inches below the finished surface grade. We obtained an allowable bearing capacity of about 2,000 pounds per square foot for this foundation with a factor of safety of about 1.0 against a bearing capacity failure.

We believe you should consider a minimum factor of safety of about 1.5 and therefore recommend the bottoms of the foundations be embedded a minimum of 16 inches below the finished surface grade. For this placement we obtained a factor of safety of about 1.6 against a bearing capacity failure assuming a foundation width of 16 inches. We also recommend all bearing soils for the proposed foundations be proof-compacted to a minimum of 95% of the Modified Proctor maximum dry density to a depth of 2 feet below the bottoms of the foundations.

Provided suitable foundation width and embedment are provided, it is our opinion the subgrade soils at the area of investigation are suitable for an allowable soil bearing pressure of 2,000 pounds per square foot. Compaction of the bearing soils is recommended.

We appreciate the opportunity to be of service and look forward to a continued association. Please do not hesitate to contact us should you have questions.

Respectfully submitted,

Cal-Tech Testing, Inc.

Linda Creamer


President / CEO

John C. Dorman, Jr., Ph.D., P.E.


Geotechnical Engineer

1/14/07

B-1
Water Table: N/A



Boring Log: Lake City Christian Academy Lake City, Florida



PINEMOUNT ROAD



STATE OF FLORIDA DEPARTMENT OF HEALTH

otes: See attiched
Die Frank E
O. Signi E
Oc. From E
0.0 1550 E
Oc. Free E
Do Time E
Out style E
Do MAN E
DO THE

ALL CHANGES MUST BE APPROVED BY THE COUNTY HEALTH DEPARTMENT

```
Print Key Output
                                                                    Face 1
   5716951 V3R7MO 961108
                                       S1032F6G
                                                          06/26/00
                                                                    14:39:37
   Display Device . . . :
                               W8
   User . . . . . . . ENVIRON
 CAM112MO1 S CamaUSA Appraisal System
                                                              Columbia County
  6/26/2000 14:39 Legal Description Maintenance
                                                            1000
                                                                  Land
                                                                        001
Year T Property
                                      Sel
                                                            3526
                                                                  AG
                                                                        001
2000 R 07-4S-16-02792-003
                                                                        000
                                                                  Bldg
                                                           35520
                                                                  Xfea
                                                                        902
       LAKE CITY CHRISTIAN ACADEMY IN
                                                           40046
                                                                  TOTAL
     COMM NE COR, RUN S 56.08 FT TO S R/W CR-252, RUN W ALONG R/W
    60.01 FT FOR POB, S 1270.51 FT, W 684.42 FT, N 1275.43 FT
  3
                                                                     4
     TO S R/W OF CR-252, E 684.42
                                   FT TO POB. ORB 841-769.
                                                                     6
  7
                                                                     8
  9
                                                                    10
 11
                                                                    12
 13
                                                                    14
 15
                                                                    16
 17
                                                                    18
 19
                                                                    20
21
                                                                    22
 23
                                                                    24
25
                                                                    26
27
                                                                    28
                                            Mnt 10/14/1997 TERR
F1=Help F3=Exit F4=Prompt F10=GoTo PGUP/PGDN F24=MoreKeys
```



Cal-Tech Testing, Inc.

 Engineering Geotechnical

P.O. Box 1625 • Lake City, FL 32056-1625 6919 Distribution Avenue S., Unit #5 • Jacksonville, FL 32257 Environmental

Tel. (386) 755-3633 • Fax (386) 752-5456 Tel. (904) 262-4046 • Fax (904) 262-4047

July 27, 2006

Lake City Christian Academy 3035 S. W. Pinemount Road Lake City, Florida 32024

Attention:

Tana Espenship

Reference:

Prefabricated Buildings

Lake City Christian Academy

Lake City, Florida

Cal-Tech Project No. 06-411

reamer

Dear Ms. Espenship,

At your request, Cal-Tech Testing, Inc. has performed an investigation of foundation embedment provided for two prefabricated buildings recently placed at the referenced site. The purpose of our work was to determine if embedment provided for isolated footings used for the structures was sufficient to provide the required allowable bearing pressure of 2,000 pounds per square foot. Additionally, recommendations were to be provided as appropriate.

Investigation

Both structures were investigated, and embedment was found to vary from about 12 to 14 inches. Based upon the subsurface conditions previously determined, the foundations used, and embedment of 12 to 14 inches, we obtained an allowable bearing pressure of 2,000 pounds per square foot with factors of safety on the order of 1.3 to 1.4. Based upon this finding, it is our opinion the foundations used are sufficient to provide the required support for the structures. We recommend all foundation excavations be backfilled to grade following placement of the utilities.

We appreciate the opportunity to be of service on this project and look forward to a continued association. Please do not hesitate to contact us should you have questions concerning this report or if we may be of further assistance.

Respectfully submitted.

Cal-Tech Testing, Inc.

President / CEO

John C. Dorman, Jr., Ph.D., P.E.

Geotechnical Engineer 7/27/06

62612

Form 400B-97

Component Performance Method for Commercial Buildings

OWNER/AGENT

DATE:

ENERGY EFFICIENCY CODE FOR BUILDING CONSTRUCTION Florida Department of Community Affairs

FLA/COM-97 Ver	sion 2.2		
PROJECT NAME_MDS005209ADDRESS:	E	PERMITTING OFFICE: DUVAL COUNTY CLIMATE ZONE:	3
OWNER: GE CAPITAL MODULAR SPACE	E	PERMIT NO:	261000
BUILDING TYPE: _EducationalCONSTRUCTION CONDITION: New constructions: _Finished Building CONDITIONED FLOOR AREA: _840MAX. TONNAGE OF EQUIPMENT PER SYSTEM	tion g	NUMBER OF	ZONES: 1
COMPLIANCE CALCULATION:	DESIGN	CRITERIA	RESULT
METHOD B	62.85	72.11	PASSES PASSES
ENVELOPE PERFORMANCE OTHER ENVELOPE REQUIREMENTS LIGHTING INTERIOR LIGHTING EXTERIOR LIGHTING LIGHTING CONTROL REQUIREMENTS	175.20	518.03 75.00	PASSES PASSES PASSES
HVAC EQUIPMENT COOLING EQUIPMENT	10.00	9.70	PASSES
1. SEER HEATING EQUIPMENT 1. Et AIR DISTRIBUTION SYSTEM INSULATI 1. Ventilated REHEAT SYSTEM TYPES USED	1.00 ON REQUIREM 6.00	MENTS 6.00	n/A PASSES
NO REHEAT SYSTEM IS OBED WATER HEATING EQUIPMENT	1.50	0.92	PASSES
1. EF PIPING INSULATION REQUIREMENTS 1. Non-Circulating w/o H	1.00	1.00	PASSES
COMPLIANCE CERTIFICATION: I hereby certify that the plans an specifications covered by this cal lation are in compliance with the Florida Energy Efficiency Code. PREPARED BY: DATE: I hereby certify that this building in compliance with the Florida Energy Efficiency Code.	cu- tic ind Flo Bef the	riew of the plans ons covered by this dicates compliant or ida Energy Efficience construction is building will by compliance in acction 553.908, Flant ILDING OFFICIAL:	ce with the ciency Code. is completed, be inspected accordance with

I hereby certify(*) that the system design is in compliance with the Florida
I fieldby cold and Code
Energy Efficiency Code. REGISTRATION/STATE
SYSTEM DESIGNER AROOFOLT
11//
ARCHITECT :
MECHANICAL:
PLUMBING :
ELECTRICAL:
TIGHTING . /// degign to be performed
distribution numbers may
(*) Signature 17 require forming Typed names and registration numbers may
(*) Signature is required where Florida law requires design to be possible to be
by where all relevant information is contained on Degree and process of the second subject to the second subje
be used where dri age.

BUILDING ENVELOPE SYSTEMS

							V
01G levation		1 U	SC	VLT	Shadir	ng	Area (Sqrt)
est est ast	Commercial Commercial Commercial Commercial	1.13 1.13 1.13 1.13 Tot	1.0 1.0 1.0 1.0 1.0	1.0 1.0 1.0 1.0 1.0	None None None None a in Zo	one 1 =	18 1 26 9 80 134 134
Elevation					_		Gross(Sqft)
Vest North South	Frame Wall + Frame Wall + Frame Wall + Frame Wall +	3" InS. 3" InS. 3" InS. 3" InS.	otal Wa	ll Are	0.081 0.081 0.081 0.081 ea in Z	0.0 0.0 0.0 0.0 one 1 =	396 396 210 210 1212 1212
Elevation	DOORSZONE 1 Type						
East West	0.0 STORE I 1-3/4 Steel I	RONT Door-Pape: To	r Honey otal Do	comb or Ar	core ea in Z	1.13 0.56 Sone 1 =	19 19 19
404 Type	ROOFSZONE	L		Color	 آ 	J Insul R	Area(Sqft)
STD. TRUSS	5	T	I otal Ro	ight of Ar	.0526 ea in 2	Zone 1 =	1027
405 Type	-FLOORS - ZONE	1					Area(Sqft)
	r Unconditione	d Space/I To	nsulate tal Flo	ed oor Ar	ea in	I1 Zone 1 = or Area =	1027
	-INFILTRATION-						CHECK
Infil	tration Criter	ia in 406 MECHAN			2 Deell		1 1
							CHECK
	load sizing ha	s been pe	erforme	d. (4	07.1.AE	BCD)	
Type			MO		CICHOI		
			2		10.0	0.0	3.00 BTU/hr
Type				140			
1. Elect	ric Resistanc VENTILATION-	e 	-,	2		1.0	35000

409.1.ABCD have been met.
CHECK
nave been performed. (410.1.ABCD) Duct Location R-value
Ventilated 6 CHECK
ill be performed. (410.1.ABCD) ONE irements in 411.1.ABCD have been met.
JMBING SYSTEMS
ONE 1
t 3.63 0.75 1.0 EMS-ZONE 1 Efficiency StandbyLoss InputRate Gallons
1.5 0.0 3.5 6
ECTRICAL SYSTEMS CHECK ISTRIBUTION
3.1.ABCD have been met. 14.1.ABCD have been met.
ONE 1 e 1 No Control Type 2 No Watts Area(Sqft)
2 None 00 175 140 Total Watts for Zone 1 = 175 Total Area for Zone 1 = 140 Total Watts = 175 Total Area = 140