

FLORIDA ENERGY EFFICIENCY CODE FOR BUILDING CONSTRUCTION

Florida Department of Business and Professional Regulation - Residential Performance Method

Project Name: Lot 31 Jewel Lake II Street: City, State, Zip: Lake City, FL, 32025 Owner: Design Location: FL, Gainesville	Builder Name: Century CMP Florida Permit Office: Columbia County Permit Number: Jurisdiction: County: Columbia (Florida Climate Zone 2)
---	---

1. New construction or existing: New (From Plans) 2. Single family or multiple family: Detached 3. Number of units, if multiple family: 1 4. Number of Bedrooms: 4 5. Is this a worst case?: No 6. Conditioned floor area above grade (ft²): 1398 Conditioned floor area below grade (ft²): 0 7. Windows (123.3 sqft.) <table style="width: 100%;"> <tr> <th>Description</th> <th>Area</th> </tr> <tr> <td>a. U-Factor: Dbl, U=0.36 SHGC: SHGC=0.25</td> <td>123.33 ft²</td> </tr> <tr> <td>b. U-Factor: N/A SHGC:</td> <td>ft²</td> </tr> <tr> <td>c. U-Factor: N/A SHGC:</td> <td>ft²</td> </tr> <tr> <td>Area Weighted Average Overhang Depth:</td> <td>2.473 ft.</td> </tr> <tr> <td>Area Weighted Average SHGC:</td> <td>0.250</td> </tr> </table> 8. Skylights <table style="width: 100%;"> <tr> <th>Description</th> <th>Area</th> </tr> <tr> <td>c. U-Factor (AVG): N/A SHGC (AVG): N/A</td> <td>ft²</td> </tr> </table> 9. Floor Types (1398.0 sqft.) <table style="width: 100%;"> <tr> <th>Insulation</th> <th>Area</th> </tr> <tr> <td>a. Slab-On-Grade Edge Insulation: R=0.0</td> <td>1398.00 ft²</td> </tr> <tr> <td>b. N/A: R=</td> <td>ft²</td> </tr> <tr> <td>c. N/A: R=</td> <td>ft²</td> </tr> </table>	Description	Area	a. U-Factor: Dbl, U=0.36 SHGC: SHGC=0.25	123.33 ft²	b. U-Factor: N/A SHGC:	ft²	c. U-Factor: N/A SHGC:	ft²	Area Weighted Average Overhang Depth:	2.473 ft.	Area Weighted Average SHGC:	0.250	Description	Area	c. U-Factor (AVG): N/A SHGC (AVG): N/A	ft²	Insulation	Area	a. Slab-On-Grade Edge Insulation: R=0.0	1398.00 ft²	b. N/A: R=	ft²	c. N/A: R=	ft²	10. Wall Types (1380.7 sqft.) <table style="width: 100%;"> <tr> <th>Insulation</th> <th>Area</th> </tr> <tr> <td>a. Frame - Wood, Exterior: R=13.0</td> <td>1090.00 ft²</td> </tr> <tr> <td>b. Frame - Wood, Adjacent: R=13.0</td> <td>290.67 ft²</td> </tr> <tr> <td>c. N/A: R=</td> <td>ft²</td> </tr> <tr> <td>d. N/A: R=</td> <td>ft²</td> </tr> </table> 11. Ceiling Types (1468.0 sqft.) <table style="width: 100%;"> <tr> <th>Insulation</th> <th>Area</th> </tr> <tr> <td>a. Under Attic (Vented): R=38.0</td> <td>1468.00 ft²</td> </tr> <tr> <td>b. N/A: R=</td> <td>ft²</td> </tr> <tr> <td>c. N/A: R=</td> <td>ft²</td> </tr> </table> 12. Ducts <table style="width: 100%;"> <tr> <th>R</th> <th>ft²</th> </tr> <tr> <td>a. Sup: Attic, Ret: Attic, AH: Main: 6</td> <td>349.5</td> </tr> </table> 13. Cooling systems <table style="width: 100%;"> <tr> <th>kBtu/hr</th> <th>Efficiency</th> </tr> <tr> <td>a. Central Unit: 17.8</td> <td>SEER: 15.00</td> </tr> </table> 14. Heating systems <table style="width: 100%;"> <tr> <th>kBtu/hr</th> <th>Efficiency</th> </tr> <tr> <td>a. Electric Heat Pump: 21.9</td> <td>HSPF: 8.20</td> </tr> </table> 15. Hot water systems <table style="width: 100%;"> <tr> <td>a. Electric</td> <td>Cap: 50 gallons</td> </tr> <tr> <td>b. Conservation features: None</td> <td>EF: 0.920</td> </tr> </table> 16. Credits: CV, Pstat	Insulation	Area	a. Frame - Wood, Exterior: R=13.0	1090.00 ft²	b. Frame - Wood, Adjacent: R=13.0	290.67 ft²	c. N/A: R=	ft²	d. N/A: R=	ft²	Insulation	Area	a. Under Attic (Vented): R=38.0	1468.00 ft²	b. N/A: R=	ft²	c. N/A: R=	ft²	R	ft²	a. Sup: Attic, Ret: Attic, AH: Main: 6	349.5	kBtu/hr	Efficiency	a. Central Unit: 17.8	SEER: 15.00	kBtu/hr	Efficiency	a. Electric Heat Pump: 21.9	HSPF: 8.20	a. Electric	Cap: 50 gallons	b. Conservation features: None	EF: 0.920
Description	Area																																																										
a. U-Factor: Dbl, U=0.36 SHGC: SHGC=0.25	123.33 ft²																																																										
b. U-Factor: N/A SHGC:	ft²																																																										
c. U-Factor: N/A SHGC:	ft²																																																										
Area Weighted Average Overhang Depth:	2.473 ft.																																																										
Area Weighted Average SHGC:	0.250																																																										
Description	Area																																																										
c. U-Factor (AVG): N/A SHGC (AVG): N/A	ft²																																																										
Insulation	Area																																																										
a. Slab-On-Grade Edge Insulation: R=0.0	1398.00 ft²																																																										
b. N/A: R=	ft²																																																										
c. N/A: R=	ft²																																																										
Insulation	Area																																																										
a. Frame - Wood, Exterior: R=13.0	1090.00 ft²																																																										
b. Frame - Wood, Adjacent: R=13.0	290.67 ft²																																																										
c. N/A: R=	ft²																																																										
d. N/A: R=	ft²																																																										
Insulation	Area																																																										
a. Under Attic (Vented): R=38.0	1468.00 ft²																																																										
b. N/A: R=	ft²																																																										
c. N/A: R=	ft²																																																										
R	ft²																																																										
a. Sup: Attic, Ret: Attic, AH: Main: 6	349.5																																																										
kBtu/hr	Efficiency																																																										
a. Central Unit: 17.8	SEER: 15.00																																																										
kBtu/hr	Efficiency																																																										
a. Electric Heat Pump: 21.9	HSPF: 8.20																																																										
a. Electric	Cap: 50 gallons																																																										
b. Conservation features: None	EF: 0.920																																																										

Glass/Floor Area: 0.088	Total Proposed Modified Loads: 36.67	PASS
	Total Baseline Loads: 38.16	

I hereby certify that the plans and specifications covered by this calculation are in compliance with the Florida Energy Code. PREPARED BY: <u>Will C. My</u> DATE: <u>3 / 8 / 2022</u> I hereby certify that this building, as designed, is in compliance with the Florida Energy Code. OWNER/AGENT: <u>Brittany Dunn</u> DATE: _____	Review of the plans and specifications covered by this calculation indicates compliance with the Florida Energy Code. Before construction is completed this building will be inspected for compliance with Section 553.908 Florida Statutes. BUILDING OFFICIAL: _____ DATE: _____
---	---



- Compliance requires certification by the air handler unit manufacturer that the air handler enclosure qualifies as certified factory-sealed in accordance with R403.3.2.1.
- Compliance requires an Air Barrier and Insulation Inspection Checklist in accordance with R402.4.1.1 and this project requires an envelope leakage test report with envelope leakage no greater than 5.00 ACH50 (R402.4.1.2).

INPUT SUMMARY CHECKLIST REPORT

PROJECT

Title:	Lot 31 Jewel Lake II	Bedrooms:	4	Address Type:	Lot Information
Building Type:	User	Conditioned Area:	1398	Lot #	31
Owner Name:		Total Stories:	1	Block/Subdivision:	Jewel Lake II
# of Units:	1	Worst Case:	No	PlatBook:	
Builder Name:	Century CMP Florida	Rotate Angle:	0	Street:	
Permit Office:	Columbia County	Cross Ventilation:	Yes	County:	Columbia
Jurisdiction:		Whole House Fan:	No	City, State, Zip:	Lake City , FL , 32025
Family Type:	Detached				
New/Existing:	New (From Plans)				
Comment:					

CLIMATE

✓	Design Location	TMY Site	Design Temp 97.5 %	2.5 %	Int Design Temp Winter	Summer	Heating Degree Days	Design Moisture	Daily Temp Range
_____	FL, Gainesville	FL_GAINESVILLE_REGI	32	92	70	75	1305.5	51	Medium

BLOCKS

Number	Name	Area	Volume
1	Block1	1398	11184

SPACES

Number	Name	Area	Volume	Kitchen	Occupants	Bedrooms	Infil ID	Finished	Cooled	Heated
1	Main	1398	11184	Yes	8	4	1	Yes	Yes	Yes

FLOORS

✓	#	Floor Type	Space	Perimeter	R-Value	Area		Tile	Wood	Carpet
_____	1	Slab-On-Grade Edge Insulation	Main	172.5 ft	0	1398 ft²	----	0	0	1

ROOF

✓	#	Type	Materials	Roof Area	Gable Area	Roof Color	Rad Barr	Solar Absor.	SA Tested	Emitt Tested	Emitt Tested	Deck Insul.	Pitch (deg)
_____	1	Hip	Composition shingles	1563 ft²	0 ft²	Medium	Y	0.96	No	0.9	No	0	26.57

ATTIC

✓	#	Type	Ventilation	Vent Ratio (1 in)	Area	RBS	IRCC
_____	1	Full attic	Vented	300	1398 ft²	Y	N

CEILING

✓	#	Ceiling Type	Space	R-Value	Ins Type	Area	Framing Frac	Truss Type
_____	1	Under Attic (Vented)	Main	38	Double Batt	1468 ft²	0.11	Wood

INPUT SUMMARY CHECKLIST REPORT

WALLS

✓ #	Ornt	Adjacent To	Wall Type	Space	Cavity R-Value	Width Ft	In	Height Ft	In	Area	Sheathing R-Value	Framing Fraction	Solar Absor.	Below Grade%
___ 1	E	Exterior	Frame - Wood	Main	13	11	10	8		94.7 ft²		0.23	0.75	0
___ 2	S	Exterior	Frame - Wood	Main	13	4		8		32.0 ft²		0.23	0.75	0
___ 3	E	Exterior	Frame - Wood	Main	13	4	3	8		34.0 ft²		0.23	0.75	0
___ 4	S	Garage	Frame - Wood	Main	13	16	4	8		130.7 ft²		0.23	0.75	0
___ 5	E	Garage	Frame - Wood	Main	13	20		8		160.0 ft²		0.23	0.75	0
___ 6	S	Exterior	Frame - Wood	Main	13	29	8	8		237.3 ft²		0.23	0.75	0
___ 7	W	Exterior	Frame - Wood	Main	13	36	6	8		292.0 ft²		0.23	0.75	0
___ 8	N	Exterior	Frame - Wood	Main	13	50		8		400.0 ft²		0.23	0.75	0

DOORS

✓ #	Ornt	Door Type	Space	Storms	U-Value	Width Ft	In	Height Ft	In	Area
___ 1	E	Insulated	Main	None	.46	3		6	8	20 ft²
___ 2	E	Insulated	Main	None	.46	3		6	8	20 ft²

WINDOWS

Orientation shown is the entered, Proposed orientation.

✓ #	Ornt	Wall ID	Frame	Panes	NFRC	U-Factor	SHGC	Imp	Area	Overhang Depth	Separation	Int Shade	Screening
___ 1	E	1	Vinyl	Low-E Double	Yes	0.36	0.25	N	30.0 ft²	5 ft 6 in	1 ft 0 in	None	None
___ 2	S	6	Vinyl	Low-E Double	Yes	0.36	0.25	N	15.0 ft²	1 ft 6 in	1 ft 0 in	None	None
___ 3	W	7	Vinyl	Low-E Double	Yes	0.36	0.25	N	30.0 ft²	1 ft 6 in	1 ft 0 in	None	None
___ 4	W	7	Metal	Low-E Double	Yes	0.36	0.25	N	33.3 ft²	1 ft 6 in	1 ft 0 in	None	None
___ 5	N	8	Vinyl	Low-E Double	Yes	0.36	0.25	N	15.0 ft²	1 ft 6 in	1 ft 0 in	None	None

GARAGE

✓ #	Floor Area	Ceiling Area	Exposed Wall Perimeter	Avg. Wall Height	Exposed Wall Insulation
___ 1	416.765 ft²	416.765 ft²	44.833 ft	8 ft	1

INFILTRATION

#	Scope	Method	SLA	CFM 50	ELA	EqLA	ACH	ACH 50
1	Wholehouse	Proposed ACH(50)	.000254	932	51.13	96	.098	5

HEATING SYSTEM

✓ #	System Type	Subtype	Speed	Efficiency	Capacity	Block	Ducts
___ 1	Electric Heat Pump/	None	Single	HSPF:8.2	21.87 kBtu/hr	1	sys#1

INPUT SUMMARY CHECKLIST REPORT

COOLING SYSTEM													
✓	#	System Type	Subtype	Subtype	Efficiency	Capacity	Air Flow	SHR	Block	Ducts			
_____	1	Central Unit/	None	Single	SEER: 15	17.82 kBtu/hr	540 cfm	0.7	1	sys#1			
HOT WATER SYSTEM													
✓	#	System Type	SubType	Location	EF	Cap	Use	SetPnt	Conservation				
_____	1	Electric	None	Main	0.92	50 gal	40 gal	120 deg	None				
SOLAR HOT WATER SYSTEM													
✓	FSEC Cert #	CompanyName	System Model#	Collector Model#	Collector Area	Storage Volume	FEF						
_____	None	None						ft²					
DUCTS													
✓	#	--- Supply ---			--- Return ---			Air	CFM 25	CFM25		HVAC #	
		Location	R-Value	Area	Location	Area	LeakageType	Handler	TOT	OUT	QN	RLF Heat Cool	
_____	1	Attic	6	349.5 ft²	Attic	69.9 ft²	Default Leakage	Main	(Default) c	(Default) c		1 1	
TEMPERATURES													
ProgramableThermostat: Y				Ceiling Fans:									
Cooling Heating Venting	☐ Jan ☒ Jan ☐ Jan	☐ Feb ☒ Feb ☐ Feb	☐ Mar ☒ Mar ☐ Mar	☐ Apr ☒ Apr ☐ Apr	☐ May ☒ May ☐ May	☒ Jun ☐ Jun ☐ Jun	☒ Jul ☐ Jul ☐ Jul	☒ Aug ☐ Aug ☐ Aug	☒ Sep ☐ Sep ☐ Sep	☐ Oct ☒ Oct ☐ Oct	☐ Nov ☒ Nov ☐ Nov	☐ Dec ☒ Dec ☐ Dec	
Thermostat Schedule: HERS 2006 Reference													
Schedule Type		1	2	3	4	5	6	7	8	9	10	11	12
Cooling (WD)	AM PM	78 80	78 80	78 78	78 78	78 78	78 78	78 78	78 78	80 78	80 78	80 78	80 78
Cooling (WEH)	AM PM	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78	78 78
Heating (WD)	AM PM	66 68	66 68	66 68	66 68	66 68	68 68	68 68	68 68	68 68	68 68	68 66	68 66
Heating (WEH)	AM PM	66 68	66 68	66 68	66 68	66 68	68 68	68 68	68 68	68 68	68 68	68 66	68 66
MASS													
Mass Type		Area	Thickness	Furniture Fraction	Space								
Default(8 lbs/sq.ft.)		0 ft²	0 ft	0.3	Main								

ENERGY PERFORMANCE LEVEL (EPL) DISPLAY CARD

ESTIMATED ENERGY PERFORMANCE INDEX* = 96

The lower the EnergyPerformance Index, the more efficient the home.

, Lake City, FL, 32025

1. New construction or existing	New (From Plans)		10. Wall Type and Insulation	Insulation	Area
2. Single family or multiple family	Detached		a. Frame - Wood, Exterior	R=13.0	1090.00 ft ²
3. Number of units, if multiple family	1		b. Frame - Wood, Adjacent	R=13.0	290.67 ft ²
4. Number of Bedrooms	4		c. N/A	R=	ft ²
5. Is this a worst case?	No		d. N/A	R=	ft ²
6. Conditioned floor area (ft ²)	1398		11. Ceiling Type and insulation level	Insulation	Area
7. Windows**	Description	Area	a. Under Attic (Vented)	R=38.0	1468.00 ft ²
a. U-Factor:	Dbl, U=0.36	123.33 ft ²	b. N/A	R=	ft ²
SHGC:	SHGC=0.25		c. N/A	R=	ft ²
b. U-Factor:	N/A	ft ²	12. Ducts, location & insulation level	R	ft ²
SHGC:			a. Sup: Attic, Ret: Attic, AH: Main	6	349.5
c. U-Factor:	N/A	ft ²	13. Cooling systems	kBtu/hr	Efficiency
SHGC:			a. Central Unit	17.8	SEER:15.00
d. U-Factor:	N/A	ft ²	14. Heating systems	kBtu/hr	Efficiency
SHGC:			a. Electric Heat Pump	21.9	HSPF:8.20
Area Weighted Average Overhang Depth:	2.473 ft.		15. Hot water systems	Cap: 50 gallons	
Area Weighted Average SHGC:	0.250		a. Electric	EF: 0.92	
8. Skylights	Description	Area	b. Conservation features		
a. U-Factor(AVG):	N/A	ft ²	None		
SHGC(AVG):	N/A		Credits (Performance method)		CV, Pstat
9. Floor Types	Insulation	Area			
a. Slab-On-Grade Edge Insulation	R=0.0	1398.00 ft ²			
b. N/A	R=	ft ²			
c. N/A	R=	ft ²			

I certify that this home has complied with the Florida Energy Efficiency Code for Building Construction through the above energy saving features which will be installed (or exceeded) in this home before final inspection. Otherwise, a new EPL Display Card will be completed based on installed Code compliant features.

Builder Signature: Brittany Dunn Date: _____

Address of New Home: _____ City/FL Zip: _____



*Note: This is not a Building Energy Rating. If your Index is below 70, your home may qualify for energy efficient mortgage (EEM) incentives if you obtain a Florida Energy Rating. For information about the Florida Building Code, Energy Conservation, contact the Florida Building Commission's support staff.

**Label required by Section R303.1.3 of the Florida Building Code, Energy Conservation, if not DEFAULT.