Items to Include-Each Box shall be

Marked as Applicable



COLUMBIA COUNTY BUILDING DEPARTMENT RESIDENTIAL CHECK LIST

MINIMUM PLAN REQUIREMENTS: FLORIDA BUILDING CODE RESIDENTIAL 2014 EFFECTIVE 1 JULY 2015 AND THE NATIONAL ELECTRICAL CODE 2011 EFFECTIVE 1 JULY 2015

ALL REQUIREMENTS ARE SUBJECT TO CHANGE

ALL BUILDING PLANS MUST INDICATE COMPLIANCE WITH THE CURRENT 2014 FLORIDA BUILDING CODES RESIDENTIAL, EFFECTIVE 1 JULY 2015. NATIONAL ELECTRICAL CODE 2011 EFFECTIVE 1 JULY 2015. ALL PLANS OR DRAWINGS SHALL PROVIDE CALCULATIONS AND DETAILS THAT HAVE THE SEAL AND SIGNATURE OF A CERTIFIED ARCHITECT OR ENGINEER REGISTERED IN THE STATE OF FLORIDA, OR ALTERNATE METHODOLOGIES, APPROVED BY THE STATE OF FLORIDA BUILDING COMMISSION FOR ONE-AND-TWO FAMILY DWELLINGS.

FOR DESIGN PURPOSES THE FOLLOWING BASIC WIND SPEEDS ARE PER FLORIDA BUILDING CODE FIGURE 1609-A THROUGH 1609-C ULTIMATE DESIGN WIND SPEEDS FOR RISK CATEGORY AND BUILDINGS AND OTHER STRUCTURES Revised 12/2016

GENERAL REQUIREMENTS: APPLICANT - PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL

1	Two (2) complete sets of plans containing	and the City	Select I	Applica From th		onh
2	Two (2) complete sets of plans containing the following: All drawings must be clear, concise, drawn to scale, details that are not used shall be marked void Condition space (Sq. Et.)			- om th	DI	Opt
3	Condition space (Sq. Ft.)	wn to scale, details that are not used shall be marked void	YES			十
_	Solution space (Sq. Ft.)	Total (Sq. Ft.) under roof	YES	NO	T	N/
D be	esigners name and signature shall be on all affixed to the plans and documents as per ite Plan information including:	documents and a licensed architect or engineer, signature at the FLORIDA BUILDING CODES RESIDENTIAL R101	and official	emboss	ed se	eal s
4	Dimensions of lot or parcel of land					
5	Dimensions of all building set backs		YES			7
6	Location of all other structures (include s	equare footoge of the second	YES			1
Location of all other structures (include square footage of structures) on parcel, existing or proposed well and septic tank and all utility easements. Provide a full legal description of proposity.			YES			7
•	Provide a full legal description of property. Vind-load Engineering Summary, calculations and any details are required. GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL Plans or specifications must show compliance with FBCR Chapter 3			YES		
3				Items to Include- Each Box shall be Marked as Applicable		
_			YES	NO		N/A
	Basic wind speed (3-second gust), miles	per hour	Select Fr	om the	Drop	obo
0	(Wind exposure - if more than one wind	Pynogura	YES		1	
1	is used, the wind exposure and applicable Wind importance factor and nature of occ	e wind direction shall be in direction	YES]
	restance suctor and nature of oc	cupancy	lv=0			,
2	The applicable internal pressure coefficie	ent Components - 101 11	YES]
3	The applicable internal pressure coefficient, Components and Cladding The design wind pressure in terms of psf (kN/m²), to be used for the design of exterior component, cladding materials not specifally designed by the registered design professional.		YES			
	The state of the s		YES			
le	vations Drawing including:					16
1	All side views of the structure		1 5			
	Roof pitch			YES		
	Overhang dimensions and detail with at	tic ventilation		YES		
	Location size and height above and Co	TOTALION TOTALION	YES			

Location, size and height above roof of chimneys

Location and size of skylights with Florida Product Approval

Building height from the established grade to the roofs highest peak

18 18

20A

Number of stories

YES

YES

YES YES

Floor Plan including: Dimensioned area plan showing rooms, attached garage, breeze ways, covered porches, xleck, 20 YES Raised floor surfaces located more than 30 inches above the floor or grade 21 YES All exterior and interior shear walls indicated Shear wall opening shown (Windows, Doors and Garage doors) YES Show compliance with Section FBCR 310 Emergency escape and rescue opening shown in each YES bedroom (net clear opening shown) and Show compliance with Section FBC 1405.13.2 where the opening of an operable window is located more than 72 inches above the finished grade or surface below, the lowest part of the clear opening of the window shall be a minimum of 24 inches above YES the finished floor of the room in which the window is located. Glazing between the floor and 24 inches shall be fixed or have openings through which a 4-inch-diameter sphere cannot pass. Safety glazing of glass where needed Fireplaces types (gas appliance) (vented or non-vented) or wood burning with Hearth YES (see chapter 10 and chapter 24 of FBCR) 26 YES Show stairs with dimensions (width, tread and riser and total run) details of guardrails, Handrails 27 YES Identify accessibility of bathroom (see FBCR SECTION 320) YES All materials placed within opening or onto/into exterior walls, soffits or roofs shall have Florida product approval number and mfg. installation information submitted with the plans (see Florida product approval GENERAL REQUIREMENTS: APPLICANT - PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL Items to Include-Each Box shall be Marked as Applicable FBCR 403: Foundation Plans YES / NO / N/A 29 | Location of all load-bearing walls footings indicated as standard, monolithic, dimensions, size Select From the Dropbox and type of reinforcing. YES 30 All posts and/or column footing including size and reinforcing Any special support required by soil analysis such as piling. YES YES 32 | Assumed load-bearing valve of soil Pound Per Square Foot 33 Location of horizontal and vertical steel, for foundation or walls (include # size and type) For structures YES with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an grounding electrode system. YES Per the National Electrical Code article 250.52.3 FBCR 506: CONCRETE SLAB ON GRADE 34 Show Vapor retarder (6mil. Polyethylene with joints lapped 6 inches and sealed) 35 Show control joints, synthetic fiber reinforcement or welded fire fabric reinforcement and Supports YES YES FBCR 318: PROTECTION AGAINST TERMITES Indicate on the foundation plan if soil treatment is used for subterranean termite prevention or Submit other approved termite protection methods. Protection shall be provided by registered 36 YES termiticides FBCR 606: Masonry Walls and Stem walls (load bearing & shear Walls) 37 Show all materials making up walls, wall height, and Block size, mortar type 38 Show all Lintel sizes, type, spans and tie-beam sizes and spacing of reinforcement YES Metal frame shear wall and roof systems shall be designed, signed and sealed by Florida Prof. Engineer or Architect Floor Framing System: First and/or second story Floor truss package shall including layout and details, signed and sealed by Florida Registered Professional Engineer YES

Sn	ow conventional floor joist type, size, span, spacing and attachment to load bearing walls,		
		YES	
41 Gi	rder type, size and spacing to load bearing walls, stem wall and/or priers	YES	
	- that in joist to girder		
44 Sh	ind load requirements where applicable	YES YES	
45 Sh	ow required under-floor crawl space	YES	
46 Sho	ow required amount of ventilation opening for under-floor spaces	YES	
40 2110	ow required covering of ventilation opening	YES	
47 Sho	ow the required access opening to access to under-floor spaces	YES	
DIIC	JW tile sub-floor structural panel sheathing type thickness and 6	YES	
49 Snc	OW Draftstopping. Fire caulking and Fire blocking	YES	
50 Sho	ow fireproofing requirements for garages attached to living spaces, per FBCR section 302.6	YES	
51 Pro	vide live and dead load rating of floor framing systems (psf).	YES	
	CHAPTER 6 WOOD WALL FRAMING CONSTRUCTION	YES / NO / N/	
	TRANSPORTED IN		
Δ	PPLICANT DIFFACE CHECK AND PROPERTY.	Items to Include- Each Box shall be	
	PPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL		
		Marked as	
-a a.		Applicable	
Stud	type, grade, size, wall height and oc spacing for all load bearing or shear walls	elect From the Dropb	
- A CHOL	oner schedule for structural members per table IRC 602 3 are to be above		
DHO	W WOOD STructural panel's sheathing attachment to the desired	YES	
	and wing testerior scriedure attachment on the edges & intermediate of the		
		YES	
Show	w all required connectors with a max uplift rating and required number of connectors and		
5 ocs	pacing for continuous connection of structural walls to foundation and roof trusses or		
1 101100	1 Systems	YES	
Shov	w sizes, type, span lengths and required number of support jack studs, king studs for shear		
6 wall	opening and girder or header per IRC Table 502.5 (1)	YES	
/ Indic	rate where pressure treated wood will be placed		
Show	vall wall structural panel sheathing, grade, thickness and show fastener schedule for structural	YES	
8 pane	el sheathing edges & intermediate areas	YES	
9 A det	tail showing gable truss bracing, wall balloon framing details or/ and wall hinge bracing detail		
	g gaste traces oracing, wan bandon framing details or/ and wall hinge bracing detail	YES	
BCR	:ROOF SYSTEMS:	COLUMN TO THE CO	
) Truss	design drawing shall meet section FRCP 802 1 6 1 Words		
menu	de a layout and truss details, signed and sealed by Florida Described.	YES	
Show	types of connector's assemblies' and resistance uplift rating for all trusses and rafters	YES	
Show	gable ends with rake beams showing reinforcement or gable truss and wall bracing details	YES	
Provi	de dead load rating of trusses	YES	
	g	YES	
BCR	802:Conventional Roof Framing Layout		
Rafter	r and ridge beams sizes, span, species and spacing		
Conne	ectors to wall assemblies' include assembly	YES	
Valley	ectors to wall assemblies' include assemblies' resistance to uplift rating y framing and support details	YES	
	de dead load rating of rafter system	YES	
110010	dead road rating of ratter system	YES	
BCR	803 ROOF SHEATHING		
Includ	e all materials which will make up the second in the second		
sheath	e all materials which will make up the roof decking, identification of structural panel	YES	
DITORETT	dumis, grade, unexpess		
J SHOW	fastener Size and schedule for structural panel sheathing on the edges & intermediate areas	YES	
OOF A	SSEMBLIES FRC Chapter 9		
Include	e all materials which will make up the roof assembles		
Cuhmii	t Florida Product Approval numbers for each component of the roof assembles covering	YES	
Submit		YES	

FBCR Chapter 11 Energy Efficiency Code for residential building

Residential construction shall comply with this code by using the following compliance methods in the FBCR chapter 11 Residential buildings compliance methods. Two of the required forms are to be submitted, N1100.1.1.1 As an alternative to the computerized Compliance Method A, the Alternate Residential Point System Method hand calculation, Alternate Form 600A, may be used. All requirements specific to this calculation are located in Sub appendix C to Appendix G. Buildings complying by this alternative shall meet all mandatory requirements of this chapter. Computerized versions of the Alternate Residential Point System Method shall not be acceptable for code compliance.

YES / NO / N/A Items to Include-GENERAL REQUIREMENTS: APPLICANT - PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL Each Box shall be Marked as Applicable Select From the Dropbox Show the insulation R value for the following areas of the structure YES 74 Attic space YES 75 Exterior wall cavity YES 76 Crawl space YES **HVAC** information Submit two copies of a Manual J sizing equipment or equivalent computation study YES Exhaust fans shown in bathrooms Mechanical exhaust capacity of 50 cfm intermittent or 20 cfm continuous required YES Show clothes dryer route and total run of exhaust duct YES Plumbing Fixture layout shown 80 All fixtures waste water lines shall be shown on the foundation plan YES 81 Show the location of water heater YES Private Potable Water 82 | Pump motor horse power YES 83 Reservoir pressure tank gallon capacity YES 84 Rating of cycle stop valve if used YES Electrical layout shown including 85 | Show Switches, receptacles outlets, lighting fixtures and Ceiling fans YES Show all 120-volt, single phase, 15- and 20-ampere branch circuits outlets required to be protected by Ground-Fault Circuit Interrupter (GFCI) Article 210.8 A YES Show the location of smoke detectors & Carbon monoxide detectors 87 YES Show service panel, sub-panel, location(s) and total ampere ratings YES On the electrical plans identify the electrical service overcurrent protection device for the main electrical service. This device shall be installed on the exterior of structures to serve as a disconnecting means for the utility company electrical service. Conductors used from the exterior disconnecting means to a panel or sub panel shall have four-wire conductors, of which one conductor shall be used as an equipment ground. Indicate if the utility company service entrance YES cable will be of the overhead or underground type. For structures with foundation which establish new electrical utility companies service connection a Concrete Encased Electrode will be required within the foundation to serve as an Grounding electrode system. Per the National Electrical Code article 250.52.3 Appliances and HVAC equipment and disconnects YES Show all 120-volt, single phase, 15- and 20-ampere branch circuits supplying outlets installed in dwelling unit family rooms, dining rooms, living rooms, parlors, libraries, dens, bedrooms, sunrooms, recreation rooms, closets, hallways, or similar rooms or areas shall be protected by N/A a listed Combination arc-fault circuit interrupter, Protection device.

GENERAL REQUIREMENTS: APPLICANT – PLEASE CHECK ALL APPLICABLE BOXES BEFORE SUBMITTAL

Items to Include-Each Box shall be Circled as Applicable

THE FOLLOWING ITEMS MUST BE SUBMITTED WITH BUILDING PLANS

92	Ruilding Permit Application	YES	NO	N/A
	Building Permit Application A current Building Permit Application is to be completed, by following the Checklist all supporting documents must be submitted. There is a \$15.00 application fee. The completed application with attached documents and application fee can be mailed.	YES		
93	Parcel Number The parcel number (Tax ID number) from the Property Appraisers Office (386) 758-1083 is required. A copy of property deed is also required. www.columbiacountyfla.com	YES		
24	Town of Fort White (386) 497-2321 If the parcel in the application for building permit is within the Corporate city limits of Fort White, an approval land use development letter issued by the Town of Fort is required to be submitted with the application for a building permit.	NO		
***	BELOW ITEMS ONLY NEEDED AFTER ZONING APPROVAL HAS GIVEN.	****	***	***
95	Environmental Health Permit or Sewer Tap Approval A copy of a approved Columbia County Environmental Health (386) 758-1058	YES		500
96	City of Lake City A City Water and/or Sewer letter Call 386-752 2021	1 1		_
97	shall require permitting through the Suwannee River Water Management District, before submitting a application to this office. Any project located within a flood zone where the base flood elevation (100 year flood) has been established shall meet the requirements of Section 8.5.2 of the Columbia County Land Development Regulations. Any project located within a flood zone where the base flood elevation has not been established (Zone A) shall meet the requirements of Section 8.5.3 of the Columbia County Land Development Regulations.	NO		
	CERTIFIED FINISHED FLOOR ELEVATIONS will be required on any project where the approved FIRM Flood Maps show the property is in a AE, Floodway, and AH flood zones. Additionally One Foot Rise letters are required for AE and AH zones. In the Floodway Flood zones a Zero Rise letter is required.			
99	22 200 de veropinent permit is also required for AE. Floodway & AH. Development nouvit and in one	-	-	-
100	an application for a culvert permit (\$25.00) must be made. County Public Works Dept. determines the size and length of every culvert before instillation and completes a final inspection before permanent power is granted. The applicant feels that a culvert is not needed, they may apply for a culvert waiver (\$50.00) Separate the check when issued. If the project is to be located on an F.D.O.T. maintained road, then an F.D.O.T. access permit is required.		1	
01	911 Address: An application for a 911address must be applied for and received through the Columbia County Emergency Management Office of 911 Addressing Department (386) 758-1125.	YES	+	

TOILET FACILITIES SHALL BE PROVIDED FOR ALL CONSTRUCTION SITES. NO

<u>Disclosure Statement for Owner Builders</u> If you as the applicant will be acting as an owner/builder under section 489.103(7) of the Florida Statutes, submit the required owner builder disclosure statement form.

Notice Of Commencement

A notice of commencement form **recorded** in the Columbia County Clerk Office is required to be filed with the building department Before Any Inspections can be preformed.

Section R101.2.1 of the Florida Building Code Residential:

The provisions of Chapter 1, Florida Building Code shall govern the administration and enforcement of the Florida Building Code, Residential.